

Zelig Styler SDK — iOS Integration Guide

This guide covers embedding the Zelig Styler widget into a third-party iOS app. Shoppers build looks, try on outfits, and add items to cart; your app handles dismissal and cart operations through a small delegate / closure bridge.

The SDK ships as a **pre-built closed-source binary** (ZeligStylerSDK.xcframework) — no source code is included.

Prerequisites

- iOS 13.0+
- Xcode 14+ (Xcode 15+ requires one extra build setting for CocoaPods — see Option B, step 4)
- Swift 5.7+
- Your **storeId** and **storeKey** — provided by your Zelig solutions engineer

Release artifacts

Current version: 1.0.2 — the URLs below are pinned to it. When Zelig publishes a newer native SDK, bump these version strings (see Step 10).

Artifact	URL
XCFramework zip (Option A)	https://storage.googleapis.com/ios-widget-sdk-zelig-prod/ZeligStylerSDK-1.0.2.xcframework.zip
CocoaPods podspec (Option B)	https://raw.githubusercontent.com/wearezelig/ZeligStylerSDK-binary/1.0.2/ZeligStylerSDK.podspec
SPM binary package (Option C)	repo https://github.com/wearezelig/ZeligStylerSDK-binary.git — pin by version/tag (1.0.2)

All three channels download the **same** prod XCFramework from GCS. Prefer pinning a **tag / version** (shown above), not **main**, so your app store build stays reproducible.

Step 1 — Install the SDK (pick one)

All three options deliver the same pre-built binary.

Use only one at a time. Before switching, fully remove the previous integration (dragged-in framework, pod entries, or SPM package), otherwise you'll see `Missing package product` or `duplicate-module` errors.

Option A — Direct XCFramework (simplest, no tooling required)

1. Download and unzip:

```
https://storage.googleapis.com/ios-widget-sdk-zelig-prod/  
ZeligStylerSDK-1.0.2.xcframework.zip
```

2. Drag `ZeligStylerSDK.xcframework` into your Xcode project. In the dialog that appears, make sure your **app target** is checked. Either “Reference files in place” or “Copy” works.
3. In your target's **General** → **Frameworks, Libraries, and Embedded Content**, set `ZeligStylerSDK.xcframework` to **Embed & Sign**. (Xcode may default to “Do Not Embed” — you must change it.)

That's it — no package manager involved.

This option has no automatic version management or checksum verification. Upgrading means downloading the **new versioned zip URL** and swapping the file. For SHA-256-verified pinned installs, prefer Option B or C.

Upgrading (example → 1.0.2): download .../
`ZeligStylerSDK-1.0.2.xcframework.zip` → remove the old
`ZeligStylerSDK.xcframework` from the project navigator → drag in the new one
→ confirm **Embed & Sign** → rebuild and ship.

Option A — Direct XCFramework
Option A — Direct XCFramework

Option B — CocoaPods

1. Add one line to your Podfile:

```
platform :ios, '13.0'  
use_frameworks!  
  
target 'YourApp' do  
  # Pin a tagged release (recommended – keep builds  
  # reproducible):  
  pod 'ZeligStylerSDK', :podspec => 'https://  
    raw.githubusercontent.com/wearezelig/ZeligStylerSDK-  
    binary/1.0.2/ZeligStylerSDK.podspec'  
end
```

CocoaPods fetches the podspec from the binary repo tag (GitHub raw); the podspec downloads the pre-built zip from GCS and verifies SHA-256.

2. Run:

```
pod install
```

A successful install prints Installing ZeligStylerSDK (1.0.2).

3. **Always open YourApp.xcworkspace from this point on, not .xcodproj.**
Opening the wrong file causes “no such module ‘ZeligStylerSDK’” at compile time.
4. **Required on Xcode 15+:** target → Build Settings → search User Script Sandboxing → set to **No** (both Debug and Release). Skipping this causes Command PhaseScriptExecution failed with a nonzero exit code — Xcode 15’s sandbox blocks CocoaPods’ framework-embed script on every pod-based project.

Upgrading (example → 1.0.2): change the tag in the Podfile URL, then reinstall:

```
pod 'ZeligStylerSDK', :podspec => 'https://  
raw.githubusercontent.com/wearezelig/ZeligStylerSDK-  
binary/1.0.2/ZeligStylerSDK.podspec'
```

```
rm -rf Pods Podfile.lock  
pod install
```

Installing ZeligStylerSDK (1.0.2) in the output confirms success. Rebuild and ship.

Changing only Podfile.lock / re-running pod install **without** bumping the tag URL will keep you on 1.0.2.

Option B — CocoaPods
Option B — CocoaPods

Option C — Swift Package Manager

The SDK ships as a binary Swift package. Pin it by **version**, not branch.

1. Xcode: **File** → **Add Package Dependencies...**
2. Paste the **git repo URL** — not the zip URL. (Pasting a zip URL prompts for a username/password; Xcode downloads and SHA-256-verifies the zip automatically based on the package’s declaration.)

```
https://github.com/wearezelig/ZeligStylerSDK-binary.git
```

3. Set the **Dependency Rule** to **Up to Next Major Version**, starting at 1.0.2. That locks you to the 1.x line (safe under semver) without picking up a breaking 1.0.2 automatically.
Use **Exact Version 1.0.2** only if your release process requires freezing a single binary until an explicit bump.

4. **Add to Project** → select your app project → **Add Package**. In the sheet that appears, **Add to Target** → select your app target → **Add**.
5. Verify: the Project Navigator shows **zeligstylersdk-binary**, and your target's **General** → **Frameworks, Libraries, and Embedded Content** lists ZeligStylerSDK.

Upgrading within 1.x (recommended rule = Up to Next Major):

1. Zelig tags a new release on ZeligStylerSDK-binary (e.g. 1.0.2) and publishes a new GCS zip.
2. Xcode → **File** → **Packages** → **Update to Latest Package Versions** (or **Resolve Package Versions**). If Xcode won't refresh: **File** → **Packages** → **Reset Package Caches**, then update again.
3. Confirm the resolved version in the Project navigator / Package.resolved is the new tag.
4. Rebuild and ship.

Upgrading if you used Exact Version: change the rule to the new tag (e.g. 1.0.2), resolve packages, rebuild, and ship.

Option C — Swift Package Manager
Option C — Swift Package Manager

Step 2 — Import

```
import ZeligStylerSDK
```

If this compiles, the installation succeeded. If you see `Unable to resolve module`: Option A — check target membership and the Embed setting; Option B — make sure you opened the `.xcworkspace`.

Step 3 — Store credentials

Your Zelig solutions engineer will provide your **storeId** and **storeKey**.

Security: treat `storeKey` like a password. Do not commit it to source control or embed it as a string literal in your binary. Load it from a secrets manager, a remote config endpoint, or your app's secure configuration layer.

Code examples in this guide use a placeholder store; substitute your own credentials.

Step 4 — Basic integration

Integration Note: The examples below show adding ZeligStyler to a product page, but you can integrate it anywhere in your app — product detail pages, cart, home recommendations, or a dedicated “Stylist” entry point. Replace class/view names with your actual implementation.

SwiftUI (recommended)

```
import SwiftUI
import ZeligStylerSDK

// Example: Add a "Build a Look" button to your existing view
struct ProductDetailView: View {
    let productCode: String // The product SKU/code to open on –
                           // passed from your product page
    let userId: String?     // Current logged-in user ID from
                           // your auth system, or nil for guests
    @State private var showStyler = false

    var body: some View {
        Button("Build a Look") { showStyler = true }
            .sheet(isPresented: $showStyler) {
                ZeligStylerView(
                    config: ZeligStylerConfig(
                        storeId: "YOUR_STORE_ID", //
                        // Replace with your storeId from Zelig
                        storeKey: "YOUR_STORE_KEY", //
                        // Replace with your storeKey from Zelig
                        productCode: productCode,
                        userId: userId
                    ),
                    onAddToCart: handleAddToCart, // Revolve's
                    // method (see Step 5)
                    onClose: { showStyler = false },
                    onError: { error in
                        print("Zelig error: \(error)")
                    }
                )
                .ignoresSafeArea()
            }
    }

    // Revolve's own method – the SDK calls it through the
    // `onAddToCart` hook so
    // Revolve can add the item to its cart and run any logging /
    // analytics it needs.
    // Revolve owns the body; full version in Step 5.
    private func handleAddToCart(item: ZeligCartItem,
                                completion: @escaping (Bool) ->
                                Void) { /* see Step 5 */ }
}
```

UIKit

```
import UIKit
import ZeligStylerSDK

// Example: Add a "Build a Look" button to your existing view
// controller
```

```

final class ProductViewController: UIViewController,
    ZeligStylerDelegate {
    private var styler: ZeligStyler?

    func showStyler(productCode: String, userId: String? = nil) {
        let config = ZeligStylerConfig(
            storeId: "YOUR_STORE_ID",           // Replace with your
            // storeId from Zelig
            storeKey: "YOUR_STORE_KEY",        // Replace with your
            // storeKey from Zelig
            productCode: productCode,
            userId: userId                      // Pass logged-in
            // user ID, or nil for guests
        )
        let styler = ZeligStyler(config: config, delegate: self)
        self.styler = styler                  // retain the reference
        styler.present(from: self)
    }

    // Required delegate method – the SDK calls this when the
    // shopper taps Add to
    // Bag, so Revolve can add the item to its cart and run any
    // logging / analytics
    // it needs. Revolve owns the body; full version in Step 5.
    func zeligStyler(_ styler: ZeligStyler,
        didRequestAddToCart item: ZeligCartItem,
        completion: @escaping (Bool) -> Void) {
        // ... your cart call, then completion(true) /
        // completion(false) – see Step 5
    }

    // Optional – defaults to dismissing the styler.
    func zeligStylerDidRequestClose(_ styler: ZeligStyler) {
        styler.dismiss(animated: true)
    }

    // Optional – called on load or initialization failures.
    func zeligStyler(_ styler: ZeligStyler, didFailWith error:
        ZeligStylerError) {
        print("Zelig error: \(error)")
    }
}

```

Presentation style: sheet (card) or full screen

The widget places no restriction on how it's presented. The examples above use a **sheet (card style, .sheet)**; **full-screen presentation** is equally supported — the SDK handles both, so pick whichever fits the product.

SwiftUI — the two styles are almost identical; the only difference is `.sheet(isPresented:)` [\[?\]](#) `.fullScreenCover(isPresented:)` (config below is the same `ZeligStylerConfig` as in the example above):

```

// Style 1: sheet (card, half-height, with the system's built-in
// swipe-to-dismiss)
.sheet(isPresented: $showStyler) {
    ZeligStylerView(
        config: config,
        onAddToCart: handleAddToCart,
        onClose: { showStyler = false },
        onError: { error in print("Zelig error: \(error)") }
    )
    .ignoresSafeArea()
}

// Style 2: full screen – the only difference from above is .sheet
// → .fullScreenCover
.fullScreenCover(isPresented: $showStyler) {
    ZeligStylerView(
        config: config,
        onAddToCart: handleAddToCart,
        onClose: { showStyler = false },
        onError: { error in print("Zelig error: \(error)") }
    )
    .ignoresSafeArea()
}

```

UIKit — `ZeligStyler.present(from:)` currently supports full screen only; there is no card (sheet) mode.

Preheating

The first open requires a full load (a few seconds). Call `prepare()` to preheat the widget asynchronously in the background — e.g. when the home screen appears; once preheating completes, the user can open Build a Look with no wait.

```

// SwiftUI – warm when the home view appears, and re-warm if the
// user changes
// Full reference: ZeligWebViewDemo/TestApp/TestApp/
// ContentView.swift
.task(id: userId) {
    ZeligStyler(config: ZeligStylerConfig(
        storeId: "YOUR_STORE_ID",
        storeKey: "YOUR_STORE_KEY",
        productCode:
            "", // any value – the shared widget is warmed
            regardless
        userId: userId
    )).prepare()
}

// UIKit – warm ahead of the open (e.g. on viewDidLoad)
let styler = ZeligStyler(config: ZeligStylerConfig(
    storeId: "YOUR_STORE_ID",
    storeKey: "YOUR_STORE_KEY",
    productCode: "",

```

```

        userId: userId
    ), delegate: self)
    styler.prepare()
    // ... later, when the user opens:
    styler.present(from: self)

```

`prepare()` is scoped to the identity (`storeId + userId`): calling it again for the **same** identity is a no-op, but a **new** `userId` re-injects the cookie and reloads. So when `userId` can change at runtime (login, logout, account switch), preheat again under the new identity — otherwise the preheat done under the old identity no longer applies and the first open after a switch pays the full load again. In SwiftUI, keying the `.task` on `userId` (as above) does this automatically; in UIKit, call `prepare()` again with the new `userId` after the identity changes.

Step 5 — The add-to-cart bridge

When a shopper taps **Add to Bag** in the widget, the SDK calls **`handleAddToCart`**, a **function Revolve provides**, to add the item to the cart — the same role `window.addToBagWithData` plays in the web integration.

The example below shows `handleAddToCart` in full (pseudocode), including how `fromZelig` drives add-source attribution. `revolveCustomCartService` and `revolveCustomAnalyticsService` are pseudocode placeholders for Revolve’s existing cart and tracking modules; the `insertPageTrackWithData` method is named after the web integration’s own call, so the two sides line up.

SwiftUI — the `handleAddToCart` method you passed to `onAddToCart` in Step 4:

```

private func handleAddToCart(item: ZeligCartItem,
                             completion: @escaping (Bool) ->
                                Void) {
    // `revolveCustomCartService` is Revolve's own cart layer –
    // not part of the SDK.
    revolveCustomCartService.add(
        sku: item.sku,
        size: item.size,
        quantity: item.quantity ?? 1,
        fromZelig: item.fromZelig ?? true
    ) { didSucceed in
        // After the add, report the source with Revolve's own
        // tracking. The
        // name/fields here just mirror web for easy comparison –
        // what matters
        // is passing `fromZelig` through as the source flag.
        revolveCustomAnalyticsService.insertPageTrackWithData(
            addToCartFlag: true,
            productCode: item.sku,
            isZeligAddToBag: item.fromZelig ?? true // web's
            fromZelig
        )
        completion(didSucceed) // true = added · false = failed
    }
}

```

```

    }
}

```

Reference (SwiftUI): a runnable version ships in the sample app — `handleStylerAddToCart` in `ZeligWebViewDemo/TestApp/TestApp/ProductDetail.swift:206`. It's a SwiftUI implementation, so it maps to the SwiftUI code above (not the UIKit delegate below).

Real-world example (Revolve's production app). The same `onAddToCart` hook wired into a real cart layer. `RShopManager` / `RShoppingBag` are Revolve's own types — not part of the SDK — so this does not compile in the sample as-is (it's kept there as a comment); it shows the real shape:

```

private func handleAddToCart(_ item: ZeligCartItem, completion:
    @escaping (Bool) -> Void) {
    guard let shopManager = RShopManager.sharedInstance() else {
        completion(false)
        return
    }

    let quantity = String(item.quantity ?? 1)

    shopManager.updateShoppingCart(
        forEmail: "",
        action: "add",
        code: item.sku,
        numSku: "1",
        prevSize: nil,
        qty: quantity,
        newSize: item.size,
        newCode: nil,
        itemDepartment: "",
        department: nil,
        pageType: "PDP",
        additionalQueryForURL: nil,
        success: { responseObject in
            DispatchQueue.main.async {
                guard let shoppingBag = responseObject as?
                    RShoppingBag else {
                    completion(false)
                    return
                }

                if shoppingBag.success {
                    shopManager.bagBadgeCount =
                        shoppingBag.numItems
                    NotificationCenter.default.post(name:
                        NSNotification.Name.bagBadgeUpdated, object: nil)
                    completion(true)
                } else {
                    completion(false)
                }
            }
        },

```

```

        failure: { _ in
            DispatchQueue.main.async {
                completion(false)
            }
        }
    }
)

// Add-source attribution fires on *intent*: a tap in the
// widget counts as a
// Zelig-originated add, even if the cart write above fails.
// Report it after
// kicking off the cart call – decoupled from the success/
// failure branches.
revolveCustomAnalyticsService.insertPageTrackWithData(
    addToCartFlag: true,
    productCode: item.sku,
    isZeligAddToBag: item.fromZelig ?? true
)
}

```

UIKit — the `ZeligStylerDelegate` method (the empty one from Step 4, now filled in).

As above, `revolveCustomCartService`, `revolveCustomAnalyticsService`, and `insertPageTrackWithData` are pseudocode placeholders — **replace them with the real definitions in your host app**.

```

func zeligStyler(_ styler: ZeligStyler,
    didRequestAddToCart item: ZeligCartItem,
    completion: @escaping (Bool) -> Void) {
    // `revolveCustomCartService` is Revolve's own cart layer –
    // not part of the SDK.
    revolveCustomCartService.add(
        sku: item.sku,
        size: item.size,
        quantity: item.quantity ?? 1,
        fromZelig: item.fromZelig ?? true
    ) { didSucceed in
        // After the add, report the source with Revolve's own
        // tracking. The
        // name/fields here just mirror web for easy comparison –
        // what matters
        // is passing `fromZelig` through as the source flag.
        revolveCustomAnalyticsService.insertPageTrackWithData(
            addToCartFlag: true,
            productCode: item.sku,
            isZeligAddToBag: item.fromZelig ?? true // web's
            fromZelig
        )
        completion(didSucceed) // true = added · false = failed
    }
}

```

What fromZelig is for — add-source attribution. `insertPageTrackWithData` uses it to decide whether to tag the call as Zelig-originated, exactly as on web. The whole Zelig-specific difference is one line inside it:

```
// web (pseudocode): inside insertPageTrackWithData
if (isZeligAddToBag) u += "&navsrc=zeligplp"; // tag the source
    only when it came from Zelig
```

If your cart API reports success differently — say it returns a `Result` or throws — map that to the boolean: `completion(true)` on the success path, `completion(false)` on the failure path.

The item carries these fields:

Field	Description
<code>sku</code>	Normalized product SKU (from the widget's code / <code>productCode</code>).
<code>size</code>	Selected size string ("all" for one-size items).
<code>quantity</code>	Quantity if the widget supplied one; otherwise <code>nil</code> .
<code>fromZelig</code>	<code>true</code> when the widget flagged this as a Zelig-originated add-to-cart; <code>nil</code> if absent.

The contract: you only need to call `completion` once — `true` if the item made it into the cart, `false` if not. The widget drives its in-modal UI from that signal and falls back to a ~2–4 s timeout; if the timeout fires first, its displayed state can drift from the cart, so respond promptly.

Step 6 — Configuration reference

Parameter	Type	Required	Default	Description
<code>storeId</code>	<code>String</code>	Yes	—	Your Zelig store identifier.
<code>storeKey</code>	<code>String</code>	Yes	—	Your store API secret, paired with <code>storeId</code> .
<code>productCode</code>	<code>String</code>	Yes for <code>.productDetail</code>	—	Hero SKU to open on. Pass "" for <code>.buildALook/.myClo</code>
<code>userId</code>	<code>String?</code>	No	<code>nil</code>	Your app's logged-in user ID. See Step 7.
<code>entry</code>	<code>ZeligStylerEntry</code>	No	<code>.productDetail</code>	Which experience to open. See “Entry modes” below.

Entry modes

```
public enum ZeligStylerEntry { case productDetail, buildALook, myCloset }
```

Two ways the styler is launched:

CTA launch — **.productDetail** (*default*) Opened from a product's Style-It CTA, on a specific product. `productCode` must be non-empty.

Banner launch — **.buildALook** / **.myCloset** Opened from a banner entry point with no host-provided product (pass `productCode: ""`):

- **.buildALook** — opens the Build a Look experience. The widget picks the hero product itself (the shopper's last look, else the store's default recommendation).
- **.myCloset** — same as **.buildALook**, but lands directly on the My Closet tab.

SwiftUI landing: see `ZeligWebViewDemo/TestApp/TestApp/ContentView.swift` — `editorialBanner` renders the block and `.sheet(item:)` presents the styler.

Banner launch — Build a Look / My Closet

Banner launch — Build a Look / My Closet

// Open on a specific product (e.g. from a PDP):

```
ZeligStylerConfig(
  storeId: "YOUR_STORE_ID",
  storeKey: "YOUR_STORE_KEY",
  productCode: "PRODUCT_123"
)
```

// Entry points with no specific product:

```
ZeligStylerConfig(
  storeId: "YOUR_STORE_ID",
  storeKey: "YOUR_STORE_KEY",
  productCode: "",
  entry: .buildALook
)
```

```
ZeligStylerConfig(
  storeId: "YOUR_STORE_ID",
  storeKey: "YOUR_STORE_KEY",
  productCode: "",
  userId: "USER_123", // Pass user ID for authenticated users
  entry: .myCloset
)
```

Step 7 — Shopper identity & closet

`userId` tells the Zelig backend how to scope the shopper's closet:

- **Non-nil (signed in)** — the closet is tied to this user and syncs across devices. An anonymous closet is automatically inherited on first sign-in.
- **nil (guest)** — a device-local anonymous closet is used instead.

```
let config = ZeligStylerConfig(
  storeId: "YOUR_STORE_ID",      // Replace with your storeId
    from Zelig
  storeKey: "YOUR_STORE_KEY",    // Replace with your storeKey
    from Zelig
  productCode: productCode,
  userId: userId                 // Pass your logged-in user ID,
    or nil for guests
)
```

Step 8 — Error handling

When the widget fails to load or initialize, the SDK hands you a `ZeligStylerError` through the optional error callback — the `onError` closure in `SwiftUI`, the `zeligStyler(_:didFailWith:)` method in `UIKit` (both wired up in Step 4). Implementing it is optional but recommended, so you can show the shopper a graceful fallback instead of a stuck screen.

All cases occur during load / initialization — they do not interrupt an already-open session:

Case	What it means
<code>.loaderLoadFailed(URL)</code>	The widget loader couldn't be fetched from the CDN (the failing URL is attached).
<code>.widgetInitTimeout</code>	The widget didn't finish initializing within the timeout.
<code>.modalMountTimeout</code>	The widget's modal UI didn't mount in time.
<code>.webViewNavigationFailed(underlying:)</code>	The underlying <code>WKWebView</code> navigation failed (the underlying <code>Error</code> is attached).
<code>.hostPageUnavailable</code>	The page hosting the widget couldn't be reached.

This error callback is separate from the add-to-cart completion contract (which must fire on both success and failure) — see Step 5 for that.

Step 9 — Testing & debugging

Use the test SKUs your Zelig solutions engineer provides for your store.

Your main signal for diagnosing problems is the **error callback** (SwiftUI `onError` / UIKit `didFailWith`): handle the `ZeligStylerError` cases there, and add your own logging in that callback and in `onAddToCart` to trace behaviour.

Step 10 — SDK versions & updates (how Revolve / hosts upgrade)

Two layers update independently:

Layer	What it is	How it updates
Widget (JS)	Styler UI, looks, algorithms	Loaded at runtime from Zelig's CDN. No app store release required — shoppers get the latest widget the next time they open the styler.
Native SDK	<code>ZeligStylerSDK.xcframework</code> bridge	Version-pinned in your Xcode project. You only bump it when Zelig ships a new native release (bridge / public API). Your solutions engineer notifies you in advance.

Pinning `1.0.2` is intentional: your App Store binary stays reproducible until you choose to upgrade the native SDK.

When Zelig publishes a new native version (e.g. `1.0.2` → `1.0.2`)

Zelig will:

1. Upload `ZeligStylerSDK-1.0.2.xcframework.zip` to GCS (`ios-widget-sdk-zelig-prod`).
2. Tag <https://github.com/wearezelig/ZeligStylerSDK-binary> as `1.0.2` (Package.swift + podspec updated with the new URL + SHA-256).
3. Tell you the new version number.

Then upgrade with **your** install method only:

Your install	What to do
A — Direct XCFramework	Download the new versioned zip (<code>.../ZeligStylerSDK-1.0.2.xcframework.zip</code>) → remove the old framework → drag in the new one → Embed & Sign → rebuild → ship
B — CocoaPods	Bump the tag in the Podfile URL (<code>.../ZeligStylerSDK-binary/1.0.2/ZeligStylerSDK.podspec</code>) →

Your install	What to do
C — SPM	<pre>rm -rf Pods Podfile.lock && pod install → confirm Installing ZeligStylerSDK (1.0.2) → rebuild → ship</pre> • Up to Next Major rule: File → Packages → Update to Latest Package Versions → confirm the resolved version → rebuild → ship. • Exact Version rule: change it to 1.0.2 first, then resolve → rebuild → ship.

Previous version zips remain online — old app builds keep resolving.

The SDK follows semantic versioning. Any **1.x** update is backward-compatible with your existing integration code. A future **2.x** would be a breaking change and would be called out explicitly (SPM’s “Up to Next Major” would not auto-adopt it).

Step 11 — Release checklist

☐

Your storeId / storeKey are correct.

☐

storeKey not committed to source control.

☐

productCode passed and present in your store’s catalog.

☐

Add-to-cart callback implemented; completion called on both success and failure.

☐

Logged-in userId passed for authenticated shoppers (nil only for guests).

☐

Tested on multiple device sizes (phone and tablet).

Troubleshooting

Symptom	Fix
Missing package product 'ZeligStylerSDK'	A previous install method wasn’t fully removed. Check Package Dependencies, the Frameworks list, and the Podfile — keep exactly one.
Command PhaseScriptExecution failed (CocoaPods)	Xcode 15+ sandbox restriction. Build Settings → User Script

Symptom	Fix
Unable to resolve module 'ZeligStylerSDK'	Sandboxing → No (see Option B, step 4). Option B: you opened <code>.xcodeproj</code> — open <code>.xcworkspace</code> instead. Option A: check target membership and the Embed & Sign setting.
Widget blank or not loading	Check network connectivity; verify <code>storeId</code> / <code>storeKey</code>; open Safari Web Inspector and filter for [Zelig iOS] logs.
Add to cart hangs or never resolves	Confirm your <code>onAddToCart</code> / <code>delegate</code> method is wired up and that <code>completion(true/false)</code> is called on every code path.
Wrong product opens	Verify <code>productCode</code> is correct and exists in your store's catalog.
Touches not registering on a physical device	Contact your Zelig solutions engineer — this is typically a host-app layout configuration issue.

API reference

```
public enum ZeligStylerEntry { case productDetail, buildALook, myCloset }
```

```
public struct ZeligStylerConfig {
    public let storeId: String
    public let storeKey: String
    public let productCode: String
    public let userId: String?
    public let entry: ZeligStylerEntry

    public init(
        storeId: String,
        storeKey: String,
        productCode: String,
        userId: String? = nil,
        entry: ZeligStylerEntry = .productDetail
    )
}
```

```

public struct ZeligCartItem {
    public let sku: String
    public let size: String
    public let quantity: Int?
    public let fromZelig: Bool?
}

public enum ZeligStylerError: Error {
    case loaderLoadFailed(URL)
    case widgetInitTimeout
    case modalMountTimeout
    case webViewNavigationFailed(underlying: Error)
    case hostPageUnavailable
}

public protocol ZeligStylerDelegate: AnyObject {
    // Required:
    func zeligStyler(_ styler: ZeligStyler,
                    didRequestAddToCart item: ZeligCartItem,
                    completion: @escaping (Bool) -> Void)

    // Optional:
    func zeligStylerDidRequestClose(_ styler: ZeligStyler)
    func zeligStyler(_ styler: ZeligStyler, didFailWith error:
        ZeligStylerError)
}

public final class ZeligStyler {
    public init(config: ZeligStylerConfig, delegate:
        ZeligStylerDelegate? = nil)

    /** Whether the widget has finished warming (true after
        prepare() / first open). */
    public var isReady: Bool { get }

    /** Fires when warming completes (main thread). May fire again
        on a reload. */
    public var onReady: (() -> Void)?

    /** Warm the widget in the background ahead of time.
        Idempotent – a no-op if
        already warmed for the same identity. Call early for an
        instant first open. */
    public func prepare()

    /** Present and open on the given product/entry. Near-instant
        if already warmed. */
    public func open(productCode: String = "", entry:
        ZeligStylerEntry = .productDetail,
        from presenter: UIViewController, animated:
        Bool = true)

    public func present(from presenter: UIViewController,
        animated: Bool = true)
    public func dismiss(animated: Bool = true)

```

```

}

public struct ZeligStylerView: UIViewControllerRepresentable {
    public init(
        config: ZeligStylerConfig,
        onAddToCart: @escaping (ZeligCartItem, @escaping (Bool)
            -> Void) -> Void,
        onClose: (() -> Void)? = nil,
        onError: ((ZeligStylerError) -> Void)? = nil
    )
}

```

Support

Contact your Zelig solutions engineer for store credentials, environment configuration, and any merchant-specific setup.

Version: 1.0.2 · **Last updated:** July 2026