



8. Rotary switch 63A with LED
9. Neutral bar-as per way-10x8 mm Brass (Shrouded)
10. Earth bar-as per way- 9x7 mm Aluminium

CODE	DESCRIPTION	A	B	C	INCOMER
	4W DB	450	400	310	8 Pole
	6W DB	486	436	346	
	8W DB	522	472	382	
	12W DB	594	544	454	

1. Material: GI/IS277 120GSM regular spangle,
Thickness: Box, Door, frame, Gland Plate: 1.2 mm, Shield: 1.2 mm,
2. Unspecified tolerance: IS:2102 Medium,
3. Degree of protection : IP=43 & IK=09,
4. Finish: Powder coating RAL 9003 White texture Finish,
5. Powder Coating Thickness: 60 microns,
6. Detachable Gland Plate at Top & Bottom,
7. D-Type gasket below door,
8. Door earthing not required,
9. Outer dimension tolerances within ± 2.0 mm,
- 10.MCB's are shown only for graphical Representation.

REV No. 0		MATERIAL See Notes			SURFACE TREATMENT RAL-9003 Fine texture finish 60~120 micron.	PRODUCT NAME DISTRIBUTION BOARDS
DIMENSION IN mm	SCALE 1 : 1	DRAWING NO AL-PR-VPS-DD-001			ITEM DESCRIPTION ALRIC VERTICAL PHASE SELECTOR DD DB IP43	TITLE G.A.DRAWING
DESIGNED Kalpesh	DATE 22-12-2025	DRAWN Kalpesh	CHECKED Satish	APPROVED -	 SPECTRUM ELECTRICAL INDUSTRIES LTD. Gat No. 139/1 & 139/2, Umale, Tal. & Dist. Jalgaon 425003.	