




CODE	DESCRIPTION	A	B	C	D
	SPN 4 WAY	246	196	136	72
	SPN 6 WAY	282	232	172	108
	SPN 8 WAY	318	268	208	144
	SPN 12 WAY	390	340	280	216
	SPN 16 WAY	462	412	352	288
	SPN 18 WAY	498	448	388	324
	SPN 20 WAY	534	484	424	360

1. Material: CRCA/IS513 CR2,
Thickness: Box 0.9 mm, Gland Plate 0.9 mm,
Frame 0.9 mm, Door 1.0 mm,
2. Unspecified tolerance: IS:2102 Medium,
3. Degree of protection : IP=43,
4. Finish: Powder coating RAL 9003 White fine texture Finish,
5. Fork type bus bar- as per way.
6. Powder Coating Thickness: 60-90 microns
7. Detachable Gland Plate at Top & Bottom,
8. D-Type gasket below door,
9. Door earthing not required,
10. Door reversible with frame.
11. Outer dimension tolerances within ± 2.0 mm
12. MCB's are shown only for graphical Representation.

UNSPECIFIED TOLERANCE, IS:2102 MEDIUM								
LINEAR						ANGULAR		
DIVER	0.4000	3	6	30	120	0	10	
UP TO	3	6	30	120	400	10	50	
DEV.	± 0.1	± 0.1	± 0.2	± 0.3	± 0.5	± 1°	± 10°	

REV No. 0		MATERIAL See Notes			SURFACE TREATMENT RAL-9003 Fine texture finish 60-120 micron.		PRODUCT NAME DISTRIBUTION BOARDS	
DIMENSION IN mm	SCALE 1 : 1	DRAWING NO AL-PR-SPN-DD-001			ITEM DESCRIPTION ALRIC SPN DD DB IP43		TITLE G.A.DRAWING	
DESIGNED Kalpesh	DATE 16-11-2025	DRAWN Kalpesh	CHECKED Satish	APPROVED -	 SPECTRUM ELECTRICAL INDUSTRIES LTD. Gat No. 139/1 & 139/2, Umale, Tal. & Dist. Jalgaon 425003.			