

Reference document

webalorn



This document contains examples for many of the functionalities of md2book.
Cover image by @nervum (unsplash.com/@nervum).

-
- I. Introduction _____
 - II. Markdown - Title level 1 _____
 - 1. Markdown - Title level 2 _____
 - 1. Markdown - Title level 3 _____
 - 2. Simple markdown _____
 - 3. Tables _____
 - 4. LaTeX math equations _____
 - III. Templates _____
 - 1. Counters _____
 - 2. Variables _____
 - 3. Sep _____
 - 4. Skip _____
 - 5. Include _____
 - 6. Font, size and color _____
 - 7. Conditions _____
 - IV. Second markdown document _____
-

Introduction

This document contains various styles and formatting options. The links may not be clickable on the github pdf viewer, so you can download the pdf. You can look at the source code [in the repository](#), and the rendered document [here in pdf](#). Any valid html can be inserted into the markdown code, and it will be rendered. The configuration file used here is :

```
all : [docx, epub, html, pdf]

targets:
  main:
    chapters:
      - book.md
      - next_chapter.md
    by : webalorn
    name : reference
    title : "Reference document"

    titlepage:
      image : dragon.jpg
    images:
      cover : dragon.jpg

    font:
      include:
        - calligraffiti

    metadata:
      abstract : "This document contains examples for many of the functionalities of md2
Cover image by @nervum (unsplash.com/@nervum)."

    variables:
      names:
        character1 : "This is a custom variable"
      todo:
        - item1
        - item2
        - item3
```

Some other formats are supported :

- [Html document](#)
- [epub \(ebook\)](#)
- [docx document](#)
- And others...

Markdown - Title level 1

Markdown - Title level 2

Markdown - Title level 3

Markdown - Title level 4

Markdown - Title level 5

Markdown - Title level 6

Simple markdown

The table of contents is generated by the [TOC] below. This is a paragraph

This is another paragraph.

Simple lines breaks can be used, and two line breaks to create another paragraph. The next paragraph is separated by an horizontal line, using --- .

You can use [markdown links](#) or [html links](#). Transform an url or an e-mail into a link using <...> : <https://google.com>, contact@example.org. You can use all sort of formating : *italic*, **bold**, underlined (with html), ~~striked~~, `inline-code` , **highlighted**, super^{super}, inf_{inf}.

- This is a dotted list
- With multiple
- Items
 - And
 - One sublist
 - Two sublists
- 1. This is a numbered list
- 2. With multiple
- 3. Items
 - i. And
 - ii. One sublist
 - a. Two sublists

- ☐ This is a task list
- ☒ Task 2 (done)

This is a blockquote
with multiple lines

And paragraphs !

And even a nested blockquote

```
This is a multiline  
code block
```

And definitions : the HTML specification is maintained by the W3C. Awesome HTML !



Tables

First Header	Second Header
Content Cell	Content Cell
Content Cell	Content Cell

header 1	header 2	header 3
three	columns	
		.
		...

LaTeX math equations

You can insert *inline – latex* inside the text : $3 + 4 = 5 = \sum_{i=0}^4 \frac{1}{2} \times 2$. For bigger equations, math blocks can be used :

$$\frac{1}{\Gamma(s)} \int_0^\infty \frac{u^{s-1}}{e^u - 1} du$$

Templates

A template system is used by `md2book`, and allow inserting variables, and special html elements. The variables names must be written like this : `{ { variable_name } }`.

- **Date** : 21/06/2020
- **Datetime** : 21/06/2020 11:15:10
- **Time** : 11:15:10
- **Hour** : 11:15

Counters

We can use counters to count occurrences, for instance to auto-number chapters. You can replace `chapter` within the template by anything else.

- Chapter 1
- Chapter 2
- Chapter 3
- Chapter 4

Variables

You can defines a variable using `{ % var_name:set:value % }`. In this example, we will use it to store a name with `{ % name1:set:The Great Warrior Kron % }`.

It can then be used multiple times : **The Great Warrior Kron** is great, and The Great Warrior Kron is a warrior. And this paragraph doesn't even used the name of *The Great Warrior Kron*.

All the variables defined in the configuration file can be used in the document : This document used the font `opensans`, with the theme `github`, and is written by `webalorn`. The chapters are `book.md`, `next_chapter.md`. Keywords are not set in the configuration file : `None`.

You can use your own variables, by setting them under `variables` in the configuration file : This is a custom variable, and `item1`, `item2`, `item3`.

Sep

It create a separation than can be customized with the configuration file.

Laboris irure culpa irure dolore dolor nostrud minim dolor ex nostrud quis mollit non in velit mollit. Lorem ipsum dolore velit sint esse laboris culpa sit sed et excepteur ullamco sint veniam dui laboris aute in deserunt commodo veniam anim in anim labore nostrud cillum laborum.

* * *

Ut id tempor ut dui qui ut officia cillum deserunt. Duis dolore est sunt reprehenderit veniam ut sunt tempor deserunt ut sit ut nostrud excepteur veniam eu. Nulla incididunt cupidatat tempor cillum et amet amet enim non excepteur quis officia do ad incididunt dolor enim consectetur culpa et sit.

Skip

Using skip will force a page break. The default behavior is to also insert a page break between every level 1 title, but it can be overwrite with the configuration file.

Laboris irure culpa irure dolore dolor nostrud minim dolor ex nostrud quis mollit non in velit mollit. Reprehenderit reprehenderit nostrud commodo eu sunt aliqua in magna ut consequat voluptate incididunt quis qui velit reprehenderit incididunt laborum nostrud qui ut laboris est labore.

Ut id tempor ut dui qui ut officia cillu. Consectetur sunt exercitation exercitation officia esse dolore laborum dolore cupidatat sed in sed magna enim nostrud velit dolor eu nisi adipisicing in elit dolor sit mollit anim labore. Cupidatat dolor ex excepteur aute officia nostrud ex culpa elit officia eiusmod nisi sint amet excepteur deserunt in dolore est sint.

Include

We can include a file multiple time. This template is useful for inserting small blocks without copy-pasting. But we recommend using the chapters to split your text into multiple main files.

This is an included document. It can use templates : written by webalorn.

This is an included document. It can use templates : written by webalorn.

Font, size and color

I want to use a more funny font. The text will now use the `calligraffiti` font. Do not insert templates to change the font, the color or the size in the middle of a paragraph, it can cause bugs. Use pure html if you really want to do it. Font template must be used on a line without leading or trailing spaces and without any other template, include font templates.

Wow, this paragraph uses `calligraffiti` ! Now I can change the color.

This text is now in blue. But I can make it bigger.

This is a bigger text, indeed. But before going to the next section, I will reset all the text properties.

Conditions

This code will display the subtitle only if it exists : .

- $2 + 2 = 2$?
- $2 + 2 = 4$? OUI ! : else : Non...

Second markdown document

This document is merged with the first one.