

# Reference document

*webalorn*

- 
- I. Introduction \_\_\_\_\_
  - II. Markdown - Title level 1 \_\_\_\_\_
    - 1. Markdown - Title level 2 \_\_\_\_\_
      - 1. Markdown - Title level 3 \_\_\_\_\_
    - 2. Simple markdown \_\_\_\_\_
    - 3. Tables \_\_\_\_\_
  - III. Templates \_\_\_\_\_
    - 1. Counters \_\_\_\_\_
    - 2. Variables \_\_\_\_\_
    - 3. Sep \_\_\_\_\_
    - 4. Skip \_\_\_\_\_
    - 5. Include \_\_\_\_\_
  - IV. Second markdown document \_\_\_\_\_
-

# Introduction

---

This document contains various styles and formatting options. You can look at the source code [in the repository](#), and the rendered document [here in pdf](#). You can also insert any valid html in your markdown code, and it will be rendered. The configuration file used is :

```
targets:
  main:
    chapters:
      - book.md
      - next_chapter.md
    by : webalorn
    name : reference
    title : "Reference document"

  variables:
    names:
      character1 : "This is a custom variable"
    todo:
      - item1
      - item2
      - item3
```

Some other formats are supported :

- [Html document](#)
- [epub \(ebook\)](#)
- [docx document](#)
- And others...

# Markdown - Title level 1

---

## Markdown - Title level 2

---

### Markdown - Title level 3

#### Markdown - Title level 4

#### Markdown - Title level 5

#### Markdown - Title level 6

## Simple markdown

---

The table of contents is generated by the [TOC] below. This is a paragraph

This is another paragraph.

Simple lines breaks can be used, and two line breaks to create another paragraph. The next paragraph is separated by an horizontal line, using ---.

---

You can use [markdown links](#) or [html links](#). Transform an url or an e-mail into a link using `<...>` : <https://google.com>, [contact@example.org](mailto:contact@example.org). You can use all sort of formating : *italic*, **bold**, underlined (with html), ~~striked~~, `inline-code`, **highlighted**, super<sup>super</sup>, inf<sub>inf</sub>.

- This is a dotted list
  - With multiple
  - Items
    - And
    - One sublist
      - Two sublists
1. This is a numbered list
  2. With multiple
  3. Items
    - i. And
    - ii. One sublist
      - a. Two sublists

- ☐ This is a task list
- ☒ Task 2 (done)

This is a blockquote  
with multiple lines

And paragraphs !

And even a nested blockquote

```
This is a multiline  
code block
```

And definitions : the HTML specification is maintained by the W3C. Awesome HTML !



## Tables

---

First Header	Second Header
Content Cell	Content Cell
Content Cell	Content Cell

header 1	header 2	header 3
three	columns	
		.
		...

# Templates

---

A template system is used by `md2book`, and allow inserting variables, and special html elements. The variables names must be written like this : `{ { variable_name } }`.

- **Date** : 17/06/2020
- **Datetime** : 17/06/2020 10:30:30
- **Time** : 10:30:30
- **Hour** : 10:30

## Counters

---

We can use counters to count occurrences, for instance to auto-number chapters. You can replace `chapter` within the template by anything else.

- Chapter 1
- Chapter 2
- Chapter 3
- Chapter 4

## Variables

---

You can define a variable using `{ { var_name:set:value } }`. In this example, we will use it to store a name with `{ { name1:set:The Great Warrior Kron } }`.

It can then be used multiple times : **The Great Warrior Kron** is great, and The Great Warrior Kron is a warrior. And this paragraph doesn't even use the name of *The Great Warrior Kron*.

All the variables defined in the configuration file can be used in the document : This document used the font `opensans`, with the theme `github`, and is written by `webalorn`. The chapters are `book.md`, `next_chapter.md`. Keywords are not set in the configuration file : `None`.

You can use your own variables, by setting them under `variables` in the configuration file : This is a custom variable, and `item1`, `item2`, `item3`.

## Sep

---

It creates a separation that can be customized with the configuration file.

Laboris irure culpa irure dolore dolor nostrud minim dolor ex nostrud quis mollit non in velit mollit. Lorem ipsum dolore velit sint esse laboris culpa sit sed et excepteur ullamco sint veniam dui laboris aute in deserunt commodo veniam anim in anim labore nostrud cillum laborum.

\* \* \*

Ut id tempor ut dui qui ut officia cillum deserunt. Duis dolore est sunt reprehenderit veniam ut sunt tempor deserunt ut sit ut nostrud excepteur veniam eu. Nulla incididunt cupidatat tempor cillum et

amet amet enim non excepteur quis officia do ad incididunt dolor enim consectetur culpa et sit.

## Skip

---

Using skip will force a page break. The default behavior is to also insert a page break between every level 1 title, but it can be overwrite with the configuration file.

Laboris irure culpa irure dolore dolor nostrud minim dolor ex nostrud quis mollit non in velit mollit. Reprehenderit reprehenderit nostrud commodo eu sunt aliqua in magna ut consequat voluptate incididunt quis qui velit reprehenderit incididunt laborum nostrud qui ut laboris est labore.

Ut id tempor ut duis qui ut officia cillu. Consectetur sunt exercitation exercitation officia esse dolore laborum dolore cupidatat sed in sed magna enim nostrud velit dolor eu nisi adipisicing in elit dolor sit mollit anim labore. Cupidatat dolor ex excepteur aute officia nostrud ex culpa elit officia eiusmod nisi sint amet excepteur deserunt in dolore est sint.

## **Include**

---

We can include a file multiple time. This template is useful for inserting small blocks without copy-pasting. But we recommend using the chapters to split your text into multiple main files.

This is an included document. It can use templates : written by webalorn.

This is an included document. It can use templates : written by webalorn.



# Second markdown document

---

This document is merged with the first one.