BinsApp Backend — Fixes & Changes Summary

Work completed on the `new_flow_uber` branch

Prepared: July 23, 2026 • Covers roughly July 17–23, 2026
Scope: authentication/OTP, dispatch, payments & ledger, notifications, operator scoring, live tracking, ratings, and partner-service applications.

How to save as PDF: open this file in a browser and choose *Print* → *Save as PDF* (letter/A4, default margins). All content is print-optimized.

1. Authentication & OTP
2. Dispatch (Uber-style)
3. Dumpster Matching
4. Payments & Ledger
5. Notifications & Copy
6. Order Timeline
7. Live Location Tracking
8. Operator Scoring
9. Ratings & Reviews
10. Partner Services (Tree/Junk)
11. Diagnostic Scripts & Deploy

1. Authentication & OTP

FIX "OTP limit exceeded" on all numbers (static & real)

Problem: Every number, including static test numbers, hit rate limits; `+92` numbers were blocked by region gating; the express limiter bucketed everyone under a single `unknown` key.

Fix:

- Static test numbers now fully bypass Redis + express limiters and use fixed OTP `1234`.
- Allowed `+92` region; raised per-day cap; limiter now falls back to a per-IP bucket when phone is missing.
- Twilio Verify path confirmed; static numbers skip Twilio send entirely.

Files: `utils/staticOtpPhones.js`, `utils/otpProtection.js`, `config/env.js`, `modules/auth/routes.js`

ADD New static test numbers

Added `+923467893622` and `+923703839371` as static test numbers (login with OTP `1234`, no rate limits).

Files: `utils/staticOtpPhones.js`

CONFIRM `send-otp` hash & SMS Retriever behavior

- Endpoint accepts optional 11-char app `hash`; it is preserved through validation and forwarded to Twilio as `AppHash` (uses the client's per-install hash, no hardcoded fallback).
- Twilio Verify composes the SMS body and appends the hash on the last line automatically.
- Added a server log confirming the hash was forwarded (`appHashForwarded`, `appHashLength`).

> Action item (Twilio console, not code): set Verify Service **Code Length = 4** if the app expects 4-digit SMS codes — real codes are otherwise 6 digits.

Files: `utils/sendOTP.js`, `modules/auth/controller.js`

---

2. Dispatch (Uber-style Priority)

ADD Multi-wave priority dispatch with immediate-dispatch fallback

Problem: With tiers configured but no operators holding real tier data, every booking still scheduled a delayed first wave (~40s) — customers waited for nothing in the early launch phase.
Fix: If no *meaningful* tier/score data exists among matched operators, skip all delays and notify everyone immediately. Waves resume automatically once real tier data accrues.

Files: `utils/dispatchService.js`, `utils/dispatchWorker.js`

FIX Notify all eligible owners + "missed opportunity" message

- Confirmed all eligible owners are notified when a customer books.
- When one owner accepts, the others get a `request-unavailable` event + a "you missed this one, stay tuned" notification.

Files: `socket/socket.js`, `utils/orderMessages.js`

---

3. Dumpster Matching Consistency

FIX `/api/dumbster/nearby` vs availability check disagreed

Problem: `nearby` showed sizes that could not actually be booked (ignored radius, real capacity, and booking conflicts).
Fix: Centralized matching logic using capacity-aware calculation (`quantity - overlapping bookings`). Removed date filter from `nearby` (dates are chosen on a later screen).

Files: `utils/dustbinMatching.js`, `modules/dumbster/service.js`, `modules/dumbster/controller.js`

FIX Owner accept failed when size matched but catalog ID differed

Problem: Accept compared catalog ObjectIds only, rejecting valid same-size matches (e.g. both 30 Yard, different catalog entry).
Fix: Accept if catalog IDs match *or* normalized yard sizes are equal. Error copy corrected to "Selected dumpster size doesn't match the customer's requested dumpster size."

Files: `socket/socket.js`

---

4. Payments & Ledger

MONEY Add-on fees split correctly (driveway / insurance)

Problem: The 15% admin commission was applied to the entire order total, including the flat add-on fees.
Fix: Insurance ($39) and driveway ($50) protection now go 100% to admin; the 15% commission applies only to the remaining base amount. Backfilled pending orders (incl. `QQadu`).

Files: `utils/paymentHold.js`, `scripts/backfill-order-amount.js`

FLOW Capture on owner-accept (was capturing at completion)

Card is now captured when the owner accepts (matching business intent and avoiding the 7-day Stripe hold expiry). Funds sit on the platform account and transfer to the owner on completion. Rollback restores inventory/status if capture fails.

Files: `socket/socket.js`, `utils/StripePayment.js`

FIX Refunds work for uncaptured holds

Admin cancel now *cancels* uncaptured PaymentIntents and *refunds* captured ones, normalizing success detection.

Files: `utils/StripePayment.js`, `modules/order/service.js`

FIX Ledger accuracy (4 issues)

- Booking debit is now reversed (credit entry) on cancel/expiry.
- Wallet platform commission is explicitly credited to the admin balance + transaction record.
- Assign-order completion now captures the hold and guards against double-settlement.
- Admin-cancel-after-accept refund now writes a matching credit ledger entry for the customer.

Files: `modules/order/service.js`, `socket/socket.js`, `modules/assign_order/service.js`, `utils/orderExpiryWorker.js`

FIX Customer cancel of a pending request rebuilt

Now allowed only while `pending` & `unmatched`; reverses payment, cancels dispatch/expiry jobs, and notifies owners/customer/admin with correct copy.

Files: `modules/order/service.js`

---

5. Notifications & Copy

ADD Real-time notification badge (`new:notification`)

Every new notification is emitted to the recipient's socket room so the app can update the Notifications tab badge instantly.

Files: `utils/notifications.js`

ADD FCM push payload for Android & iOS

Android channel `bins_order_alerts` + `order_alert` sound + high priority; iOS APNs sound/alert; stringified `data.order` / `data.orderId` for tap-navigation. A sample payload is logged in staging for QA.

Files: `utils/notifications.js`

FIX Role-correct notification & email text

- Customer accept notification now says "Order Accepted" (was "provider matched"); customer email no longer contained owner-facing copy.
- Admin cancel-approval no longer told the customer their order was "accepted".
- Email template made role-neutral and driven by the passed title/description.
- Rating email fixed (a duplicate `html` key was overwriting the detailed template).
- "On my way" and "Confirm drop off" are now distinct notifications with different titles/bodies.

Files: `utils/orderMessages.js`, `utils/emailTemplate.js`, `modules/order/service.js`, `modules/assign_order/service.js`, `modules/rating/service.js`

---

6. Order Timeline

FIX Role-specific, clearer timeline text

Problem: Timeline stored one message shown identically to customer and owner, with awkward wording.
Fix: Added `customerMessage` / `operatorMessage` to the timeline model; every event now has role-specific copy read based on who's viewing.

Files: `models/OrderTimeline.js`, `utils/orderMessages.js`, `modules/order/service.js`, `modules/order/controller.js`

FIX "is complete" → "is completed"

Corrected the customer completion timeline line grammar.

Files: `utils/orderMessages.js`

---

7. Live Location Tracking

ADD Unified `location-update` channel + live-location endpoint

- All driver GPS relays go through a single `location-update` event with a consistent payload (`orderId` , `userId` , `currentlat/lng` , `onway` , `status` , origin + dropoff coordinates).
- Added `GET /api/order/:id/live-location` for seed-on-focus + polling.
- Legacy `location-recieved` kept temporarily as a fallback.

Files: `socket/socket.js` , `modules/assign_order/service.js` , `modules/order/service.js` , `modules/order/routes.js`

---

8. Operator Scoring & Tiers

FIX Inaccurate metrics & missing fields

- `NOTIFICATION_RECEIVED` events now logged → real acceptance rate.
- `onTime` tracked on completion → real on-time rate.
- Added `responseRate` ; separated it from response *time*; score returned as a number; `nextTier` resolved even for new operators.

Files: `modules/scoring/scoreEngine.js` , `models/JobEvent.js` , `models/User.js` , `utils/dispatchWorker.js` , `modules/users/service.js`

FIX Score dropped after a completed order + full rating

Problem: Operator score fell 71 → ~61 after a good outcome. Two causes: (1) historical completions had no `onTime` flag so they counted as "late"; (2) the deadline used `end_date` at midnight, flagging same-day completions as late.
Fix: New `isDeliveredOnTime()` helper counts the whole end-date day; both completion sites use it. Backfilled historical events and recomputed scores (operator restored to 71, on-time 100%).

Files: `utils/deliveryTiming.js` , `socket/socket.js` , `modules/order/service.js` , `scripts/backfill-ontime-and-rescore.js`

---

9. Ratings & Reviews

FIX Rating notification went to the rater instead of the ratee

Problem: `user` / `to_id` were swapped, so the in-app notification & real-time badge landed on the person giving the rating.
Fix: Recipient (`to_id`) is now always the person being rated; all channels (in-app, badge, push, email) aligned.

Files: `modules/rating/service.js`

ADD Order-ratings endpoint returns both ratings

`GET /api/rating/order/:orderId` now returns all ratings for the order plus role-labeled fields (`customerRating` , `ownerRating` , `renterRating` , `renteeRating`) so both sides display correctly.

Files: `modules/rating/service.js`

---

10. Partner Services — Tree & Junk Removal

DIAGNOSE "Rejected on admin, pending on app"

Finding: The application's real `status` in the DB was `pending` ; the backend returns the same `status` to both app and admin. The admin panel was *deriving* "rejected" from the per-document approval checkboxes (all `false` on a new application). This is an admin-frontend display issue, not a backend bug.
Recommendation: Admin UI should render the `status` field directly; only treat as rejected when `status === "rejected"` .

DOCS Required vs optional fields

Service	Required	Optional
Tree Removal	companyName, legalBusinessName, sameDayAvailable, location, ownerFullName, drivers_license (≥1), COI, Tree_removal_license, radius (defaults 25)	ein, address, city, state, zip, country, License_Type, License_Number, License_State, License_Expiration, Workers_comp, Certified_arborist, Arborist_credential
Junk Removal	companyName, legalBusinessName, sameDayAvailable, location, ein, ownerFullName	email, address, city, state, zip, country, drivers_license, COI, Business_license, minimum_insurance_amount

Admin/review fields (`status` , `notes` , all `is*Approved` + `*_note` , `userId` , `bookings`) must not be sent by the apply form. On every resubmit the backend forces `status: "pending"` . Note the field-name quirk: junk uses `isCOIAApproved` , tree uses `isCOIApproved` .

---

11. Diagnostic Scripts & Deploy

- `scripts/diagnose-operator-score.js` — dump an operator's stats + job-event breakdown.
- `scripts/backfill-ontime-and-rescore.js` — backfill historical `onTime` and recompute scores (dry-run by default, `--apply` to write).
- `scripts/check-portapotty-source.js` — check whether a user has a verified porta-potty source.
- `scripts/simulate-dropoff.js` — testing helper to advance an order to "confirm drop off" on a simulator (DB-only; does not fire notifications).
- `scripts/backfill-order-amount.js` — recompute order amounts for the payment-split fix.
- `deploy.sh` hardened: correct branch, Redis `otp:*` clear, PM2 restart, post-deploy smoke test.

BinsApp Backend — internal change summary. All items are on the `new_flow_uber` branch and take effect on the next deploy (data backfills already applied to the live DB where noted). Generated automatically from the working session.