



UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
.XX +/-0.010 .XXX +/-0.005
ANGLES +/-0.5 DEG
BREAK SHARP EDGES 0.010 MAX

NOTES:

1. MOLD THE RUN-IN PREFORM ONLY — NOT THE SET OD 8.720 CUP (IN-WELL ENVELOPE).
2. CONTINUOUS 360 DEG RING; 4 PER PLUG (SEAL LANDS, ITEMS 7-10).
3. PARTING LINE MID-THICKNESS TYP; DRAFT 1 DEG MIN; FLASH 0.010 MAX.
4. MECHANICAL GRIP IN CARRIER — NO BOND TO PETAL FACES.
5. POST-MOLD TRIM FLASH; NO MOLD RELEASE IN SEAL ZONE
6. SET CONTACT OD 8.720 AFTER PETAL DEPLOYMENT + MANDREL RAMP COMPRESSION.

SHEX-BP-UHEX-54 HIGH-EXPANSION BRIDGE PLUG
HNBR SEAL LAND LINER PREFORM

DWG NO: DWG-007B-SHP REV A

PART NO: SHEX-004 QTY/PLUG: 4

MATL: HNBR 90 SHORE A

UNITS: INCH PROJECTION: THIRD ANGLE SIZE B

GENERATED FROM cad/release_solids.py PARAMETRIC MODEL