

Documentation Index

Summary

There are 346 gems installed:

[actionpack](#), [actionpack](#), [actionview](#), [actionview](#), [activemodel](#), [activemodel](#), [activerecord](#), [activerecord](#), [activesupport](#), [activesupport](#), [activesupport](#), [addressable](#), [addressable](#), [afm](#), [arel](#), [arel-helpers](#), [arel-helpers](#), [Ascii85](#), [Ascii85](#), [asciidoctor](#), [ast](#), [ast](#), [aws-eventstream](#), [aws-partitions](#), [aws-sdk-core](#), [aws-sdk-ec2](#), [aws-sdk-iam](#), [aws-sdk-kms](#), [aws-sdk-s3](#), [aws-sigv4](#), [backports](#), [bcrypt](#), [bcrypt](#), [bcrypt_pbkdf](#), [bcrypt_pbkdf](#), [benchmark](#), [bigdecimal](#), [bindata](#), [bindata](#), [bit-struct](#), [builder](#), [builder](#), [bundle](#), [bundler](#), [bundler](#), [byebug](#), [cgi](#), [cms_scanner](#), [coderay](#), [coderay](#), [concurrent-ruby](#), [concurrent-ruby](#), [cookiejar](#), [crack](#), [crass](#), [csv](#), [daemons](#), [date](#), [dbm](#), [delegate](#), [did_you_mean](#), [diff-lcs](#), [diff-lcs](#), [dnstruby](#), [dnstruby](#), [docile](#), [docile](#), [ed25519](#), [em-http-request](#), [em-socksify](#), [erubis](#), [etc](#), [ethon](#), [eventmachine](#), [factory_bot](#), [factory_bot rails](#), [factory_girl](#), [factory_girl rails](#), [faker](#), [faraday](#), [faraday](#), [faraday](#), [faye-websocket](#), [fcntl](#), [ffi](#), [ffi](#), [fiddle](#), [filesize](#), [filesize](#), [fileutils](#), [fivemat](#), [fivemat](#), [forwardable](#), [get_process_mem](#), [getoptlong](#), [google-protobuf](#), [googleauth](#), [hashdiff](#), [hashery](#), [hrr_rb_ssh](#), [http_parser.rb](#), [i18n](#), [i18n](#), [i18n](#), [io-console](#), [ipaddr](#), [irb](#), [jaro_winkler](#), [jmespath](#), [jsobfu](#), [json](#), [json](#), [jwt](#), [little-plugger](#), [logger](#), [logging](#), [lolcat](#), [loofah](#), [loofah](#), [manpages](#), [matrix](#), [memoist](#), [memory_profiler](#), [metasm](#), [metasm](#), [metasploit-concern](#), [metasploit-credential](#), [metasploit-credential](#), [metasploit-model](#), [metasploit-payloads](#), [metasploit-payloads](#), [metasploit data models](#), [metasploit data models](#), [metasploit payloads-mettle](#),

[metasploit](#), [payloads-mettle](#), [method source](#), [method source](#), [mini_portile2](#), [mini_portile2](#), [minitest](#), [minitest](#), [minitest](#), [minitest](#), [mqtt](#), [msgpack](#), [msgpack](#), [multi_json](#), [multipart-post](#), [multipart-post](#), [mutex m](#), [nessus rest](#), [net-pop](#), [net-smtp](#), [net-ssh](#), [net-ssh](#), [net-telnet](#), [network interface](#), [nexpose](#), [nexpose](#), [nokogiri](#), [nokogiri](#), [nokogiri](#), [observer](#), [octokit](#), [octokit](#), [open3](#), [openssl](#), [openssl-ccm](#), [openssl-ccm](#), [openvas-omp](#), [opt_parse validator](#), [optimist](#), [os](#), [ostruct](#), [packetfu](#), [paint](#), [parallel](#), [parallel](#), [parser](#), [parser](#), [patch finder](#), [pcaprub](#), [pcaprub](#), [pdf-reader](#), [pdf-reader](#), [pg](#), [pg](#), [pg_array_parser](#), [postgres_ext](#), [postgres_ext](#), [power assert](#), [prime](#), [pry](#), [pry](#), [pry-byebug](#), [pstore](#), [psych](#), [public suffix](#), [public suffix](#), [public suffix](#), [racc](#), [rack](#), [rack](#), [rack-protection](#), [rack-test](#), [rails-deprecated sanitizer](#), [rails-dom-testing](#), [rails-dom-testing](#), [rails-html-sanitizer](#), [rails-html-sanitizer](#), [railties](#), [railties](#), [rainbow](#), [rake](#), [rake](#), [rb-readline](#), [rdoc](#), [readline](#), [readline-ext](#), [recog](#), [recog](#), [redcarpet](#), [redcarpet](#), [regexp_parser](#), [reline](#), [rex-arch](#), [rex-arch](#), [rex-bin tools](#), [rex-bin tools](#), [rex-core](#), [rex-core](#), [rex-encoder](#), [rex-exploitation](#), [rex-exploitation](#), [rex-java](#), [rex-mime](#), [rex-nop](#), [rex-ole](#), [rex-powershell](#), [rex-powershell](#), [rex-random identifier](#), [rex-random identifier](#), [rex-registry](#), [rex-rop builder](#), [rex-socket](#), [rex-socket](#), [rex-sslsan](#), [rex-struct2](#), [rex-text](#), [rex-text](#), [rex-zip](#), [rexml](#), [rexml](#), [rkelly-remix](#), [rspec](#), [rspec](#), [rspec](#), [rspec-core](#), [rspec-core](#), [rspec-core](#), [rspec-core](#), [rspec-expectations](#), [rspec-expectations](#), [rspec-expectations](#), [rspec-expectations](#), [rspec-its](#), [rspec-mocks](#), [rspec-mocks](#), [rspec-mocks](#), [rspec-mocks](#), [rspec-rails](#), [rspec-rails](#), [rspec-rerun](#), [rspec-support](#), [rspec-support](#), [rspec-support](#), [rspec-support](#), [rss](#), [rubocop](#), [rubocop](#), [rubocop-ast](#), [rubocop-performance](#), [ruby-macho](#), [ruby-prof](#), [ruby-progressbar](#), [ruby-rc4](#), [ruby_smb](#), [ruby_smb](#), [rubygems](#), [rubygems-update](#), [rubyntlm](#), [rubyzip](#), [rubyzip](#), [sawyer](#), [sawyer](#), [sdbm](#), [signet](#), [simplecov](#), [simplecov](#), [simplecov](#), [simplecov-html](#), [simplecov-html](#), [simplecov-html](#), [simplecov-html](#), [simplecov-lcov](#), [sinatra](#), [singleton](#), [slop](#), [sqlite3](#), [sshkey](#), [sshkey](#), [stackprof](#), [stringio](#), [strscan](#), [swagger-blocks](#), [sys-proctable](#), [test-unit](#), [thin](#), [thor](#), [thor](#), [thread safe](#), [tilt](#), [timecop](#), [timeout](#), [tracer](#), [ttfunk](#), [ttfunk](#), [typhoeus](#), [tzinfo](#), [tzinfo](#), [tzinfo](#), [tzinfo](#)

[data](#), [tzinfo-data](#), [unicode-display_width](#), [unicode-display_width](#), [uri](#), [warden](#), [webmock](#), [webrick](#), [websocket-driver](#), [websocket-extensions](#), [windows_error](#), [xdr](#), [xmlrpc](#), [xmlrpc](#), [yajl-ruby](#), [yaml](#), [yard](#), [yard](#), [zeitwerk](#), [zlib](#).

Gems

actionpack 4.2.11.1 [rdoc] [\[www\]](#) - depends on [actionview](#), [activemodel](#), [activesupport](#), [rack](#), [rack-test](#), [rails-dom-testing](#), [rails-html-sanitizer](#).

Web-flow and rendering framework putting the VC in MVC (part of Rails).

actionpack 4.2.9 [rdoc] [\[www\]](#) - depends on [actionview](#), [activemodel](#), [activesupport](#), [rack](#), [rack-test](#), [rails-dom-testing](#), [rails-html-sanitizer](#).

Web-flow and rendering framework putting the VC in MVC (part of Rails).

actionview 4.2.11.1 [rdoc] [\[www\]](#) - depends on [actionpack](#), [activemodel](#), [activesupport](#), [builder](#), [erubis](#), [rails-dom-testing](#), [rails-html-sanitizer](#).

Rendering framework putting the V in MVC (part of Rails).

actionview 4.2.9 [rdoc] [\[www\]](#) - depends on [actionpack](#), [activemodel](#), [activesupport](#), [builder](#), [erubis](#), [rails-dom-testing](#), [rails-html-sanitizer](#).

Rendering framework putting the V in MVC (part of Rails).

activemodel 4.2.11.1 [rdoc] [\[www\]](#) - depends on [activesupport](#), [builder](#).

A toolkit for building modeling frameworks (part of Rails).

activemodel 4.2.9 [rdoc] [[www](#)] - depends on [activesupport](#), [builder](#).

A toolkit for building modeling frameworks (part of Rails).

activerecord 4.2.11.1 [rdoc] [[www](#)] - depends on [activemodel](#), [activesupport](#), [arel](#).

Object-relational mapper framework (part of Rails).

activerecord 4.2.9 [rdoc] [[www](#)] - depends on [activemodel](#), [activesupport](#), [arel](#).

Object-relational mapper framework (part of Rails).

activesupport 4.2.11.1 [rdoc] [[www](#)] - depends on [i18n](#), [minitest](#), [thread_safe](#), [tzinfo](#).

A toolkit of support libraries and Ruby core extensions extracted from the Rails framework.

activesupport 4.2.9 [rdoc] [[www](#)] - depends on [i18n](#), [minitest](#), [thread_safe](#), [tzinfo](#).

A toolkit of support libraries and Ruby core extensions extracted from the Rails framework.

activesupport 6.0.3.4 [rdoc] [[www](#)] - depends on [concurrent-ruby](#), [i18n](#), [minitest](#), [tzinfo](#), [zeitwerk](#).

A toolkit of support libraries and Ruby core extensions extracted from the Rails framework.

addressable 2.5.2 [rdoc] [[www](#)] - depends on [bundler](#), [public_suffix](#).

URI Implementation

addressable 2.7.0 [rdoc] [[www](#)] - depends on [bundler](#), [public_suffix](#).

URI Implementation

afm 0.2.2 [rdoc] [[www](#)] - depends on [minitest](#), [rake](#), [rdoc](#).

reading Adobe Font Metrics (afm) files

arel 6.0.4 [rdoc] [[www](#)] - depends on [minitest](#), [rake](#), [rdoc](#).
Arel Really Exasperates Logicians Arel is a SQL AST manager for Ruby

arel-helpers 2.11.0 [rdoc] [[www](#)] - depends on [activerecord](#), [rake](#), [rr](#), [rspec](#).

Useful tools to help construct database queries with ActiveRecord and Arel.

arel-helpers 2.4.0 [rdoc] [[www](#)] - depends on [activerecord](#).
Useful tools to help construct database queries with ActiveRecord and Arel.

Ascii85 1.0.2 [rdoc] [[www](#)] - depends on [bundler](#), [minitest](#), [rake](#).

Ascii85 encoder/decoder
Executable is ascii85.

Ascii85 1.0.3 [rdoc] [[www](#)] - depends on [bundler](#), [minitest](#), [rake](#).

Ascii85 encoder/decoder
Executable is ascii85.

asciidocctor 2.0.12 [rdoc] [[www](#)] - depends on [asciimath](#), [coderay](#), [concurrent-ruby](#), [cucumber](#), [erubi](#), [haml](#), [minitest](#), [nokogiri](#), [rake](#), [rouge](#), [rspec-expectations](#), [slim](#), [tilt](#).

An implementation of the AsciiDoc text processor and publishing toolchain
Executable is asciidoctor.

ast 2.4.0 [rdoc] [[www](#)] - depends on [bacon](#), [bacon-colored_output](#), [coveralls](#), [json_pure](#), [kramdown](#), [mime-types](#), [rake](#), [rest-client](#), [simplecov](#), [yard](#).

A library for working with Abstract Syntax Trees.

ast 2.4.1 [rdoc] [[www](#)] - depends on [bacon](#), [bacon-colored_output](#), [coveralls](#), [kramdown](#), [rake](#), [simplecov](#), [yard](#).
A library for working with Abstract Syntax Trees.

aws-eventstream 1.0.3 [rdoc] [[www](#)]
AWS Event Stream Library

aws-partitions 1.288.0 [rdoc] [[www](#)]
Provides information about AWS partitions, regions, and services.

aws-sdk-core 3.92.0 [rdoc] [[www](#)] - depends on [aws-eventstream](#), [aws-partitions](#), [aws-sigv4](#), [jmespath](#).
AWS SDK for Ruby - Core

aws-sdk-ec2 1.151.0 [rdoc] [[www](#)] - depends on [aws-sdk-core](#), [aws-sigv4](#).
AWS SDK for Ruby - Amazon EC2

aws-sdk-iam 1.34.0 [rdoc] [[www](#)] - depends on [aws-sdk-core](#), [aws-sigv4](#).
AWS SDK for Ruby - IAM

aws-sdk-kms 1.30.0 [rdoc] [[www](#)] - depends on [aws-sdk-core](#), [aws-sigv4](#).
AWS SDK for Ruby - KMS

aws-sdk-s3 1.61.1 [rdoc] [[www](#)] - depends on [aws-sdk-core](#), [aws-sdk-kms](#), [aws-sigv4](#).
AWS SDK for Ruby - Amazon S3

aws-sigv4 1.1.1 [rdoc] [[www](#)] - depends on [aws-eventstream](#).
AWS Signature Version 4 library.

backports 3.8.0 [rdoc] [[www](#)]
Backports of Ruby features for older Ruby.

bcrypt 3.1.11 [rdoc] [[www](#)] - depends on [rake-compiler](#), [rdoc](#), [rspec](#).

OpenBSD's bcrypt() password hashing algorithm.

bcrypt 3.1.12 [rdoc] [[www](#)] - depends on [rake-compiler](#), [rdoc](#), [rspec](#).

OpenBSD's bcrypt() password hashing algorithm.

bcrypt_pbkdf 1.0.0 [rdoc] [[www](#)] - depends on [minitest](#), [rake-compiler](#), [rake-compiler-dock](#), [rbnac](#), [rbnacl-libsodium](#), [rdoc](#).

OpenBSD's bcrypt_pdkfd (a variant of PBKDF2 with bcrypt-based PRF)

bcrypt_pbkdf 1.0.1 [rdoc] [[www](#)] - depends on [minitest](#), [openssl](#), [rake-compiler](#), [rake-compiler-dock](#), [rdoc](#).

OpenBSD's bcrypt_pdkfd (a variant of PBKDF2 with bcrypt-based PRF)

benchmark 0.1.0 [rdoc] [[www](#)]

a performance benchmarking library

bigdecimal 2.0.0 [rdoc] [[www](#)] - depends on [minitest](#), [pry](#), [rake](#), [rake-compiler](#).

Arbitrary-precision decimal floating-point number library.

bindata 2.4.0 [rdoc] [[www](#)] - depends on [coveralls](#), [minitest](#), [rake](#).

A declarative way to read and write binary file formats

bindata 2.4.6 [rdoc] [[www](#)] - depends on [coveralls](#), [minitest](#), [rake](#).

A declarative way to read and write binary file formats

bit-struct 0.16 [rdoc] [[www](#)]

Library for packed binary data stored in ruby Strings

builder 3.2.3 [rdoc] [[www](#)]

Builders for MarkUp.

builder 3.2.4 [rdoc] [[www](#)]

Builders for MarkUp.

bundle 0.0.1 [rdoc] [[www](#)] - depends on [bundler](#).
s/bundle/bundler

bundler 1.17.3 [rdoc] [[www](#)] - depends on [automatiek](#),
[mustache](#), [rake](#), [rdiscount](#), [ronn](#), [rspec](#).

The best way to manage your application's
dependencies

Executables are bundle, bundler.

bundler 2.1.4 [rdoc] [[www](#)]

The best way to manage your application's
dependencies

Executables are bundle, bundler.

byebug 11.1.1 [rdoc] [[www](#)] - depends on [bundler](#).

Ruby fast debugger - base + CLI

Executable is byebug.

cgi 0.1.0 [rdoc] [[www](#)]

Support for the Common Gateway Interface protocol.

cms_scanner 0.12.1 [rdoc] [[www](#)] - depends on [bundler](#),
[get_process_mem](#), [nokogiri](#), [opt_parse_validator](#),
[public_suffix](#), [rake](#), [rspec](#), [rspec-its](#), [rubocop](#), [rubocop-](#)
[performance](#), [ruby-progressbar](#), [simplecov](#), [simplecov-lcov](#),
[sys-proctable](#), [typhoeus](#), [webmock](#), [xmlrpc](#), [yajl-ruby](#).

CMS Scanner Framework (experimental)

coderay 1.1.1 [rdoc] [[www](#)]

Fast syntax highlighting for selected languages.
Executable is coderay.

coderay 1.1.2 [rdoc] [[www](#)]

Fast syntax highlighting for selected languages.
Executable is coderay.

concurrent-ruby 1.0.5 [rdoc] [[www](#)]

Modern concurrency tools for Ruby. Inspired by Erlang, Clojure, Scala, Haskell, F#, C#, Java, and classic concurrency patterns.

concurrent-ruby 1.1.7 [rdoc] [[www](#)]

Modern concurrency tools for Ruby. Inspired by Erlang, Clojure, Scala, Haskell, F#, C#, Java, and classic concurrency patterns.

cookiejar 0.3.3 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#), [rspec-collection_matchers](#), [yard](#).

Client-side HTTP Cookie library

crack 0.4.4 [rdoc] [[www](#)]

Really simple JSON and XML parsing, ripped from Merb and Rails.

crass 1.0.6 [rdoc] [[www](#)] - depends on [minitest](#), [rake](#).

CSS parser based on the CSS Syntax Level 3 spec.

csv 3.1.2 [rdoc] [[www](#)] - depends on [benchmark_driver](#), [bundler](#), [rake](#), [simplecov](#).

CSV Reading and Writing

daemons 1.3.1 [rdoc] [[www](#)] - depends on [pry-bybug](#), [rake](#), [rspec](#), [simplecov](#).

A toolkit to create and control daemons in different ways

date 3.0.0 [rdoc] [[www](#)]

A subclass of Object includes Comparable module for handling dates.

dbm 1.1.0 [rdoc] [[www](#)] - depends on [rake-compiler](#), [test-unit](#).

Provides a wrapper for the UNIX-style Database Manager Library

delegate 0.1.0 [rdoc] [[www](#)]

Provides three abilities to delegate method calls to an object.

did_you_mean 1.4.0 [rdoc] [[www](#)] - depends on [rake](#).

"Did you mean?" experience in Ruby

diff-lcs 1.3 [rdoc] [[www](#)] - depends on [hoe](#), [hoe-doofus](#), [hoe-gemspec2](#), [hoe-git](#), [hoe-rubygems](#), [hoe-travis](#), [rake](#), [rdoc](#), [rspec](#).

Diff::LCS computes the difference between two Enumerable sequences using the McIlroy-Hunt longest common subsequence (LCS) algorithm
Executables are `htmldiff`, `ldiff`.

diff-lcs 1.4.4 [rdoc] [[www](#)] - depends on [hoe](#), [hoe-doofus](#), [hoe-gemspec2](#), [hoe-git](#), [hoe-rubygems](#), [rake](#), [rdoc](#), [rspec](#).

Diff::LCS computes the difference between two Enumerable sequences using the McIlroy-Hunt longest common subsequence (LCS) algorithm
Executables are `htmldiff`, `ldiff`.

dnstruby 1.60.2 [rdoc] [[www](#)] - depends on [coveralls](#), [minitest](#), [minitest-display](#), [nio4r](#), [pry](#), [pry-byebug](#), [rake](#), [rubydns](#).

Ruby DNS(SEC) implementation

dnstruby 1.61.3 [rdoc] [[www](#)] - depends on [addressable](#), [coveralls](#), [minitest](#), [minitest-display](#), [nio4r](#), [pry](#), [pry-bybug](#), [rake](#), [rubydns](#).

Ruby DNS(SEC) implementation

docile 1.1.5 [rdoc] [[www](#)] - depends on [coveralls](#), [github-markup](#), [rake](#), [redcarpet](#), [rspec](#), [yard](#).

Docile keeps your Ruby DSLs tame and well-behaved

docile 1.3.2 [rdoc] [[www](#)] - depends on [github-markup](#), [rake](#), [redcarpet](#), [rspec](#), [rspec-expectations](#), [yard](#).

Docile keeps your Ruby DSLs tame and well-behaved.

ed25519 1.2.4 [rdoc] [[www](#)] - depends on [bundler](#).

An efficient digital signature library providing the Ed25519 algorithm

em-http-request 1.1.5 [rdoc] [[www](#)] - depends on [addressable](#), [cookiejar](#), [em-socksify](#), [eventmachine](#), [http_parser.rb](#), [mongrel](#), [multi_json](#), [rack](#), [rake](#), [rspec](#).

EventMachine based, async HTTP Request client

em-socksify 0.3.2 [rdoc] [[www](#)] - depends on [eventmachine](#), [rake](#), [rspec](#).

Transparent proxy support for any EventMachine protocol

erubis 2.7.0 [rdoc] [[www](#)]

a fast and extensible eRuby implementation which supports multi-language

Executable is erubis.

etc 1.1.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rake-compiler](#), [test-unit](#).

Provides access to information typically stored in UNIX /etc directory.

ethon 0.12.0 [rdoc] [[www](#)] - depends on [ffi](#).
Libcurl wrapper.

eventmachine 1.2.7 [rdoc] [[www](#)] - depends on [rake-compiler](#), [rake-compiler-dock](#), [test-unit](#).
Ruby/EventMachine library

factory_bot 5.1.2 [rdoc] [[www](#)] - depends on [activerecord](#), [activesupport](#), [appraisal](#), [aruba](#), [cucumber](#), [rake](#), [rspec](#), [rspec-its](#), [rubocop](#), [rubocop-performance](#), [rubocop-rails](#), [simplecov](#), [yard](#).
factory_bot provides a framework and DSL for defining and using model instance factories.

factory_bot_rails 5.1.1 [rdoc] [[www](#)] - depends on [factory_bot](#), [railties](#).
factory_bot_rails provides integration between factory_bot and rails 4.2 or newer

factory_girl 4.8.0 [rdoc] [[www](#)] - depends on [activerecord](#), [activesupport](#), [appraisal](#), [aruba](#), [bourne](#), [cucumber](#), [mocha](#), [rspec](#), [rspec-its](#), [simplecov](#), [timecop](#), [yard](#).
factory_girl provides a framework and DSL for defining and using model instance factories.

factory_girl_rails 4.8.0 [rdoc] [[www](#)] - depends on [factory_girl](#), [railties](#).
factory_girl_rails provides integration between factory_girl and rails 3 or newer

faker 2.2.1 [rdoc] [[www](#)] - depends on [i18n](#), [minitest](#), [pry](#), [rake](#), [rubocop](#), [simplecov](#), [test-unit](#), [timecop](#).
Easily generate fake data
Executable is faker.

faraday 0.13.1 [rdoc] [[www](#)] - depends on [multipart-post](#).

HTTP/REST API client library.

faraday 0.17.3 [rdoc] [[www](#)] - depends on [multipart-post](#).
HTTP/REST API client library.

faraday 1.0.0 [rdoc] [[www](#)] - depends on [multipart-post](#).
HTTP/REST API client library.

faye-websocket 0.10.9 [rdoc] [[www](#)] - depends on
[eventmachine](#), [goliath](#), [passenger](#), [permessage_deflate](#),
[progressbar](#), [puma](#), [rack](#), [rainbows](#), [rspec](#), [rspec-](#)
[eventmachine](#), [thin](#), [websocket-driver](#).

Standards-compliant WebSocket server and client

fcntl 1.0.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rake-](#)
[compiler](#).

Loads constants defined in the OS fcntl.h C header file

ffi 1.13.1 [rdoc] [[www](#)] - depends on [rake](#), [rake-compiler](#),
[rake-compiler-dock](#), [rspec](#), [rubygems-tasks](#).

Ruby FFI

ffi 1.9.18 [rdoc] [[www](#)] - depends on [rake](#), [rake-compiler](#),
[rake-compiler-dock](#), [rspec](#), [rubygems-tasks](#).

Ruby FFI

fiddle 1.0.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rake-](#)
[compiler](#).

A libffi wrapper for Ruby.

filesize 0.1.1 [rdoc] [[www](#)] - depends on [rspec](#).

filesize is a small class for handling file sizes with both
the SI and binary prefixes, allowing conversion from
any size to any other size.

filesize 0.2.0 [rdoc] [[www](#)] - depends on [rspec](#).

filesize is a small class for handling file sizes with both the SI and binary prefixes, allowing conversion from any size to any other size.

fileutils 1.4.1 [rdoc] [[www](#)]

Several file utility methods for copying, moving, removing, etc.

fivemat 1.3.5 [rdoc] [[www](#)]

Why settle for a test output format when you could have a test output fivemat?

fivemat 1.3.7 [rdoc] [[www](#)] - depends on [rake](#).

Why settle for a test output format when you could have a test output fivemat?

forwardable 1.3.1 [rdoc] [[www](#)]

Provides delegation of specified methods to a designated object.

get_process_mem 0.2.7 [rdoc] [[www](#)] - depends on [ffi](#), [rake](#), [sys-proctable](#), [test-unit](#).

Use GetProcessMem to find out the amount of RAM used by any process

getoptlong 0.1.0 [rdoc] [[www](#)]

GetoptLong for Ruby

google-protobuf 3.14.0 [rdoc] [[www](#)] - depends on [rake-compiler](#), [rake-compiler-dock](#), [rubygems-tasks](#), [test-unit](#).

Protocol Buffers

googleauth 0.5.3 [rdoc] [[www](#)] - depends on [faraday](#), [jwt](#), [logging](#), [memoist](#), [multi_json](#), [os](#), [signet](#).

Google Auth Library for Ruby

hashdiff 1.0.1 [rdoc] [[www](#)] - depends on [bluecloth](#), [rspec](#), [rubocop](#), [rubocop-rspec](#), [yard](#).

Hashdiff is a diff lib to compute the smallest difference between two hashes.

hashery 2.1.2 [rdoc] [[www](#)] - depends on [lemon](#), [ged](#), [rubytest-cli](#).

Facets-bread collection of Hash-like classes.

hrr_rb_ssh 0.3.0.pre2 [rdoc] [[www](#)] - depends on [ed25519](#), [rake](#), [rspec](#), [simplecov](#).

Pure Ruby SSH 2.0 server implementation

http_parser.rb 0.6.0 [rdoc] [[www](#)] - depends on [benchmark_suite](#), [ffi](#), [json](#), [rake-compiler](#), [rspec](#), [yajl-ruby](#).

Simple callback-based HTTP request/response parser

i18n 0.8.6 [rdoc] [[www](#)]

New wave Internationalization support for Ruby

i18n 0.9.5 [rdoc] [[www](#)] - depends on [concurrent-ruby](#).

New wave Internationalization support for Ruby

i18n 1.8.5 [rdoc] [[www](#)] - depends on [concurrent-ruby](#).

New wave Internationalization support for Ruby

io-console 0.5.6 [rdoc] [[www](#)]

Console interface

ipaddr 1.2.2 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [test-unit](#).

A class to manipulate an IP address in ruby

irb 1.2.6 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [reline](#).

Interactive Ruby command-line tool for REPL (Read Eval Print Loop).

Executable is irb.

jaro_winkler 1.5.4 [rdoc] [[www](#)] - depends on [bundler](#), [minitest](#), [rake](#), [rake-compiler](#).

An implementation of Jaro-Winkler distance algorithm written \ in C extension which supports any kind of string encoding.

jmespath 1.4.0 [rdoc] [[www](#)]
JMESPath - Ruby Edition

jsobfu 0.4.2 [rdoc] [[www](#)] - depends on [execjs](#), [rake](#), [rkelly-remix](#), [rspec](#), [simplecov](#), [yard](#).

A Javascript code obfuscator
Executable is jsobfu.

json 2.1.0 [rdoc] [[www](#)] - depends on [rake](#), [test-unit](#).
JSON Implementation for Ruby

json 2.3.0 [rdoc] [[www](#)] - depends on [rake](#), [test-unit](#).
JSON Implementation for Ruby

jwt 1.5.6 [rdoc] [[www](#)] - depends on [bundler](#), [codeclimate-test-reporter](#), [json](#), [rake](#), [rspec](#), [simplecov](#), [simplecov-json](#).
JSON Web Token implementation in Ruby

little-plugger 1.1.4 [rdoc] [[www](#)] - depends on [rspec](#).
LittlePlugger is a module that provides Gem based plugin management.

logger 1.4.2 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rdoc](#), [test-unit](#).
Provides a simple logging utility for outputting messages.

logging 2.3.0 [rdoc] [[www](#)] - depends on [bones](#), [bones-git](#), [little-plugger](#), [multi_json](#), [test-unit](#).

A flexible and extendable logging library for Ruby

lolcat 100.0.1 [[rdoc](#)] [[www](#)] - depends on [manpages](#), [optimist](#), [paint](#), [rake](#).

Okay, no unicorns. But rainbows!!
Executable is lolcat.

loofah 2.0.3 [[rdoc](#)] [[www](#)] - depends on [hoe](#), [hoe-bundler](#), [hoe-debugging](#), [hoe-gemspec](#), [hoe-git](#), [json](#), [minitest](#), [nokogiri](#), [rake](#), [rdoc](#), [rr](#).

Loofah is a general library for manipulating and transforming HTML/XML documents and fragments

loofah 2.4.0 [[rdoc](#)] [[www](#)] - depends on [concourse](#), [crass](#), [hoe](#), [hoe-bundler](#), [hoe-debugging](#), [hoe-gemspec](#), [hoe-git](#), [json](#), [minitest](#), [nokogiri](#), [rake](#), [rdoc](#), [rr](#), [rubocop](#).

Loofah is a general library for manipulating and transforming HTML/XML documents and fragments, built on top of Nokogiri

manpages 0.6.1 [[rdoc](#)] [[www](#)] - depends on [bundler](#), [pry](#), [rake](#), [rspec](#), [rubocop](#).

Adds support for man pages to rubygems

matrix 0.2.0 [[rdoc](#)] [[www](#)] - depends on [bundler](#), [rake](#).

An implementation of Matrix and Vector classes.

memoist 0.16.2 [[rdoc](#)] [[www](#)] - depends on [benchmark-ips](#), [bundler](#), [minitest](#), [rake](#).

memoize methods invocation

memory_profiler 0.9.14 [[rdoc](#)] [[www](#)]

Memory profiling routines for Ruby 2.3+

metasm 1.0.3 [[rdoc](#)] [[www](#)] - depends on [bundler](#), [rake](#).

Metasm is a cross-architecture assembler, disassembler, linker, and debugger.

metasm 1.0.4 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [test-unit](#).

Metasm is a cross-architecture assembler, disassembler, linker, and debugger.

metasploit-concern 2.0.5 [rdoc] [[www](#)] - depends on [activemodel](#), [activesupport](#), [metasploit-erd](#), [metasploit-yard](#), [railties](#).

Automatically include Modules from app/concerns

metasploit-credential 2.0.12 [rdoc] [[www](#)] - depends on [metasploit-concern](#), [metasploit-model](#), [metasploit data models](#), [pg](#), [railties](#), [rex-socket](#), [rubyntlm](#), [rubyzip](#).

Credential models for metasploit-framework and Metasploit Pro

metasploit-credential 3.0.4 [rdoc] [[www](#)] - depends on [metasploit-concern](#), [metasploit-model](#), [metasploit data models](#), [net-ssh](#), [pg](#), [railties](#), [rex-socket](#), [rubyntlm](#), [rubyzip](#).

Credential models for metasploit-framework and Metasploit Pro

metasploit-model 2.0.4 [rdoc] [[www](#)] - depends on [activemodel](#), [activesupport](#), [bundler](#), [metasploit-erd](#), [metasploit-yard](#), [railties](#), [rake](#), [redcarpet](#), [yard](#).

Metasploit Model Mixins and Validators

metasploit-payloads 1.3.1 [rdoc] [[www](#)] - depends on [bundler](#), [gem-release](#), [rake](#).

This gem contains the compiled binaries required to make Meterpreter function, and eventually other payloads that require compiled binaries.

metasploit-payloads 1.3.86 [rdoc] [[www](#)] - depends on [bundler](#), [gem-release](#), [rake](#).

This gem contains the compiled binaries required to make Meterpreter function, and eventually other payloads that require compiled binaries.

metasploit_data_models 2.0.15 [rdoc] [[www](#)] - depends on [activerecord](#), [activesupport](#), [arel-helpers](#), [metasploit-concern](#), [metasploit-model](#), [metasploit-yard](#), [pg](#), [postgres_ext_pry](#), [railties](#), [rake](#), [recog](#), [redcarpet](#), [yard](#), [yard-activerecord](#), [yard-metasploit-erd](#).

Database code for MSF and Metasploit Pro
Executable is `mdm_console`.

metasploit_data_models 3.0.10 [rdoc] [[www](#)] - depends on [activerecord](#), [activesupport](#), [arel-helpers](#), [metasploit-concern](#), [metasploit-model](#), [metasploit-yard](#), [pg](#), [postgres_ext_pry](#), [railties](#), [rake](#), [recog](#), [redcarpet](#), [yard](#), [yard-activerecord](#), [yard-metasploit-erd](#).

Database code for MSF and Metasploit Pro
Executable is `mdm_console`.

metasploit_payloads-mettle 0.2.2 [rdoc] [[www](#)] - depends on [bundler](#), [gem-release](#), [rake](#).

This gem contains the compiled binaries required to make Mettle function, and eventually their stages and stagers

metasploit_payloads-mettle 0.5.21 [rdoc] [[www](#)] - depends on [bundler](#), [gem-release](#), [rake](#).

This gem contains the compiled binaries required to make Mettle function, and eventually their stages and stagers

method_source 0.8.2 [rdoc] [[www](#)] - depends on [bacon](#), [rake](#).

retrieve the sourcecode for a method

method_source 1.0.0 [rdoc] [[www](#)] - depends on [rake](#), [rspec](#).
retrieve the sourcecode for a method

mini_portile2 2.2.0 [rdoc] [[www](#)] - depends on [bundler](#),
[concourse](#), [minitar](#), [minitest](#), [minitest-hooks](#), [rake](#).
Simplistic port-like solution for developers

mini_portile2 2.4.0 [rdoc] [[www](#)] - depends on [bundler](#),
[concourse](#), [minitar](#), [minitest](#), [minitest-hooks](#), [rake](#).
Simplistic port-like solution for developers

minitest 5.10.3 [rdoc] [[www](#)] - depends on [hoe](#), [rdoc](#).
minitest provides a complete suite of testing facilities
supporting TDD, BDD, mocking, and benchmarking

minitest 5.13.0 [rdoc] [[www](#)] - depends on [hoe](#), [rdoc](#).
minitest provides a complete suite of testing facilities
supporting TDD, BDD, mocking, and benchmarking

minitest 5.14.0 [rdoc] [[www](#)] - depends on [hoe](#), [rdoc](#).
minitest provides a complete suite of testing facilities
supporting TDD, BDD, mocking, and benchmarking

minitest 5.14.2 [rdoc] [[www](#)] - depends on [hoe](#), [rdoc](#).
minitest provides a complete suite of testing facilities
supporting TDD, BDD, mocking, and benchmarking

mqtt 0.5.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#),
[simplecov](#), [yard](#).
Implementation of the MQTT protocol

msgpack 1.1.0 [rdoc] [[www](#)] - depends on [bundler](#), [json](#),
[rake](#), [rake-compiler](#), [rake-compiler-dock](#), [rspec](#), [yard](#).
MessagePack, a binary-based efficient data interchange
format.

msgpack 1.3.3 [rdoc] [[www](#)] - depends on [bundler](#), [json](#), [rake](#), [rake-compiler](#), [rake-compiler-dock](#), [rspec](#), [yard](#).

MessagePack, a binary-based efficient data interchange format.

multi_json 1.15.0 [rdoc] [[www](#)] - depends on [rake](#), [rspec](#).

A common interface to multiple JSON libraries.

multipart-post 2.0.0 [rdoc] [[www](#)]

A multipart form post accessory for Net::HTTP.

multipart-post 2.1.1 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#).

A multipart form post accessory for Net::HTTP.

mutex_m 0.1.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [test-unit](#).

Mixin to extend objects to be handled like a Mutex.

nessus_rest 0.1.6 [rdoc] [[www](#)] - depends on [bundler](#), [pry](#), [rake](#), [yard](#).

Communicate with Nessus Scanner (version 6+) over REST/JSON interface

net-pop 0.1.0 [rdoc] [[www](#)]

Ruby client library for POP3.

net-smtp 0.1.0 [rdoc] [[www](#)]

Simple Mail Transfer Protocol client library for Ruby.

net-ssh 4.1.0 [rdoc] [[www](#)] - depends on [bundler](#), [minitest](#), [mocha](#), [rake](#), [rbnacl](#), [rbnacl-libsodium](#), [rubocop](#).

Net::SSH: a pure-Ruby implementation of the SSH2 client protocol.

net-ssh 5.2.0 [rdoc] [[www](#)] - depends on [bcrypt_pbkdf](#), [bundler](#), [ed25519](#), [minitest](#), [mocha](#), [rake](#), [rubocop](#).
Net::SSH: a pure-Ruby implementation of the SSH2 client protocol.

net-telnet 0.2.0 [rdoc] [[www](#)] - depends on [bundler](#), [minitest](#), [mspec](#), [rake](#).
Provides telnet client functionality.

network_interface 0.0.2 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rake-compiler](#), [rspec](#).
A cross platform gem to help get network interface information
Executable is list_interfaces.rb.

nexpose 6.1.1 [rdoc] [[www](#)] - depends on [bundler](#), [codeclimate-test-reporter](#), [rake](#), [rspec](#), [rubocop](#), [simplecov](#), [vcr](#), [webmock](#).
Ruby API for Rapid7 Nexpose

nexpose 7.2.1 [rdoc] [[www](#)] - depends on [bundler](#), [codeclimate-test-reporter](#), [github_changelog_generator](#), [pry](#), [rake](#), [rspec](#), [rubocop](#), [simplecov](#), [vcr](#), [webmock](#).
Ruby API for Rapid7 Nexpose

nokogiri 1.10.10 [rdoc] [[www](#)] - depends on [concourse](#), [hoe](#), [hoe-bundler](#), [hoe-debugging](#), [hoe-gemspec](#), [hoe-git](#), [mini_portile2](#), [minitest](#), [racc](#), [rake](#), [rake-compiler](#), [rake-compiler-dock](#), [rdoc](#), [rexical](#), [rubocop](#), [simplecov](#).
Nokogiri (éç) is an HTML, XML, SAX, and Reader parser
Executable is nokogiri.

nokogiri 1.10.9 [rdoc] [[www](#)] - depends on [concourse](#), [hoe](#), [hoe-bundler](#), [hoe-debugging](#), [hoe-gemspec](#), [hoe-git](#), [mini_portile2](#), [minitest](#), [racc](#), [rake](#), [rake-compiler](#), [rake-compiler-dock](#), [rdoc](#), [rexical](#), [rubocop](#), [simplecov](#).

Nokogiri (é) is an HTML, XML, SAX, and Reader parser
Executable is nokogiri.

nokogiri 1.8.0 [rdoc] [\[www\]](#) - depends on [concourse](#), [hoe](#), [hoe-bundler](#), [hoe-debugging](#), [hoe-gemspec](#), [hoe-git](#), [mini_portile2](#), [minitest](#), [racc](#), [rake](#), [rake-compiler](#), [rake-compiler-dock](#), [rdoc](#), [rexical](#).

Nokogiri (é) is an HTML, XML, SAX, and Reader parser
Executable is nokogiri.

observer 0.1.0 [rdoc] [\[www\]](#)

Implementation of the Observer object-oriented design
pattern.

octokit 4.18.0 [rdoc] [\[www\]](#) - depends on [bundler](#), [faraday](#), [sawyer](#).

Ruby toolkit for working with the GitHub API

octokit 4.7.0 [rdoc] [\[www\]](#) - depends on [bundler](#), [sawyer](#).

Ruby toolkit for working with the GitHub API

open3 0.1.0 [rdoc] [\[www\]](#)

Popen, but with stderr, too

openssl 2.1.2 [rdoc] [\[www\]](#) - depends on [ipaddr](#), [rake](#), [rake-compiler](#), [rdoc](#), [test-unit](#).

OpenSSL provides SSL, TLS and general purpose
cryptography.

openssl-ccm 1.2.1 [rdoc] [\[www\]](#) - depends on [coveralls](#), [rake](#), [rdoc](#), [rubocop](#), [test-unit](#), [yard](#).

RFC 3610 - CCM

openssl-ccm 1.2.2 [rdoc] [\[www\]](#) - depends on [coveralls](#), [rake](#), [rdoc](#), [rubocop](#), [test-unit](#), [yard](#).

RFC 3610 - CCM

openvas-omp 0.0.4 [rdoc] [[www](#)] - depends on [bundler](#), [jeweler](#), [rcov](#), [shoulda](#).

Communicate with OpenVAS manager through OMP

opt_parse_validator 1.9.2 [rdoc] [[www](#)] - depends on [activesupport](#), [addressable](#), [bundler](#), [rake](#), [rspec](#), [rspec-its](#), [rubocop](#), [rubocop-performance](#), [simplecov](#), [simplecov-lcov](#).

Ruby OptionParser Validators

optimist 3.0.1 [rdoc] [[www](#)] - depends on [chronic](#), [minitest](#), [rake](#).

Optimist is a commandline option parser for Ruby that just gets out of your way.

os 0.9.6 [rdoc] [[www](#)] - depends on [rspec](#).

Simple and easy way to know if you're on windows or not (reliably), as well as how many bits the OS is, etc.

ostruct 0.2.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#).

Class to build custom data structures, similar to a Hash.

packetfu 1.1.13 [rdoc] [[www](#)] - depends on [coveralls](#), [pcaprub](#), [pry](#), [rake](#), [rspec](#), [rspec-its](#), [sdcc](#).

PacketFu is a mid-level packet manipulation library.

paint 2.2.0 [rdoc] [[www](#)] - depends on [ansi](#), [benchmark-ips](#), [hansi](#), [pastel](#), [rainbow](#), [rake](#), [rspec](#), [term-ansicolor](#).

Terminal painter!

parallel 1.19.1 [rdoc] [[www](#)]

Run any kind of code in parallel processes

parallel 1.20.1 [rdoc] [[www](#)]

Run any kind of code in parallel processes

parser 2.7.0.5 [rdoc] [[www](#)] - depends on [ast](#), [bundler](#), [cliver](#), [gauntlet](#), [kramdown](#), [minitest](#), [racc](#), [rake](#), [simplecov](#), [yard](#).

A Ruby parser written in pure Ruby.
Executables are ruby-parse, ruby-rewrite.

parser 2.7.2.0 [rdoc] [[www](#)] - depends on [ast](#), [bundler](#), [cliver](#), [gauntlet](#), [kramdown](#), [minitest](#), [racc](#), [rake](#), [simplecov](#), [yard](#).

A Ruby parser written in pure Ruby.
Executables are ruby-parse, ruby-rewrite.

patch_finder 1.0.2 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#).

Patch Finder
Executable is msu_finder.

pcaprub 0.12.4 [rdoc] [[www](#)] - depends on [bundler](#), [minitest](#), [rake](#), [rake-compiler](#), [shoulda-context](#).

libpcap bindings for ruby

pcaprub 0.13.0 [rdoc] [[www](#)] - depends on [bundler](#), [minitest](#), [rake](#), [rake-compiler](#), [shoulda-context](#).

libpcap bindings for ruby

pdf-reader 2.0.0 [rdoc] [[www](#)] - depends on [afm](#), [Ascii85](#), [cane](#), [hashery](#), [ir_b](#), [morecane](#), [rake](#), [rdoc](#), [rspec](#), [ruby-rc4](#), [ttfunk](#).

A library for accessing the content of PDF files
Executables are pdf_callbacks, pdf_object, pdf_text.

pdf-reader 2.4.0 [rdoc] [[www](#)] - depends on [afm](#), [Ascii85](#), [cane](#), [hashery](#), [ir_b](#), [morecane](#), [rake](#), [rdoc](#), [rspec](#), [ruby-rc4](#), [ttfunk](#).

A library for accessing the content of PDF files
Executables are pdf_callbacks, pdf_object, pdf_text.

pg 0.20.0 [rdoc] [[www](#)] - depends on [hoe](#), [hoe-bundler](#), [hoe-deveiate](#), [hoe-highline](#), [hoe-mercurial](#), [rake-compiler](#), [rake-compiler-dock](#), [rdoc](#), [rspec](#).

Pg is the Ruby interface to the {PostgreSQL RDBMS}
[http://www.postgresql.org/]

pg 0.21.0 [rdoc] [[www](#)] - depends on [hoe](#), [hoe-bundler](#), [hoe-deveiate](#), [hoe-highline](#), [hoe-mercurial](#), [rake-compiler](#), [rake-compiler-dock](#), [rdoc](#), [rspec](#).

Pg is the Ruby interface to the {PostgreSQL RDBMS}
[http://www.postgresql.org/]

pg_array_parser 0.0.9 [rdoc] [[www](#)] - depends on [rake](#), [rake-compiler](#), [rspec](#).

Converts PostgreSQL array strings into arrays of strings

postgres_ext 3.0.0 [rdoc] [[www](#)] - depends on [activerecord](#), [arel](#), [bourne](#), [database_cleaner](#), [dotenv](#), [m](#), [minitest](#), [pg](#), [pg_array_parser](#), [rake](#).

Extends ActiveRecord to handle native PostgreSQL data types

postgres_ext 3.0.1 [rdoc] [[www](#)] - depends on [activerecord](#), [arel](#), [bourne](#), [database_cleaner](#), [dotenv](#), [m](#), [minitest](#), [pg](#), [pg_array_parser](#), [rake](#).

Extends ActiveRecord to handle native PostgreSQL data types

power_assert 1.1.7 [rdoc] [[www](#)] - depends on [benchmark-ips](#), [bundler](#), [byebug](#), [pry](#), [rake](#), [simplecov](#), [test-unit](#).

Power Assert for Ruby

prime 0.1.1 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [test-unit](#).

Prime numbers and factorization library.

pry 0.10.4 [rdoc] [[www](#)] - depends on [bundler](#), [coderay](#), [method_source](#), [slop](#).

An IRB alternative and runtime developer console
Executable is pry.

pry 0.13.0 [rdoc] [[www](#)] - depends on [coderay](#),
[method source](#).

A runtime developer console and IRB alternative with
powerful introspection capabilities.
Executable is pry.

pry-byebug 3.9.0 [rdoc] [[www](#)] - depends on [byebug](#), [pry](#).
Fast debugging with Pry.

pstore 0.1.0 [rdoc] [[www](#)]
Transactional File Storage for Ruby Objects

psych 3.1.0 [rdoc] [[www](#)]
Psych is a YAML parser and emitter

public_suffix 3.0.0 [rdoc] [[www](#)] - depends on [mocha](#), [rake](#),
[yard](#).

Domain name parser based on the Public Suffix List.

public_suffix 4.0.3 [rdoc] [[www](#)] - depends on [mocha](#), [rake](#),
[yard](#).

Domain name parser based on the Public Suffix List.

public_suffix 4.0.6 [rdoc] [[www](#)]
Domain name parser based on the Public Suffix List.

racc 1.4.16 [rdoc] [[www](#)] - depends on [hoe](#), [minitest](#), [rake-](#)
[compiler](#), [rdoc](#).

Racc is a LALR(1) parser generator
Executables are racc, racc2y, y2racc.

rack 1.6.13 [rdoc] [[www](#)] - depends on [bacon](#), [rake](#).
a modular Ruby webserver interface
Executable is rackup.

rack 1.6.8 [rdoc] [[www](#)] - depends on [bacon](#), [rake](#).

a modular Ruby webserver interface
Executable is rackup.

rack-protection 1.5.5 [rdoc] [[www](#)] - depends on [rack](#), [rack-test](#), [rspec](#).

You should use protection!

rack-test 0.6.3 [rdoc] [[www](#)] - depends on [rack](#).

Simple testing API built on Rack

rails-deprecated_sanitizer 1.0.3 [rdoc] [[www](#)] - depends on [activesupport](#), [bundler](#), [rake](#).

Deprecated sanitizer API extracted from Action View.

rails-dom-testing 1.0.8 [rdoc] [[www](#)] - depends on [activesupport](#), [bundler](#), [minitest](#), [nokogiri](#), [rails-deprecated_sanitizer](#), [rake](#).

Dom and Selector assertions for Rails applications

rails-dom-testing 1.0.9 [rdoc] [[www](#)] - depends on [activesupport](#), [bundler](#), [minitest](#), [nokogiri](#), [rails-deprecated_sanitizer](#), [rake](#).

Dom and Selector assertions for Rails applications

rails-html-sanitizer 1.0.3 [rdoc] [[www](#)] - depends on [bundler](#), [loofah](#), [minitest](#), [rails-dom-testing](#), [rake](#).

This gem is responsible to sanitize HTML fragments in Rails applications.

rails-html-sanitizer 1.3.0 [rdoc] [[www](#)] - depends on [bundler](#), [loofah](#), [minitest](#), [rails-dom-testing](#), [rake](#).

This gem is responsible to sanitize HTML fragments in Rails applications.

railties 4.2.11.1 [rdoc] [[www](#)] - depends on [actionpack](#), [actionview](#), [activesupport](#), [rake](#), [thor](#).

Tools for creating, working with, and running Rails applications.
Executable is rails.

railties 4.2.9 [rdoc] [[www](#)] - depends on [actionpack](#), [actionview](#), [activesupport](#), [rake](#), [thor](#).

Tools for creating, working with, and running Rails applications.
Executable is rails.

rainbow 3.0.0 [rdoc] [[www](#)] - depends on [bundler](#).
Colorize printed text on ANSI terminals

rake 12.0.0 [rdoc] [[www](#)] - depends on [bundler](#), [minitest](#), [rdoc](#).

Rake is a Make-like program implemented in Ruby
Executable is rake.

rake 13.0.1 [rdoc] [[www](#)]

Rake is a Make-like program implemented in Ruby
Executable is rake.

rb-readline 0.5.5 [rdoc] [[www](#)] - depends on [minitest](#), [rake](#).
Pure-Ruby Readline Implementation

rdoc 6.2.1 [rdoc] [[www](#)]

RDoc produces HTML and command-line documentation for Ruby projects
Executables are rdoc, ri.

readline 0.0.2 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [reline](#).

It's a loader for "readline".

readline-ext 0.1.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rake-compiler](#).

Provides an interface for GNU Readline and Edit Line (libedit).

recog 2.1.12 [rdoc] [[www](#)] - depends on [aruba](#), [cucumber](#), [nokogiri](#), [redcarpet](#), [rspec](#), [simplecov](#), [yard](#).

Network service fingerprint database, classes, and utilities

Executables are recog_export, recog_match, recog_verify.

recog 2.3.7 [rdoc] [[www](#)] - depends on [aruba](#), [cucumber](#), [nokogiri](#), [redcarpet](#), [rspec](#), [simplecov](#), [yard](#).

Network service fingerprint database, classes, and utilities

Executables are recog_export, recog_match, recog_verify.

redcarpet 3.4.0 [rdoc] [[www](#)] - depends on [rake](#), [rake-compiler](#), [test-unit](#).

Markdown that smells nice

Executable is redcarpet.

redcarpet 3.5.0 [rdoc] [[www](#)] - depends on [rake](#), [rake-compiler](#), [test-unit](#).

Markdown that smells nice

Executable is redcarpet.

regexp_parser 2.0.0 [rdoc] [[www](#)]

Scanner, lexer, parser for ruby's regular expressions

reline 0.1.5 [rdoc] [[www](#)] - depends on [bundler](#), [io-console](#), [rake](#), [test-unit](#).

Alternative GNU Readline or Editline implementation by pure Ruby.

rex-arch 0.1.11 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-text](#), [rspec](#).

Ruby Exploitation Library - rex-arch

rex-arch 0.1.13 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-text](#), [rspec](#).

Ruby Exploitation Library - rex-arch

rex-bin_tools 0.1.4 [rdoc] [[www](#)] - depends on [bundler](#), [metasm](#), [rake](#), [rex-arch](#), [rex-core](#), [rex-struct2](#), [rex-text](#), [rspec](#).

Ruby Exploitation(rex) Library containing a suite of binary reading and manipulation tools

Executables are msfbinscan, msfelfscan, msfmachscan, msfpescan.

rex-bin_tools 0.1.6 [rdoc] [[www](#)] - depends on [bundler](#), [metasm](#), [rake](#), [rex-arch](#), [rex-core](#), [rex-struct2](#), [rex-text](#), [rspec](#).

Ruby Exploitation(rex) Library containing a suite of binary reading and manipulation tools

Executables are msfbinscan, msfelfscan, msfmachscan, msfpescan.

rex-core 0.1.12 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#).

Core libraries required for the Ruby Exploitation (Rex) Suite.

rex-core 0.1.13 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#).

Core libraries required for the Ruby Exploitation (Rex) Suite.

rex-encoder 0.1.4 [rdoc] [[www](#)] - depends on [bundler](#), [metasm](#), [rake](#), [rex-arch](#), [rex-text](#), [rspec](#).

Ruby Exploitation(Rex) library for various polymorphic encoders.

rex-exploitation 0.1.14 [rdoc] [[www](#)] - depends on [bundler](#), [jsobfu](#), [metasm](#), [rake](#), [rex-arch](#), [rex-encoder](#), [rex-text](#), [rspec](#).

Ruby Exploitation(Rex) library for various exploitation helpers

rex-exploitation 0.1.22 [rdoc] [[www](#)] - depends on [bundler](#), [jsobfu](#), [metasm](#), [rake](#), [rex-arch](#), [rex-encoder](#), [rex-text](#), [rspec](#).

Ruby Exploitation(Rex) library for various exploitation helpers

rex-java 0.1.5 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#).

Rex library for parsing serialized Java streams.

rex-mime 0.1.5 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-text](#), [rspec](#).

This library is for creating and/or parsing MIME messages.

rex-nop 0.1.1 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-arch](#), [rspec](#).

Ruby Exploitation(REX) library for NOP generation.

rex-ole 0.1.6 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-text](#), [rspec](#).

Rex Library for working with OLE

rex-powershell 0.1.72 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-random_identifier](#), [rex-text](#), [rspec](#).

Rex Powershell Utilities

rex-powershell 0.1.87 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-random_identifier](#), [rex-text](#), [rspec](#), [ruby-rc4](#).

Rex Powershell Utilities

rex-random_identifier 0.1.3 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-text](#), [rspec](#).

Random Identifier Generator

rex-random_identifier 0.1.4 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-text](#), [rspec](#).

Random Identifier Generator

rex-registry 0.1.3 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#).

Rex Library for parsing offline registry hives

rex-rop_builder 0.1.3 [rdoc] [[www](#)] - depends on [bundler](#), [metasm](#), [rake](#), [rex-core](#), [rex-text](#), [rspec](#).

Ruby Exploitation(Rex) Library for building ROP chains.
Executable is msfrop.

rex-socket 0.1.23 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-core](#), [rspec](#).

The Ruby Exploitation (Rex) Socket Abstraction Library.

rex-socket 0.1.8 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-core](#), [rspec](#).

The Ruby Exploitation (Rex) Socket Abstraction Library.

rex-sslscan 0.1.5 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-core](#), [rex-socket](#), [rex-text](#), [rspec](#).

Ruby Exploitation(REX) Library for scanning the
SSL/TLS capabilities of a server

rex-struct2 0.1.2 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#).

Rex C-Struct Library

rex-text 0.2.15 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#).

Provides Text Manipulation Methods for Exploitation

rex-text 0.2.25 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rspec](#).

Provides Text Manipulation Methods for Exploitation

rex-zip 0.1.3 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rex-text](#), [rspec](#).

Rex Zip Library

rexml 3.2.3 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#).

An XML toolkit for Ruby

rexml 3.2.4 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#).

An XML toolkit for Ruby

rkelly-remix 0.0.7 [rdoc] [[www](#)] - depends on [hoe](#), [rdoc](#).

RKelly Remix is a fork of the

RKelly[<https://github.com/tenderlove/rkelly>] JavaScript parser.

rspec 3.10.0 [rdoc] [[www](#)] - depends on [rspec-core](#), [rspec-expectations](#), [rspec-mocks](#).

rspec-3.10.0

rspec 3.6.0 [rdoc] [[www](#)] - depends on [rspec-core](#), [rspec-expectations](#), [rspec-mocks](#).

rspec-3.6.0

rspec 3.9.0 [rdoc] [[www](#)] - depends on [rspec-core](#), [rspec-expectations](#), [rspec-mocks](#).

rspec-3.9.0

rspec-core 3.10.0 [rdoc] [[www](#)] - depends on [aruba](#), [coderay](#), [cucumber](#), [flexmock](#), [minitest](#), [mocha](#), [rr](#), [rspec-support](#), [thread_order](#).

rspec-core-3.10.0

Executable is rspec.

rspec-core 3.6.0 [rdoc] [[www](#)] - depends on [aruba](#), [coderay](#), [cucumber](#), [flexmock](#), [minitest](#), [mocha](#), [rr](#), [rspec-support](#),

[thread_order](#).

rspec-core-3.6.0

Executable is rspec.

rspec-core 3.9.1 [rdoc] [[www](#)] - depends on [aruba](#), [coderay](#), [cucumber](#), [flexmock](#), [minitest](#), [mocha](#), [rr](#), [rspec-support](#), [thread_order](#).

rspec-core-3.9.1

Executable is rspec.

rspec-expectations 3.10.0 [rdoc] [[www](#)] - depends on [aruba](#), [cucumber](#), [diff-lcs](#), [minitest](#), [rake](#), [rspec-support](#).

rspec-expectations-3.10.0

rspec-expectations 3.6.0 [rdoc] [[www](#)] - depends on [aruba](#), [cucumber](#), [diff-lcs](#), [minitest](#), [rake](#), [rspec-support](#).

rspec-expectations-3.6.0

rspec-expectations 3.9.1 [rdoc] [[www](#)] - depends on [aruba](#), [cucumber](#), [diff-lcs](#), [minitest](#), [rake](#), [rspec-support](#).

rspec-expectations-3.9.1

rspec-its 1.3.0 [rdoc] [[www](#)] - depends on [aruba](#), [bundler](#), [cucumber](#), [rake](#), [rspec-core](#), [rspec-expectations](#).

Provides "its" method formerly part of rspec-core

rspec-mocks 3.10.0 [rdoc] [[www](#)] - depends on [aruba](#), [cucumber](#), [diff-lcs](#), [minitest](#), [rake](#), [rspec-support](#).

rspec-mocks-3.10.0

rspec-mocks 3.6.0 [rdoc] [[www](#)] - depends on [aruba](#), [cucumber](#), [diff-lcs](#), [minitest](#), [rake](#), [rspec-support](#).

rspec-mocks-3.6.0

rspec-mocks 3.9.1 [rdoc] [[www](#)] - depends on [aruba](#), [cucumber](#), [diff-lcs](#), [minitest](#), [rake](#), [rspec-support](#).

rspec-mocks-3.9.1

rspec-rails 3.6.1 [rdoc] [[www](#)] - depends on [actionpack](#), [activesupport](#), [ammeter](#), [aruba](#), [cucumber](#), [railties](#), [rspec-core](#), [rspec-expectations](#), [rspec-mocks](#), [rspec-support](#).

RSpec for Rails

rspec-rails 4.0.0 [rdoc] [[www](#)] - depends on [actionpack](#), [activesupport](#), [ammeter](#), [aruba](#), [cucumber](#), [railties](#), [rspec-core](#), [rspec-expectations](#), [rspec-mocks](#), [rspec-support](#).

RSpec for Rails

rspec-rerun 1.1.0 [rdoc] [[www](#)] - depends on [bump](#), [bundler](#), [rake](#), [rspec](#), [rubocop](#).

Re-run failed RSpec tests.

rspec-support 3.10.0 [rdoc] [[www](#)] - depends on [rake](#), [thread_order](#).

rspec-support-3.10.0

rspec-support 3.6.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [thread_order](#).

rspec-support-3.6.0

rspec-support 3.9.2 [rdoc] [[www](#)] - depends on [rake](#), [thread_order](#).

rspec-support-3.9.2

rss 0.2.8 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [test-unit](#).

Family of libraries that support various formats of XML "feeds".

rubocop 0.80.1 [rdoc] [[www](#)] - depends on [bundler](#), [jaro_winkler](#), [parallel](#), [parser](#), [rainbow](#), [rexml](#), [ruby-progressbar](#), [unicode-display_width](#).

Automatic Ruby code style checking tool.

Executable is rubocop.

rubocop 1.4.2 [rdoc] [[www](#)] - depends on [bundler](#), [parallel](#), [parser](#), [rainbow](#), [regexp_parser](#), [rexml](#), [rubocop-ast](#), [ruby-progressbar](#), [unicode-display_width](#).

Automatic Ruby code style checking tool.
Executable is rubocop.

rubocop-ast 1.2.0 [rdoc] [[www](#)] - depends on [bundler](#), [parser](#).

RuboCop tools to deal with Ruby code AST.

rubocop-performance 1.9.1 [rdoc] [[www](#)] - depends on [rubocop](#), [rubocop-ast](#).

Automatic performance checking tool for Ruby code.

ruby-macho 2.2.0 [rdoc] [[www](#)]

ruby-macho - Mach-O file analyzer.

ruby-prof 1.3.1 [rdoc] [[www](#)] - depends on [minitest](#), [rake-compiler](#), [rdoc](#).

Fast Ruby profiler
Executables are ruby-prof, ruby-prof-check-trace.

ruby-progressbar 1.10.1 [rdoc] [[www](#)] - depends on [fuubar](#), [rspec](#), [rspectacular](#), [timecop](#), [warning_filter](#).

Ruby/ProgressBar is a flexible text progress bar library for Ruby.

ruby-rc4 0.1.5 [rdoc] [[www](#)] - depends on [rspec](#).

RubyRC4 is a pure Ruby implementation of the RC4 algorithm.

ruby_smb 0.0.18 [rdoc] [[www](#)] - depends on [bindata](#), [bundler](#), [fivemat](#), [rake](#), [redcarpet](#), [rubyntlm](#), [windows_error](#), [yard](#).

A pure Ruby implementation of the SMB Protocol Family

ruby_smb 1.1.0 [rdoc] [\[www\]](#) - depends on [bindata](#), [bundler](#), [fivemat](#), [rake](#), [redcarpet](#), [rubyntlm](#), [windows_error](#), [yard](#).
A pure Ruby implementation of the SMB Protocol Family

rubygems 3.1.4 [rdoc] [\[www\]](#)
RubyGems itself
Executable is gem.

rubygems-update 3.1.4 [rdoc] [\[www\]](#)
RubyGems is a package management framework for Ruby.
Executable is update_rubygems.

rubyntlm 0.6.2 [rdoc] [\[www\]](#) - depends on [github_changelog_generator](#), [pry](#), [rake](#), [rspec](#), [simplecov](#).
Ruby/NTLM library.

rubyzip 1.2.1 [rdoc] [\[www\]](#) - depends on [coveralls](#), [minitest](#), [pry](#), [rake](#).
rubyzip is a ruby module for reading and writing zip files

rubyzip 2.3.0 [rdoc] [\[www\]](#) - depends on [coveralls](#), [minitest](#), [pry](#), [rake](#), [rubocop](#).
rubyzip is a ruby module for reading and writing zip files

sawyer 0.8.1 [rdoc] [\[www\]](#) - depends on [addressable](#), [faraday](#).
Secret User Agent of HTTP

sawyer 0.8.2 [rdoc] [\[www\]](#) - depends on [addressable](#), [faraday](#).
Secret User Agent of HTTP

sdbm 1.0.0 [rdoc] [[www](#)] - depends on [rake-compiler](#), [test-unit](#).

Provides a simple file-based key-value store with String keys and values.

signet 0.14.0 [rdoc] [[www](#)] - depends on [addressable](#), [faraday](#), [google-style](#), [jwt](#), [kramdown](#), [launchy](#), [multi_json](#), [rake](#), [rspec](#), [simplecov](#), [yard](#).

Signet is an OAuth 1.0 / OAuth 2.0 implementation.

simplecov 0.15.0 [rdoc] [[www](#)] - depends on [bundler](#), [docile](#), [json](#), [simplecov-html](#).

Code coverage for Ruby 1.9+ with a powerful configuration library and automatic merging of coverage across test suites

simplecov 0.18.2 [rdoc] [[www](#)] - depends on [docile](#), [simplecov-html](#).

Code coverage for Ruby

simplecov 0.19.1 [rdoc] [[www](#)] - depends on [docile](#), [simplecov-html](#).

Code coverage for Ruby

simplecov-html 0.10.2 [rdoc] [[www](#)] - depends on [bundler](#).

Default HTML formatter for SimpleCov code coverage tool for ruby 1.9+

simplecov-html 0.12.2 [rdoc] [[www](#)]

Default HTML formatter for SimpleCov code coverage tool for ruby 2.4+

simplecov-html 0.12.3 [rdoc] [[www](#)]

Default HTML formatter for SimpleCov code coverage tool for ruby 2.4+

simplecov-lcov 0.8.0 [rdoc] [[www](#)] - depends on [activesupport](#), [bundler](#), [coveralls](#), [rake](#), [rdoc](#), [rspec](#), [simplecov](#).

Custom SimpleCov formatter to generate a lcov style coverage.

sinatra 1.4.8 [rdoc] [[www](#)] - depends on [rack](#), [rack-protection](#), [tilt](#).

Classy web-development dressed in a DSL

singleton 0.1.0 [rdoc] [[www](#)]

The Singleton module implements the Singleton pattern.

slop 3.6.0 [rdoc] [[www](#)] - depends on [minitest](#), [rake](#).

Simple Lightweight Option Parsing

sqlite3 1.3.13 [rdoc] [[www](#)] - depends on [hoe](#), [hoe-bundler](#), [mini_portile](#), [minitest](#), [rake-compiler](#), [rake-compiler-dock](#), [rdoc](#).

This module allows Ruby programs to interface with the SQLite3 database engine (<http://www.sqlite.org>)

sshkey 1.9.0 [rdoc] [[www](#)] - depends on [rake](#), [test-unit](#).

SSH private/public key generator in Ruby

sshkey 2.0.0 [rdoc] [[www](#)] - depends on [rake](#), [test-unit](#).

SSH private/public key generator in Ruby

stackprof 0.2.16 [rdoc] [[www](#)] - depends on [minitest](#), [mocha](#), [rake-compiler](#).

sampling callstack-profiler for ruby 2.2+

Executables are stackprof, stackprof-flamegraph.pl, stackprof-gprof2dot.py.

stringio 0.1.0 [rdoc] [[www](#)] - depends on [rake-compiler](#).

Pseudo IO on String

strscan 1.0.3 [rdoc] [[www](#)] - depends on [benchmark-driver](#), [rake-compiler](#).

Provides lexical scanning operations on a String.

swagger-blocks 3.0.0 [rdoc] [[www](#)] - depends on [bundler](#), [pry](#), [rake](#), [rspec](#).

Define and serve live-updating Swagger JSON for Ruby apps.

sys-proctable 1.2.6 [rdoc] [[www](#)] - depends on [ffi](#), [rake](#), [rspec](#).

An interface for providing process table information

test-unit 3.3.4 [rdoc] [[www](#)] - depends on [bundler](#), [kramdown](#), [packnga](#), [power_assert](#), [rake](#), [yard](#).

An xUnit family unit testing framework for Ruby.

thin 1.7.2 [rdoc] [[www](#)] - depends on [daemons](#), [eventmachine](#), [rack](#).

A thin and fast web server
Executable is thin.

thor 0.20.0 [rdoc] [[www](#)] - depends on [bundler](#).

Thor is a toolkit for building powerful command-line interfaces.
Executable is thor.

thor 1.0.1 [rdoc] [[www](#)] - depends on [bundler](#).

Thor is a toolkit for building powerful command-line interfaces.
Executable is thor.

thread_safe 0.3.6 [rdoc] [[www](#)] - depends on [atomic](#), [rake](#), [rspec](#).

Thread-safe collections and utilities for Ruby

tilt 2.0.10 [rdoc] [\[www\]](#)

Generic interface to multiple Ruby template engines
Executable is tilt.

timecop 0.9.1 [rdoc] [\[www\]](#)

A gem providing "time travel" and "time freezing" capabilities, making it dead simple to test time-dependent code. It provides a unified method to mock Time.now, Date.today, and DateTime.now in a single call.

timeout 0.1.0 [rdoc] [\[www\]](#)

Auto-terminate potentially long-running operations in Ruby.

tracer 0.1.0 [rdoc] [\[www\]](#)

Outputs a source level execution trace of a Ruby program.

ttfunk 1.5.1 [rdoc] [\[www\]](#) - depends on [rake](#), [rspec](#), [rubocop](#), [yard](#).

TrueType Font Metrics Parser

ttfunk 1.6.2.1 [rdoc] [\[www\]](#) - depends on [rake](#), [rspec](#), [rubocop](#), [rubocop-performance](#), [rubocop-rspec](#), [yard](#).

TrueType Font Metrics Parser

typhoeus 1.4.0 [rdoc] [\[www\]](#) - depends on [ethon](#).

Parallel HTTP library on top of libcurl multi.

tzinfo 1.2.3 [rdoc] [\[www\]](#) - depends on [thread_safe](#).

Daylight savings aware timezone library

tzinfo 1.2.6 [rdoc] [\[www\]](#) - depends on [thread_safe](#).

Daylight savings aware timezone library

tzinfo 1.2.8 [rdoc] [[www](#)] - depends on [thread safe](#).

Daylight savings aware timezone library

tzinfo-data 1.2017.2 [rdoc] [[www](#)] - depends on [tzinfo](#).

Timezone Data for TZInfo

tzinfo-data 1.2019.3 [rdoc] [[www](#)] - depends on [tzinfo](#).

Timezone Data for TZInfo

unicode-display_width 1.6.1 [rdoc] [[www](#)] - depends on [rake](#), [rspec](#).

Determines the monospace display width of a string in Ruby.

unicode-display_width 1.7.0 [rdoc] [[www](#)] - depends on [rake](#), [rspec](#).

Determines the monospace display width of a string in Ruby.

uri 0.10.0 [rdoc] [[www](#)]

URI is a module providing classes to handle Uniform Resource Identifiers

warden 1.2.7 [rdoc] [[www](#)] - depends on [rack](#).

Rack middleware that provides authentication for rack applications

webmock 3.10.0 [rdoc] [[www](#)] - depends on [addressable](#), [async-http](#), [crack](#), [curb](#), [em-http-request](#), [em-synchrony](#), [excon](#), [hashdiff](#), [http](#), [httpclient](#), [minitest](#), [patron](#), [rack](#), [rdoc](#), [rspec](#), [test-unit](#), [typhoeus](#).

Library for stubbing HTTP requests in Ruby.

webrick 1.6.0 [rdoc] [[www](#)] - depends on [rake](#).

HTTP server toolkit

websocket-driver 0.7.1 [rdoc] [[www](#)] - depends on [eventmachine](#), [permessage_deflate](#), [rake-compiler](#), [rspec](#), [websocket-extensions](#).

WebSocket protocol handler with pluggable I/O

websocket-extensions 0.1.4 [rdoc] [[www](#)] - depends on [rspec](#).

Generic extension manager for WebSocket connections

windows_error 0.1.2 [rdoc] [[www](#)] - depends on [bundler](#), [fivemat](#), [rake](#), [yard](#).

Provides a way to look up Windows NTSTATUS and Win32 Error Codes

xdr 2.0.0 [rdoc] [[www](#)] - depends on [activemodel](#), [activesupport](#), [bundler](#), [guard-rspec](#), [rake](#), [rspec](#), [simplecov](#).

XDR Helper Library

xmlrpc 0.3.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [test-unit](#).

XMLRPC is a lightweight protocol that enables remote procedure calls over HTTP.

xmlrpc 0.3.1 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [test-unit](#).

XMLRPC is a lightweight protocol that enables remote procedure calls over HTTP.

yajl-ruby 1.4.1 [rdoc] [[www](#)] - depends on [activesupport](#), [benchmark-memory](#), [json](#), [rake-compiler](#), [rspec](#).

Ruby C bindings to the excellent Yajl JSON stream-based parser library.

yaml 0.1.0 [rdoc] [[www](#)]

YAML Ain't Markup Language

yard 0.9.24 [rdoc] [[www](#)]

Documentation tool for consistent and usable documentation in Ruby.

Executables are yard, yardoc, yri.

yard 0.9.9 [rdoc] [[www](#)]

Documentation tool for consistent and usable documentation in Ruby.

Executables are yard, yardoc, yri.

zeitwerk 2.4.2 [rdoc] [[www](#)]

Efficient and thread-safe constant autoloader

zlib 1.1.0 [rdoc] [[www](#)] - depends on [bundler](#), [rake](#), [rake-compiler](#).

Ruby interface for the zlib compression/decompression library

[\[Validate\]](#)