

Specification Driven Delivery using TDD & Agile

The Complete Drydock Documentation

Ed Barlow Web Cloud Studio June 28, 2026



THE SAIL METHOD

You are the Commander (product owner)

The LLM is your agile and test driven best practices team.

The QuarterDeck web server enables communication with your team

Your Compass guides the build

Builds with ultra low end models

S

Setup and Install Drydock

- pip install
- drydock config
- drydock init

A

Agile Analyze

- drydock import - ingest your specifications and notes for analysis
- drydock analyze - agile story planning/Decomposition and question time
- drydock plan - convert your specifications into Blueprints and create AC

I

Implement

- drydock build - implement your software plan in managed chunks using the Manifest
- drydock score - evaluate acceptance and release readiness
- drydock rigging - manage your enterprise branding and build rules

L

Loop

- drydock refit - remaps the manifest for easy incremental builds
- drydock document - create consistent documentation from your specification

What is Drydock

Drydock is a specification-driven software build pipeline.

The user is the **Commander**, who owns the product direction, reviews the work, and approves decisions.

Drydock imports specifications for your project in any format.

Drydock turns this material into **Blueprints**, the authoritative definition of your software product. `drydock plan` writes the **Blueprints** and a **Manifest** (graph database) that tracks build order, runnable work, and incremental build scope.


Blueprints represent the smallest **building block** of your software. Blueprints are agile stories with a full definition of done and Acceptance Criteria. Drydock groups related **building blocks** into **blocks**. A **block** combines **Blueprints** with **Rigging**. Blocks are deterministically optimized for context. **Rigging** is enterprise business rules, technology rules, stack guidance, and branding so they provide common behavior and style.

Drydock uses test-driven development. Each **building block** carries acceptance criteria that must pass before the next step. This lets the process use low level models to create working software. The process can create working software for large projects for which frontier models will lose the thread and perform poorly.

The process is geared towards quick revision and long term maintainance of your software. At the start of the project, drydock lets you quickly iterate and get your project 'correct' and once you have production quality software, drydock enables a full maintenance cycle. Users can either edit specifications, add change tickets, or provide comments on their blueprints and `drydock refit` will manage the process to create new stories and blueprints which let you rebuild quickly and cleanly.

`drydock score` verifies software quality against a variety of metrics. It can test programmatic acceptance criteria and it can test project intent so the **Commander** can know the quality of the build.

The **QuarterDeck** is a simple yet flexible web console enabling the **Commander** to understand and guides the build. It shows blockers, decisions, questionnaires, and build progress. The quarterdeck provides full agile tooling such as a kanban board and a log of decisions and activities.



Glossary

Drydock term	Meaning
Commander	The operator. The Agile Product Owner.

Drydock term	Meaning
Target	The named project under <code>\$DRYDOCK_WORKSPACE/targets/<Target></code> .
Blueprint	The Typed Specification files that define the product. The source of truth.
Manifest	The executable build plan and dependency graph, <code>MANIFEST.md</code> .
Frontier	The set of Manifest blocks that are runnable now.
QuarterDeck	The web review console between the Commander and the LLM process.
Compass	Persistent project guidance used by Drydock commands.
Rigging	Shared branding, technology rules, business rules, and their compact context derivatives.
Soundings	Blueprint acceptance-criterion summary and verification.
Sea Trials	Product-level objectives and proof-of-delivery criteria.
Refit	Change process that maps updates into the Manifest .
Crew	The LLM agents that perform the work.
Building Block	A story representing the smallest buildable specification.
Block	A group of Manifest stories built as one unit.
Tier	A Blueprint's build order.

The drydock CLI

```
drydock <verb> [<sub-verb>] [arguments] [--options]
```

LLM actions are scoped to the workspace at `$DRYDOCK_WORKSPACE/targets/<Target>` and software in `$DRYDOCK_BUILD_DIRECTORY/<Target>` .

S — Set Up

```
drydock init MyApp          # create the workspace
```

A — Analyze and Plan

```
drydock import MyApp ./notes    # load specifications
drydock analyze MyApp           # stories, questions, blockers
drydock run quarterdeck MyApp   # review and answer
drydock plan MyApp              # Blueprints and Manifest
```

I — Implement

```
n=1; max=5
while drydock status MyApp --ready
do
    echo "*** BUILD ATTEMPT $n ***"
    drydock build MyApp || drydock diagnose MyApp --apply || true
    n=$((n+1))
    if [ "$n" -ge "$max" ]; then
        echo "hit $max build attempts - aborting"
        exit 1
    fi
done
drydock status MyApp --check
```

Score the result.


```
drydock score ac MyApp          # story acceptance
drydock score build MyApp       # build evidence
drydock score release MyApp     # release gate
```

L — Loop

```
drydock refit MyApp             # map changes into the Manifest- rerun the build
```

SAIL Phase 1 — Set Up: Laying the Keel

Install Drydock, configure runtime defaults, and create a workspace for each **Target**.



Installation

Prerequisites

- Python 3.11 or later
- A subscription-authenticated CLI, `claude` (Anthropic) or `codex` (OpenAI), or the token-billed `gemini` (Google).

Install

```
uv tool install drydock-sdd
# or: pipx install drydock-sdd
```

`uv tool` and `pipx` place `drydock` on `$PATH` automatically.

Configure the workspace

`$PROJECTS` is the directory for your built software.

```
drydock config set drydock_workspace "$PROJECTS/drydock"
drydock config set drydock_build_directory "$PROJECTS"
```

Initialize the target workspace

```
drydock init <Target>
```

The resulting layout is shown below.

```
$PROJECTS/
├── drydock/                # Drydock workspace
│   └── targets/<Target>/    # Created by drydock init - Project Workspace
└── <Target>/               # Final Build Location for projects
```

General Setup Commands

```
drydock --help
drydock --version
drydock config show
drydock config set <key> <value>
drydock init <Target> [--display-name <name>] [--description <desc>]
drydock status [<Target>] [--check | --ready]
drydock run quarterdeck [<Target>] [--host HOST] [--port PORT]
```

drydock status

```
`drydock status` shows the status of a project.
`drydock status <Target> --check` `reports the terminal state (for batch)
`drydock status <Target> --ready` reports whether the project has work to do (for I
```

drydock config

`drydock config` sets user-scoped defaults.

Variable	Purpose
<code>drydock_build_directory</code>	Build root
<code>drydock_workspace</code>	Workspace root
<code>change_ticket_directory</code>	Refit ticket directory
<code>drydock_model</code>	Default model
<code>drydock_effort</code>	Reasoning effort
<code>drydock_build_escalate_model</code>	Model for the final repair attempt
<code>codex_sandbox</code>	Codex OS sandbox policy
<code>prompt_warn_tokens</code>	Prompt size that warns

Variable	Purpose
<code>prompt_error_tokens</code>	Prompt size that fails
<code>block_min_savings</code>	Shared tokens needed to group two stories
<code>quarterdeck_port</code>	QuarterDeck port
<code>diagnose</code>	Diagnose failures automatically
<code>sandbox_mem_limit</code>	Acceptance-run memory cap (MB)
<code>capture_output_limit</code>	Captured command output cap (MB)
<code>repair_attempts</code>	Repair passes per failed block
<code>repair_stall_limit</code>	Passes without progress before repair stops
<code>max_output_tokens</code>	Output tokens per response
<code>haiku_thinking_tokens</code>	Haiku thinking budget - Required for haiku builds.

drydock init


`drydock init <Target>` creates `$DRYDOCK_WORKSPACE/targets/<Target>` .

`--display-name` sets a human-readable project name. `--description` seeds the one-line project summary in **Target** metadata.

SAIL Phase 2 — Agile Analyze: Charting the Course

Analyze Commands

```
drydock import <Target> <Source> --format <auto|markdown|source|speckit|compass> [
drydock score spec <Target>
drydock analyze <Target>
drydock run quarterdeck [<Target>] [--host HOST] [--port PORT]
drydock plan [--overwrite] [--no-conform] <Target>
```



1. `drydock import` brings source material into the Drydock workspace.
2. `drydock score spec` (optional) scores your imported specifications.
3. `drydock analyze` derives stories, acceptance milestones, blockers, and questions.
4. `drydock run quarterdeck` starts the web server for **Commander** review.
5. `drydock plan` creates the **Blueprint** files and the **Manifest**.

drydock import

`drydock import <Target> <Source> --format <auto|markdown|source|speckit|compass>` copies your source material into the **Target** workspace. Your guidance and intent is set with `--compass` which writes `COMPASS.md` .

```
drydock import <Target> <Source File> --format markdown
drydock import <Target> <Directory> --format markdown
drydock import <Target> <Source> --format <source|speckit>
drydock import <Target> <Source> --format compass [--force] # --force replaces C
drydock import <Target> --update
```

`--update` refreshes the imported snapshot from the recorded source root and records a new source version

Imported source files must be UTF-8. a file that fails UTF-8 decoding is not analyzed.

drydock score spec

`drydock score spec <Target>` diagnoses potential specification errors. This optional step attempts to find specification errors before you start.

drydock analyze

`drydock analyze` decomposes imported source material into stories, questionnaires, and blockers. `BLOCKERS.md` halts the build so if blockers exist, the **Commander** must edit (manually or in the **QuarterDeck**) and rerun `drydock analyze` until the blockers clear. `SEA_TRIALS.md` captures project success criteria for end of cycle project grading.

Epic Decomposition

Drydock decomposes source material into **Blueprints** by project type. For example, a web application decomposes by route and screens. Other system types decompose as follows.

System Type	Methodology
Web application	HTTP routes and web screens
CLI tool	Commands and sub-verbs
Library or package	Public API contract — e.g. <code>Database.items.get</code>
Data pipeline	Datasets, tables, process, inputs, and outputs
Event-driven	Topics, queues, and event types

Story Refinement

`drydock run quarterdeck` starts the web console at the listed host and port. The **QuarterDeck** shows status, blockers, questionnaires, decisions, and activity on interactive screens where the **Commander** approves or responds.

The **Commander** defines the technology stack in the **QuarterDeck** by selecting **Rigging** files. Rigging is required to build and use each component technology. A small set of rigging is provided for this open source project so if you are building in other languages and with other technologies, please provide an update with a pull request to the drydock source.

drydock plan

`drydock plan` converts the analysis into **Blueprints** stored in `<Target>/blueprint/` and will writes the optimized build graph (`MANIFEST.md`).

Input files

Artifact	Location	Purpose
<code>sources/</code> *	<code>blueprint/</code>	Imported sources
<code>ANALYSIS.md</code>	Target root	Reviewed analysis
<code>PLAN_COMPASS.md</code>	Target root	Planning and grouping guidance
<code>COMPASS.md</code>	Target root	Project guidance
<code>questionnaires/*.json</code>	<code>QuarterDeck/</code>	Resolved decisions
<code>SEA_TRIALS.md</code>	Target root	Project acceptance criteria

Output files

Artifact	Location	Purpose
<code>ARCHITECTURE.md</code> , <code>DATABASE.md</code> , <code>FEATURE-{Name}.md</code> , <code>SCREEN-{Name}.md</code> , <code>UI-GENERAL.md</code>	<code>blueprint/</code>	Blueprints
<code>MANIFEST.md</code>	Target root	Build plan

Build Order by Tier

`drydock plan` orders the build by **Tier**. We separate tiers to optimize context. Generally blueprints within a tier do not share context with blueprints in other tiers. The context optimization algorithm is deterministic and if context is not duplicated there is no savings, so combining blueprints in one step will yield no optimization.

Tier	Name	Builds
1	<code>language</code>	The tree, the environment, the test runner.
2.1	<code>platform - database</code>	The one database/persistence.
2.2	<code>platform - web server</code>	The one web server.
2.3	<code>platform - cli</code>	The command-line entry point.
3	<code>branding</code>	The palette, the typography, the voice.
4	<code>interface</code>	The shared UI shell.
5	<code>screen-foundation</code>	The screen idiom.
6	<code>application</code>	Every service and every screen.

`DATABASE.md` enforces data access encapsulation as a mechanism so that changes to the database or persistence layer do not invalidate all downstream blueprints. Application code does not call the database directly and instead uses reaches persistence through every a typed class library. Downstream objects call this library which means they do not need to be rebuilt unless the contract changes.

SAIL Phase 3 — Implement: Building The Software

Implement builds the **Blueprints** using the **Manifest**.

- `drydock build status <Target>` shows each **block**'s state and the runnable **Frontier**.
- `drydock build <Target>` runs the ready **blocks**.
- `drydock score` measures delivery health.
- **Rigging** applies company standards and branding.

The Manifest

The **Manifest** is the build graph and build plan. It is optimized deterministically so it will group similar **building blocks** into **blocks** such that token count is minimized. **Blocks** are ordered.

The **QuarterDeck** lets the **Commander**:

- Reorder stories so important or testable steps run first
- Regroup stories so one agent runs them
- Review **Blueprint** programmatic and user acceptance
- See a Kanban board of progress
- Manage changes via the **Refit** process

drydock build

```
drydock build <Target> [--continue] [--step <id|name>] [--story <id|name>]
                        [--ungate] [--reset] [--dry-run] [--build-dir <path>]
                        [--repair-attempts <n>] [--escalate-model <model>]
drydock build status <Target>
```

`drydock build` converts **Blueprints** to code, executing ready **blocks** from `MANIFEST.md` in order.

Each **building block** is checked against its deterministic acceptance criteria. A **block** completes only when all pass. `drydock build` self-repairs. It diagnoses and fixes failed **blocks**, then resumes. A failed **block** gets a configurable number of repair passes. Repair stops after two consecutive passes without progress, or at the pass limit.

The build loop

The Build is self repairing. `drydock diagnose` identifies problems with the prior build step and may update blueprints to correct identified errors. The llm is authorized to make these decisions which will show in the **QuarterDeck**. Because the LLM is non-deterministic, this self repair process finds and fixes issues which do not require human intervention. The diagnose command will stop on serious errors or misspecification.


```

n=1
max=5
while drydock status "$PROJECT" --ready
do
    echo "RUNNING BUILD ATTEMPT $n"
    drydock build "$PROJECT" $OPTS || drydock diagnose "$PROJECT" --apply
    n=$((n+1))
    if [ "$n" -ge "$max" ]
    then
        echo "ERROR - hit $max build iterations"
        exit 1
    fi
done

```

`drydock diagnose` writes a diagnostic report and recommends **Blueprint** changes. `--apply` updates the **Blueprints** and invalidates their build graph, so the build self-repairs and continues.

The **QuarterDeck** surfaces these decisions. Review is generally pro forma because `drydock diagnose` knows your intent from your **Compass** files.



`drydock build <Target>` writes the application to `$DRYDOCK_BUILD_DIRECTORY/<Target>`.

Flag	Effect
<code>--reset</code>	Discard prior work
<code>--repair-attempts <n></code>	Repair passes after a failed block (default 6)

Before building, `drydock build` checks applied **Blueprint** files for changes and possibly directs the **Commander** to `drydock refit`.

drydock score

```

drydock score spec <Target>
drydock score ac <Target> [--step <id>] [--full]
drydock score build <Target>
drydock score release <Target>
drydock score report <Target>
drydock score <Target>

```

`drydock score` audits specifications, verifies acceptance, reports build evidence, and evaluates release readiness.

Command	Behavior
<code>score spec</code>	Advisory findings on imported sources. Writes <code>SPECIFICATION_SCORECARD.md</code>
<code>score ac</code>	Verifies every acceptance criterion, with no LLM. Writes <code>SOUNDINGS.md</code>
<code>score build</code>	Reports repairs, tokens, and cache hit rate
<code>score release</code>	Runs the acceptance gate, then an LLM judges <code>SEA_TRIALS.md</code>
<code>score report</code>	Publishes the build receipt to <code>drydock_receipt/index.html</code>
<code>score</code> <code><Target></code>	Summarizes the last run of each score

drydock document

```
drydock document generate <Target> [--model <model>]
drydock document assemble <Target> [--theme <theme>]
drydock document <Target> [--model <model>] [--theme <theme>]
drydock document assemble readme <Target>
```

`drydock document` creates **Target** documentation from the **Blueprint**. `drydock document assemble` builds browsable documentation from those files. `drydock document <Target>` runs `generate`, then `assemble`. `drydock document assemble readme` regenerates the built project's `README.md`.

Configuration lives in `$DRYDOCK_WORKSPACE/targets/<Target>/documentation.yaml`.

```
theme: slate
sections:
  - OVERVIEW
  - FEATURES
  - SCREENS
  - ARCHITECTURE
  - SCHEMA
  - FLOWS
  - PIPELINE
  - SIGNALS
```

Themes are `slate`, `harbor`, and `paper`.

drydock publish

```
drydock publish <Source.md> --output <Output.html> [--theme <theme>] [--flatten]
  [--pdf] [--pdf-output <Output.pdf>]
```

`drydock publish` deterministically renders a front-matter Markdown document to HTML and pdf. Front matter sets the title, author, studio, cover text, theme, and formatting.

`--flatten` publishes each H1 and H2 section as a separate page with navigation. `--pdf` renders a PDF with the local browser.

```
drydock publish docs/Drydock_Specification.md --output docs/index.html
drydock publish docs/Drydock_Specification.md --output dist/Drydock_Whitepaper.htm
```


SAIL Phase 4 — Loop: The Refit

A **Refit** updates the **Manifest** from **Blueprint** changes and change tickets, creating new nodes for a normal build.

Build Commands

```
drydock diagnose <Target>
drydock diagnose <Target> --apply
drydock diagnose <Target> --no-apply
drydock diagnose <Target> --run <stamp>

drydock refit <Target>
```



drydock diagnose

`drydock diagnose` writes a report explaining failed builds and authorizes the LLM to create **Blueprint** diffs that let the next build proceed.

The report contains Root Cause, Details, Commander Feedback Requested, and a Repair Proposal. Commander Feedback Requested lists the next steps and asks how to proceed.

`--apply` applies the diffs and records decisions in `DECISIONS.json`.

drydock refit

`drydock refit <Target>` maps changes into new **Manifest** stories. Changes are tickets (Jira or plain English), direct **Blueprint** edits, and Feature-ticket **Blueprint** comments.

Directory Layout

Each **Target** has a workspace at `$DRYDOCK_WORKSPACE/targets/<Target>` and builds to `$DRYDOCK_BUILD_DIRECTORY/<Target>`. The **QuarterDeck** reads its configuration and Markdown from the workspace.

```

$DRYDOCK_WORKSPACE/
├─ logs/
├─ targets/
│   └─ <Target>/                                # one per project
│       ├── METADATA.md                          # identity
│       ├── ANALYSIS.md                          # output of analyze
│       ├── ANALYZE_COMPASS.md
│       ├── BLOCKERS.md
│       ├── COMPASS.md                            # intent, constraints, guardrails
│       ├── MANIFEST.md                          # the build graph
│       ├── PLAN_COMPASS.md
│       ├── SCORECARD.md
│       ├── SEA_TRIALS.md                        # project-level acceptance criteria
│       ├── SOUNDINGS.md                        # detailed acceptance criteria
│       ├── blueprint/                           # the Blueprint – conformed Typed Specif:
│           ├── sources/                          # imported material
│           ├── *.md
│           └─ changes/
│               └─ TICKET-NNN-{Name}.md
│   └─ QuarterDeck/                              # web console

```

```

$DRYDOCK_BUILD_DIRECTORY/
└─ <Target>/                                # built software

```

The Manifest Graph Database

`drydock plan` creates the build graph in `MANIFEST.md`, which the **Commander** manages in the **QuarterDeck**. The **Manifest** groups **building blocks** into **blocks**, sets build order, and tracks context and build status. **Building blocks** are deterministically optimized for context.

Grouping Blocks

The optimizer groups **building blocks** to share context. A **block** builds as one unit, runs when its dependencies are `closed/verified`, and closes when all its stories pass.

The QuarterDeck — Agile Development Console

The **QuarterDeck** is where the **Commander** reviews LLM build output and makes decisions. Its screens follow the Agile methodology and are documented in `QuarterDeck/README.md`.

Standard artifacts.

Artifact	Purpose
Commanders Chair	Default view. Shows the mission and current state.
Soundings	Acceptance checklist. Shows each capability, its state, and evidence.
Sea Trials	Objectives and success criteria for delivery
COMPASS Files	Persistent Commander guidance

`drydock init <Target>` enables the **QuarterDeck**.

Blockers. `drydock analyze` writes `BLOCKERS.md` when questions prevent planning. The **Commander** answers and reruns `drydock analyze`.

Drydock Rigging — Software Governance

Rigging is the enterprise rules governing application behavior. The **Rigging** shipped with Drydock is the Author's build rules. Organizations should supply their own stack, branding, and best-practice files.

Each technology the application uses should have a **Rigging** file. The **Commander** selects **Rigging** in the **QuarterDeck** Technology Rules questionnaire.

Business rules. `BUSINESS_RULES.md` defines agent behavior. It covers git workflow, project layout, script conventions, and error handling. Its compact derivative, `BUSINESS_RULES_compact.md`, is injected into the **Target** `AGENTS.md`. The full source stays in `Rigging/`.

Stack rules. `Rigging/stack/` holds one prescriptive, standalone file per technology. Each file's `**Tier:**` high level build order

Branding. `BRANDING_MAIN.md` defines the master palette, typography, and design philosophy. Per-medium files (`BRANDING_DOCUMENTATION.md`, `BRANDING_WHITEPAPERS.md`, `BRANDING_WEBSITE.md`) inherit from it. The built software uses the **Rigging** palette unless the imported specifications define one, in which case branding is not imported.

Compaction

Compaction creates `<file>_compact.md` from `<file>.md`. The compacted version holds the contract, or how to use the file, for its consumers. Building the service or utility needs the full file.

Rigging uses compaction extensively. For example, `python.md` holds the rules for building with Python and is used in full in one foundational setup **block**.

`python_compact.md` is used by every story that uses Python and holds the minimum a **block** needs to build in Python.

The plan and build steps may compact **Blueprints** injected into three or more **blocks**, the threshold where compaction pays off.

Rigging Commands

```
drydock rigging --add --file <path>
drydock rigging --add --dir <path>
drydock rigging compact <Target> [--all] [--force]
                                [--include-file <file.md>] [--exclude-file <file.md>]
                                [--include-dir <dir>]
drydock rigging update <Target> [--dry-run]
drydock rigging verify <Target>
```

`drydock rigging compact` recompacts stale files. `--all` includes Drydock's own **Rigging**, `--force` recompacts every file, and the include and exclude options adjust

the file set. `drydock rigging update` injects `BUSINESS_RULES_compact.md` and standard templates into the **Target** `AGENTS.md`. `--dry-run` previews. `drydock rigging verify` checks **Rigging** compliance.

Drydock Security

Drydock scopes work to `$DRYDOCK_WORKSPACE` and `$DRYDOCK_BUILD_DIRECTORY`. Each provider CLI runs headless. The agent reads none of the user's settings, `AGENTS.md`, or memories.

Drydock trusts imported material and **WILL** run it. This **can** cause unscoped calls, for example if the specifications explicitly say to do something bad. Run Drydock in Docker or bwrap (bubblewrap) for further scoping in enterprise or production use.

Claude Security

```
HOME=~/.drydock/claude-home CLAUDE_CONFIG_DIR=~/.drydock/claude-home \  
claude -p \  
  --verbose \  
  --safe-mode \  
  --output-format stream-json \  
  --include-partial-messages \  
  --dangerously-skip-permissions \  
  --model <model>
```

`--safe-mode` disables `CLAUDE.md` and `AGENTS.md` discovery, memory, hooks, plugins, and MCP servers.

Codex Security

```
CODEX_HOME=/tmp/drydock-codex-home-XXXX \  
codex exec \  
  --ignore-user-config \  
  --ignore-rules \  
  --ephemeral \  
  --sandbox <codex_sandbox> \  
  --cd <build_dir> \  
  --json \  
  --output-last-message <output_file> \  
  --model <model> -
```

`codex_sandbox` sets the OS sandbox to `danger-full-access` (default), `workspace-write`, or `read-only`.