

Technical drawing of a mechanical part, likely a bracket or support, showing multiple views (front, top, side, and detail views) with dimensions and specifications.

**Front View (Top Left):** Shows a square base with a central circular hole. Dimensions include 118 (width), 118 (height), and 45° chamfers. Four holes are indicated by '4 găuri'.

**Top View (Bottom Left):** Shows the base with a central circular hole. Dimensions include 118 (width), 118 (height), and 45° chamfers. Four holes are indicated by '4 găuri'.

**Side View (Middle Left):** Shows the profile of the part. Dimensions include 141 (total height), 120 (height to top of base), 76 (height to top of base), 52 (height to top of base), 12 (height to top of base), 8 (height to top of base), 20 (height to top of base), 30 $\pm$ 0.2 (height to top of base), 12 (height to top of base), 8 (height to top of base), 20 (height to top of base), 30 $\pm$ 0.2 (height to top of base), 12 (height to top of base), 8 (height to top of base), 20 (height to top of base), 30 $\pm$ 0.2 (height to top of base). Specifications include M12x1.5, M10, M6, W25x1,25x7f-DIN5480, f100h8, and A8x7x32.

**Detail View (Bottom Left):** Shows a detail of the base with a central circular hole. Dimensions include 2 (height to top of base), 12 (height to top of base), 42 $\pm$ 0.2 (height to top of base), 64 (height to top of base), 12 (height to top of base), 28 $\pm$ 0.2 (height to top of base), and 125 $\pm$ 0.1.

**Top View (Top Right):** Shows the base with a central circular hole. Dimensions include 26.2 (width), 13.1 (width), 9.5 (width), 52.4 (width), 26.2 (width), 19 (width), and 19 (width). Specifications include D, (S), R, (L), M10, 4 găuri, 4 holes, and A.

**Side View (Middle Right):** Shows the profile of the part. Dimensions include 50.8 (height), 25.4 (height), 11.9 (height), 23.8 (height), 19 (height), and 19 (height). Specifications include M10, 4 găuri, 4 holes, and A.

**Top View (Bottom Right):** Shows the base with a central circular hole. Dimensions include 9.5 (width), 65 (width), 22 (width), 24 (width), and 48 (width). Specifications include M33x2, D, (S), R, (L), M22x1.5, 2 găuri, 2 holes, and A.

L(mm) \ a°	25°	21°	18°	15°
L1	219	220	221	222
L2	283	284	285	286
L3	46	39	34	28
L4	97	93	90	86
L5	271	272	273	274
V <sub>g</sub> (cm³/rot)	14	11,9	10,2	8,6