



PASU AI



agents



Agents Server

Powered by **Promptbook**

Full Documentation

a few seconds ago (07/27/2026 1:38 PM)

Define the effective agent **goal**; when multiple goals exist, only the last one stays effective.

Defines the main goal which should be achieved by the AI assistant.

There can be multiple goals in source, but after inheritance/source rewriting only the last **GOAL** / **GOALS** remains effective.

Key aspects

- Both terms work identically and can be used interchangeably.
- Later goals overwrite earlier goals.
- The public agent profile text is derived from the last goal.
- Goals provide clear direction and purpose for the agent's responses.
- Goals influence decision-making and response prioritization.

Priority system

When multiple goals are defined, they are processed in order, with later goals taking precedence over earlier ones when there are conflicts.

Examples

bookCopyDownload

bookCopyDownload



Add behavioral rules the agent must follow.

Adds behavioral constraints and guidelines that the agent must follow.

Key aspects

- All rules are treated equally regardless of singular/plural form.
- Rules define what the agent must or must not do.

Examples

bookCopyDownload

bookCopyDownload



Add domain **knowledge** via direct text or external sources (RAG).

Adds specific knowledge, facts, or context to the agent using a RAG (Retrieval-Augmented Generation) approach for external sources.

Key aspects

- Both terms work identically and can be used interchangeably.
- Supports both direct text knowledge and external URLs.
- External sources (PDFs, websites) are processed via RAG for context retrieval.

Supported formats

- Direct text: Immediate knowledge incorporated into agent
- URLs: External documents processed for contextual retrieval
- Supported file types: PDF, text, markdown, HTML

Examples

book

Copy Download

book



PASU AI



Copy Download

TEAM

Enable the agent to consult teammate agents via dedicated tools.

Registers teammate agents that the current agent can consult via tools.

Examples

book

Copy Download

Remember past interactions and user **preferences** for personalized responses.

Enables persistent user memory for the current agent. The memory is stored by the runtime and can be retrieved in future conversations.

Key aspects

- Both `MEMORY` and `MEMORIES` work identically.
- Stores user-specific details through runtime tools.
- Retrieves relevant memories for personalized responses.
- Supports optional extra instructions in the commitment content.

Examples

book

CopyDownload

book

CopyDownload



LANGUAGE

/ LANGUAGES

Specifies the language(s) the agent should use.

Specifies the language(s) the agent should use in its responses.

This is a specialized variation of the RULE commitment focused on language constraints.

Examples

book

Copy Download

book

Copy Download



Provide explicit sample-only text that demonstrates the desired voice.

Provides explicit 1:1 sample text that demonstrates how the agent should sound.

Key aspects

- Use it for **voice exemplars**, not for behavioral rules or tool-usage instructions.
- The content should be sample-only text without meta commentary.
- Multiple writing samples can stack, with newer samples carrying the highest weight.
- If WRITING RULES add explicit constraints, those constraints override conflicting details from the sample while the sample still anchors the voice.

Examples

book

Copy Download

book

Copy Download

Add writing-only constraints such as tone, length, formatting, or emoji usage.

Adds instructions that apply strictly to how the agent writes.

Key aspects

- Use it for writing-only constraints such as tone, formatting, length, emoji usage, punctuation, or reading level.
- Do **not** use it for problem-solving behavior, policy, tool usage, or decision-making logic. Use `RULE` for that.
- Newer writing-rules blocks override conflicting earlier writing-rules blocks.
- When a writing rule conflicts with a `WRITING SAMPLE`, prefer the explicit rule for the constraint while keeping the sample as the main voice exemplar.

Examples

book

CopyDownload

book

CopyDownload



FROM

Inherit agent source from another agent.

Inherits agent source from another agent.

Examples

book

Copy Download



IMPORT / IMPORTS

Import content from another agent or a generic text file.

Imports content from another agent or a generic text file at the location of the commitment.

Examples

book

Copy Download

Define a UI component that the agent can render in the chat.

Defines a UI component that the agent can render in the chat.

Key aspects

- Tells the agent that a specific component is available.
- Provides syntax for using the component.

Example

book

CopyDownload

Set the agent's built-in avatar visual.

Sets the built-in avatar visual used for the agent when no explicit `META IMAGE` is provided.

`META AVATAR` and `META VISUAL` are equivalent.

Key aspects

- Does not modify the agent's behavior or responses.
- Only one `META AVATAR` or `META VISUAL` should be used per agent.
- If multiple are specified, the last one takes precedence.
- Values are matched case-insensitively and spaces, hyphens, and underscores are normalized.
- Supported visuals are derived from the shared avatar registry: `pixel-art`, `octopus`, `octopus2`, `octopus3`, `octopus3d`, `octopus3d2`, `octopus3d3`, `octopus3d4`, `ascii-octopus`, `minecraft`, `minecraft2`, `fractal`, `orb`.

Examples

bookCopyDownload

bookCopyDownload

Set the agent's profile image URL.

Sets the agent's avatar/profile image URL.

Key aspects

- Does not modify the agent's behavior or responses.
- Only one `META IMAGE` should be used per agent.
- If multiple are specified, the last one takes precedence.
- Used for visual representation in user interfaces.

Examples

book

CopyDownload

book

CopyDownload

Set the agent's accent color or gradient.

Sets the agent's accent color or gradient.

Key aspects

- Does not modify the agent's behavior or responses.
- Only one `META COLOR` should be used per agent.
- If multiple are specified, the last one takes precedence.
- Used for visual representation in user interfaces.
- Can specify multiple colors separated by comma to create a gradient.

Examples

bookCopyDownload

bookCopyDownload

bookCopyDownload



abc

META FONT

Set the agent's font.

Sets the agent's font.

Key aspects

- Does not modify the agent's behavior or responses.
- Only one `META FONT` should be used per agent.
- If multiple are specified, the last one takes precedence.
- Used for visual representation in user interfaces.
- Supports Google Fonts.

Examples

book

[Copy](#) [Download](#)

book

[Copy](#) [Download](#)

Provide profile/source links for the person the agent models.

Represents a profile or source link for the person the agent is modeled after.

Key aspects

- Does not modify the agent's behavior or responses.
- Multiple

META LINK

 commitments can be used for different social profiles.
- Used for attribution and crediting the original person.
- Displayed in user interfaces for transparency.

Examples

book

CopyDownload

book

CopyDownload



Set the agent's canonical domain/host.

Sets the canonical domain (host) of the agent, for example a custom domain that should open this agent directly.

Key aspects

- Does not modify the agent's behavior or responses.
- Used by server routing to map incoming hostnames to this agent.
- If multiple `META DOMAIN` commitments are specified, the last one takes precedence.
- Prefer hostname-only values such as `my-agent.com`.

Examples

book

Copy Download



Defines a markdown disclaimer shown to users before they can start chatting with the agent.

- Does not modify the system message or model requirements.
- Supports multiline markdown content.
- Intended for legal warnings, safety notices, and mandatory acknowledgements.
- If multiple `META DISCLAIMER` commitments are present, the last one takes precedence.

Copy Download



META INPUT PLACEHOLDER



PASU AI



Set custom placeholder text shown in the chat input.

Sets custom placeholder text for the chat input field.

Key aspects

- Does not modify model behavior, system message, or tools.
- If multiple `META INPUT PLACEHOLDER` lines are provided, the last one wins.
- Used by chat UIs to customize the message input hint.

Example

book

Copy Download



META THINKING MESSAGE



PASO AI



Add a custom thinking placeholder shown while the agent replies.

Adds one custom placeholder variant shown while the agent is composing a reply.

Key aspects

- Does not modify model behavior, system message, or tools.
- Multiple `META THINKING MESSAGE` commitments define multiple variants.
- Chat UIs randomly rotate between the configured variants while the reply is running.
- When no non-empty variants are configured, the server-level `THINKING_MESSAGES` metadata is used.
- Supports multiline markdown content.

Example

book

Copy Download

Set whether the agent is private, unlisted, or public.

Sets the agent visibility used by Agents Server.

Allowed values

- PRIVATE

 - accessible only to signed-in users with access.
- UNLISTED

 - accessible by direct link but hidden from public listings.
- PUBLIC

 - visible in public listings and accessible by anyone.

Key aspects

- Does not modify the agent's behavior, system message, or tools.
- Whitespace and letter case are normalized when persisted.
- If multiple

META VISIBILITY

 commitments are present, persistence keeps one normalized value.
- Agents Server mirrors the value into the database for filtering, but the book is the source of truth.

Example

book

CopyDownload

Set meta-information about the agent (IMAGE, LINK, TITLE, DESCRIPTION, etc.).

Sets meta-information about the agent that is used for display and attribution purposes.

Supported META types

- **META AVATAR / META VISUAL** - Sets the agent's built-in default avatar visual
- **META IMAGE** - Sets the agent's avatar/profile image URL
- **META LINK** - Provides profile/source links for the person the agent models
- **META DOMAIN** - Sets the canonical custom domain/host of the agent
- **META TITLE** - Sets the agent's display title
- **META DESCRIPTION** - Sets the agent's description
- **META INPUT PLACEHOLDER** - Sets chat input placeholder text
- **META THINKING MESSAGE** - Adds custom thinking placeholder variants
- **META [ANYTHING]** - Any other meta information in uppercase format

Key aspects

- Does not modify the agent's behavior or responses
- Used for visual representation and attribution in user interfaces
- Multiple META commitments of different types can be used
- Multiple META LINK commitments can be used for different social profiles
- Multiple META THINKING MESSAGE commitments can be used for different thinking placeholder variants
- If multiple META commitments of the same type are specified, the last one takes precedence (except for LINK)

Examples

Basic meta information

book



PASU AI



Copy Download

Multiple links and custom meta

book

Copy Download

Creative assistant

book

Copy Download

Select the ElevenLabs voice iD used for this agent.

Instructs the UI to use a specific ElevenLabs voice when reading this agent's replies aloud.

Key aspects

- Only affects ElevenLabs TTS playback, not agent behavior or system prompts
- If multiple `META VOICE` lines are provided, the last one wins
- The value should match one of the voice IDs listed in the ElevenLabs console

Example

book

CopyDownload

Add developer-facing notes without changing behavior or output.

Adds comments for documentation without changing agent behavior.

Key aspects

- Does not modify the agent's behavior or responses.
- Multiple `NOTE`, `NOTES`, `COMMENT`, and `NONCE` commitments are aggregated for debugging.
- All four terms work identically and can be used interchangeably.
- Useful for documenting design decisions and reminders.
- Content is preserved in metadata for inspection.

Examples

bookCopyDownload

bookCopyDownload



Defines the **initial message** shown to the user when the chat starts.

Defines the first message that the user sees when opening the chat. This message is purely for display purposes in the UI and does not inherently become part of the LLM's system prompt context (unless also included via other means).

Key aspects

- Used to greet the user.
- Sets the tone of the conversation.
- Displayed immediately when the chat interface loads.

Examples

book

Copy Download



Defines a ****message from the user**** in the conversation history.

Defines a message from the user in the conversation history. This is used to pre-fill the chat with a conversation history or to provide few-shot examples.

Key aspects

- Represents a message sent by the user.
- Used for setting up conversation context.
- Can be used in conjunction with AGENT MESSAGE.

Examples

book

Copy Download



Defines an **internal trace message** (tool calls/thinking metadata) in conversation history.

Defines an internal trace message related to one interaction. This is intended mainly for self-learning analytics and future training datasets.

Key aspects

- Stores internal execution context such as tool-call payloads.
- Can contain structured JSON payloads.
- Preserves additional context between USER MESSAGE and AGENT MESSAGE.
- Does not directly modify model requirements.

Examples

book

Copy Download



Defines a ****message from the agent**** in the conversation history.

Defines a message from the agent in the conversation history. This is used to pre-fill the chat with a conversation history or to provide few-shot examples.

Key aspects

- Represents a message sent by the agent.
- Used for setting up conversation context.
- Can be used in conjunction with USER MESSAGE.

Examples

book

Copy Download

Set a hardcoded suffix appended to every assistant response.

Defines a hardcoded message appended to every assistant response.

Key aspects

- Does not modify the system message or model requirements.
- Supports multiline markdown content.
- Useful for branding, legal notes, and disclosure notices.
- If multiple `MESSAGE SUFFIX` commitments are present, the last one takes precedence.

Example

book

CopyDownload



Include actual **messages** the AI assistant has sent during conversation history.

Contains 1:1 text of the message which AI assistant already sent during the conversation. Later messages are later in the conversation. It is similar to **WRITING SAMPLE**, but it is not a sample. It is the real message which the AI assistant already sent.

Key aspects

- Multiple **MESSAGE** and **MESSAGES** commitments represent the conversation timeline.
- Both terms work identically and can be used interchangeably.
- Later messages are later in the conversation chronologically.
- Contains actual historical messages, not examples or templates.
- Helps maintain conversation continuity and context.

Differences from WRITING SAMPLE

- **WRITING SAMPLE** shows hypothetical sample-only voice exemplars
- **MESSAGE / MESSAGES** contains actual historical conversation content
- **MESSAGE / MESSAGES** preserves the exact conversation flow
- **MESSAGE / MESSAGES** helps with context awareness and consistency

Use cases

- Maintaining conversation history context
- Ensuring consistent tone and style across messages
- Referencing previous responses in ongoing conversations
- Building upon previously established context

Examples



PASU AI



book

Copy Download

book

Copy Download

book

Copy Download



Enable persistent private credential storage (tokens, logins, cookies) scoped per agent or globally.

Enables private credential storage for tokens, usernames/passwords, and session cookies.

Define specific **situations** or contexts for AI responses, with later scenarios having higher priority.

Defines a specific situation or context in which the AI assistant should operate. It helps to set the scene for the AI's responses. Later scenarios are more important than earlier scenarios.

Key aspects

- Multiple **SCENARIO** and **SCENARIOS** commitments build upon each other.
- Both terms work identically and can be used interchangeably.
- Later scenarios have higher priority and can override earlier scenarios.
- Provides situational context that influences response tone and content.
- Helps establish the environment and circumstances for interactions.

Priority system

When multiple scenarios are defined, they are processed in order, with later scenarios taking precedence over earlier ones when there are conflicts.

Use cases

- Setting the physical or virtual environment
- Establishing time constraints or urgency
- Defining relationship dynamics or power structures
- Creating emotional or situational context

Examples

book

Copy Download

book



PASU AI



Copy Download

book

Copy Download

book

Copy Download



Define terms and their meanings for consistent terminology usage.

Defines specific terms and their meanings that the agent should use correctly in reasoning and responses.

Key aspects

- Multiple DICTIONARY commitments are merged together.
- Terms are defined in the format: "Term is definition"
- The agent should use these terms consistently in responses.
- Definitions help ensure accurate and consistent terminology.

Examples

book

Copy Download

book

Copy Download

Allow the agent to be modified by conversation (default) and optionally guide the teacher.

OPEN

Specifies that the agent can be modified by conversation with it.
This means the agent will learn from interactions and update its source code.
This is the default behavior if neither `OPEN` nor `CLOSED` is specified.

“See also [CLOSED](#)”

Example

book

CopyDownload

CLOSED

Specifies that the agent **cannot** be modified by conversation with it.
This means the agent will **not** learn from interactions and its source code will remain static during conversation.
By default (if not specified), agents are `OPEN` to modification.

“See also [OPEN](#)”

Example

book

CopyDownload



Enable the agent to use browser tools for accessing internet information.

Enables the agent to use browser tools to access and retrieve up-to-date information from the internet.

Key aspects

- The content following `USE BROWSER` is an arbitrary text that the agent should know (e.g. browsing scope or preferred sources).
- Provides two levels of browser access:
 1. **One-shot URL fetching:** Simple function to fetch and scrape URL content (active)
 2. **Running browser:** For complex tasks like scrolling, clicking, form filling, etc. (runtime-dependent)
 - The actual browser tool usage is handled by the agent runtime
 - On the Agents Server, every agent browses in its own persistent isolated browser profile, so cookies and logged-in sessions survive across chats (the profile is linked from the agent wallet)
 - Allows the agent to fetch current information from websites and documents
 - Useful for research tasks, fact-checking, and accessing dynamic content
 - Supports various content types including HTML pages and PDF documents

Examples

book

Copy Download

book



PASU AI



Copy Download

book

Copy Download

Enable the agent to use DeepSearch for more thorough internet research.

Enables the agent to use DeepSearch for broader, more thorough internet research than lightweight web search.

Key aspects

- The content following `USE DEEPSEARCH` is arbitrary guidance for the research workflow.
- In Agents Server, the OpenAI Agents SDK runtime uses a nested deep-research agent for this tool.
- Use this for investigations, comparisons, market scans, or other tasks that benefit from deeper synthesis.
- Prefer regular `USE SEARCH ENGINE` when a quick factual lookup is enough.

Examples

book

CopyDownload

book

CopyDownload



Enable the agent to use a search engine tool for accessing internet information.

Enables the agent to use a search engine tool to access and retrieve up-to-date information from the internet.

Key aspects

- The content following `USE SEARCH ENGINE` is an arbitrary text that the agent should know (e.g. search scope or instructions).
- The actual search engine tool usage is handled by the agent runtime
- Allows the agent to search for current information from the web
- Useful for research tasks, finding facts, and accessing dynamic content

Examples

book

Copy Download

book

Copy Download



Enable the agent to create persistent child agents via Agents Server create-agent flow.

Enables the agent to create a new persistent child agent using the `spawn_agent` tool.

Key aspects

- The spawned agent is persisted exactly like manually created agents.
- Tool input mirrors create-agent fields currently supported by Agents Server:
- `source` (required)
- `folderId` (optional)
- `sortOrder` (optional)
- `visibility` (optional)
- Unknown fields are rejected to avoid silent misconfiguration.
- `source` payload is size-limited.
- Agents Server applies permission and abuse protections (auth checks, limits).
- Optional text after `USE SPAWN` is treated as spawn-policy instructions.

Examples

book

Copy Download



Enable timeout wake-ups plus scoped timeout listing, updates, and cancellation across chats.

Enables timeout wake-ups and timeout management for the same user+agent scope.

Key aspects

- The agent uses `set_timeout` to schedule a future wake-up in the same chat thread.
- The tool returns immediately while the timeout is stored and executed by the runtime later.
- The wake-up arrives as a new user-like timeout message in the same conversation.
- The agent can inspect known timeout details via `list_timeouts`.
- The agent can cancel one timeout by `timeoutId` or cancel all active timeouts via `cancel_timeout`.
- The agent can pause/resume and edit timeout details via `update_timeout`.
- Commitment content is treated as optional timeout policy instructions.

Examples

book

Copy Download

Enable the agent to determine the current date and time.

Enables the agent to determine the current date and time.

Key aspects

- This tool won't receive any input.
- It outputs the current date and time as an ISO 8601 string.
- Allows the agent to answer questions about the current time or date.
- The content following `USE TIME` is an arbitrary text that the agent should know (e.g. timezone preference).

Examples

book

CopyDownload

book

CopyDownload

Enable the agent to determine the user location when browser permission is granted.

Enables the agent to retrieve the user's location from runtime context.

Key aspects

- The location is requested by the browser runtime (with user permission).
- Use the tool `get_user_location` when an answer depends on user's location.
- If location is unavailable or denied, ask the user to enable location sharing or provide location manually.
- The content following `USE USER LOCATION` can define additional location usage instructions.

Examples

book

CopyDownload

book

CopyDownload

Enable calendar tools for reading and managing events through Google Calendar.

Enables the agent to access and manage one Google Calendar.

Key aspects

- The first URL in the commitment should point to a Google Calendar URL.
- Optional `SCOPES` lines can provide explicit OAuth scopes.
- Optional extra instructions can follow calendar reference lines.
- Runtime provides Google Calendar OAuth token (manual wallet token or host-managed OAuth token).
- Tools support listing events, reading one event, creating events, updating events, deleting events, and inviting guests.

Examples

book

CopyDownload

book

CopyDownload

Enable outbound email sending through a wallet-backed SMTP configuration.

Enables the agent to send outbound emails through SMTP.

Key aspects

- The agent sends email via the `send_email` tool.
- SMTP credentials are expected from wallet records (`ACCESS_TOKEN` , service `smtp` , key `use-email-smtp-credentials`).
- Commitment content can optionally begin with a default sender email address:
- `USE EMAIL agent@example.com`
- Remaining commitment content is treated as optional email-writing instructions.

Examples

book

Copy Download

book

Copy Download



Enable the agent to open a popup window with a specific website.

Enables the agent to open a popup window with a specific website.

Key aspects

- The content following `USE POPUP` is an arbitrary text that the agent should know (e.g. constraints or instructions).
- The actual popup opening is handled by the agent runtime (usually in the browser)
- Allows the agent to open websites for the user to interact with (e.g. social media posts)

Examples

book

Copy Download



USE IMAGE GENERATOR



PASU AI

Enable the agent to output markdown image placeholders that the UI turns into generated images.

Enables the agent to output markdown image placeholders that trigger image generation in the user interface.

Key aspects

- The content following `USE IMAGE GENERATOR` is an arbitrary text that the agent should know (e.g. style instructions or safety guidelines).
- The agent does **not** call an image-generation tool directly.
- The agent inserts markdown notation: `![alt](?image-prompt=...)`.
- The user interface detects the notation and generates the image asynchronously.

Examples

book Copy Download

book Copy Download

Connects the agent to an external MCP server for additional capabilities.

Connects the agent to an external Model Context Protocol (MCP) server.

Key aspects

- The content following `USE MCP` must be a valid URL
- Multiple MCP servers can be connected by using multiple `USE MCP` commitments
- The agent will have access to tools and resources provided by the MCP server

Example

book

CopyDownload

Enable the agent to request turning private mode on for sensitive conversations.

Enables the agent to request turning on private mode in chat.

Key aspects

- The tool `turn_privacy_on` asks the UI to show a confirmation dialog to the user.
- Private mode is enabled only after explicit user confirmation in the UI.
- In the current implementation, this reuses existing private mode behavior in chat.
- While private mode is active, chat persistence, memory persistence, and self-learning are disabled.
- Proper encryption is planned for future updates, but not implemented by this commitment yet.
- Optional content after `USE PRIVACY` can provide additional privacy instructions.

Examples

book

CopyDownload

book

CopyDownload

Enable GitHub project tools for reading/editing repository files and creating pull requests.

Enables the agent to work with files in a GitHub repository and create pull requests.

Key aspects

- The first repository reference in the commitment should point to GitHub repository (for example `https://github.com/owner/repo`).
- Optional extra instructions can follow the repository reference.
- The runtime provides a GitHub token (manual wallet token or host-managed integration token).
- Tools support listing files, reading files, editing files, deleting files, creating branches, and opening pull requests.

Examples

book

CopyDownload

Deprecated legacy profile commitment. Prefer `GOAL` for agent profile text and inheritance-safe rewrites.

Deprecated commitment

Use `GOAL` for agent profile text and inheritance-safe rewrites. Preferred replacement: `GOAL`.

Deprecated legacy commitment that defines who the agent is, their background, expertise, and personality traits.

Migration

- Existing `PERSONA` books still parse and compile.
- New books should prefer `GOAL`.
- Agent profile rendering now prefers the last `GOAL` and only falls back to `PERSONA` when no goal exists.
- Runtime compilation keeps the legacy multi-`PERSONA` merge behavior for backward compatibility.

Preferred replacement

bookCopyDownload

Legacy compatibility example

bookCopyDownload

Deprecated legacy writing-style commitment. Prefer “WRITING RULES” for new books.

Deprecated commitment

Use **WRITING RULES** for writing-only constraints such as tone, length, formatting, or emoji usage. Preferred replacement: **WRITING RULES**.

Deprecated legacy commitment for writing and presentation instructions.

Migration

- Existing **STYLE** books still parse and compile.
- New books should prefer **WRITING RULES**.
- Use **WRITING SAMPLE** when you want to anchor voice by example instead of stating constraints directly.
- The plural alias **STYLES** is the same legacy commitment family.

Key aspects

- STYLE** remains functional for backward compatibility only.
- Later style instructions can override earlier ones.
- Style affects both tone and presentation format.

Preferred replacement

book

Copy Download

Legacy compatibility examples



PASU AI



book

Copy Download

book

Copy Download

Deprecated legacy alias for `WRITING SAMPLE`.

Deprecated commitment

Use `WRITING SAMPLE` for explicit voice exemplars. Preferred replacement: `WRITING SAMPLE`.

Deprecated legacy alias for `WRITING SAMPLE`.

Migration

- Existing `SAMPLE` blocks still work.
- New books should use `WRITING SAMPLE` instead.
- Runtime behavior is intentionally unchanged for backward compatibility.

Preferred replacement

book

CopyDownload

Legacy compatibility example

book

CopyDownload



Deprecated legacy formatting commitment. Prefer `WRITING SAMPLE` and `WRITING RULES` for new books.

Deprecated commitment

Use `WRITING SAMPLE` and `WRITING RULES` instead. Preferred replacement: `WRITING SAMPLE`, `WRITING RULES`.

Deprecated legacy commitment for output formatting and response structure.

Migration

- Existing `FORMAT` and `FORMATS` books still parse and compile.
- New books should use `WRITING RULES` for formatting or structure constraints and `WRITING SAMPLE` when a concrete example communicates the target shape better.
- Runtime behavior is intentionally unchanged for backward compatibility.

Preferred replacement

book

Copy Download

Legacy compatibility example



PASU AI



book

Copy Download

Deprecated legacy template commitment. Prefer `WRITING SAMPLE` and `WRITING RULES` for new books.

Deprecated commitment

Use `WRITING SAMPLE` and `WRITING RULES` instead. Preferred replacement: `WRITING SAMPLE`, `WRITING RULES`.

Deprecated legacy commitment for response structure and templates.

Migration

- Existing `TEMPLATE` and `TEMPLATES` books still parse and compile.
- New books should use `WRITING SAMPLE` for concrete response exemplars and `WRITING RULES` for structure or formatting constraints.
- Runtime behavior is intentionally unchanged for backward compatibility.

Preferred replacement

book

CopyDownload

Legacy compatibility example

book

CopyDownload

Deprecated legacy capability commitment. Prefer concrete `USE\*` commitments.

Deprecated commitment

Use a concrete **USE*** commitment instead.

Deprecated legacy commitment for broad capability notes.

Migration

- Existing **ACTION** and **ACTIONS** books still parse and compile.
- New books should prefer the appropriate **USE*** commitment instead.
- Keep **ACTION** only when maintaining older books that already rely on it.

Preferred replacement

book

Copy Download

Legacy compatibility example

book

Copy Download

book

Copy Download

Unfinished low-level commitment for removing or disregarding information. Use carefully.

Low-level commitment

This commitment is unfinished and not ready to use. Be careful when using it.

A low-level unfinished commitment to remove or disregard certain information or context. It is not ready to use broadly yet, so use it carefully.

Status

- This commitment is unfinished and not ready to use yet.
- Treat it as a low-level prompt-surgery tool rather than a general-purpose commitment.
- Prefer higher-level commitments when a clearer dedicated commitment exists.

Aliases

- **DELETE** - Remove or eliminate something
- **CANCEL** - Cancel or nullify something
- **DISCARD** - Discard or ignore something
- **REMOVE** - Remove or take away something

Key aspects

- Multiple delete commitments can be used to remove different aspects.
- Useful for overriding previous commitments in the same agent definition.
- Can be used to remove inherited behaviors from base personas.
- Helps fine-tune agent behavior by explicitly removing unwanted elements.
- Because this commitment is unfinished, keep an eye on future changes before relying on it in production books.

Use cases

- Overriding inherited persona characteristics
- Removing conflicting or outdated instructions
- Disabling specific response patterns
- Canceling previous formatting or style requirements

- Experimenting with low-level prompt rewrites when you know exactly what needs to be removed



PASU AI



Examples

book


Copy Download

book

Copy Download

book

Copy Download





Low-level commitment for explicit model selection and technical parameters. Use carefully.

Low-level commitment

This commitment is low-level and not used by most of the users. Be careful when using it.

Low-level commitment for explicit AI model selection and technical parameters.

Status

- This commitment is low-level and not used by most of the users.
- Use it when you need to pin a specific model or fine-tune model parameters directly.
- Prefer automatic model selection when you do not need manual control.

Key aspects

- When no `MODEL` commitment is specified, the best model requirement is picked automatically based on the agent `PERSONA`, `KNOWLEDGE`, `TOOLS` and other commitments.
- Multiple `MODEL` commitments can be used to specify different parameters
- Both `MODEL` and `MODELS` terms work identically and can be used interchangeably
- Parameters control the randomness, creativity, and technical aspects of model responses

Syntax variations

Single-line format (legacy support)

book

Copy Download

Multi-line named parameter format (recommended)

book



PASU AI



Copy Download

Supported parameters

- **NAME**: The specific model to use (e.g., 'gpt-4', 'claude-3-opus')
- **TEMPERATURE**: Controls randomness (0.0 = deterministic, 1.0+ = creative)
- **TOP_P**: Nucleus sampling parameter for controlling diversity
- **TOP_K**: Top-k sampling parameter for limiting vocabulary
- **MAX_TOKENS**: Maximum number of tokens the model can generate

Examples

Precise deterministic assistant

book

Copy Download

Creative writing assistant

book

 PASU AI ▶

CopyDownload

Balanced conversational agent

book

CopyDownload

Promptbook

Create persistent AI agents that turn your company's scattered knowledge into action

Product

[Get started](#)

[Manifest](#)

[Documentation](#)

[Terms of Service](#)

[Privacy Policy](#)

Company

[AI Web, LLC](#)

[About Us](#)

[Blog](#)

[Logos & Branding](#)

Connect

[GitHub](#)

[LinkedIn](#)

[Discord](#)

[More](#)



PASU AI



© 2026 Promptbook

Made with  in Europe

v0.113.0-14