Biscuit, Bearing, Cake, Scotch Bar, Tray Pack Items etc.

Horizontal Flow Wrape Packaging Machine



AC drive/PLC/Micro view	L&T
All product contact parts	SS made
Compressed air require	10 CFM @ 6 BAR
Cylinders	Festo/Camozzi/SMC
Electrical power	3 x 380 3 KW
Filling system	Cup filler system
Hopper material	(SS-316 food grade)
Machine Body	MS with powder coated
Machines weight	1200Kg (Approx.)
Main motor	1 HP Crompton Make, 3phase/servo motor
Maximum film roll width	450mm
Packaging film	Heat sealable laminated film in roll form.
Packing speed	Up to 80 PPM
Product application	100gm to 1kg
Quick speed control	By AC drive
Sealing Mechanism	Intermittent
Sealing type	Center side seal

HUN-811

Filter Khaini, Naswar etc.

Pouch Width	12 mm to 18 mm
Pouch Length	25 mm to 35 mm
Film Width	30 mm to 40 mm
Filling Volume	0.2 gm to 1.0 gm
Packing Speed	up to 300 pouches per minutes
Air Connection	6 Bar
Packing Material	Non Woven Fabrics
Power Load	2.5 KW, 440V, AC
Weight of M/c	525 KG

SPECIFICATION

□ PLC Mitsubishi Japan

HMI Mitsubishi Japan

Geared Motor : Bonvario (Italian)

A.C. Drive : Fuji (Japanese)

Pneumatic : Festo (German) , SMC (Japanese)

Sensor : P&F (German)

Temperature controller: Omron PID (Japanese) Contact parts: Stainless steel 304 Food Grade

Auto Counting system Conveyor system

Filter Khaini Machine

