

Chapter IR:V

V. Evaluation

- ❑ Laboratory Experiments
- ❑ Measuring Performance
- ❑ Set Retrieval Effectiveness
- ❑ Ranked Retrieval Effectiveness
- ❑ Training and Testing
- ❑ Logging

Laboratory Experiments

Experiment Scope

Interactive retrieval:

- ❑ Processing a query **depending** on other queries (of the user).
- ❑ The user has a goal or a task that requires many queries and exploration.
- ❑ Dependent variables are result quality, human factors, context, user interface and experience, and the retrieval system's supporting facilities.
- ➔ Experiments typically require user studies
- ➔ Measurement of retrieval performance depends on the setup

Laboratory Experiments

Experiment Scope

Interactive retrieval:

- ❑ Processing a query **depending** on other queries (of the user).
- ❑ The user has a goal or a task that requires many queries and exploration.
- ❑ Dependent variables are result quality, human factors, context, user interface and experience, and the retrieval system's supporting facilities.
- ➔ Experiments typically require user studies
- ➔ Measurement of retrieval performance depends on the setup

Ad hoc retrieval:

- ❑ Processing a query **independently** from other queries (of the user).
- ➔ Amenable to laboratory environments
- ➔ Canonical measurement of retrieval performance
- ➔ Reproducibility and scalability

Remarks:

- ❑ “ad hoc” (Latin: “for this”) means “concerned with a particular end or purpose” and “formed or used for specific or immediate problems or needs” [\[Merriam Webster\]](#)

Laboratory Experiments

Experimental Setup

A laboratory experiment for ad hoc retrieval requires three items:

1. A document collection (corpus)

- ❑ A representative sample of documents from the domain of interest.
- ❑ If representativeness is difficult to achieve, the larger the sample, the better.

2. A set of information needs (topics)

- ❑ Formalized, written descriptions of users' tasks, goals, or gaps of knowledge.
- ❑ Alternatively, declarative descriptions of desired search results.
- ❑ Often accompanied by specific queries the users (would) have used.

3. A set of relevance judgments (ground truth)

- ❑ Pairs of topics and documents, where each document has been manually assessed with respect to its relevance to the associated topic.
- ❑ Ideally, the users who supplied topics also judge, in practice third parties do so.
- ❑ Judgments may be given in binary form, or on a Likert scale.

Every retrieval system has parameters. Parameter optimization must use an experimental setup (training, validation) different from that used for evaluation (test).

Remarks:

- ❑ This setup is sometimes referred to as an experiment under the Cranfield paradigm, in reference to Cyril Cleverdon's series of projects at the Cranfield University in the 1960s, which first used this evaluation methodology. [\[codalism.com 1\]](#) [\[codalism.com 2\]](#)
- ❑ In linguistics, a corpus (plural corpora) or text corpus is a large and structured set of texts. They are used to carry out statistical analysis and hypothesis testing, checking occurrences or validating linguistic rules within a specific language territory. [\[Wikipedia\]](#)

The term has been adopted in various other branches of the human language technologies.

- ❑ The evaluation corpus split between training, validation, and test set should be used in conjunction with k -fold cross-validation, since the variance of performance results is often high. [\[Fuhr 2017\]](#)

Laboratory Experiments

Experimental Setup: Document Collections / Corpora

For ad hoc retrieval, the [Text Retrieval Conference \(TREC\)](#) has organized evaluation tracks since 1992, inviting scientists to compete.

Key document collections used:

Collection	Documents	Size	Words/Doc.	Topics	Words/Query	Jdgmts/Query
CACM	3,204	2.2 MB	64	64	13.0	16
AP	242,918	0.7 GB	474	100	4.3	220
GOV2	25 million	426.0 GB	1073	150	3.1	180
ClueWeb09	1 billion	25.0 TB	459	200	2.5	821
ClueWeb12	733 million	27.3 TB	448	200	3.6	793
ClueWeb22B	200 million	11.7 TB	—	—	—	—

- ❑ CACM: titles and abstracts from Communications of the ACM 1958–1979
- ❑ AP: newswire documents from Associated Press 1988–1990
- ❑ GOV2: crawl of .gov domains early 2004
- ❑ ClueWeb: web crawls from 2009, 2012, and 2022 (not in use, yet)

Reusing experimental setups renders previous approaches comparable.

Remarks:

- ❑ TREC is organized by the United States National Institute of Standards and Technology (NIST). The conference has been key to popularize laboratory evaluation of retrieval systems; every year, evaluation tracks on [many different retrieval-related tasks](#) are organized.
- ❑ At TREC, usually 50 topics are provided per edition of a shared task. The ones from previous years can be used for training.
- ❑ Ad hoc retrieval has been studied in the [ad hoc tracks](#), the [terabyte tracks](#), and the [web tracks](#).
- ❑ Several initiatives similar to TREC have formed, namely [CLEF](#), [NTCIR](#), and [FIRE](#).

Laboratory Experiments

Experimental Setup: Topics

<topic number="794" type="single">

<query> pet therapy </query>

<description>

How are pets or animals used in therapy for humans and what are the benefits?

</description>

<narrative>

Relevant documents must include details of how pet or animal-assisted therapy is or has been used. Relevant details include information about pet therapy programs, descriptions of the circumstances in which pet therapy is used, the benefits of this type of therapy, the degree of success of this therapy, and any laws or regulations governing it.

</narrative>

</topic>

Remarks:

- ❑ The description element is a longer version of the query, clarifying it, since the short query itself may be ambiguous.
- ❑ The narrative field is optional. It usually describes the criteria for relevance and is used by assessors to carry out relevance judgments.
- ❑ Another topic type are faceted topics:

```
<topic number="265" type="faceted">
  <query>F5 tornado</query>
  <description>What were the ten worst tornadoes in the USA?</description>
  <subtopic number="1" type="inf">What were the ten worst tornadoes in the USA?</subtopic>
  <subtopic number="2" type="inf">Where is tornado alley?</subtopic>
  <subtopic number="3" type="inf">What damage can an F5 tornado do?</subtopic>
  <subtopic number="4" type="inf">Find information on tornado shelters.</subtopic>
  <subtopic number="5" type="nav">What wind speed defines an F5 tornado?</subtopic>
</topic>
```

Laboratory Experiments

Experimental Setup: Relevance Judgments

<topic number="794" type="single">

<query> pet therapy </query>

<description>

How are pets or animals used in therapy for humans and what are the benefits?

</description>

<narrative>

Relevant documents must include details of how pet or animal-assisted therapy is or has been used. Relevant details include information about pet therapy programs, descriptions of the circumstances in which pet therapy is used, the benefits of this type of therapy, the degree of success of this therapy, and any laws or regulations governing it.

</narrative>

</topic>

Laboratory Experiments

Experimental Setup: Relevance Judgments

<topic number="794" type="single">

<query> pet therapy </query>

<description>

How are pets or animals used in therapy?
What are the benefits?

</description>

<narrative>

Relevant documents must include details about animal-assisted therapy or details that include information about descriptions of the circumstances used, the benefits of this type of therapy, and any laws governing it.

</narrative>

</topic>

Secure | https://en.wikipedia.org/wiki/Canine_physical_therapy

Not logged in | [Talk](#) | [Contributions](#) | [Create account](#) | [Log in](#)


Article | **Talk** | [Read](#) | [Edit](#) | [View history](#) |

Canine physical therapy

From Wikipedia, the free encyclopedia

Physical therapy for canines, or **canine rehabilitation**, adapts human physical therapy techniques to increase function and mobility of joints and muscles in animals. Animal rehabilitation can reduce pain and enhance recovery from injury, surgery, degenerative diseases, age-related diseases, and obesity.^[1]

The goal of physical therapy for animals is to improve quality of life and decrease pain. Although most veterinary practices offering physical therapy are geared toward canines, techniques used in this discipline can also be applied to horses, cats, birds, rabbits, rodents and other small animals.^[2]



Hydrotherapy is one of the many physical therapy techniques used at animal physical therapy practices. Above, a veterinary technician assists a dog to swim.

Classification and external resources

[\[edit on Wikidata\]](#)

Contents [hide]

- History
- Education
 - 1 The University of Tennessee
- Techniques
 - 3.1 Massage
 - 3.2 Thermo and cryotherapy
 - 3.3 Passive range of motion
 - 3.4 Balance Exercises
 - 3.5 Coordination exercises
 - 3.6 Strengthening exercises
 - 3.7 Hydrotherapy
 - 3.8 Electrical Stimulation
 - 3.9 Acupuncture
- References

History [edit]

The benefits of physical therapy for animals have been widely accepted in the veterinary community for many years. However, clinical practice of physical therapy for animals is a relatively new field in the U.S. In Europe, equine and canine physical therapy have been widely recommended and used for at least the last fifteen years. In the last three to five years, the veterinary community in the U.S. has seen a large growth in physical therapy practices for animals, making it a more available resource for practicing veterinarians.

Laboratory Experiments

Experimental Setup: Relevance Judgments

<topic number="794" type="single">

<query> pet therapy </query>

<description>

How are pets or animals used in the laboratory?
What are the benefits?

</description>

<narrative>

Relevant documents must include details about animal-assisted therapy is or has been used. Details include information about the circumstances used, the benefits of this type of therapy, and any laws governing it.

</narrative>

</topic>

Secure | https://en.wikipedia.org/wiki/Canine_physical_therapy

Not logged in | Talk | Contributions | Create account | Log in


Article | Talk | Read | Edit | View history | Search Wikipedia

Canine physical therapy

From Wikipedia, the free encyclopedia

Physical therapy for canines, or **canine rehabilitation**, adapts human physical therapy techniques to increase function and mobility of joints and muscles in animals. Animal rehabilitation can reduce pain and enhance recovery from injury, surgery, degenerative diseases, age-related diseases, and obesity.^[1]

The goal of physical therapy for animals is to improve quality of life and decrease pain. Although most veterinary practices offering physical therapy are geared toward canines, techniques used in this discipline can also be applied to horses, cats, birds, rabbits, rodents and other small animals.^[2]



Hydrotherapy is one of the many physical therapy techniques used at animal physical therapy practices. Above, a veterinary technician assists a dog to swim.

Classification and external resources [edit on Wikidata]

Contents [hide]

- History
- Education
 - 1 The University of Tennessee
- Techniques
 - 3.1 Massage
 - 3.2 Thermo and cryotherapy
 - 3.3 Passive range of motion
 - 3.4 Balance Exercises
 - 3.5 Coordination exercises
 - 3.6 Strengthening exercises
 - 3.7 Hydrotherapy
 - 3.8 Electrical Stimulation
 - 3.9 Acupuncture
- References

History [edit]

The benefits of physical therapy for animals have been widely accepted in the veterinary community for many years. However, clinical practice of physical therapy for animals is a relatively new field in the U.S. In Europe, equine and canine physical therapy have been widely recommended and used for at least the last fifteen years. In the last three to five years, the veterinary community in the U.S. has seen a large growth in physical therapy practices for animals, making it a more available resource for practicing veterinarians.

non-relevant

Laboratory Experiments

Experimental Setup: Relevance Judgments

<topic number="794" type="single">

<query> pet therapy </query>

<description>

How are pets or animals used in therapy?
What are the benefits?

</description>

<narrative>

Relevant documents must include details about animal-assisted therapy is or has included information about descriptions of the circumstances used, the benefits of this type of success of this therapy, and any laws governing it.

</narrative>

</topic>

Secure | https://en.wikipedia.org/wiki/Animal-assisted_therapy


Not logged in | Talk | Contributions | Create account | Log in

Article | Talk | Read | Edit | View history | Search Wikipedia

Animal-assisted therapy

From Wikipedia, the free encyclopedia

Animal-assisted therapy (AAT) is a type of therapy that involves animals as a form of treatment. The goal of AAT is to improve a patient's social, emotional, or cognitive functioning. Advocates state that animals can be useful for educational and motivational effectiveness for participants.^[1] A therapist who brings along a pet may be viewed as being less threatening, increasing the rapport between patient and therapist.^[2] Animals used in therapy include domesticated pets, farm animals and marine mammals (such as dolphins). The research literature states concerns about the poor quality of medical evidence underpinning AAT.^[3]



Dogs are common in animal-assisted therapy.

Wilson's (1984) **biophilia hypothesis** is based on the premise that our attachment to and interest in animals stems from the strong possibility that human survival was partly dependent on signals from animals in the environment indicating safety or threat. The biophilia hypothesis suggests that now, if we see animals at rest or in a peaceful state, this may signal to us safety, security and feelings of well-being which in turn may trigger a state where personal change and healing are possible.^[4] A contrast is sometimes made with *Animal assisted activity* (AAA).^[5] AAA is more casual and unstructured than AAT, involving perhaps more than one patient and with the primary focus on the presence of the animal itself. By contrast, AAT includes a handler which together with the animal has been trained for the role. AAT is more structured with specific objectives for each session. However, in common usage terms like these for animal assisted interventions are often used rather loosely.^[6]

Contents [hide]

- 1 Medical uses
 - 1.1 Pediatric care
 - 1.2 Institutional care
 - 1.3 Prisons
 - 1.4 Nursing homes
- 2 Types
 - 2.1 Dolphin therapy
 - 2.2 Equine-related therapy
- 3 Effectiveness
 - 3.1 Dementia
- 4 History
- 5 See also
- 6 References
- 7 External links

relevant

Laboratory Experiments

Experimental Setup: Relevance Judgments

A relevance judgment requires the **manual** assessment of whether a document returned by a retrieval system for a given query is relevant for a given topic.

Assessment depth

- ❑ Assessment does not scale with the number of documents retrieved by retrieval systems.
- ❑ A sampling strategy called pooling is used.

Assessment scale

- ❑ Binary scale: relevant and non-relevant
- ❑ n -point Likert scale of degrees of relevance: from non-relevant (0) to highly relevant ($n \leq 5$)

Assessor selection and instruction

- ❑ The people who had the information needs underlying the topics, if available.
- ❑ Volunteer assessors who receive training and exhaustive topics.

Assessor reliability

- ❑ Assessors make errors, which affects the objectivity of the results.
- ❑ Multiple assessments can be used to verify the reliability of assessors and assessments.

Remarks:

- ❑ At TREC, assessors are recruited from retired NIST staff:



Laboratory Experiments

Experimental Setup: Pooling

Pooling is a sampling strategy for documents retrieved by to-be-evaluated retrieval systems for a given set of topics.

For each topic:

1. Collect the top- k results returned by each retrieval system (variant).
2. Merge the results, omitting duplicates, obtaining a “pool” of documents.
3. Present the pool of documents in random order to assessors.

Caveats:

- ❑ Only documents “considered” relevant enough by one of the participating retrieval system are analyzed.
- ❑ All documents ranked below the pooling depth are deemed non-relevant by default, regardless the truth.
- ❑ New retrieval systems that are evaluated later may retrieve many unjudged documents; probably requiring new judgments from different assessors.

Laboratory Experiments

Assessor Reliability

The degree of agreement between assessors and the degree of consistency of the same assessor are quantified using assessor reliability measures. Lack of agreement or consistency indicate flawed setups or insufficient training.

Assessor reliability is measured whenever ambiguous or subjective decisions have to be made. Relevance is a subjective notion.

Several alternative approaches have been proposed:

- ❑ **Joint probability of agreement**

Percentage of times the raters agree. Here, agreement by chance is not taken into account.

- ❑ **Kappa Statistics**

Improvement over joint probability, taking into account agreement by chance.

- ❑ **Correlation coefficient**

Pairwise correlation among assessors on ordered scales. Full rankings are required.

Laboratory Experiments

Assessor Reliability: Kappa Statistics

Given the judgments of two annotators on a given topic, a kappa statistic measures their agreement as follows:

$$\kappa = \frac{p_o - p_e}{1 - p_e},$$

where p_o denotes the proportion of agreement observed, and p_e the expected proportion of agreement by chance.

Properties:

- $\kappa \in (-\infty, 1]$, where 1 indicates perfect agreement, 0 random agreement, and $\kappa < 0$ has no meaningful interpretation [\[Kvålseth 2015\]](#)
- At $p_e = 1$, κ is undefined.
- $p_o - p_e$ denotes the agreement **attained** above chance
- $1 - p_e$ denotes the agreement **attainable** above chance

Laboratory Experiments

Assessor Reliability: Kappa Statistics

Given the judgments of two annotators on a given topic, a kappa statistic measures their agreement as follows:

$$\kappa = \frac{p_o - p_e}{1 - p_e},$$

where p_o denotes the proportion of agreement observed, and p_e the expected proportion of agreement by chance.

Suppose A and B are two annotators asked to make n binary relevance judgments. Then a simple kappa statistic can be computed as follows:

		B		Σ
		yes	no	
A	yes	a	b	c
	no	d	e	f
Σ		g	h	n

$$p_o = \frac{a + e}{n}$$

$$p_e = P(\text{yes})^2 + P(\text{no})^2$$

$$P(\text{yes}) = \frac{c + g}{2n}, \quad P(\text{no}) = \frac{f + h}{2n}$$

Laboratory Experiments

Assessor Reliability: Kappa Statistics

Given the judgments of two annotators on a given topic, a kappa statistic measures their agreement as follows:

$$\kappa = \frac{p_o - p_e}{1 - p_e},$$

where p_o denotes the proportion of agreement observed, and p_e the expected proportion of agreement by chance.

Suppose A and B are two annotators who made the following $n = 400$ binary relevance judgments. The simple kappa statistic then yields:

		B		Σ
		yes	no	
A	yes	300	20	320
	no	10	70	80
Σ		310	90	400

$$p_o = \frac{300 + 70}{400}$$

$$p_e = P(\text{yes})^2 + P(\text{no})^2$$

$$P(\text{yes}) = \frac{320 + 310}{2 \cdot 400}, \quad P(\text{no}) = \frac{80 + 90}{2 \cdot 400}$$

$$\kappa = 0.776$$

Remarks:

- ❑ Well-known kappa statistics include Cohen's κ , Scott's π , and Fleiss' κ .
- ❑ Scott's π is the one exemplified.
- ❑ Fleiss' κ is a generalization of Scott's π to arbitrary numbers of annotators and categories. It also does not presume that all cases have been annotated by the same group of people.
- ❑ Presuming that annotators A and B work independently, the probability $P(\text{yes})^2$ (and similarly $P(\text{no})^2$) denotes the probability of both voting yes (no) by chance. Another way of computing p_e is to sum the multiplication of the rater-specific probabilities of each rater voting yes (no).
- ❑ Some assign the following interpretations to κ values measured (disputed):

κ	Agreement
< 0	poor
0.01 – 0.20	slight
0.21 – 0.40	fair
0.41 – 0.60	moderate
0.61 – 0.80	substantial
0.81 – 1.00	almost perfect

[\[Wikipedia\]](#)

- ❑ Within TREC evaluations, typically a “substantial” agreement ($\kappa \approx [0.67, 0.8]$) is achieved.

[Manning 2008]