

Chapter NLP:V

V. Syntax



- ☐ Introduction
- ☐ Context-Free Grammar
- ☐ **Dependency Grammars**
- ☐ Features and Unification

Dependency Grammars

Definition

Dependency grammars describe syntax with a directed **head-dependent relationship** between words.

- There is exactly one **root** (usually the verb).
 - Each word has 1 head and 0– n dependents.
 - The head-dependent relation has a **grammatical function**.
 - There is a single path from root to each vertex.
- Dependency structures are directed, acyclic, single-headed trees.



Dependency Grammars

Properties of Dependencies

Text features can be exploited in dependency parsing:

Plausibility Some dependencies are more plausible than others.

“issues → the” is more plausible than “the → issues”.


Distance Dependencies more often hold between nearby words.

Long-distance dependencies are often problematic.

“Ich **muss** um 17 Uhr mit dem Bus nach Hause *fahren*.”.

Breaks Dependencies rarely span intervening verbs or punctuation.

Valency Usual numbers of dependents for a head on each side.



Remarks:

- ❑ Dependencies often approximate semantic relationships. Knowing the head-dependent relations of a sentence is very useful for coreference resolution, question answering, and information extraction.
- ❑ Lexicalized CFGs often add the head relation.

Dependency Grammars

Dependency Treebanks: Universal Dependencies [\[UD, 2021\]](#)

The largest treebank for dependencies is **Universal Dependencies** with “nearly 200 treebanks in over 100 languages”.

UD uses the CoNLL-U format to store dependency annotations:

| ID | Lexic | | Morphology | | | Syntax | | |
|----|-------|-------|------------|------|-------|--------|--------|-----------------|
| | Form | Lemma | UPOS | XPOS | Feats | Head | Deprel | Deps |
| 1 | They | they | PRON | PRP | ... | 2 | nsubj | 2:nsubj 4:nsubj |
| 2 | buy | buy | VERB | VBP | ... | 0 | root | 0:root |
| 3 | and | and | CONJ | CC | ... | 4 | cc | 4:cc |
| 4 | sell | sell | VERB | VBP | ... | 2 | conj | 0:root 2:conj |
| 5 | books | book | NOUN | NNS | ... | 2 | obj | 2:obj 4:obj |
| 6 | . | . | PUNCT | . | ... | 2 | punct | 2:punct |

- ❑ **Head:** The ID of the head of this item.
- ❑ **Deprel:** The dependency relation.
- ❑ **Deps:** A head:relation list of the **Enhanced Dependencies**, which includes advanced concepts but escalates the dependency tree to a graph.

Dependency Grammars

Universal Dependency Relations [de Marneffe et al., 2014]

The UD annotation guidelines use 37 “universal syntactic relations”.

Example selection of dependency relations:

| Relation | Description | Example with head and dependent |
|--------------------------|-----------------------------|--|
| <i>Clausal Arguments</i> | | |
| NSUBJ | Nominal subject | United canceled the flight. |
| DOBJ | Direct object | We booked her the flight to Miami. |
| IOBJ | Indirect object | We booked her the flight to Miami. |
| <i>Nominal Modifier</i> | | |
| NMOD | Nominal modifier | We took the morning flight. |
| AMOD | Adjectival modifier | Book the cheapest flight. |
| CASE | Pre- and postpositions, ... | Book the flight through Houston. |
| <i>Others</i> | | |
| CONJ | Conjunct | We flew to Denver and drove to Steamboat. |
| CC | Coordinating conjunction | We flew to Denver and drove to Steamboat. |

Dependency Grammars

Universal Dependency Relations [de Marneffe et al., 2014]

The UD annotation guidelines use 37 “universal syntactic relations”.

Example selection of dependency relations:

| Relation | Description | Example with head and dependent |
|--------------------------|-----------------------------|---|
| <i>Clausal Arguments</i> | | |
| NSUBJ | Nominal subject | United canceled the flight. |
| DOBJ | Direct object | We booked her the flight to Miami. |
| IOBJ | Indirect object | We booked her the flight to Miami. |
| <i>Nominal Modifier</i> | | |
| NMOD | Nominal modifier | We took the morning flight. |
| AMOD | Adjectival modifier | Book the cheapest flight. |
| CASE | Pre- and postpositions, ... | Book the flight through Houston. |
| <i>Others</i> | | |
| CONJ | Conjunct | We flew to Denver and drove to Steamboat. |
| CC | Coordinating conjunction | We flew to Denver and drove to Steamboat. |

Dependency Grammars

Universal Dependency Relations [de Marneffe et al., 2014]

The UD annotation guidelines use 37 “universal syntactic relations”.

Example selection of dependency relations:

| Relation | Description | Example with head and dependent |
|--------------------------|-----------------------------|---|
| <i>Clausal Arguments</i> | | |
| NSUBJ | Nominal subject | United canceled the flight. |
| DOBJ | Direct object | We booked her the flight to Miami. |
| IOBJ | Indirect object | We booked her the flight to Miami. |
| <i>Nominal Modifier</i> | | |
| NMOD | Nominal modifier | We took the morning flight. |
| AMOD | Adjectival modifier | Book the cheapest flight. |
| CASE | Pre- and postpositions, ... | Book the flight through Houston. |
| <i>Others</i> | | |
| CONJ | Conjunct | We flew to Denver and drove to Steamboat. |
| CC | Coordinating conjunction | We flew to Denver and drove to Steamboat. |

Dependency Grammars

Transition-based parsing [Nivre, 2008]

Dependency trees can be parsed in linear time using an incremental transition system S and an oracle o :

$$S = (C, T, c_s, C_t)$$

C Set of configurations $\{(\beta_1, A_1), (\beta_2, A_2), \dots\}$

β is a buffer of remaining nodes

A is a set of dependency arcs

T Set of transitions $t : C \rightarrow C$

c_s Initialization function mapping w_1, \dots, w_n to (β, A) with $\beta = [1, \dots, n], A = \emptyset$

C_t Set of terminal configurations (parses) $C_t \subseteq C$

Dependency Grammars

Transition-based parsing [Nivre, 2008]

Dependency trees can be parsed in linear time using an incremental transition system S and an oracle o :

$$S = (C, T, c_s, C_t)$$

C Set of configurations $\{(\beta_1, A_1), (\beta_2, A_2), \dots\}$

β is a buffer of remaining nodes

A is a set of dependency arcs

T Set of transitions $t : C \rightarrow C$

c_s Initialization function mapping w_1, \dots, w_n to (β, A) with $\beta = [1, \dots, n], A = \emptyset$

C_t Set of terminal configurations (parses) $C_t \subseteq C$

- The buffer β never increases.
- If β is empty, the parser terminates. a C_t should have been reached
- A never decreases. arcs are only added, never removed

Dependency Grammars

Transition-based parsing [Nivre, 2008]

Dependency trees can be parsed in linear time using an incremental transition system S and an oracle o :

$$S = (C, T, c_s, C_t)$$

C Set of configurations $\{(\beta_1, A_1), (\beta_2, A_2), \dots\}$

β is a buffer of remaining nodes

A is a set of dependency arcs

T Set of transitions $t : C \rightarrow C$

c_s Initialization function mapping w_1, \dots, w_n to (β, A) with $\beta = [1, \dots, n], A = \emptyset$

C_t Set of terminal configurations (parses) $C_t \subseteq C$

There is an **oracle** $o : C \rightarrow T$:


- ❑ The oracle determines the next transition given the current configuration. the history of buffers and arcs
- ❑ S applies the determined transition, leading to the next configuration.

Dependency Grammars

Arc-Standard Parsing

Arc-Standard is a transition-based parser with a stack σ and 3 transitions T :

- SHIFT Remove the first node from β and push it to σ .
- LEFT Add an arc from the first node in β to the top of σ .
Pop σ . Don't LEFT if top of stack is `root` or top of stack has a head
- RIGHT Add an arc from the top of σ to the first node in β .
Replace the first node in β with the top of σ .
Pop σ . Don't RIGHT if the first node in β has a head




Dependency Grammars

Arc-Standard Parsing

Arc-Standard is a transition based parser with a stack σ and 3 transitions T :

- SHIFT** Remove the first node from β and push it to σ .
- LEFT** Add an arc from the first node in β to the top of σ .
Pop σ . Don't **LEFT** if top of stack is `root` or top of stack has a head
- RIGHT** Add an arc from the top of σ to the first node in β .
Replace the first node in β with the top of σ .
Pop σ . Don't **RIGHT** if the first node in β has a head




| Transition | Stack σ | Buffer β | Relations A |
|--------------------|----------------|------------------------------------|---------------|
| init \rightarrow | [root] | [colorless, green, ..., furiously] | – |

Dependency Grammars

Arc-Standard Parsing

Arc-Standard is a transition based parser with a stack σ and 3 transitions T :

- SHIFT** Remove the first node from β and push it to σ .
- LEFT** Add an arc from the first node in β to the top of σ .
Pop σ . Don't **LEFT** if top of stack is `root` or top of stack has a head
- RIGHT** Add an arc from the top of σ to the first node in β .
Replace the first node in β with the top of σ .
Pop σ . Don't **RIGHT** if the first node in β has a head




| Transition | Stack σ | Buffer β | Relations A |
|---------------------|-------------------|---------------------------------------|---------------|
| init \rightarrow | [root] | [colorless, green, . . . , furiously] | – |
| SHIFT \rightarrow | [root, colorless] | [green, ideas, sleep, furiously] | – |

Dependency Grammars

Arc-Standard Parsing

Arc-Standard is a transition based parser with a stack σ and 3 transitions T :

- SHIFT** Remove the first node from β and push it to σ .
- LEFT** Add an arc from the first node in β to the top of σ .
Pop σ . Don't **LEFT** if top of stack is `root` or top of stack has a head
- RIGHT** Add an arc from the top of σ to the first node in β .
Replace the first node in β with the top of σ .
Pop σ . Don't **RIGHT** if the first node in β has a head




| Transition | Stack σ | Buffer β | Relations A |
|---------------------|--------------------------|---------------------------------------|---------------|
| init \rightarrow | [root] | [colorless, green, . . . , furiously] | – |
| SHIFT \rightarrow | [root, colorless] | [green, ideas, sleep, furiously] | – |
| SHIFT \rightarrow | [root, colorless, green] | [ideas, sleep, furiously] | – |

Dependency Grammars

Arc-Standard Parsing

Arc-Standard is a transition based parser with a stack σ and 3 transitions T :

- SHIFT** Remove the first node from β and push it to σ .
- LEFT** Add an arc from the first node in β to the top of σ .
Pop σ . Don't LEFT if top of stack is root or top of stack has a head
- RIGHT** Add an arc from the top of σ to the first node in β .
Replace the first node in β with the top of σ .
Pop σ . Don't RIGHT if the first node in β has a head




| Transition | Stack σ | Buffer β | Relations A |
|---------------------|--------------------------|---------------------------------------|--|
| init \rightarrow | [root] | [colorless, green, . . . , furiously] | – |
| SHIFT \rightarrow | [root, colorless] | [green, ideas, sleep, furiously] | – |
| SHIFT \rightarrow | [root, colorless, green] | [ideas, sleep, furiously] | – |
| LEFT \rightarrow | [root, colorless] | [ideas, sleep, furiously] | $A \cup (\text{ideas} \rightarrow \text{green})$ |

Dependency Grammars

Arc-Standard Parsing

Arc-Standard is a transition based parser with a stack σ and 3 transitions T :

- SHIFT** Remove the first node from β and push it to σ .
- LEFT** Add an arc from the first node in β to the top of σ .
Pop σ . Don't **LEFT** if top of stack is `root` or top of stack has a head
- RIGHT** Add an arc from the **top of σ** to the **first node in β** .
Replace the **first node in β** with the **top of σ** .
Pop σ . Don't **RIGHT** if the first node in β already has a head




| Transition | Stack σ | Buffer β | Relations A |
|---------------------|-----------------------|----------------------|--|
| ... | | | |
| SHIFT \rightarrow | [root, sleep] | [furiously] | |
| RIGHT \rightarrow | [root] | [sleep] | $A \cup (\text{sleep} \rightarrow \text{furiously})$ |

Dependency Grammars

Arc-Standard Parsing

Complete transition sequence until termination. A now contains all relations.



| Transition | Stack σ | Buffer β | Relations A |
|---------------------|--------------------------|---------------------------------------|--|
| init \rightarrow | [root] | [colorless, green, . . . , furiously] | – |
| SHIFT \rightarrow | [root, colorless] | [green, ideas, sleep, furiously] | – |
| SHIFT \rightarrow | [root, colorless, green] | [ideas, sleep, furiously] | – |
| LEFT \rightarrow | [root, colorless] | [ideas, sleep, furiously] | $A \cup (\text{ideas} \rightarrow \text{green})$ |
| LEFT \rightarrow | [root] | [ideas, sleep, furiously] | $A \cup (\text{ideas} \rightarrow \text{colorless})$ |
| SHIFT \rightarrow | [root, ideas] | [sleep, furiously] | – |
| LEFT \rightarrow | [root] | [furiously] | $A \cup (\text{sleep} \rightarrow \text{ideas})$ |
| SHIFT \rightarrow | [root, sleep] | [furiously] | – |
| RIGHT \rightarrow | [root] | [sleep] | $A \cup (\text{sleep} \rightarrow \text{furiously})$ |
| RIGHT \rightarrow | [] | [root] | $A \cup (\text{root} \rightarrow \text{sleep})$ |
| SHIFT \rightarrow | [root] | [] | – |

Dependency Grammars

Arc-Standard Parsing: Oracles

The oracle $o : C \rightarrow T$ predicts which transition in $T = \{\text{SHIFT}, \text{LEFT}, \text{RIGHT}\}$ is next.

- Usually classification models, neural or feature based.
- Typical features are based on the stack, buffer, and previous decisions.
→ similar to span-based sequence labeling.

Some training examples with class c_i :

$$\begin{aligned} o((\text{Top of } \sigma_{i-1}, \text{POS of } \sigma_{i-1}, \text{Top of } \beta_{i-1}, \text{POS of } \beta_{i-1}, c_{i-1}, c_{i-2})) &= c_i \\ o((\text{green, JJ, idea, NN, Shift, Shift})) &= \text{LEFT} \\ o((\text{colorless, JJ, idea, NN, Left, Shift})) &= \text{LEFT} \\ o((\text{root, root, idea, NN, Left, Left})) &= ? \end{aligned}$$

| i | $o(C_{i-1})$ | Configuration C_i | | |
|-----|--------------|--------------------------|---------------------------|--|
| | | Stack σ | Buffer β | Relations A |
| 3 | SHIFT → | [root, colorless, green] | [ideas, sleep, furiously] | – |
| 4 | LEFT → | [root, colorless] | [ideas, sleep, furiously] | $A \cup (\text{ideas} \rightarrow \text{green})$ |
| 5 | LEFT → | [root] | [ideas, sleep, furiously] | $A \cup (\text{ideas} \rightarrow \text{colorless})$ |

Dependency Grammars

Arc-Standard Parsing: Oracles

Training data can be generated from reference treebank parses:

- Transition through arc-standard as done when parsing.
- Instead of using the oracle, select the transition from the reference parse in this order:
 1. Use `LEFT` if (First of $\beta \rightarrow$ Top of σ) is in the reference parse.
 2. Else, use `RIGHT` if
 - (a) (Top of $\sigma \rightarrow$ First of β) is in the reference parse and
 - (b) all dependents of First of β are assigned.
otherwise, First of β would vanish before all dependents were assigned.
 3. Else, use `SHIFT`.

The arc-standard parse table can be reproduced from its reference parse in this way. The features to train the oracle can then be derived from the parse table.

Dependency Grammars

Remarks:

- ❑ There are several extensions to arc-standard, changing the transition rules. *Arc-eager*, for example, adds a `REDUCE` operator.
- ❑ Since the greedy transition system forces a decision and can't revise them, there are frequent errors with, for example, long-distance dependencies. A beam search can mitigate this.
- ❑ Predicting the dependency relations is done by extending the transitions to
$$T = \{\text{SHIFT}, \text{RIGHT}_{nsubj}, \text{LEFT}_{nsubj}, \text{RIGHT}_{dobj}, \dots\}$$

Dependency Grammars

Projectivity [McDonald et al., 2005]

Definition 1 (Projectivity)

A dependency relation (arc) is projective if there is a **path** from the **head** of the relation to **every word between head and dependent**.

A dependency tree is projective if every arc in it is projective.

- ❑ Common in languages with free word (and attachment) order.
- ❑ Standard transition-based parsers can not parse non-projective trees.
- ❑ Trees are projective when generated from CFG's. *via head-finding rules*
- ❑ In non-projective trees, the arcs overlap.



Dependency Grammars


Graph-based Parsing

Idea: Use graph-algorithms to find the best dependency tree in a fully-connected, directed, weighted graph.

- ❑ More accurate on long-distance dependencies.
- ❑ Can solve projective sentences.

Two problems to solve:

1. How to assign scores to each edge?
→ Machine Learning
2. How to find the best parse?
→ Maximum Spanning Tree



Graph construction:

- ❑ Create vertices for each word.
- ❑ Create a directed connection from each vertex to all other vertices.
- ❑ Create a root vertex.
- ❑ Create a directed connection from the root to all other vertices.

Dependency Grammars


Evaluation

Dependency parsing is evaluated with the **Unlabeled Attachment Score** (UAS) and the **Labeled Attachment Score** (LAS). Both are similar to accuracy.

Unlabeled Attachment Score:

- ❑ Fraction of correctly attached heads.
- ❑ Independent of the assigned label.
- ❑ Example: $4/5 = 0.8$.
green has the wrong head.


Reference parse:



Labeled Attachment Score:

- ❑ Fraction of correctly attached heads and labels.
- ❑ Example: $3/5 = 0.6$.
green has the wrong head.
(sleep ***dobj*** furiously) has a wrong label.

System output:



Dependency Grammars

Evaluation: Comparison of Methods

- All on the same setting: Stanford Dependency conversion of the Penn Treebank.

| Approach | Source | UAS | LAS |
|--|----------------------------------|------|------|
| Large Language Models | [Mrini et al., 2019] | 97.4 | 96.3 |
| Transition (beam search, dense features) | [Weiss, 2015] | 94.0 | 92.0 |
| Transition (arc-hybrid, LSTM features) | [Kiperwasser and Goldberg, 2016] | 93.9 | 91.9 |
| Transition (arc-hybrid, LSTM features) | [Dallesteros, 2016] | 93.8 | 91.5 |
| Graph (LSTM features) | [Kiperwasser and Goldberg, 2016] | 93.0 | 90.9 |
| Transition (arc-eager, beam search) | [Zhang and Nivre, 2011] | 92.9 | |

- Note that the progress since 2011 is marginal.