Chapter IR:IV

IV. Indexes

- □ Inverted Indexes
- Query Processing
- □ Index Construction
- □ Index Compression

Index [ANSI/NISO 1997]

An index is a systematic guide designed to indicate topics or features of documents in order to facilitate retrieval of documents or parts of documents.

The function of an index is to provide users with an effective and systematic means for locating documentary units (complete documents or parts of documents) that are relevant to information needs or requests.

```
thesauri
                                                               vectors
    definition: 12
                                                                   definition: 12
titles of documents: 6.2.9, 6.2.9.4
                                                                  in searching: 7.5.2
    capitalization: 6.2.3
                                                               vertical spacing
   initial articles in alphanumeric arrangement: 9.4
                                                                   in indexes: 8.2.4
topical headings
                                                               video recordings
       see also: entries, headings, terms
                                                                   locators: 7.4.2b
                                                               visual indexes
   initial articles in alphanumeric arrangement: 9.4
                                                                  see: displayed indexes
topics
                                                               vocabulary: 6
   definition: 12
                                                                      see also: descriptors; terminology of indexing;
   major versus minor topics: 7.3
transcription
   definition: 12
                                                                  control, tracking, management: 3h, 5.13; as essential
                                                                          process: preface; definition: 12
transliteration: 6.2.10
                                                                  display in displayed indexes: 6.8.1; non-displayed
   definition: 12
truncation
                                                                          electronic search indexes: 6.8.2
   definition: 12
                                                                  entry. definition: 12
   in searching: 7.5.3
                                                                  lead-in: 5.13
turnover lines: 8.2.5.1, 8.2.5.3
                                                                  sources: 3d-e, 6.1
   definition: 12
```

Index [ANSI/NISO 1997]

Requirements:

- identify documentary units that treat particular topics or possess particular features.
- 2. indicate all important topics or features of documentary units in accordance with the level of exhaustivity appropriate for the index.
- 3. discriminate between major and minor treatments of particular topics or manifestations of particular features.
- 4. provide access to topics or features using the terminology of prospective users.
- 5. provide access to topics or features using the terminology of verbal texts being indexed whenever possible.

Index [ANSI/NISO 1997]

Requirements: (continued)

- 6. use terminology that is as specific as documentary units warrant and the indexing language permits.
- 7. provide access through synonymous and equivalent terms.
- 8. guide users to terms representing related concepts (narrower terms, other related terms, and if possible, broader terms).
- 9. provide for the combination of terms to facilitate the identification of particular types or aspects of topics or features and to eliminate unwanted types or aspects.
- 10. provide a means for searching for particular topics or features by means of a systematic arrangement of entries in displayed indexes or, for non-displayed indexes, by means of a clearly documented and displayed method for entering, combining, and modifying terms to create search statements and for reviewing retrieved items.

Remarks:

- Several standards worldwide govern the (manual) construction and formatting of indexes.
 [Gibbs 2015]
- □ ANSI = American National Standards Institute
- □ NISO = National Information Standards Organization

Data Structure

Term-document matrix:

	d_1	d_2	d_3	d_4	d_5	•••
$\overline{t_1}$	w_{1_1}	$oxed{w_{1_2}}$	w_{1_3}	$\boxed{w_{1_4}}$	w_{1_5}	
t_2	w_{2_1}	w_{2_2}	$\boxed{w_{2_3}}$	$\boxed{ w_{2_4}}$	w_{2_5}	
t_3	w_{3_1}	w_{3_2}	w_{3_3}	$oxed{w_{3_4}}$	w_{3_5}	
t_4	$\boxed{w_{4_1}}$	$oxed{w_{4_2}}$	$\boxed{w_{4_3}}$	$\boxed{ w_{4_4}}$	$oxed{w_{4_5}}$	
t_5	$\boxed{w_{5_1}}$	w_{5_2}	w_{5_3}	$\boxed{ w_{5_4}}$	w_{5_5}	
÷						

Observations:

- □ Most information retrieval models induce a term-document matrix by computing term weights w_{i_i} for each pair of term $t_i \in T$ and document $d_i \in D$.
- \Box Query-independent computations that only depend on D are done offline.
- \Box Online, given a query q, the term weights required are looked up to score documents.

Data Structure

Term-document matrix:

	d_1	d_2	d_3	d_4	d_5	
$\overline{t_1}$	w_{1_1}	$oxed{w_{1_2}}$	w_{1_3}	$\boxed{w_{1_4}}$	$oxed{w_{1_5}}$	
t_2	$\boxed{ \ w_{2_1} \ }$			$\boxed{ w_{2_4}}$	$\boxed{ w_{2_5}}$	
t_3		$\boxed{ w_{3_2}}$	$oxed{w_{3_3}}$			
t_4			lacksquare	$\boxed{ w_{4_4}}$		
t_5		$\boxed{ w_{5_2}}$				
÷						

Observations:

- \Box The size of the term-document matrix is $|T| \cdot |D|$.
- The term-document matrix is sparse: the vast majority of term weights are 0.
- Therefore, most of the storage space required for the full matrix is wasted.
- Using a sparse-matrix representation yields significant space savings.

Data Structure

Term-document matrix as inverted index data structure:

\overline{T}	Postings				
$\overline{t_1}$	$[d_1,w_{1_1}]$	$[d_2,w_{1_2}]$	$\boxed{d_3,w_{1_3}}$	$\boxed{d_4,w_{1_4}}$	$\boxed{d_5,w_{1_5}}$
t_2	$[d_1,w_{2_1}]$	$[d_4,w_{2_4}]$	$[d_5,w_{2_5}]$		
t_3	$[d_2,w_{3_2}]$	$[d_3, w_{3_3}]$			
t_4	$[d_3, w_{4_3}]$	$[d_4,w_{4_4}]$			
t_5	$[d_2,w_{5_2}]$				
÷					

Components:

□ Term vocabulary file

Lookup table which maps terms T to the start of their postings list in the postings file.

Postings file

File(s) that store postings lists on disk.

□ Index entries □ . . . , so-called postings

Data Structure

Term-document matrix as inverted index data structure:

\overline{T}	Postings				
$\overline{t_1}$	$\boxed{d_1,w_{1_1}}$	$[d_2,w_{1_2}]$	$[d_3,w_{1_3}]$	$[d_4,w_{1_4}]$	$[d_5,w_{1_5}]$
t_2	$[d_1,w_{2_1}]$	$[d_4,w_{2_4}]$	$[d_5,w_{2_5}]$		
t_3	$[d_2,w_{3_2}]$	$[d_3,w_{3_3}]$			
t_4	$[d_3,w_{4_3}]$	$[d_4,w_{4_4}]$			
t_5	$[d_2,w_{5_2}]$				
:					

Design choices:

- Information stored in a posting
- Ordering of each term's postings list
- Encoding and compression techniques for further space savings
- Physical implementation details, such as external memory and distribution

Remarks:

- □ The name "inverted index" is redundant: an index always maps terms to (parts of) documents where they occur. Better suited, but used less often, is "inverted file", which conveys that a (document) file is inverted to form an index.
- Some retrieval models do not assign zero weights, but default non-zero weights instead. Such weights can be omitted from an inverted index as well; they can be stored as a constant and used whenever a term weight for a given term-document pair is required that is not present in the inverted index.

Postings

Given term t and document d, their posting may include the following:

```
<document> [<weights>] [<position>] [...]
```

<document>:

 \Box Reference to the document d in which a given term t occurs.

<weights>:

- \Box Term weight w for term t in document d.
- \Box Term weights can be stored, say, tf(t,d) or the term weights of the retrieval model used. Saves query time computations, but fixes a retrieval model.

<position>:

- □ Term positions within the document, i.e., term, sentence, page, chapter, etc.
- □ Field information, e.g., title, author, introduction, etc.

Postings

Two special-purpose entries are distinguished:

<list length>:

- \Box First entry of the postings list of a term t.
- Stores the length of the postings list, excluding special-purpose entries.
- What does the length of a postings list indicate?

<skip pointer>:

- Used to implement a skip list in a term's postings list.
- \Box Allows for random access to postings in $O(\log n)$.
- \Box Second entry of a postings list, and then at random (or regular) intervals. An effective amount of skip entries has been found to be $\sqrt{df(t,D)}$.

Postings

Two special-purpose entries are distinguished:

```
... <skip pointer>
```

<list length>:

- \Box First entry of the postings list of a term t.
- Stores the length of the postings list, excluding special-purpose entries.
- \Box Corresponds to the document frequency df(t, D) of term t in collection D.

<skip pointer>:

- Used to implement a skip list in a term's postings list.
- \Box Allows for random access to postings in $O(\log n)$.
- \Box Second entry of a postings list, and then at random (or regular) intervals. An effective amount of skip entries has been found to be $\sqrt{df(t,D)}$.

Postings Lists

Example for two postings lists, where for term t_i postings k, $tf(t_i, d_k)$ are stored:

\overline{T}	Postings
:	
t_i	[2,4] $[4,9]$ $[8,2]$ $[16,1]$ $[19,7]$ $[23,5]$ $[28,6]$ $[41,8]$ $[50,6]$ $[77,8]$
t_{j}	[1,1] $[2,3]$ $[3,5]$ $[5,2]$ $[8,17]$ $[41,6]$ $[51,5]$ $[60,5]$ $[71,3]$ $[77,2]$
:	

Ordering:

- by document identifier. Problem: good documents may end up last.
- by term weight. Early termination, but renders skip lists useless.
- by document quality. Early termination, but renders skip lists useless.

Compression:

- \Box The size of an index is in O(|D|), where |D| denotes the disk size of D.
- Postings lists can be effectively compressed with tailored techniques.

Remarks:

- ☐ There is a tradeoff between the amount if information stored in a posting, and the time it takes to process a postings list in search of a document. The more information is stored in a posting, the more must be decoded or at least loaded into memory during postlist traversal.
- A skip entry may include more than one pointer, allowing for skip steps of various lengths.
- □ Dependent on the search scenario, constructing more than one index with different properties may be beneficial.