

Chapter IR:V

V. Retrieval Models

- ❑ Overview of Retrieval Models
- ❑ Empirical Models
- ❑ Boolean Retrieval
- ❑ Vector Space Model
- ❑ Probabilistic Models
- ❑ Binary Independence Model
- ❑ Okapi BM25
- ❑ Hidden Variable Models
- ❑ Latent Semantic Indexing
- ❑ Explicit Semantic Analysis
- ❑ Generative Models
- ❑ Language Models
- ❑ Combining Evidence
- ❑ Web Search
- ❑ Learning to Rank

Learning to Rank

Machine Learning and IR

- ❑ Considerable interaction between these fields
 - Rocchio algorithm (1960s) is a simple learning approach
 - 1980s, 1990s: learning ranking algorithms based on user feedback
 - 2000s: text categorization
- ❑ Limited by amount of training data
- ❑ Web query logs have generated new wave of research
 - e.g., “Learning to Rank”

Learning to Rank

Generative vs. Discriminative

- ❑ All probabilistic retrieval models presented so far fall into the category of generative models
 - Assume that documents were generated from some underlying model
 - Use training data to estimate the parameters of the model
 - Probability of belonging to a class (i.e., the relevant documents for a query) is then estimated using Bayes' Rule and the document model
- ❑ A discriminative model estimates the probability of belonging to a class directly from the observed features of the document based on the training data
- ❑ Generative models perform well with low numbers of training examples
- ❑ Discriminative models usually have the advantage given enough training data
 - Can also easily incorporate many features

Learning to Rank

Discriminative Models for IR

- ❑ Discriminative models can be trained using explicit relevance judgments or click data in query logs
 - Click data is much cheaper, more noisy
 - E.g., a Ranking Support Vector Machine (SVM) takes as input partial rank information for queries
 - Partial information about which documents should be ranked higher than others
 - Partial rank information comes from relevance judgments (allows multiple levels of relevance) or click data
 - E.g., d_1 , d_2 and d_3 are the documents in the first, second and third rank of the search output, only d_3 clicked on
 - (d_3, d_1) and (d_3, d_2) will be in desired ranking for this query