

# Chapter ML:VI

## VI. Decision Trees

- ❑ Decision Trees Basics
- ❑ Impurity Functions
- ❑ Decision Tree Algorithms
- ❑ Decision Tree Pruning

# Impurity Functions

## Splitting

Let  $t$  be a leaf node of an incomplete decision tree, and let  $D(t)$  be the subset of the example set  $D$  that is represented by  $t$ . [\[illustration\]](#)

Possible criteria for a splitting of  $X(t)$  :

1. Size of  $D(t)$ .
2. Purity of  $D(t)$ .
3. Impurity reduction of  $D(t)$ .

# Impurity Functions

## Splitting (continued)

Let  $t$  be a leaf node of an incomplete decision tree, and let  $D(t)$  be the subset of the example set  $D$  that is represented by  $t$ . [\[illustration\]](#)

Possible criteria for a splitting of  $X(t)$  :

1. Size of  $D(t)$ .

$D(t)$  is not split if  $|D(t)|$  is below a threshold.

2. Purity of  $D(t)$ .

$D(t)$  is not split if all examples in  $D(t)$  are members of the same class.


3. Impurity reduction of  $D(t)$ .

$D(t)$  is not split if its impurity reduction,  $\Delta_I$ , is below a threshold.

# Impurity Functions

## Splitting (continued)


Let  $X$  be a multiset of feature vectors,  $D \subseteq X$  a multiset of examples, and  $C = \{c_1, c_2, c_3, c_4\}$  a set of classes. Distribution of  $D$  for two splittings of  $X$ :



# Impurity Functions

## Splitting (continued)

Let  $X$  be a multiset of feature vectors,  $D \subseteq X$  a multiset of examples, and  $C = \{c_1, c_2, c_3, c_4\}$  a set of classes. Distribution of  $D$  for two splittings of  $X$ :



- ❑ Splitting (a) minimizes the *impurity* of the subsets of  $D$  in the leaf nodes and should be preferred over splitting (b). This argument presumes that the misclassification costs are independent of the classes.
- ❑ The impurity is a function defined on  $\mathcal{P}(D)$ , the set of all subsets of an example set  $D$ .

# Impurity Functions

## Definition 4 (Impurity Function $\iota$ )

Let  $k \in \mathbb{N}$ . An impurity function  $\iota : [0; 1]^k \rightarrow \mathbb{R}$  is a function defined on the standard  $k-1$ -simplex, denoted  $\Delta^{k-1}$ , for which the following properties hold:

- (a)  $\iota$  becomes minimum at points  $(1, 0, \dots, 0), (0, 1, \dots, 0), \dots, (0, \dots, 0, 1)$ .
- (b)  $\iota$  is symmetric with regard to its arguments,  $p_1, \dots, p_k$ .
- (c)  $\iota$  becomes maximum at point  $(1/k, \dots, 1/k)$ .

# Impurity Functions

## Definition 5 (Impurity of an Example Set $\iota(D)$ )

Let  $X$  be a multiset of feature vectors,  $C = \{c_1, \dots, c_k\}$  a set of classes and  $D \subseteq X \times C$  a multiset of examples. Moreover, let  $\iota : [0; 1]^k \rightarrow \mathbb{R}$  be an impurity function. Then, the impurity of  $D$ , denoted as  $\iota(D)$ , is defined as follows:

$$\iota(D) = \iota \left( \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|}, \dots, \frac{|\{(\mathbf{x}, c_k) \in D\}|}{|D|} \right)$$

# Impurity Functions

## Definition 5 (Impurity of an Example Set $\iota(D)$ )

Let  $X$  be a multiset of feature vectors,  $C = \{c_1, \dots, c_k\}$  a set of classes and  $D \subseteq X \times C$  a multiset of examples. Moreover, let  $\iota : [0; 1]^k \rightarrow \mathbf{R}$  be an impurity function. Then, the impurity of  $D$ , denoted as  $\iota(D)$ , is defined as follows:

$$\iota(D) = \iota \left( \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|}, \dots, \frac{|\{(\mathbf{x}, c_k) \in D\}|}{|D|} \right)$$

## Definition 6 (Impurity Reduction $\Delta\iota$ )

Let  $D_1, \dots, D_m$  be a splitting of an example set  $D$ , which is induced by a splitting of  $X$ . Then, the resulting impurity reduction, denoted as  $\Delta\iota(D, \{D_1, \dots, D_m\})$ , is defined as follows:

$$\Delta\iota(D, \{D_1, \dots, D_m\}) = \iota(D) - \sum_{l=1}^m \frac{|D_l|}{|D|} \cdot \iota(D_l)$$



## Remarks:

- $\Delta^{k-1}$  denotes the standard  $k-1$ -simplex, which contains all  $k$ -tuples with non-negative elements that sum to 1:

$$\Delta^{k-1} = \left\{ (p_1, \dots, p_k) \in \mathbf{R}^k : \sum_{i=1}^k p_i = 1 \text{ and } p_i \geq 0 \text{ for all } i \right\}$$

- Observe the different domains of the impurity function  $\iota$  in the definitions for  $\iota$  and  $\iota(D)$ , namely,  $[0; 1]^k$  and  $D$ . The domains correspond to each other: the set of examples,  $D$ , defines via its class ratios an element from  $[0; 1]^k$  and vice versa.
- The properties in the definition of the impurity function  $\iota$  suggest to minimize the external path length of  $T$  with respect to  $D$  in order to minimize the overall impurity characteristics of  $T$ .
- Within the DT-construct algorithm usually a greedy strategy (local optimization) is employed to minimize the overall impurity characteristics of a decision tree  $T$ .

# Impurity Functions

## Impurity Functions Based on the Misclassification Rate

Definition for two classes [impurity function] :

$$\iota_{misclass}(p_1, p_2) = 1 - \max\{p_1, p_2\} = \begin{cases} p_1 & \text{if } 0 \leq p_1 \leq 0.5 \\ 1 - p_1 & \text{otherwise} \end{cases}$$

# Impurity Functions

## Impurity Functions Based on the Misclassification Rate (continued)

Definition for two classes [impurity function] :

$$\iota_{misclass}(p_1, p_2) = 1 - \max\{p_1, p_2\} = \begin{cases} p_1 & \text{if } 0 \leq p_1 \leq 0.5 \\ 1 - p_1 & \text{otherwise} \end{cases}$$

$$\iota_{misclass}(D) = 1 - \max \left\{ \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|}, \frac{|\{(\mathbf{x}, c_2) \in D\}|}{|D|} \right\}$$

# Impurity Functions


## Impurity Functions Based on the Misclassification Rate (continued)

Definition for two classes [impurity function] :

$$\iota_{\text{misclass}}(p_1, p_2) = 1 - \max\{p_1, p_2\} = \begin{cases} p_1 & \text{if } 0 \leq p_1 \leq 0.5 \\ 1 - p_1 & \text{otherwise} \end{cases}$$

$$\iota_{\text{misclass}}(D) = 1 - \max \left\{ \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|}, \frac{|\{(\mathbf{x}, c_2) \in D\}|}{|D|} \right\}$$

Graph of the function  $\iota_{\text{misclass}}(p_1, 1 - p_1)$ , i.e., for two classes:



[Graphs: misclassification, entropy, Gini]

# Impurity Functions

## Impurity Functions Based on the Misclassification Rate (continued)

Definition for  $k$  classes:

$$\iota_{\text{misclass}}(p_1, \dots, p_k) = 1 - \max_{i=1, \dots, k} p_i$$


$$\iota_{\text{misclass}}(D) = 1 - \max_{c \in C} \frac{|\{(\mathbf{x}, c) \in D\}|}{|D|}$$

# Impurity Functions

## Impurity Functions Based on the Misclassification Rate (continued)

Problems:

- $\Delta \mathcal{L}_{\text{misclass}} = 0$  may hold for all possible splittings.
- The impurity function that is induced by the misclassification rate underestimates pure nodes, as illustrated in splitting (b):




# Impurity Functions

## Impurity Functions Based on the Misclassification Rate (continued)

Problems:

- $\Delta \iota_{\text{misclass}} = 0$  may hold for all possible splittings.
- The impurity function that is induced by the misclassification rate underestimates pure nodes, as illustrated in splitting (b):



$$\Delta \iota_{\text{misclass}} = \iota_{\text{misclass}}(D) - \left( \frac{|D_1|}{|D|} \cdot \iota_{\text{misclass}}(D_1) + \frac{|D_2|}{|D|} \cdot \iota_{\text{misclass}}(D_2) \right)$$

left splitting:  $\Delta \iota_{\text{misclass}} = \frac{1}{2} - \left( \frac{1}{2} \cdot \frac{1}{4} + \frac{1}{2} \cdot \frac{1}{4} \right) = \frac{1}{4}$

right splitting:  $\Delta \iota_{\text{misclass}} = \frac{1}{2} - \left( \frac{3}{4} \cdot \frac{1}{3} + \frac{1}{4} \cdot 0 \right) = \frac{1}{4}$

# Impurity Functions

## Definition 7 (Strict Impurity Function)

Let  $\iota : [0; 1]^k \rightarrow \mathbb{R}$  be an impurity function and let  $\mathbf{p}, \mathbf{p}' \in \Delta^{k-1}$ . Then  $\iota$  is called strict, if it is strictly concave:

$$(c) \rightarrow (c') \quad \iota(\lambda \mathbf{p} + (1-\lambda)\mathbf{p}') > \lambda \iota(\mathbf{p}) + (1-\lambda) \iota(\mathbf{p}'), \quad 0 < \lambda < 1, \mathbf{p} \neq \mathbf{p}'$$



# Impurity Functions

## Definition 7 (Strict Impurity Function)

Let  $\iota : [0; 1]^k \rightarrow \mathbb{R}$  be an impurity function and let  $\mathbf{p}, \mathbf{p}' \in \Delta^{k-1}$ . Then  $\iota$  is called strict, if it is strictly concave:

$$(c) \rightarrow (c') \quad \iota(\lambda \mathbf{p} + (1-\lambda)\mathbf{p}') > \lambda \iota(\mathbf{p}) + (1-\lambda) \iota(\mathbf{p}'), \quad 0 < \lambda < 1, \mathbf{p} \neq \mathbf{p}'$$

## Lemma 8

Let  $\iota$  be a *strict* impurity function and let  $D_1, \dots, D_m$  be a splitting of an example set  $D$ , which is induced by a splitting of  $X$ . Then the following inequality holds:

$$\Delta \iota(D, \{D_1, \dots, D_m\}) \geq 0$$

The equality is given iff for all  $i \in \{1, \dots, k\}$  and  $l \in \{1, \dots, m\}$  holds:

$$\frac{|\{(\mathbf{x}, c_i) \in D\}|}{|D|} = \frac{|\{(\mathbf{x}, c_i) \in D_l\}|}{|D_l|}$$

## Remarks:

- ❑ Equality means that the splitting of  $D$  resembles exactly the class distribution of  $D$ .
- ❑ Strict concavity entails Property (c) of the [impurity function](#) definition.
- ❑ For two classes, strict concavity means  $\iota(p_1, 1 - p_1) > 0$ , where  $0 < p_1 < 1$ .
- ❑ If  $\iota$  is a twice differentiable function, strict concavity is equivalent with a negative definite Hessian of  $\iota$ .
- ❑ With properly chosen coefficients, polynomials of second degree fulfill the Properties (a) and (b) of the [impurity function](#) definition as well as strict concavity. See impurity functions based on the [Gini index](#) in this regard.
- ❑ The impurity function that is induced by the misclassification rate is concave, but it is not strictly concave.
- ❑ The proof of Lemma 8 exploits the strict concavity property of  $\iota$ .

# Impurity Functions

## Impurity Functions Based on Entropy

### Definition 9 (Entropy)

Let  $A$  denote an event and let  $P(A)$  denote the occurrence probability of  $A$ . Then the entropy (self-information, information content) of  $A$  is defined as  $-\log_2(P(A))$ .

Let  $\mathcal{A}$  be an experiment with the exclusive outcomes (events)  $A_1, \dots, A_k$ . Then the mean information content of  $\mathcal{A}$ , denoted as  $H(\mathcal{A})$ , is called Shannon entropy or entropy of experiment  $\mathcal{A}$  and is defined as follows:

$$H(\mathcal{A}) = - \sum_{i=1}^k P(A_i) \cdot \log_2(P(A_i))$$

## Remarks:

- ❑ The smaller the occurrence probability of an event, the larger is its entropy. An event that is certain has zero entropy.
- ❑ The Shannon entropy combines the entropies of all outcomes of an experiment, using the outcome probabilities as weights.
- ❑ In the entropy definition we stipulate the identity  $0 \cdot \log_2(0) = 0$ .
- ❑ Related. Entropy encoding methods such as Huffman coding. [\[Wikipedia\]](#)
- ❑ Related. The perplexity of a discrete probability distribution  $p$  is defined as  $2^{H(p)}$ . [\[Wikipedia\]](#)

# Impurity Functions

## Impurity Functions Based on Entropy (continued)

### Definition 10 (Conditional Entropy, Information Gain)

Let  $\mathcal{A}$  be an experiment with the exclusive outcomes (events)  $A_1, \dots, A_k$ , and let  $\mathcal{B}$  be another experiment with the exclusive outcomes (events)  $B_1, \dots, B_m$ . Then the conditional entropy of the conditional experiment  $\mathcal{A} \mid \mathcal{B}$ , i.e., “the entropy of  $\mathcal{A}$  if the outcome of  $\mathcal{B}$  is known”, is defined as follows:

$$H(\mathcal{A} \mid \mathcal{B}) = \sum_{l=1}^m P(B_l) \cdot H(\mathcal{A} \mid B_l),$$

where  $H(\mathcal{A} \mid B_l) = - \sum_{i=1}^k P(A_i \mid B_l) \cdot \log_2(P(A_i \mid B_l))$

# Impurity Functions

## Impurity Functions Based on Entropy (continued)

### Definition 10 (Conditional Entropy, Information Gain)

Let  $\mathcal{A}$  be an experiment with the exclusive outcomes (events)  $A_1, \dots, A_k$ , and let  $\mathcal{B}$  be another experiment with the exclusive outcomes (events)  $B_1, \dots, B_m$ . Then the conditional entropy of the conditional experiment  $\mathcal{A} \mid \mathcal{B}$ , i.e., “the entropy of  $\mathcal{A}$  if the outcome of  $\mathcal{B}$  is known”, is defined as follows:

$$H(\mathcal{A} \mid \mathcal{B}) = \sum_{l=1}^m P(B_l) \cdot H(\mathcal{A} \mid B_l),$$

where  $H(\mathcal{A} \mid B_l) = - \sum_{i=1}^k P(A_i \mid B_l) \cdot \log_2(P(A_i \mid B_l))$

# Impurity Functions

## Impurity Functions Based on Entropy (continued)

### Definition 10 (Conditional Entropy, Information Gain)

Let  $\mathcal{A}$  be an experiment with the exclusive outcomes (events)  $A_1, \dots, A_k$ , and let  $\mathcal{B}$  be another experiment with the exclusive outcomes (events)  $B_1, \dots, B_m$ . Then the conditional entropy of the conditional experiment  $\mathcal{A} \mid \mathcal{B}$ , i.e., “the entropy of  $\mathcal{A}$  if the outcome of  $\mathcal{B}$  is known”, is defined as follows:

$$H(\mathcal{A} \mid \mathcal{B}) = \sum_{l=1}^m P(B_l) \cdot H(\mathcal{A} \mid B_l),$$

$$\text{where } H(\mathcal{A} \mid B_l) = - \sum_{i=1}^k P(A_i \mid B_l) \cdot \log_2(P(A_i \mid B_l))$$

The information **gain** owed to experiment  $\mathcal{B}$  is defined as follows:

$$H(\mathcal{A}) - H(\mathcal{A} \mid \mathcal{B}) = H(\mathcal{A}) - \sum_{l=1}^m P(B_l) \cdot H(\mathcal{A} \mid B_l)$$

Remarks [\[Bayes for classification\]](#) :

- Information gain is defined as reduction in entropy.
- In the context of decision trees, experiment  $\mathcal{A}$  corresponds to classifying feature vector  $\mathbf{x}$  with regard to the target concept. A question, whose answer will inform us about which of the events in  $A \in \mathcal{A}$  occurred, is the following:
  - “Does  $\mathbf{x}$  belong to class  $c$  ?” or
  - “ $C=c$  ?” (random variable  $C$  has realization  $c$ )

Likewise, experiment  $\mathcal{B}$  corresponds to evaluating feature  $j$  of feature vector  $\mathbf{x}$ . A question, whose answer will inform us about which of the events in  $B \in \mathcal{B}$  occurred, is the following:

- “Does  $\mathbf{x}$  have value  $a$  for feature  $j$  ?” or
  - “ $X_j=a$  ?” (random variable  $X_j$  has realization  $a$ )
- Rationale: Typically, the events “ $\mathbf{x}$  belongs to class  $c$ ” and “ $\mathbf{x}$  has value  $a$  for feature  $j$ ” are statistically dependent. Hence, the entropy of the event “ $\mathbf{x}$  belongs to class  $c$ ” will become smaller if we learn about the value of feature  $j$  of  $\mathbf{x}$  (recall that the class of  $\mathbf{x}$  is unknown). We experience an information gain with regard to the outcome of experiment  $\mathcal{A}$ , which is rooted in our information about the outcome of experiment  $\mathcal{B}$ . Under no circumstances the information gain will be negative; the information gain is zero if the involved events are *conditionally independent*:

$$P(A_i) = P(A_i \mid B_l), \quad i \in \{1, \dots, k\}, \quad l \in \{1, \dots, m\},$$

which leads to a split as specified as the special case in Lemma 8.



Remarks: (continued)

- Since  $H(\mathcal{A})$  is constant, the feature that provides the maximum information gain (= the maximally informative feature) is given by the minimization of  $H(\mathcal{A} \mid \mathcal{B})$ .
- The expanded form of  $H(\mathcal{A} \mid \mathcal{B})$  reads as follows:

$$H(\mathcal{A} \mid \mathcal{B}) = - \sum_{l=1}^m P(B_l) \cdot \sum_{i=1}^k P(A_i \mid B_l) \cdot \log_2(P(A_i \mid B_l))$$

# Impurity Functions

## Impurity Functions Based on Entropy (continued)

Definition for two classes [impurity function] :

$$\iota_{entropy}(p_1, p_2) = -(p_1 \cdot \log_2(p_1) + p_2 \cdot \log_2(p_2))$$

# Impurity Functions

## Impurity Functions Based on Entropy (continued)

Definition for two classes [impurity function] :

$$\iota_{entropy}(p_1, p_2) = -(p_1 \cdot \log_2(p_1) + p_2 \cdot \log_2(p_2))$$

$$\iota_{entropy}(D) = - \left( \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|} \cdot \log_2 \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|} + \frac{|\{(\mathbf{x}, c_2) \in D\}|}{|D|} \cdot \log_2 \frac{|\{(\mathbf{x}, c_2) \in D\}|}{|D|} \right)$$

# Impurity Functions


## Impurity Functions Based on Entropy (continued)

Definition for two classes [impurity function] :

$$\iota_{entropy}(p_1, p_2) = -(p_1 \cdot \log_2(p_1) + p_2 \cdot \log_2(p_2))$$

$$\iota_{entropy}(D) = - \left( \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|} \cdot \log_2 \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|} + \frac{|\{(\mathbf{x}, c_2) \in D\}|}{|D|} \cdot \log_2 \frac{|\{(\mathbf{x}, c_2) \in D\}|}{|D|} \right)$$

Graph of the function  $\iota_{entropy}(p_1, 1 - p_1)$ , i.e., for two classes:





[graphs: [misclassification](#), [entropy](#), [Gini](#)]

# Impurity Functions

## Impurity Functions Based on Entropy (continued)

Graph of the function  $\iota_{entropy}(p_1, p_2, 1 - p_1 - p_2)$ , i.e., for three classes:



# Impurity Functions

## Impurity Functions Based on Entropy (continued)

Definition for  $k$  classes:

$$\iota_{entropy}(p_1, \dots, p_k) = - \sum_{i=1}^k p_i \cdot \log_2(p_i)$$

$$\iota_{entropy}(D) = - \sum_{i=1}^k \frac{|\{(\mathbf{x}, c_i) \in D\}|}{|D|} \cdot \log_2 \frac{|\{(\mathbf{x}, c_i) \in D\}|}{|D|}$$

# Impurity Functions

## Impurity Functions Based on Entropy (continued)

$\Delta \iota_{entropy}$  corresponds to the information gain  $H(\mathcal{A}) - H(\mathcal{A} \mid \mathcal{B})$ :

$$\Delta \iota_{entropy} = \underbrace{\iota_{entropy}(D)}_{H(\mathcal{A})} - \underbrace{\sum_{l=1}^m \frac{|D_l|}{|D|} \cdot \iota_{entropy}(D_l)}_{H(\mathcal{A} \mid \mathcal{B})}$$

# Impurity Functions

## Impurity Functions Based on Entropy (continued)

$\Delta \iota_{\text{entropy}}$  corresponds to the information gain  $H(\mathcal{A}) - H(\mathcal{A} \mid \mathcal{B})$ :

$$\Delta \iota_{\text{entropy}} = \underbrace{\iota_{\text{entropy}}(D)}_{H(\mathcal{A})} - \underbrace{\sum_{l=1}^m \frac{|D_l|}{|D|} \cdot \iota_{\text{entropy}}(D_l)}_{H(\mathcal{A} \mid \mathcal{B})}$$

Mapping:

- $A_i, i = 1, \dots, k$ , denotes the event that  $\mathbf{x} \in X(t)$  belongs to class  $c_i$ .  
The experiment  $\mathcal{A}$  corresponds to the classification  $c : X(t) \rightarrow C$ .
- $B_l, l = 1, \dots, m$ , denotes the event that  $\mathbf{x} \in X(t)$  has value  $a_l$  for feature  $j$ .  
The experiment  $\mathcal{B}$  corresponds to evaluating feature  $A$  and entails the following splitting:  
$$X(t) = X(t_1) \cup \dots \cup X(t_m) = \{\mathbf{x} \in X(t) : \mathbf{x}|_j = a_1\} \cup \dots \cup \{\mathbf{x} \in X(t) : \mathbf{x}|_j = a_m\}$$
- $\iota_{\text{entropy}}(D) = \iota_{\text{entropy}}(P(A_1), \dots, P(A_k)) = -\sum_{i=1}^k P(A_i) \cdot \log_2(P(A_i)) = H(\mathcal{A})$
- $\frac{|D_l|}{|D|} \cdot \iota_{\text{entropy}}(D_l) = P(B_l) \cdot \iota_{\text{entropy}}(P(A_1 \mid B_l), \dots, P(A_k \mid B_l)) = H(\mathcal{A} \mid B_l), l = 1, \dots, m$
- $P(A_i), P(B_l), P(A_i \mid B_l)$  are estimated as relative frequencies based on  $D$ .



# Impurity Functions

## Impurity Functions Based on the Gini Index

Definition for two classes [[impurity function](#)] :

$$\iota_{Gini}(p_1, p_2) = 1 - (p_1^2 + p_2^2) = 2 \cdot p_1 \cdot p_2$$

# Impurity Functions

## Impurity Functions Based on the Gini Index (continued)

Definition for two classes [[impurity function](#)] :

$$\iota_{Gini}(p_1, p_2) = 1 - (p_1^2 + p_2^2) = 2 \cdot p_1 \cdot p_2$$

$$\iota_{Gini}(D) = 2 \cdot \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|} \cdot \frac{|\{(\mathbf{x}, c_2) \in D\}|}{|D|}$$

# Impurity Functions


## Impurity Functions Based on the Gini Index (continued)

Definition for two classes [\[impurity function\]](#):

$$\iota_{Gini}(p_1, p_2) = 1 - (p_1^2 + p_2^2) = 2 \cdot p_1 \cdot p_2$$

$$\iota_{Gini}(D) = 2 \cdot \frac{|\{(\mathbf{x}, c_1) \in D\}|}{|D|} \cdot \frac{|\{(\mathbf{x}, c_2) \in D\}|}{|D|}$$

Graph of the function  $\iota_{Gini}(p_1, 1 - p_1)$ , i.e., for two classes:



[Graphs: [misclassification](#), [entropy](#), Gini]

# Impurity Functions

## Impurity Functions Based on the Gini Index (continued)

Definition for  $k$  classes:

$$\iota_{Gini}(p_1, \dots, p_k) = 1 - \sum_{i=1}^k (p_i)^2$$

$$\begin{aligned}\iota_{Gini}(D) &= \left( \sum_{i=1}^k \frac{|\{(\mathbf{x}, c_i) \in D\}|}{|D|} \right)^2 - \sum_{i=1}^k \left( \frac{|\{(\mathbf{x}, c_i) \in D\}|}{|D|} \right)^2 \\ &= 1 - \sum_{i=1}^k \left( \frac{|\{(\mathbf{x}, c_i) \in D\}|}{|D|} \right)^2\end{aligned}$$