



University Institute of Engineering
Department of Computer Science & Engineering

EXPERIMENT: 4

NAME: Devjot Singh

UID: 23BCS10864

BRANCH: BE-CSE

SECTION / GROUP: KRG_3B

SEMESTER: 5TH

SUBJECT CODE: 23CSP-339

SUBJECT NAME: ADBMS

1. Consider a relation R having attributes as R(ABCD), functional dependencies are given below:

$AB \rightarrow C$

$C \rightarrow D$

$D \rightarrow A$

Identify the set of candidate keys possible in relation R. List all the set of prime and non-prime attributes.

Ans:

Given:

R(A, B, C, D)

Functional Dependencies:

$AB \rightarrow C$

$C \rightarrow D$

$D \rightarrow A$

Finding candidate keys by
computing closures:

1. Closure of AB:

$(AB)^+ = \{A, B, C, D\}$

Since closure contains all
attributes, AB is a
candidate key.

2. Closure of BC:

$(BC)^+ = \{A, B, C, D\}$

Since closure contains all attributes, BC is a candidate key.

3. Closure of BD:

$(BD)^+ = \{A, B, C, D\}$

Since closure contains all attributes, BD is a candidate key.

Candidate Keys:

$\{AB\}, \{BC\}, \{BD\}$

Prime and Non-prime

Attributes:

Prime Attributes = A, B, C, D

Non-prime Attributes = None

2. Relation R(ABCDE) having functional dependencies as:

$A \rightarrow D$

$B \rightarrow A$

$BC \rightarrow D$

$AC \rightarrow BE$

Identify the set of candidate keys possible in relation R. List all the set of prime and nonprime attributes.

Ans:

Start with $\{B, C\}$

$B \rightarrow A \Rightarrow \text{add } A \Rightarrow \{B, C, A\}$

$A \rightarrow D \Rightarrow \text{add } D \Rightarrow \{B, C, A, D\}$

$AC \rightarrow BE \Rightarrow \text{since } A \text{ and } C \text{ present, add } B \text{ and } E \Rightarrow \{B, C, A, D, E\}$

All attributes covered \Rightarrow
BC is a candidate key.

3. Consider a relation R having attributes as R(ABCDE), functional dependencies are given below:

$B \rightarrow A$

$A \rightarrow C$

$BC \rightarrow D$

$AC \rightarrow BE$

Identify the set of candidate keys possible in relation R. List all the set of prime and non-prime attributes.

Ans:

Start with {B, C}

$B \rightarrow A \Rightarrow$ add A \Rightarrow {B, C, A}

$A \rightarrow C \Rightarrow$ already present

$BC \rightarrow D \Rightarrow$ add D \Rightarrow {B, C, A, D}

$AC \rightarrow BE \Rightarrow$ since A and C present, add B and E \Rightarrow {B, C, A, D, E}

All attributes covered \Rightarrow
BC is a candidate key.

Conclusion:

Candidate Key: {B, C}

Prime Attributes: B, C

Non-prime Attributes: A, D, E

4. Consider a relation R having attributes as R(ABCDEF), functional dependencies are given below: $A \rightarrow BCD$

$BC \rightarrow DE$

$B \rightarrow D$

$D \rightarrow A$

Identify the set of candidate keys possible in relation R. List all the set of prime and non-prime attributes.

Ans:

R (A, B, C, D, E, F)

Closure:

$A^+ \sqsupseteq A, B, C, D, E$

$B^+ \sqsupseteq B, D, A, C, E$

$C^+ \sqsupseteq C$

$D^+ \sqsupseteq D, A, B, C, E$

$E^+ \sqsupseteq E$

$F^+ \sqsubseteq E$

$AF^+ \sqsubseteq A, B, C, D, E, F$

$BF^+ \sqsubseteq B, F, D, A, C, E$

$CF^+ \sqsubseteq C, F$

$DF^+ \sqsubseteq D, F, A, B, C, E$

Candidate Keys: AF, BF, DF

Prime Attributes: A, B, D, F Non-prime

Attributes: C, E

Normal Form: 1NF

5. Designing a student database involves certain dependencies which are listed below:

$X \rightarrow Y$

$WZ \rightarrow X$

$WZ \rightarrow Y$

$Y \rightarrow W$

$Y \rightarrow X$

$Y \rightarrow Z$

The task here is to remove all the redundant FDs for efficient working of the student database management system.

Ans:

1. $WZ \rightarrow Y$ is
redundant because:

- Y can be derived from
 $Y \rightarrow X$ and $X \rightarrow Y$

2. $Y \rightarrow X$ is redundant
because:

- X can be derived from
 $WZ \rightarrow X$ and $Y \rightarrow W$

After removing redundant
dependencies, we have:

$X \rightarrow Y$

$WZ \rightarrow X$

$Y \rightarrow W$

$Y \rightarrow Z$

Conclusion:

The minimal set of
functional dependencies
is:

$X \rightarrow Y$

$WZ \rightarrow X$

$Y \rightarrow W$

$Y \rightarrow Z$

6. Debix Pvt Ltd needs to maintain database having dependent attributes ABCDEF. These attributes are functionally dependent on each other for which functionally dependency set F given as:

$A \rightarrow BC$

$D \rightarrow E$

$BC \rightarrow D$

$A \rightarrow D$

Consider a universal relation R1(A, B, C, D, E, F) with functional dependency set F, also all attributes are simple and take atomic values only. Find the highest normal form along with the candidate keys with prime and non-prime attribute.

Ans:

Closure of A and F ($\{A, F\}$):

Start with $\{A, F\}$

$A \rightarrow BC \Rightarrow$ add B, C $\Rightarrow \{A, F, B, C\}$

$BC \rightarrow D \Rightarrow$ add D $\Rightarrow \{A, F, B, C, D\}$

$D \rightarrow E \Rightarrow$ add E $\Rightarrow \{A, F, B, C, D, E\}$

All attributes covered $\Rightarrow \{A, F\}$ is a candidate key.

Checking minimality:

Removing A or F from $\{A, F\}$ will not cover all attributes, hence it's minimal.

Determining normal form:

No partial or transitive dependencies remain in $\{A, F\}$.

Therefore, the highest normal form is 3NF (Third Normal Form).

Conclusion:

Candidate Key: $\{A, F\}$

Prime Attributes: A, F

Non-prime Attributes: B, C, D, E

Highest Normal Form: 3NF