

```
my-project/
├── public/
│   ├── assets/
│   │   ├── images/
│   │   ├── videos/
│   │   ├── gifs/
│   │   ├── icons/
│   │   └── pdfs/
│   └── favicon.ico
├── src/
│   ├── components/
│   │   ├── common/
│   │   │   ├── Header.jsx
│   │   │   ├── Footer.jsx
│   │   │   ├── Button.jsx
│   │   │   └── Loader.jsx
│   │   ├── forms/
│   │   │   ├── QueryForm.jsx
│   │   │   └── InputField.jsx
│   │   └── maps/
│   │       └── GoogleMap.jsx
│   ├── pages/
│   │   ├── Home.jsx
│   │   ├── About.jsx
│   │   ├── Contact.jsx
│   │   └── NotFound.jsx
│   ├── hooks/
│   │   ├── useFormValidation.js
│   │   └── useFetchData.js
│   ├── styles/
│   │   ├── global.css
│   │   ├── variables.css
│   │   └── components/
│   │       ├── Header.css
│   │       └── QueryForm.css
│   ├── utils/
│   │   ├── api.js
│   │   ├── constants.js
│   │   └── helpers.js
│   ├── App.jsx
│   ├── main.jsx
│   └── router/
│       └── AppRouter.jsx
├── .env
├── package.json
├── vite.config.js
└── README.md
```

Explanation & Benefits

1. `public/` **Folder**

- **Purpose:** Static assets like images, videos, PDFs, etc.
 - **Structure:**
 - `images/` : Logos, banners, etc.
 - `videos/` : Embedded or downloadable videos.
 - `gifs/` : Animations.
 - `icons/` : SVGs or icon sets.
 - `pdfs/` : Files for user download.
 - **Why?** Vite serves files from `public/` directly, making it ideal for assets that don't need bundling.
- 

2. `src/components/` **Folder**

- **Purpose:** Reusable UI components.
- **Subfolders:**
 - `common/` : Shared components like `Header`, `Footer`, `Button`, `Loader`.
 - `forms/` : Form-related components, like `QueryForm`.
 - `maps/` : Components for map integration like `GoogleMap`.
- **Why?** Separating by feature makes components reusable and easier to maintain.

3. `src/pages/` **Folder**

- **Purpose:** Main pages for routing (`Home`, `About`, `Contact`).
- **Why?** Pages handle layout logic and integrate multiple components.

4. `src/hooks/` **Folder**

- **Purpose:** Custom React hooks like `useFormValidation` or `useFetchData`.
- **Why?** Hooks make logic reusable and reduce repetitive code.

5. `src/styles/` **Folder**

- **Purpose:** CSS or SCSS files for styling.
- **Structure:**
 - `global.css` : For global styles like resets and typography.
 - `variables.css` : Colors, fonts, spacing variables.
 - `components/` : Component-specific styles.
- **Why?** Keeps styles modular and maintainable.

6. `src/utils/` **Folder**

- **Purpose:** Helper functions, constants, and API services.
- **Files:**
 - `api.js` : Handles API requests with Axios or Fetch.
 - `constants.js` : Static values like URLs, API keys.
 - `helpers.js` : Reusable utility functions.
- **Why?** Centralizes non-UI logic, making it reusable and organized.

7. `src/router/` **Folder**

- **Purpose:** Routing logic using `react-router-dom`.
- **File:** `AppRouter.jsx` defines all routes like `/`, `/about`, `/contact`, etc.
- **Why?** Separates routing logic for cleaner `App.jsx`.

Features Addressed

1. Images, Videos, Gifs, Icons, PDFs:

- Stored in `public/assets/`. Easily accessible via relative paths like `/assets/images/logo.png`.

2. Google Map:

- Create a `GoogleMap.jsx` component with the `@react-google-maps/api` library for seamless integration.

3. Query Form:

- Modularize the form logic in `forms/QueryForm.jsx` and style it with `styles/components/QueryForm.css`.

4. Download Option:

- Use `<a href="/assets/pdfs/file.pdf" download>` for downloadable PDFs.

5. Read More Option:

- Create a reusable `Button` component  with toggle logic for "Read More" functionality.