NIMBUS
EQUIPMENTS
— INDUSTRIAL AIR COMPRESSRR
SPARE PARTS & SERVICE SOLUTIONS

RELIABLE SOLUTIONS.
EFFICIENT OPERATIONS.
LONG-TERM PARTNERSHIP.

ACCESSORIES

Complete Support for Your Compressed Air System

We supply a wide range of high-quality air compressor accessories to ensure better performance, higher efficiency and longer equipment life.



Key Features

- GENUINE QUALITY
- WIDE AVAILABILITY
- FAST DISPATCH
- TECHNICAL SUPPORT

NIMBUS EQUIPMENTS | YOUR TRUSTED PARTNER & SUPPLIER

NIMBUS
EQUIPMENTS
INDUSTRIAL AIR COMPRESSGR
SPARE PARTS & SERVICE SOLUTIONS

RELIABLE SOLUTIONS.
EFFICIENT OPERATIONS.
LONG-TERM PARTNERSHIP.

NIMBUS AIR RECEIVER TANKS



Technical Specifications

(Compact & Standard Industrial Range of NAR Series)

Model	LTR (Capacity)	Orientation	Working Pressure	Hydraulic Test Pressure	Shell Material	Inlet / Outlet Port Size	Standard Mountings / Ports
NAR-160	160 LTR	Horizontal	Up to 16 Bar	24 Bar	High-Grade MS	1' BSP	Safety Valve, Pressure Gauge, Drain Valve
NAR-300	300 LTR	Horizontal	Up to 16 Bar	24 Bar	High-Grade MS	1' / 1.5' BSP	
NAR-500	500 LTR	Vertical	Up to 16 Bar	24 Bar	High-Grade MS	1.5' BSP	
NAR-1000	1000 LTR	Vertical	Up to 16 Bar	24 Bar	High-Grade MS	2' BSP / Flanged	Safety Valve, Pressure Gauge, Drain Valve, Manhole
NAR-2000	2000 LTR	Vertical	Up to 16 Bar	24 Bar	High-Grade MS	2.5' / 3' Flanged	
NAR-3000	3000 LTR	Vertical	Up to 16 Bar	24 Bar	High-Grade MS	3' Flanged	
NAR-5000	5000 LTR	Vertical	Up to 16 Bar	24 Bar	High-Grade MS	4' Flanged	
NAR-10000	10000 LTR	Vertical	Up to 16 Bar	24 Bar	High-Grade MS	Customized / Flanged	Dual Safety Ports, Gauge, Auto Drain, Manhole

*** Note:** Custom capacities up to 10,000 Ltr and horizontal orientations are available upon request.

Key Technical Parameters

Capacity Range:
160 Litres to 10,000 Litres

Design & Build:
High-Grade Boiler Quality/ Structural Mild Steel

Surface Finish:
Industrial Grade Powder Coating

Standard Inclusions:
Calibrated Pressure Gauge, Spring-Loaded Safety Relief Valve (SRV), Manual Drain Valve.

NIMBUS
EQUIPMENTS
INDUSTRIAL AIR COMPRESSOR
SPARE PARTS & SERVICE SOLUTIONS

RELIABLE SOLUTIONS.
EFFICIENT OPERATIONS.
LONG-TERM PARTNERSHIP.

NIMBUS REFRIGERATED AIR DRYERS



Technical Specifications

(Compact & Standard Industrial Range of NRD Series)

Model	FAD (CFM)	FAD (m3/hr)	Dimensions (W × D × H) mm	Weight (Kg)	Power Supply (V / Ph / 50Hz)	In / Out Port
NRD 10	10	17	400 × 462 × 459	31	230V / 1 Ph	G 1/2'
NRD 20	20	34	400 × 462 × 459	32	230V / 1 Ph	G 1/2'
NRD 40	40	68	420 × 522 × 459	36	230V / 1 Ph	G 3/4'
NRD 60	60	102	420 × 522 × 459	37	230V / 1 Ph	G 3/4'
NRD 80	80	136	470 × 632 × 560	54	230V / 1 Ph	G 1'
NRD 100	100	170	470 × 632 × 560	55	230V / 1 Ph	G 1'
NRD 120	125	212	470 × 632 × 560	56	230V / 1 Ph	G 1'
NRD 150	150	255	515 × 815 × 815	79	230V / 1 Ph	G 1-1/2'
NRD 200	200	340	515 × 815 × 815	90	230V / 1 Ph	G 1-1/2'
NRD 250	250	425	515 × 815 × 815	95	230V / 1 Ph	G 1-1/2'
NRD 300	300	510	586 × 815 × 970	138	230V / 1 Ph	G 2'
NRD 400	400	680	950 × 600 × 1045	142	230V / 1 Ph	G 2-1/2'
NRD 500	500	850	950 × 600 × 1045	144	415V / 3 Ph	G 2-1/2'
NRD 600	600	1020	950 × 600 × 1045	148	415V / 3 Ph	G 2-1/2'
NRD 800	800	1360	720 × 970 × 1425	475	415V / 3 Ph	4' (DN 100)
NRD 1000	1000	1700	820 × 1095 × 1615	520	415V / 3 Ph	4' (DN 100)
NRD 1250	1250	2125	970 × 1420 × 1620	530	415V / 3 Ph	4' (DN 100)
NRD 1600	1600	2720	1470 × 1420 × 2000	600	415V / 3 Ph	6' (DN 150)
NRD 2000	2000	3400	1470 × 1420 × 2000	970	415V / 3 Ph	6' (DN 150)
NRD 2500	2500	4250	1620 × 1570 × 2000	1150	415V / 3 Ph	6' (DN 150)
NRD 4000	4000	6800	2120 × 1570 × 2000	1300	415V / 3 Ph	8' (DN 200)
NRD 5000	5000	8500	1550 × 1650 × 2000	1450	415V / 3 Ph	8' (DN 200)

*** Note:** Dimensions are approximate. Specifications are subject to change without prior notice.

Important Technical Notes & Standards

FAD Delivery:
Rated strictly in accordance with ISO 7183-2007

Connection Standards:
Flanged connections (DN) conform to ASME B16.5 CL 150 LBS SORF

Cooling Options:
Water-cooled models available as an option from 500 CFM onwards

High Capacity Systems:
Custom configurations above 10,000 CFM available on request

NIMBUS
EQUIPMENTS
INDUSTRIAL AIR COMPRESSOR
SPARE PARTS & SERVICE SOLUTIONS

RELIABLE SOLUTIONS.
EFFICIENT OPERATIONS.
LONG-TERM PARTNERSHIP.

NIMBUS HEATLESS DESICCANT AIR DRYERS



Technical Specifications

(Compact & Standard Industrial Range of NHD Series)

Model	Flow Rate (FAD CFM)	In / Out Connection	Width (mm)	Depth (mm)	Height (mm)	Weight (Kg)
NHD 40	40	G 1/2'	600	400	1740	210
NHD 60	60	G 3/4'	600	400	1800	240
NHD 80	80	G 1'	700	450	1600	290
NHD 100	100	G 1'	700	450	1780	320
NHD 120	120	G 1'	760	450	1550	370
NHD 150	150	G 1-1/2'	760	450	1750	415
NHD 200	200	G 1-1/2'	880	450	1650	450
NHD 250	250	G 1-1/2'	880	450	1900	520
NHD 300	300	G 1-1/2'	1300	600	1720	640
NHD 350	350	G 2'	1300	600	1850	700
NHD 400	400	G 2'	1400	650	1700	740
NHD 500	500	G 2'	1500	900	1850	1100
NHD 600	600	3' (80 NB / Flanged)	1500	900	2000	1250
NHD 750	750	3' (80 NB / Flanged)	1650	1000	1850	1410
NHD 1000	1000	3' (80 NB / Flanged)	2000	1200	2000	2050
NHD 1250	1250	3' (80 NB / Flanged)	2300	1200	2200	2250

* **Note**: 80 NB flanged connections conform to ASME B16.5 CL 150 LBS SORF.

Key Features & Technology

Twin Tower Desiccant System
Continuous dry air delivery with alternate drying and regeneration cycles.

Ultra-Low Dew Point
Provides -20°C to -40°C pressure dew point as per ISO 8573-1 standards.

Integrated Filtration
Comes equipped with pre-filter, oil removal filter, after-filter, and moisture indicator.

Advanced Controls
Equipped with PLC control, purge economizer, and Dew Point Dependent Switching (DDS).

NIMBUS
EQUIPMENTS
— INDUSTRIAL AIR COMPRESSOR
SPARE PARTS & SERVICE SOLUTIONS

RELIABLE SOLUTIONS.
EFFICIENT OPERATIONS.
LONG-TERM PARTNERSHIP.

NIMBUS COMPRESSED AIR LINE FILTERS



Technical Specifications

(High-Efficiency Range of NLF Series)

Brand	Model Name	CFM	Port Size	Max Pressure	TEMP	Element Grade
Nimbus	NLF-35	35	1/2"	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-58	58	3/4"	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-70	70	1"	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-120	120	1"	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-180	180	1-1/4"	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-250	250	1-1/2"	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-350	350	2"	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-500	500	DN65	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-750	750	DN80	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-1000	1000	DN100	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-1500	1500	DN125	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-2000	2000	DN150	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-3000	3000	DN200	16 BAR	80°C	C/P/F/H/A
Nimbus	NLF-5000	5000	DN200	16 BAR	80°C	C/P/F/H/A

* **Note:** Custom flanged connections and high capacity models are available upon request.

FILTRATION GRADE & PERFORMANCE

PRE FILTER
5 Micron
Removes solid particles, dost rost & acele.

MICRO FILTER
1 Micron
Removes fine particles, water & oil acrosols.

FINE FILTER
0.01 Micron
Removes very fine particles, coelesced oil & mist.

ACTIVATED CARBON FILTER
Oil Vapor Removel)
Removes oil vapor, odors & harmful hydrosaabons.

STERILE FILTER
0.01 Micron
Removes bacteria, viroses & uftra fine particles.

TECHNICAL SPECIFICATIONS

Max. Working Pressure	16 Bar (232 PSI)
Max. Temperature	80°C
Pressure Drop	≤ 0.2 Bar
Connection Size	1/2" to 3" (BSP / NPT)
Flow Capacity	35 CFM to 5000 CFM



APPLICATIONS

AUTOMOTIVE | PHARMACEUTICAL | FOOD & BEVERAGE
TEXTILE | ELECTRONICS | GENERAL INDUSTRY

IMPROVED AIR QUALITY | ENERGY EFFICIENT | LONGER EQUIPMENT LIFE | CEFFECTIVE SOLUTION

NIMBUS EQUIPMENTS | YOUR TRUSTED PARTNER & SUPPLIER

NIMBUS
EQUIPMENTS
INDUSTRIAL AIR COMPRESSOR
SPARE PARTS & SERVICE SOLUTIONS

RELIABLE SOLUTIONS.
EFFICIENT OPERATIONS.
LONG-TERM PARTNERSHIP.

NIMBUS CONDENSATE DRAIN VALVES



Technical Specifications

(CONDENSATE DRAIN VALVES – COMPLETE TECHNICAL DATA SHEET)

Parameter / Feature	Model 1	Model 2	Model 3	Model 4	Model 5	Model 6	Model 7
Model – Analogue Timer	**NDV 304 DS**	**NDV 304 FS**	**NDV 304 DU**	**NDV 604 CQ**	**NDV 3K4 CQ**	**NDV 604 CR**	**NDV 300 DT**
Quick Selection Guide	General Purpose	High Pressure	General Purpose with Ball Valve cum Strainer	High Discharge Rate	Super High Discharge Rate	Near Zero Air Loss for Air Reservoir	Zero Air Loss for Oil-Free Compressed Air System
Operation Type	Direct	Direct	Direct	Pilot	Pilot	Pilot	Float
Orifice (mm)	4.5	2	3.5	12.5	25	12.5	2.5
Operating Pressure (bar g)	16	80	16	12	12	12	16
Max. Discharge Capacity (lph)	216	128	145	1797	4320	743	2060
Rated Discharge Capacity (lph)	53	32	36	231	557	72	447
Aftercooler / Moisture Sep. Capacity	550 CFM	330 CFM	370 CFM	2400 CFM	5775 CFM	250 CFM	For Air Receiver capacity 500 Ltr & Drop legs
Air Receiver Capacity	2000 Litres	1300 Litres	1500 Litres	10000 Litres	20000 Litres	1000 Litres	
Pre-Filter Capacity	1925 CFM	1155 CFM	1295 CFM	6000 CFM	14425 CFM	625 CFM	-
Refrigerated Air Dryer Capacity	1638 CFM	2425 CFM	1100 CFM	7125 CFM	17175 CFM	750 CFM	For Air Receiver capacity 500 Ltr & Drop legs
Inlet Port Size	1/2" BSPP (F)	1/2" BSPP (F)	1/2" BSPP (M)	1/2" BSPP (F)	1" BSPP (F)	1/2" BSPP (F)	1/2" BSPP
Outlet Port Size	1/2" BSPP (F)	1/2" BSPP (F)	1/2" BSPP (F)	1/2" BSPP (F)	1" BSPP (F)	1/2" BSPP (F)	1/2" BSPP (F)
Body Material	Brass	Brass	Brass	Aluminium	Aluminium	Aluminium	Engineered Composite / Metal
Seals	FKM	FKM	FKM	Nitrile	Nitrile	Nitrile	High Temp Seals
Dimensions (W × D × H) mm	46 x 88 x 108	46 x 88 x 108	95 x 87 x 122	80 x 150 x 190	126 x 135 x 240	144 x 200 x 236	108 x 134 x 144
Weight (kg)	0.45	0.46	0.54	0.63	2.42	2.0	0.65
Power Consumption	20 Watts	20 Watts	20 Watts	8 Watts	8 Watts	8 Watts	0 Watts (Float Type)
Electrical Connection	DIN 43650-A	DIN 43650-A	DIN 43650-A	DIN 43650-A	DIN 43650-A	DIN 43650-A	N/A
Ingress Protection	IP65	IP65	IP65	IP65	IP65	IP65	N/A
ON Time (Discharge)	0.5 to 10 sec	0.5 to 10 sec	0.5 to 10 sec	0.5 to 10 sec	0.5 to 10 sec	0.5 to 10 sec	Automatic / Mechanical
OFF Time (Interval)	0.5 to 45 min	0.5 to 45 min	0.5 to 45 min	0.5 to 45 min	0.5 to 45 min	0.5 to 45 min	
Operating Temperature	5°C to 60°C	5°C to 60°C	5°C to 60°C	5°C to 60°C	5°C to 60°C	5°C to 60°C	5°C to 180°C

Key Highlights & Applications

- **Zero IOS Los Technology**
- **Rugged & Durable & Durabable**
- **Soil time / Ihoralination**
- **Precision Control & Timing** Featuress Mechanica

NIMBUS
EQUIPMENTS
INDUSTRIAL AIR COMPRESSOR
SPARE PARTS & SERVICE SOLUTIONS



Let's Power Your Compressed Air Requirements

Whether you need a new compressor, spare parts, scheduled maintenance, an AMC contract, professional installation, breakdown repair, or a rental solution — Nimbus Equipments is ready to support your industrial compressed-air requirements with the right products, expertise, and service.

Reliable Air. Reliable Support. Reliable Partnership.



Direct WhatsApp / Call:
+91-9289425601

Email:
sales@nimbusequipments.in

Website:
www.nimbusequipments.in

NIMBUS EQUIPMENTS | YOUR TRUSTED PARTNER & SUPPLIER