CENERAL TOLERANCE LINIT						1
GENERAL TOLERANCE UNIT DIM GRD A B C	REV	DATE	:	R	EASON OF MODIFY	MODIFIER
1~10 ±0.05 ±0.1 ±0.2 10~100 ±0.1 ±0.2 ±0.3	<u>A</u>					
100~500 ±0.2 ±0.3 ±0.5 500~1000 ±0.3 ±0.5 ±1.5	\triangle					
500~1000 ±0.3 ±0.5 ±1.5						
					1,232.5	
			2	65	1,252.5	
1,850 202_63 600 2-M16 EYE BOLT			501	1 <u>3</u> 202		
95 1,660 95 30 1	٦				3-PANEL HINGE	
	Ŧ	i i			DOOR OPEN (with 강화유	58*)
					(with 광화위	:4)
조도센서 IR(리모컨)				1		
				Î		
			\$ 52		7/	
					•	
			000000000000000000000000000000000000000		<i>18</i> °/	
				<i>#</i>		
	₩	i i	7	F		
♥ [외부 INNET]						
PG13.5(AC IN) PG13.5(LAN) WALL MOUNT PLATE	ı	[WALL D	BRACKET HO	OLE DATA1		
방수 USB 2PORT M12 Anchor BOLT	'	[WALL D	.50 .50	OLL DATA		
1/36 n			# T.L.	700		
				796		
		<u>50</u>	98 150	750 150 150	150 98 22-ø1	5×30
	a			<u> </u>		
		0000				
] · · ·		─, -	
				$\neg \cap$	─	
		1 g	ے مالیا			
			:-	$\overline{}$	· 🛓	
		8		_	١	
		T		600	0 0	1
			<u>, 6 600</u>	0000000	000 0 0	
	: 165~1	75kg (wai	ll brk 제외)			
	옥외형					
		TERIAL	Q'TY	NO	후가공 사임	
	NED CHI	ECKED /			1:1 MODEL PART NAME	TMN750-PN
	-	<u> </u>	-		mm DATE	ASSY 2022.08.24 ISSUE Ø
	W	EDS	-		DWG	, ,

W EDS

DWG NO

CODE NO.