

Telesale Services API Guide

Read-only API for the external Telesales application to authenticate and retrieve assigned wave export JSON.

Base URL

Use the server IP address where the Docker container is running.

Local on this PC:
`http://127.0.0.1:5185`

From another PC on the network:
`http://<server-ip>:5185`

Authentication

The Telesales app must first call the login endpoint. The returned token must be sent on later requests using the Authorization header.

Authorization: Bearer <token>

The token currently expires after 12 hours.

1. Login

POST /api/login

The login value can be the Telesale user email, full name, or initials.

Request body:

```
{
  "login": "Teletest",
  "password": "makemoney99$"
}
```

Success response:

```
{
  "token": "Bearer-token-value-here",
  "expiresAt": "2026-05-21T21:33:55.4453222+00:00",
  "user": {
    "id": 5,
    "fullName": "Teletest",
    "email": null
  }
}
```

2. Check Current User

GET /api/me

Headers:

Authorization: Bearer <token>

Response:

```
{
  "id": 5,
  "fullName": "Teletest",
  "email": null
}
```

3. Get Waves For Logged-In User

GET /api/waves

Headers:

Authorization: Bearer <token>

Returns the wave exports assigned to the logged-in Telesale user.

```
Response:
[
  {
    "exportId": 12,
    "waveId": 3,
    "campaignId": 1,
    "campaignName": "Spring Campaign",
    "waveName": "Wave 1",
    "waveNumber": 1,
    "leadCount": 40,
    "sentAt": "2026-05-21T10:15:00Z"
  }
]
```

4. Get Wave With Parsed JSON

```
GET /api/waves/{exportId}

Headers:
Authorization: Bearer <token>
```

Returns metadata plus the stored Telesale export JSON as an object.

```
Response:
{
  "exportId": 12,
  "waveId": 3,
  "campaignId": 1,
  "campaignName": "Spring Campaign",
  "waveName": "Wave 1",
  "waveNumber": 1,
  "leadCount": 40,
  "sentAt": "2026-05-21T10:15:00Z",
  "exportJson": {
    "waveId": 3,
    "waveName": "Wave 1",
    "exportedAt": "...",
    "leads": [],
    "responseStatusTypes": [],
    "priorityTypes": []
  }
}
```

5. Get Exact Original JSON

```
GET /api/waves/{exportId}/json

Headers:
Authorization: Bearer <token>
```

Use this endpoint when the other app wants the exact same JSON format as the existing Telesale download/export file.

```
Content-Type: application/json; charset=utf-8
```

Error Codes

Status	Meaning
400	Login or password was missing, or the request body was invalid.
401	Missing, invalid, or expired bearer token.
404	The requested wave export does not exist for the logged-in user.

Important Notes

The external app is read-only against this API. It does not write back to the stored JSON.

Only users marked as Telesale can log in.

The exact JSON endpoint returns the stored export JSON from the database, which was generated from the same code path as the existing Telesale download.