

Bonn-Aachen International Center for Information Technology  
University of Bonn  
Master Programme in Life Science Informatics  
Master Thesis

# **Brain Tractography Registration with Nonrigid ICP**

**Mohammed Abdelgadir Awadelkareem Hassan**

Supervisor: Prof. Thomas Schultz  
Bonn-Aachen International Center for Information Technology  
University of Bonn

Supervisor: Dr. Martin Vogt  
Bonn-Aachen International Center for Information Technology  
University of Bonn

Date: February 3, 2019



---

## ACKNOWLEDGMENT

---

I would like to start by expressing my sincere gratitude to Prof. Dr. Thomas Schultz for providing me an excellent opportunity to work on this project under his supervision.

Also, I would like to thank Mohammad Khatami for his valuable support throughout the course of the project.

I would like to extend my sincere thanks to Dr. Martin Vogt for his expert guidance and valuable input.

Last but not least, I express my very profound gratitude to all my friends and family especially my parents for always being supportive and encouraging throughout the course of my studies.

I dedicate all my hard work to my wife for always believing in me.



---

## CONTENTS

---

1	INTRODUCTION	1
1	Brain Structure (Fiber Pathways)	1
2	Registration	2
2.1	Iterative closest point (ICP)	2
3	PCA Transformation	2
4	Least squares (LSQR)	2
2	METHOD	3
3	RESULT	5
4	CONCLUSION	7



---

## LIST OF FIGURES

---





---

## LIST OF TABLES

---



---

## ABSTRACT

---

The registration problem (also known as alignment, absolute orientation) is one of the outstanding and very basic problems in computer vision. In this problem, two or more datasets of points are given and the task is to optimally align them by estimating a best transformation (combination of translation, rotation and scaling). Due to its fundamental importance, it arises as a subtask in many different applications (e.g., object recognition, tracking, range data fusion, graphics, medical image alignment, robotics and structural bioinformatics etc [1]).

In This thesis we show how to extend the ICP framework to nonrigid registration, while retaining the convergence properties of the original algorithm. The resulting optimal step nonrigid ICP framework allows the use of different regularisations, as long as they have an adjustable stiffness parameter. The registration loops over a series of decreasing stiffness weights, and incrementally deforms the template towards the target, recovering the whole range of global and local deformations. To find the optimal deformation for a given stiffness, optimal iterative closest point steps are used. Preliminary correspondences are estimated by a nearestpoint search. Then the optimal deformation of the template for these fixed correspondences and the active stiffness is calculated. Afterwards the process continues with new correspondences found by searching from the displaced template vertices. We present an algorithm using a locally affine regularisation which assigns an affine transformation to each vertex and minimises the difference in the transformation of neighbouring vertices. It is shown that for this regularisation the optimal deformation for fixed correspondences and fixed stiffness can be determined exactly and efficiently. The method succeeds for a wide range of initial conditions, and handles missing data robustly. It is compared qualitatively and quantitatively to other algorithms using synthetic examples and real world data[2].



---

## INTRODUCTION

---

### 1 BRAIN STRUCTURE (FIBER PATHWAYS)

HUMAN BRAIN, which is our focus in this thesis, is the central organ of the human nervous system, it is made up of two main components, gray matter and white matter. Scientists have learned a lot about gray and white matter and the two halves of the brain through autopsies and imaging techniques and by studying diseases or conditions associated with brain damage.

The thesis focused on **White Matter** which refers to areas of the central nervous system that are mainly made up of myelinated axons, also called tracts or fiber pathways [3]. It is composed of bundles, which connect various gray matter areas of the brain to each other, and carry nerve impulses between neurons. Myelin acts as an insulator, which allows electrical signals to jump, rather than coursing through the axon, increasing the speed of transmission of all nerve signals [4].

Long thought to be passive tissue, white matter affects learning and brain functions, modulating the distribution of action potentials, acting as a relay and coordinating communication between different brain regions [5].

The Human Brain consists of these tracts in left and right side:

- Anterior Thalamic Radiation (ATR)
- Corpus Callosum (CC)
- Genu of the Corpus Callosum (genu)
- Splenium of the Corpus Callosum (splenium)
- Body of Corpus Callosum (truncus)
- Body of Corpus Callosum (truncus)
- Cingulum (Cing)
- Corticospinal Tract (CST)
- Inferior Fronto-occipital Fasciculus (IFO)
- Inferior Longitudinal Fasciculus (ILF)
- Superior Longitudinal Fasciculus (SLF)

- Ventral Tegmental Area (VTA)

## 2 REGISTRATION

The registration problem (also known as alignment, absolute orientation) is one of the outstanding and very basic problems in computer vision. In this problem, two or more datasets of points are given and the task is to optimally align them by estimating a best transformation (combination of translation, rotation and scaling). Due to its fundamental importance, it arises as a subtask in many different applications (e.g., object recognition, tracking, range data fusion, graphics, medical image alignment, robotics and structural bioinformatics ... etc) [1].

### 2.1 *Iterative closest point (ICP)*

ICP, which is an algorithm employed to minimize the distance between two or more points clouds, is one of the widely used algorithms in aligning three dimensional models given an initial guess of the rigid body transformation required [6]. In ICP (in our case) one points cloud (vertex cloud), the reference, or target, is kept fixed, while the other one, the source, is transformed to best match the reference. The algorithm iteratively revises the transformation (combination of translation, rotation and scaling) needed to minimize a distance from the source to the reference points cloud.

## 3 PCA TRANSFORMATION

PCA is mathematically defined as an orthogonal linear transformation that transforms the data to a new coordinate system such that the greatest variance by some projection of the data comes to lie on the first coordinate (called the first principal component), the second greatest variance on the second coordinate, and so on[7]. PCA is used in the code as a preliminary step, so that the template and target are aligned as much as possible before the registration can begin.

## 4 LEAST SQUARES (LSQR)

LSQR uses an iterative method to approximate the solution. The number of iterations required to reach a certain accuracy depends strongly on the scaling of the problem ( $||Ax - b||^2$ ). Poor scaling of the rows or columns of A should therefore be avoided where possible [8].

---

## METHOD

---





---

## RESULT

---



---

## CONCLUSION

---



---

## BIBLIOGRAPHY

---

- [1] Hongdong Li and Richard Hartley. The 3d-3d registration problem revisited. In *2007 IEEE 11th International Conference on Computer Vision*. IEEE, 2007.
- [2] Brian Amberg, Sami Romdhani, and Thomas Vetter. Optimal step nonrigid icp algorithms for surface registration. In *Computer Vision and Pattern Recognition, 2007. CVPR'07. IEEE Conference on*, pages 1–8. IEEE, 2007.
- [3] Hal Blumenfeld. *Neuroanatomy through Clinical Cases*. Oxford University Press, 2010.
- [4] Stephen B. Klein. *Biological Psychology*. Worth Publishers, 2008.
- [5] R. Douglas Fields. White matter matters. *Scientific American*, 298(3):54–61, mar 2008.
- [6] Zhengyou Zhang. Iterative point matching for registration of free-form curves and surfaces. *International Journal of Computer Vision*, 13(2):119–152, oct 1994.
- [7] I.T. Jolliffe. *Principal Component Analysis (Springer Series in Statistics)*. Springer, 2002.
- [8] Christopher C. Paige and Michael A. Saunders. Lsqr: An algorithm for sparse linear equations and sparse least squares, 1982.