

Empirical Performance Investigation of a Büchi Complementation Construction

Master's Thesis Presentation

Daniel Weibel

Foundations of Dependable Systems Group
Department of Informatics
University of Fribourg
`daniel.weibel@unifr.ch`

19 August 2015




UNIVERSITÉ DE FRIBOURG
UNIVERSITÄT FREIBURG

Outline

1. GOAL

2. Results

Büchi automata




- Finite state automata running on infinite words (ω -words) $\in \Sigma^\omega$
- A word is accepted if it has an accepting run
- A run is accepting if it visits an accepting state infinitely often

Büchi complementation

The complement of a Büchi automaton A is another Büchi automaton B , such that:

B accepts a word if and only if it is not accepted by A

Büchi Complementation Constructions



- Different constructions produce different complements B for the same automaton A
- Main performance measure: number m of states of B in relation to number n of states of A
 - ▶ State complexity
 - ▶ Also known as state growth, state blow-up, or state explosion
 - ▶ E.g. if $n = 10$ and $m = 100$, then $m = n^2$
 - ▶ Biggest problem of Büchi complementation


The Fribourg Construction

- Slice-based complementation construction
- Worst-case state complexity: $(1.59n)^n$
- Optimisations:
 - ▶ R2C: if input automaton is complete, remove states whose rightmost component is 2-coloured
 - ▶ M1: merge certain adjacent components $(1.195n)^n$
 - ▶ M2: keep not more than one 2-coloured component in every state $(0.86n^n)$

GOAL

- Graphical Tool for **O**mega-**A**utomata and **L**ogics
- <http://goal.im.ntu.edu.tw/wiki/doku.php>
- Create and manipulate ω -automata

Graphical user interface



Command line interface

```
$ ./gc generate -t fsa -a nbw -s 15 -A classical -m density -dt 1.6 -da 0.3
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<Structure label-on="Transition" type="FiniteStateAutomaton">
  <Name/>
  <Description/>
  <Formula/>
  <Alphabet type="Classical">
    <Symbol>a</Symbol>
    <Symbol>b</Symbol>
  </Alphabet>
  <StateSet>
    <State sid="0">
      <Y>160</Y>
      <X>346</X>
      <Properties/>
    </State>
    <State sid="1">
      <Y>54</Y>
      <X>291</X>
      <Properties/>
    </State>
    <State sid="2">
      <Y>104</Y>
      <X>486</X>
      <Properties/>
    </State>
    <State sid="3">
      <Y>236</Y>
```

GOAL: Büchi Complementation Constructions

- Implementations of several Büchi complementation constructions (GOAL version 2014–11–17)

GOAL Name	Reference
Ramsey	[Sistla et al., 1985, Sistla et al., 1987]
Safra	[Safra, 1988a, Safra, 1988b]
MS	[Muller and Schupp, 1995]
ModifiedSafra	[Althoff et al., 2006]
Piterman	[Piterman, 2006, Piterman, 2007]
WAA	[Kupferman and Vardi, 1997, Kupferman and Vardi, 2001]
WAPA	[Thomas, 1999]
Rank	[Schewe, 2009]
Slice+P	[Vardi and Wilke, 2007]
Slice	[Kähler and Wilke, 2008]

Fribourg Construction Plugin for GOAL

- GOAL is built with the Java Plugin Framework (JPF)¹
 - ▶ Extensibility: create **plugins** containing **extensions** for pre-defined **extension points**
- Our plugin adds the Fribourg construction to GOAL
 - ▶ ... in a fully integrated way

Graphical user interface



Command line interface



- Download: https://frico.s3.amazonaws.com/goal_plugins/ch.unifr.goal.complement.zip

¹<http://jpf.sourceforge.net/>




Test Data: GOAL Test Set

- Created and used for [Tsai et al., 2011]
- 11,000 automata
 - ▶ 15 states
 - ▶ Alphabet $\Sigma = \{0, 1\}$
 - ▶ 11 transition densities
 - $\mathcal{T} = (1.0, 1.2, 1.4, 1.6, 1.8, 2.0, 2.2, 2.4, 2.6, 2.8, 3.0)$
 - ▶ 10 acceptance densities
 - $\mathcal{A} = (0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0)$
 - ▶ 110 classes at 100 automata for each combination of $\mathcal{T} \times \mathcal{A}$
- Analysis
 - ▶ 61.8% universal automata
 - ▶ 0.6% empty automata
 - ▶ 9.0% complete automata
- Download: https://frico.s3.amazonaws.com/test_sets/goal.zip

Test Data: Michel Test Set

- Four Michel automata
 - ▶ Michel 1: 3 states, 2 symbols, 5 transitions
 - ▶ Michel 2: 4 states, 3 symbols, 8 transitions
 - ▶ Michel 3: 5 states, 4 symbols, 11 transitions
 - ▶ Michel 4: 6 states, 5 symbols, 14 transitions



- Automata used by [Michel, 1988] to prove $n!$ lower bound
- Very high state complexity
- Download: https://frico.s3.amazonaws.com/test_sets/michel.zip

Test Setup

- Internal tests
 - ▶ Compare different versions of the Fribourg construction
- External tests
 - ▶ Compare Fribourg construction with other constructions

	GOAL test set	Michel test set
Internal tests	<ul style="list-style-type: none">- Fribourg- Fribourg+R2C- Fribourg+R2C+C- Fribourg+M1- Fribourg+M1+R2C- Fribourg+M1+R2C+C- Fribourg+M1+M2- Fribourg+R	<ul style="list-style-type: none">- Fribourg- Fribourg+R2C- Fribourg+M1- Fribourg+M1+M2- Fribourg+M1+M2+R2C- Fribourg+R
External tests	<ul style="list-style-type: none">- Fribourg+M1+R2C- Piterman+EQ+RO- Rank+TR+RO- Slice+P+RO+MADJ+EG	<ul style="list-style-type: none">- Fribourg+M1+M2+R2C- Piterman+EQ+RO- Rank+TR+RO- Slice+P+RO+MADJ+EG

Test Setup

- Shorthand naming for test scenarios:

	GOAL test set	Michel test set
Internal	IG	IM
External	EG	EM


- IG and EG
 - ▶ Time limit: 600 seconds CPU time
 - ▶ Memory limit: 1 GB Java heap
 - ▶ Effective samples:
 - Automata which have been successfully complemented by **all** constructions of a test scenario
- IM and EM: no limits


Results: Internal Tests on GOAL Test Set

	GOAL test set	Michel test set
Internal	IG	IM
External	EG	EM


- Fribourg
- Fribourg+R2C
- Fribourg+R2C+C
- Fribourg+M1
- Fribourg+M1+R2C
- Fribourg+M1+R2C+C
- Fribourg+M1+M2
- Fribourg+R

IG: Complement Sizes (10,939 Eff. Samples)







Fribourg




Fribourg+R2C




Fribourg+R2C+C




Fribourg+R




Fribourg+M1



Fribourg+M1+R2C



Fribourg+M1+R2C+C




Fribourg+M1+M2

Results: Internal Tests on Michel Test Set


	GOAL test set	Michel test set
Internal	IG	IM
External	EG	EM

- Fribourg
- Fribourg+R2C
- Fribourg+M1
- Fribourg+M1+M2
- Fribourg+M1+M2+R2C
- Fribourg+R

IM: Complement Sizes



IM: Execution times




Results: External Tests on GOAL Test Set


	GOAL test set	Michel test set
Internal	IG	IM
External	EG	EM


- Fribourg+M1+R2C
- Piterman+EQ+RO
- Rank+TR+RO
- Slice+P+RO+MADJ+EG

EG: Complement Sizes (7,204 Eff. Samples)




EG: Complement Sizes (10,998 Eff. Samples)






Piterman+EQ+RO



Slice+P+RO+MADJ+EG




Fribourg+M1+R2C

Results: External Tests on Michel Test Set


	GOAL test set	Michel test set
Internal	IG	IM
External	EG	EM

- Fribourg+M1+M2+R2C
- Piterman+EQ+RO
- Rank+TR+RO
- Slice+P+RO+MADJ+EG

EM: Complement Sizes



EM: Execution times



The End



Thank you very much for listening!

Thank you very much for listening!

References I

- [Althoff et al., 2006] Althoff, C., Thomas, W., and Wallmeier, N. (2006).
Observations on determinization of büchi automata.
In Farré, J., Litovsky, I., and Schmitz, S., editors, *Implementation and Application of Automata*, volume 3845 of *Lecture Notes in Computer Science*, pages 262–272. Springer Berlin Heidelberg.
- [Kähler and Wilke, 2008] Kähler, D. and Wilke, T. (2008).
Complementation, disambiguation, and determinization of büchi automata unified.
In Aceto, L., Damgård, I., Goldberg, L., Halldórsson, M., Ingólfssdóttir, A., and Walukiewicz, I., editors, *Automata, Languages and Programming*, volume 5125 of *Lecture Notes in Computer Science*, pages 724–735. Springer Berlin Heidelberg.
- [Kupferman and Vardi, 1997] Kupferman, O. and Vardi, M. Y. (1997).
Weak alternating automata are not that weak.
In *Proceedings of the 5th Israeli Symposium on Theory of Computing and Systems*, pages 147–158. IEEE Computer Society Press.
- [Kupferman and Vardi, 2001] Kupferman, O. and Vardi, M. Y. (2001).
Weak alternating automata are not that weak.
ACM Trans. Comput. Logic, 2(3):408–429.
- [Michel, 1988] Michel, M. (1988).
Complementation is more difficult with automata on infinite words.
CNET, Paris, 15.
- [Muller and Schupp, 1995] Muller, D. E. and Schupp, P. E. (1995).
Simulating alternating tree automata by nondeterministic automata: New results and new proofs of the theorems of rabin, mcnaughton and safra.
Theoretical Computer Science, 141(1–2):69 – 107.

References II

[Piterman, 2006] Piterman, N. (2006).

From nondeterministic buchi and streett automata to deterministic parity automata.
In *Logic in Computer Science, 2006 21st Annual IEEE Symposium on*, pages 255–264.

[Piterman, 2007] Piterman, N. (2007).

From nondeterministic buchi and streett automata to deterministic parity automata.
Logical Methods in Computer Science, 3(5):1–21.

[Safra, 1988a] Safra, S. (1988a).

On the complexity of omega-automata.
Journal of Computer and System Science.

[Safra, 1988b] Safra, S. (1988b).

On the complexity of omega-automata.
In *Foundations of Computer Science, 1988., 29th Annual Symposium on*, pages 319–327.

[Schewe, 2009] Schewe, S. (2009).

Büchi complementation made tight.
In *26th International Symposium on Theoretical Aspects of Computer Science-STACS 2009*, pages 661–672.

[Sistla et al., 1985] Sistla, A., Vardi, M., and Wolper, P. (1985).

The complementation problem for büchi automata with applications to temporal logic.
In Brauer, W., editor, *Automata, Languages and Programming*, volume 194 of *Lecture Notes in Computer Science*, pages 465–474. Springer Berlin Heidelberg.

[Sistla et al., 1987] Sistla, A. P., Vardi, M. Y., and Wolper, P. (1987).

The complementation problem for büchi automata with applications to temporal logic.
Theoretical Computer Science, 49(2–3):217 – 237.

References III

[Thomas, 1999] Thomas, W. (1999).

Complementation of büchi automata revisited.

In Karhumäki, J., Maurer, H., Păun, G., and Rozenberg, G., editors, *Jewels are Forever*, pages 109–120. Springer Berlin Heidelberg.

[Tsai et al., 2011] Tsai, M.-H., Fogarty, S., Vardi, M., and Tsay, Y.-K. (2011).

State of büchi complementation.

In Domaratzki, M. and Salomaa, K., editors, *Implementation and Application of Automata*, volume 6482 of *Lecture Notes in Computer Science*, pages 261–271. Springer Berlin Heidelberg.

[Vardi and Wilke, 2007] Vardi, M. Y. and Wilke, T. (2007).

Automata: From logics to algorithms.

In Flum, J., Grädel, E., and Wilke, T., editors, *Logic and Automata: History and Perspectives*, volume 2 of *Texts in Logic and Games*, pages 629–736. Amsterdam University Press.