

When insert three keys into a non-empty 2-3 tree, and if the tree gains height when the first key is in, then it is possible that the 2-3 tree will gain more height after the insertions of the next two keys.


F

The time bound of the FIND operation in a B+ tree containing  $N$  numbers is  $O(\log N)$ , no matter what the degree of the tree is.

☒ T ☐ F

答案正确: 1 分 [创建提问](#)

The following binary search tree is a valid red-black tree.



F

When inserting a node into a red-black tree, we shall first insert the node as into an ordinary binary search tree, and then color the node black.

F 先涂色

In a Red-Black tree, the path from the root to the farthest leaf is no more than twice as long as the path from the root to the nearest leaf.

☒ T ☐ F

答案正确: 1 分 [创建提问](#)

In a B+ tree, leaves and nonleaf nodes have some key values in common.

☒ T ☐ F

答案正确: 1 分 [创建提问](#)

The root of a B+ tree of order  $m$  has at most  $m$  subtrees.

☒ T ☐ F

答案正确: 1 分 [创建提问](#)

In a red-black tree with 3 nodes, there must be a red node.

F

In the worst case the DELETE operation in a RED-BLACK tree of  $n$  nodes requires  $\Omega(\log n)$  rotations.

F

In a red-black tree with 2 nodes, there must be a red node.

☒ T ☐ F

答案正确: 1 分

💡 创建提问 [↗](#)