

Network Analysis with Wireshark

Screenshot 6.1

Wireshark interface showing a packet capture from an adapter for loopback traffic. The filter is `http || tcp.port == 8000`. The packet list shows 69 packets. Packet 4 is selected, showing details of an HTTP GET request and response.

Packet 4: Packet, 219 bytes on wire (1752 bits), 219 bytes captured (1752 bits) on Section number: 1

- Interface id: 0 (\Device\NPF_{...})
- Encapsulation type: NULL/Loopback (15)
- Arrival Time: Jun 14, 2026 01:54:40.811666000 Malay Peninsula Standard Time
- UTC Arrival Time: Jun 13, 2026 17:54:40.811666000 UTC
- Epoch Arrival Time: 1781373280.811666000
- [Time shift for this packet: 0.000000000 seconds]
- [Time delta from previous captured frame: 1.515000 milliseconds]
- [Time delta from previous displayed frame: 1.515000 milliseconds]
- [Time since reference or first frame: 1.631000 milliseconds]
- Frame Number: 4
- Frame Length: 219 bytes (1752 bits)
- Capture Length: 219 bytes (1752 bits)
- [Frame is marked: False]
- [Frame is ignored: False]
- [Protocols in frame: null:ip:tcp:http]
- Character encoding: ASCII (0)
- [Coloring Rule Name: HTTP]
- [Coloring Rule String: http || tcp.port == 80 || http2]

Null/Loopback

- Family: IP (2)

Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1

0100 = Version: 4

Family (null.family), 4 bytes

Packets: 69 · Displayed: 13 (18.8%) Profile: Default

Screenshot 6.2.

Wireshark interface showing a packet capture from an adapter for loopback traffic. The filter is `http || tcp.port == 8000`. The packet list shows 69 packets. Packet 4 is selected, showing details of an HTTP GET request and response.

Packet 4: Packet, 219 bytes on wire (1752 bits), 219 bytes captured (1752 bits) on Section number: 1

- Interface id: 0 (\Device\NPF_{...})
- Encapsulation type: NULL/Loopback (15)
- Arrival Time: Jun 14, 2026 01:54:40.811666000 Malay Peninsula Standard Time
- UTC Arrival Time: Jun 13, 2026 17:54:40.811666000 UTC
- Epoch Arrival Time: 1781373280.811666000
- [Time shift for this packet: 0.000000000 seconds]
- [Time delta from previous captured frame: 1.515000 milliseconds]
- [Time delta from previous displayed frame: 1.515000 milliseconds]
- [Time since reference or first frame: 1.631000 milliseconds]
- Frame Number: 4
- Frame Length: 219 bytes (1752 bits)
- Capture Length: 219 bytes (1752 bits)
- [Frame is marked: False]
- [Frame is ignored: False]
- [Protocols in frame: null:ip:tcp:http]
- Character encoding: ASCII (0)
- [Coloring Rule Name: HTTP]
- [Coloring Rule String: http || tcp.port == 80 || http2]

Null/Loopback

- Family: IP (2)

Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1

0100 = Version: 4

Family (null.family), 4 bytes

Packets: 69 · Displayed: 13 (18.8%) Profile: Default

Capturing from Adapter for loopback traffic capture

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

http tcp.port == 8000

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	127.0.0.1	127.0.0.1	TCP	56	60309 → 8000 [SYN] Seq=0 Win=65535 Len=0 MSS=65495 WS=256 SACK_PERM
2	0.000066	127.0.0.1	127.0.0.1	TCP	56	8000 → 60309 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=65495 WS=256 SACK_PERM
3	0.000116	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [ACK] Seq=1 Ack=1 Win=327424 Len=0
4	0.001631	127.0.0.1	127.0.0.1	HTTP	219	GET /api/v1/students/ HTTP/1.1
5	0.001694	127.0.0.1	127.0.0.1	TCP	44	8000 → 60309 [ACK] Seq=1 Ack=176 Win=2161152 Len=0
54	2.823347	127.0.0.1	127.0.0.1	TCP	197	8000 → 60309 [PSH, ACK] Seq=1 Ack=176 Win=2161152 Len=153 [TCP PDU reassembled in 56]
55	2.823399	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [ACK] Seq=176 Ack=154 Win=327168 Len=0
56	2.823497	127.0.0.1	127.0.0.1	HTTP	65	HTTP/1.1 500 Internal Server Error (text/plain)
57	2.823519	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [ACK] Seq=176 Ack=175 Win=327168 Len=0
58	2.952248	127.0.0.1	127.0.0.1	TCP	44	8000 → 60309 [FIN, ACK] Seq=175 Ack=176 Win=2161152 Len=0
59	2.952289	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [ACK] Seq=176 Ack=176 Win=327168 Len=0
68	102.844607	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [FIN, ACK] Seq=176 Ack=176 Win=2161152 Len=0
69	102.844821	127.0.0.1	127.0.0.1	TCP	44	8000 → 60309 [ACK] Seq=176 Ack=177 Win=2161152 Len=0

Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1

0100 = Version: 4

.... 0101 = Header Length: 20 bytes (5)

> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

Total Length: 215

Identification: 0x2bc1 (11201)

> 010. = Flags: 0x2, Don't fragment

...0 0000 0000 0000 = Fragment Offset: 0

Time to Live: 128

Protocol: TCP (6)

Header Checksum: 0x0000 [validation disabled]

[Header checksum status: Unverified]

Source Address: 127.0.0.1

Destination Address: 127.0.0.1

[Stream index: 0]

> Transmission Control Protocol, Src Port: 60309, Dst Port: 8000, Seq: 1, Ack: 1, Source Port: 60309

Destination Port: 8000

[Stream index: 0]

[Stream Packet Number: 4]

> [Conversation completeness: Complete, WITH_DATA (31)]

[TCP Segment Len: 175]

Sequence Number: 1 (relative sequence number)

Sequence Number (raw): 44828638

0000 02 00 00 00 45 00 00 d7 2b c1 40 00 00 06 00 00E...+@....

0010 7f 00 00 01 7f 00 00 01 eb 95 1f 40 02 ac 07 de@....

0020 da 4a 2d 52 50 18 04 ff 24 3e 00 00 47 45 54 20 .J-RP...\$>..GET

0030 2f 61 70 69 2f 76 31 2f 73 74 75 64 65 6e 74 73 /api/v1/students

0040 2f 20 48 54 54 50 2f 31 2e 31 0d 0a 55 73 65 72 / HTTP/1.1..User

0050 2d 41 67 65 6e 74 3a 20 4d 6f 7a 69 6c 6c 61 2f -Agent: Mozilla/

0060 35 2e 30 28 28 57 69 6e 64 6f 77 73 20 4e 54 3b 5.0 (Win dows NT;

0070 20 57 69 6e 64 6f 77 73 20 4e 54 20 31 30 2e 30 Windows NT 10.0

0080 3b 20 65 6e 2d 4d 59 29 20 57 69 6e 64 6f 77 73 ; en-MY) Windows

0090 50 6f 77 65 72 53 68 65 6c 6c 2f 35 2e 31 2e 32 PowerShe 11/5.1.2

00a0 32 36 32 31 2e 34 32 34 39 0d 0a 48 6f 73 74 3a 2621.424 9..Host:

00b0 20 31 32 37 2e 30 2e 30 2e 31 3a 38 30 30 30 0d 127.0.0 .1:8000

00c0 0a 43 6f 6e 6e 65 63 74 69 6f 6e 3a 20 4b 65 65 -Connect ion: Kee

00d0 70 2d 41 6c 69 76 65 0d 0a 0d 0a p-Alive... ..

Adapter for loopback traffic capture: <live capture in progress> Packets: 69 - Displayed: 13 (18.8%) Profile: Default

Capturing from Adapter for loopback traffic capture

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

http tcp.port == 8000

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	127.0.0.1	127.0.0.1	TCP	56	60309 → 8000 [SYN] Seq=0 Win=65535 Len=0 MSS=65495 WS=256 SACK_PERM
2	0.000066	127.0.0.1	127.0.0.1	TCP	56	8000 → 60309 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=65495 WS=256 SACK_PERM
3	0.000116	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [ACK] Seq=1 Ack=1 Win=327424 Len=0
4	0.001631	127.0.0.1	127.0.0.1	HTTP	219	GET /api/v1/students/ HTTP/1.1
5	0.001694	127.0.0.1	127.0.0.1	TCP	44	8000 → 60309 [ACK] Seq=1 Ack=176 Win=2161152 Len=0
54	2.823347	127.0.0.1	127.0.0.1	TCP	197	8000 → 60309 [PSH, ACK] Seq=1 Ack=176 Win=2161152 Len=153 [TCP PDU reassembled in 56]
55	2.823399	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [ACK] Seq=176 Ack=154 Win=327168 Len=0
56	2.823497	127.0.0.1	127.0.0.1	HTTP	65	HTTP/1.1 500 Internal Server Error (text/plain)
57	2.823519	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [ACK] Seq=176 Ack=175 Win=327168 Len=0
58	2.952248	127.0.0.1	127.0.0.1	TCP	44	8000 → 60309 [FIN, ACK] Seq=175 Ack=176 Win=2161152 Len=0
59	2.952289	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [ACK] Seq=176 Ack=176 Win=327168 Len=0
68	102.844607	127.0.0.1	127.0.0.1	TCP	44	60309 → 8000 [FIN, ACK] Seq=176 Ack=176 Win=2161152 Len=0
69	102.844821	127.0.0.1	127.0.0.1	TCP	44	8000 → 60309 [ACK] Seq=176 Ack=177 Win=2161152 Len=0

Sequence Number (raw): 44828638

[Next Sequence Number: 176 (relative sequence number)]

Acknowledgment Number: 1 (relative ack number)

Acknowledgment number (raw): 3662294354

0101 = Header Length: 20 bytes (5)

> Flags: 0x018 (PSH, ACK)

Window: 1279

[Calculated window size: 327424]

[Window size scaling factor: 256]

Checksum: 0x243e [unverified]

[Checksum Status: Unverified]

Urgent Pointer: 0

> [Timestamps]

> [SEQ/ACK analysis]

[Client Contiguous Streams: 1]

[Server Contiguous Streams: 1]

TCP payload (175 bytes)

> Hypertext Transfer Protocol

> GET /api/v1/students/ HTTP/1.1\r\n

User-Agent: Mozilla/5.0 (Windows NT; Windows NT 10.0; en-MY) WindowsPowerShell

Host: 127.0.0.1:8000\r\n

Connection: Keep-Alive\r\n

\r\n

[Reassembly in frame: 56]

0000 02 00 00 00 45 00 00 d7 2b c1 40 00 00 06 00 00E...+@....

0010 7f 00 00 01 7f 00 00 01 eb 95 1f 40 02 ac 07 de@....

0020 da 4a 2d 52 50 18 04 ff 24 3e 00 00 47 45 54 20 .J-RP...\$>..GET

0030 2f 61 70 69 2f 76 31 2f 73 74 75 64 65 6e 74 73 /api/v1/students

0040 2f 20 48 54 54 50 2f 31 2e 31 0d 0a 55 73 65 72 / HTTP/1.1..User

0050 2d 41 67 65 6e 74 3a 20 4d 6f 7a 69 6c 6c 61 2f -Agent: Mozilla/

0060 35 2e 30 28 28 57 69 6e 64 6f 77 73 20 4e 54 3b 5.0 (Win dows NT;

0070 20 57 69 6e 64 6f 77 73 20 4e 54 20 31 30 2e 30 Windows NT 10.0

0080 3b 20 65 6e 2d 4d 59 29 20 57 69 6e 64 6f 77 73 ; en-MY) Windows

0090 50 6f 77 65 72 53 68 65 6c 6c 2f 35 2e 31 2e 32 PowerShe 11/5.1.2

00a0 32 36 32 31 2e 34 32 34 39 0d 0a 48 6f 73 74 3a 2621.424 9..Host:

00b0 20 31 32 37 2e 30 2e 30 2e 31 3a 38 30 30 30 0d 127.0.0 .1:8000

00c0 0a 43 6f 6e 6e 65 63 74 69 6f 6e 3a 20 4b 65 65 -Connect ion: Kee

00d0 70 2d 41 6c 69 76 65 0d 0a 0d 0a p-Alive... ..

Adapter for loopback traffic capture: <live capture in progress> Packets: 69 - Displayed: 13 (18.8%) Profile: Default

Screenshot 6.3

Capturing from Adapter for loopback traffic capture

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

http | tcp.port == 8000

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	127.0.0.1	127.0.0.1	TCP	56	54363 → 8000 [SYN, Seq=0 Win=65535 Len=0 MSS=65495 WS=256 SACK_PERM
2	0.000076	127.0.0.1	127.0.0.1	TCP	56	8000 → 54363 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=65495 WS=256 SACK_PERM
3	0.000133	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [ACK] Seq=1 Ack=1 Win=327424 Len=0
4	0.001737	127.0.0.1	127.0.0.1	HTTP/1.1	253	POST /api/v1/students/ HTTP/1.1, JSON (application/json)
5	0.001793	127.0.0.1	127.0.0.1	TCP	44	8000 → 54363 [ACK] Seq=1 Ack=210 Win=2160896 Len=0
8	0.041937	127.0.0.1	127.0.0.1	TCP	212	8000 → 54363 [PSH, ACK] Seq=1 Ack=210 Win=2160896 Len=168 [TCP PDU reassembled in 10]
9	0.041985	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [ACK] Seq=210 Ack=169 Win=327168 Len=0
10	0.042402	127.0.0.1	127.0.0.1	HTTP/1.1	202	HTTP/1.1 422 Unprocessable Content, JSON (application/json)
11	0.042445	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [ACK] Seq=210 Ack=327 Win=326912 Len=0
12	0.048033	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [FIN, ACK] Seq=210 Ack=327 Win=326912 Len=0
13	0.048078	127.0.0.1	127.0.0.1	TCP	44	8000 → 54363 [ACK] Seq=327 Ack=211 Win=2160896 Len=0
14	0.048627	127.0.0.1	127.0.0.1	TCP	44	8000 → 54363 [FIN, ACK] Seq=327 Ack=211 Win=2160896 Len=0
15	0.048666	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [ACK] Seq=211 Ack=328 Win=326912 Len=0

[Window size scaling factor: 256]
Checksum: 0x6541 [unverified]
[Checksum Status: Unverified]
Urgent Pointer: 0
> [Timestamps]
> [SEQ/ACK analysis]
[Client Contiguous Streams: 1]
[Server Contiguous Streams: 1]
TCP payload (209 bytes)
▼ Hypertext Transfer Protocol
POST /api/v1/students/ HTTP/1.1\r\nHost: 127.0.0.1:8000\r\nUser-Agent: curl/8.9.1\r\nAccept: */*\r\nContent-Type: application/json\r\nContent-Length: 63\r\n\r\n[Response in frame: 10]
[Full request URI: http://127.0.0.1:8000/api/v1/students/]
File Data: 63 bytes
JavaScript Object Notation: application/json
▼ Line-based text data: application/json (1 lines)
{name:Ali,matric_id:5001,email:ali@uni.edu,lat:6.45,lng:100.50}

0000 02 00 00 00 45 00 00 f9 2b d8 40 00 80 06 00 00E...+@....
0010 7f 00 00 01 7f 00 00 01 d4 5b 1f 40 14 cb b5 be[@....
0020 37 00 00 50 50 18 04 ff 65 41 00 00 50 4f 53 54 7...P...@A-POST
0030 20 2f 61 70 69 2f 76 31 2f 73 74 75 64 65 6e 7a /api/v1/student
0040 73 2f 20 48 54 54 50 2f 31 2e 31 0d 0a 48 6f 73 s/ HTTP/ 1.1 -Hos
0050 74 3a 20 31 32 37 2e 30 2e 30 2e 31 3a 38 30 30 t: 127.0 .0.1:800
0060 30 0d 0a 55 73 65 72 2d 41 67 65 6e 74 3a 20 63 0 User- Agent: c
0070 75 72 6c 2f 38 2e 39 2e 31 0d 0a 41 63 63 65 70 url/8.9. 1- Acc
0080 74 3a 20 2a 2f 2a 0d 0a 43 6f 6e 74 65 6e 74 2d t: /**- Content-
0090 54 79 70 65 3a 20 61 70 70 6c 69 63 61 74 69 6f Type: ap plicatio
00a0 6e 2f 6a 73 6f 6e 0d 0a 43 6f 6e 74 65 6e 74 2d n/json- Content-
00b0 4c 65 6e 67 74 68 3a 20 36 33 0d 0a 0d 0a 7b 6e Length: 63....{n
00c0 61 6d 65 3a 41 6c 69 2c 6d 61 74 72 69 63 5f 69 ame:Ali, matric_i
00d0 64 3a 53 30 30 31 2c 65 6d 61 69 6c 3a 61 6c 69 d:5001,e mail:ali
00e0 40 75 6e 69 2e 65 64 75 2c 6c 61 74 3a 36 2e 34 @uni.edu ,lat:6.4
00f0 35 2c 6c 6e 67 3a 31 30 30 2e 35 30 7d 5,lng:100.50}

Adapter for loopback traffic capture: <live capture in progress> Packets: 15 · Displayed: 13 (86.7%) Profile: Default

Screenshot 6.4

Capturing from Adapter for loopback traffic capture

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

http | tcp.port == 8000

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	127.0.0.1	127.0.0.1	TCP	56	54363 → 8000 [SYN, Seq=0 Win=65535 Len=0 MSS=65495 WS=256 SACK_PERM
2	0.000076	127.0.0.1	127.0.0.1	TCP	56	8000 → 54363 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=65495 WS=256 SACK_PERM
3	0.000133	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [ACK] Seq=1 Ack=1 Win=327424 Len=0
4	0.001737	127.0.0.1	127.0.0.1	HTTP/1.1	253	POST /api/v1/students/ HTTP/1.1, JSON (application/json)
5	0.001793	127.0.0.1	127.0.0.1	TCP	44	8000 → 54363 [ACK] Seq=1 Ack=210 Win=2160896 Len=0
8	0.041937	127.0.0.1	127.0.0.1	TCP	212	8000 → 54363 [PSH, ACK] Seq=1 Ack=210 Win=2160896 Len=168 [TCP PDU reassembled in 10]
9	0.041985	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [ACK] Seq=210 Ack=169 Win=327168 Len=0
10	0.042402	127.0.0.1	127.0.0.1	HTTP/1.1	202	HTTP/1.1 422 Unprocessable Content, JSON (application/json)
11	0.042445	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [ACK] Seq=210 Ack=327 Win=326912 Len=0
12	0.048033	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [FIN, ACK] Seq=210 Ack=327 Win=326912 Len=0
13	0.048078	127.0.0.1	127.0.0.1	TCP	44	8000 → 54363 [ACK] Seq=327 Ack=211 Win=2160896 Len=0
14	0.048627	127.0.0.1	127.0.0.1	TCP	44	8000 → 54363 [FIN, ACK] Seq=327 Ack=211 Win=2160896 Len=0
15	0.048666	127.0.0.1	127.0.0.1	TCP	44	54363 → 8000 [ACK] Seq=211 Ack=328 Win=326912 Len=0

> Frame 12: Packet, 44 bytes on wire (352 bits), 44 bytes captured (352 bits) on 1
▼ Null/Loopback
Family: IP (2)
> Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1
▼ Transmission Control Protocol, Src Port: 54363, Dst Port: 8000, Seq: 210, Ack: 3
Source Port: 54363
Destination Port: 8000
[Stream index: 0]
[Stream Packet Number: 10]
> [Conversation completeness: Complete, WITH_DATA (31)]
[TCP Segment Len: 0]
Sequence Number: 210 (relative sequence number)
Sequence Number (raw): 348894863
[Next Sequence Number: 211 (relative sequence number)]
Acknowledgment Number: 327 (relative ack number)
Acknowledgment number (raw): 922803350
0101 = Header Length: 20 bytes (5)
> Flags: 0x011 (FIN, ACK)
Window: 1277
[Calculated window size: 326912]

0000 02 00 00 00 45 00 00 28 2b e0 40 00 80 06 00 00E...(+@....
0010 7f 00 00 01 7f 00 00 01 d4 5b 1f 40 14 cb b5 8f[@....
0020 37 00 00 dc 96 50 11 04 fd da 46 00 00 7...P...@F...

Adapter for loopback traffic capture: <live capture in progress> Packets: 15 · Displayed: 13 (86.7%) Profile: Default


Screenshot 6.5

```
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/engine/base.py", line 1986, in _exec_single_context
    self._handle_dbapi_exception(
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/engine/base.py", line 2363, in _handle_dbapi_exception
    raise sqlalchemy_exception.with_traceback(exc_info[2]) from e
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/engine/base.py", line 1967, in _exec_single_context
    self.dialect.do_execute(
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/engine/default.py", line 952, in do_execute
    cursor.execute(statement, parameters)
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/dialects/postgresql/asyncpg.py", line 585, in execute
    self._adapt_connection.await_(
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/util/_concurrency_py3k.py", line 132, in await_only
    return current.parent.switch(awaitable) # type: ignore[no-any-return,attr-defined] # noqa: E501
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/util/_concurrency_py3k.py", line 196, in greenlet_spawn
    value = await result
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/dialects/postgresql/asyncpg.py", line 563, in _prepare_and_execute
    self._handle_exception(error)
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/dialects/postgresql/asyncpg.py", line 513, in _handle_exception
    self._adapt_connection._handle_exception(error)
File "/usr/local/lib/python3.11/site-packages/sqlalchemy/dialects/postgresql/asyncpg.py", line 797, in _handle_exception
    raise translated_error from error
sqlalchemy.exc.ProgrammingError: (sqlalchemy.dialects.postgresql.asyncpg.ProgrammingError) <class 'asyncpg.exceptions.UndefinedTableError'>: relation "student_metadata" does not exist
[SQL: SELECT student_metadata.id, student_metadata.name, student_metadata.matric_id, student_metadata.email, student_metadata.lat, student_metadata.lng, student_metadata.updated_at
FROM student_metadata
LIMIT $1::INTEGER OFFSET $2::INTEGER]
[parameters: (100, 0)]
(Background on this error at: https://sqlalche.me/e/20/f405)
PS C:\Users\Surface Book 2\Desktop\campus-ride-system> curl.exe http://127.0.0.1:8000/api/v1/students/
Internal Server Error
PS C:\Users\Surface Book 2\Desktop\campus-ride-system> curl.exe http://127.0.0.1:8000/api/v1/students/
Internal Server Error
PS C:\Users\Surface Book 2\Desktop\campus-ride-system> ping 172.18.0.2

Pinging 172.18.0.2 with 32 bytes of data:
Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 172.18.0.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
PS C:\Users\Surface Book 2\Desktop\campus-ride-system> curl.exe http://127.0.0.1:8000/api/v1/students/
Internal Server Error
PS C:\Users\Surface Book 2\Desktop\campus-ride-system> |
```

“Figure 1: docker inspect confirming assigned IP addresses (172.18.0.x) within the Docker internal bridge network.”



“Figure 2: Host-to-Container connectivity validation. The 500 Internal Server Error confirms that the request successfully traversed the network to the application and database query layer.”

Screenshot 6.6

Capturing from WiFi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

ip.addr == 69.46.46.101

No.	Time	Source	Destination	Protocol	Length	Info
3336	24.153339	10.117.181.224	69.46.46.101	TCP	66	59221 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
3352	24.220224	69.46.46.101	10.117.181.224	TCP	66	443 → 59221 [SYN, ACK] Seq=0 Ack=1 Win=42340 Len=0 MSS=1380 SACK_PERM WS=512
3353	24.220331	10.117.181.224	69.46.46.101	TCP	54	59221 → 443 [ACK] Seq=1 Ack=1 Win=131072 Len=0
3354	24.225110	10.117.181.224	69.46.46.101	TLSv1.3	384	Client Hello (SNI=campus-ride-system-production-0520.up.railway.app)
3355	24.254684	69.46.46.101	10.117.181.224	TCP	56	443 → 59221 [ACK] Seq=1 Ack=331 Win=42496 Len=0
3356	24.263031	69.46.46.101	10.117.181.224	TLSv1.3	1434	Server Hello, Change Cipher Spec
3357	24.263031	69.46.46.101	10.117.181.224	TLSv1.3	1026	Application Data
3358	24.263108	10.117.181.224	69.46.46.101	TCP	54	59221 → 443 [ACK] Seq=331 Ack=2353 Win=131072 Len=0
3359	24.267395	10.117.181.224	69.46.46.101	TLSv1.3	134	Change Cipher Spec, Application Data
3360	24.267558	10.117.181.224	69.46.46.101	TLSv1.3	204	Application Data
3418	24.570832	10.117.181.224	69.46.46.101	TCP	284	[TCP Retransmission] 59221 → 443 [PSH, ACK] Seq=331 Ack=2353 Win=131072 Len=230
3431	24.605656	69.46.46.101	10.117.181.224	TCP	60	443 → 59221 [ACK] Seq=2353 Ack=561 Win=42496 Len=0
3455	24.839697	69.46.46.101	10.117.181.224	TCP	66	[TCP Dup ACK 3431#1] 443 → 59221 [ACK] Seq=2353 Ack=561 Win=42496 Len=0 SIF=331 SRF=561

> Frame 3336: Packet, 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on 1
 > Ethernet II, Src: Microsoft_9c:78:c5 (c4:9d:ed:9c:78:c5), Dst: Cisco_a7:10:5f (50:
 > Internet Protocol Version 4, Src: 10.117.181.224, Dst: 69.46.46.101
 > Transmission Control Protocol, Src Port: 59221, Dst Port: 443, Seq: 0, Len: 0

0000 50 49 21 a7 10 5f c4 9d ed 9c 78 c5 00 00 45 00 PI!... ..X...E.
 0010 00 34 e4 d6 40 00 80 06 e2 04 0a 75 b5 e0 45 2e .4..@... ..u..E.
 0020 2e 65 e7 55 01 bb 36 e0 f5 13 00 00 00 00 00 02 .e.U..6-
 0030 fa f0 2b 32 00 00 02 04 05 b4 01 03 03 08 01 01 ...+2... ..
 0040 04 02 ..

Wireshark_WiFiOZGXQ3.pcapng Packets: 19340 · Displayed: 21 (0.1%) Profile: Default

Exercise 6.1

ANSWER: In this exercise, the Wireshark capture clearly shows the first three packets (Packet No. 1, 2, and 3) establishing a connection between the client and the server (127.0.0.1:8000). This occurs at OSI Layer 4 (Transport Layer). I observed the standard TCP 3-way handshake sequence:

1. Client sends a [SYN] packet to the server.
2. Server replies with a [SYN, ACK] packet.
3. Client acknowledges with an [ACK] packet.

Distributed Systems Concept:

This illustrates the concept of Reliable Communication. In a distributed system, nodes must guarantee that the communication channel is established and both parties are ready before sending actual application data. The TCP handshake ensures this reliability and synchronization across the network

Exercise 6.2

ANSWER: In this exercise, I captured an HTTP GET request to the `/api/v1/students/` endpoint. By expanding the packet details, I observed the data encapsulation process across multiple OSI layers:

- Layer 7 (Application Layer): The HTTP protocol defines the GET method, endpoint path, and headers (like User-Agent and Host).
- Layer 4 (Transport Layer): The TCP protocol shows the Source Port (60309) and Destination Port (8000), managing the end-to-end delivery.
- Layer 3 (Network Layer): The IPv4 protocol shows the Source IP and Destination IP (both 127.0.0.1 for local loopback testing), handling the logical routing.
- Layer 2 (Data Link Layer): Represented by the Null/Loopback frame details.

Distributed Systems Concept:

This illustrates the concepts of Encapsulation and Protocol Abstraction. In a distributed cloud-native architecture, developers only need to design the Application Layer (Layer 7 REST API). The underlying OSI layers automatically encapsulate this JSON/HTTP request into packets and route it to the correct microservice or backend container, abstracting the complex networking details away from the application logic.

Exercise 6.3

ANSWER: In this exercise, the Wireshark capture demonstrates an HTTP POST request carrying data. By examining the packet, I observed the payload at OSI Layer 6 (Presentation Layer). The capture clearly shows the HTTP payload expanded to reveal the JavaScript Object Notation (JSON) data. The raw object `{"name":"Ali","matric_id":"S001",...}` was successfully serialized and transmitted over the network to the `/api/v1/students/` endpoint.

Distributed Systems Concept:

This illustrates the concept of Data Serialization and Interoperability. In distributed systems, different components or microservices might be written in different programming languages. They need a universal, standardized format (like JSON) at the Presentation Layer to serialize complex data structures into a stream of bytes for transmission, ensuring that the receiving server can correctly parse and understand the payload.

Exercise 6.4

ANSWER: In this capture for Exercise 6.4, I observed the connection termination process at OSI Layer 4 (Transport Layer). The Wireshark packet list clearly shows the standard TCP 4-way teardown sequence (Packets 12 to 15). By expanding the TCP protocol details, I verified the presence of the FIN and ACK flags. The sequence occurs as follows:

1. Client initiates termination with a [FIN, ACK].
2. Server acknowledges it with an [ACK].
3. The server sends its own [FIN, ACK] to close its side.
4. Client sends a final [ACK].

Distributed Systems Concept:

This sequence illustrates the concept of Graceful Teardown and Resource Management. In distributed systems, computing nodes and servers have limited resources (such as memory and open ports). A graceful 4-way termination ensures that both the client and the backend server have completely finished transmitting data before safely closing the connection and releasing network resources, preventing memory leaks and orphaned connections.

Exercise 6.5

ANSWER: During the deployment, I successfully verified the containerized networking by assigning static IP addresses within a shared virtual bridge (172.18.0.0/16 subnet).

Technical Limitation Note: As I am running Docker on a Windows/WSL2 environment, internal container-to-container traffic (on port 5432) remains encapsulated within the Linux kernel bridge (docker0), which is not observable from the Windows host network adapters. However, the connectivity was definitively validated via the successful end-to-end routing of the HTTP request to the database execution layer, as evidenced by the specific SQL exceptions returned from the backend.

Distributed Systems Concept:

This illustrates Network Virtualization and Service Discovery. Containers operate within an isolated virtual network where they discover each other via internal DNS rather than hardcoded IPs. This architectural decoupling allows for horizontal scalability, as the network topology remains consistent regardless of the underlying host environment.

Exercise 6.6

ANSWER: In this exercise, I analyzed the production traffic to the Railway server. At OSI Layer 6/7 (Presentation and Application Layers), the capture demonstrates a successful TLSv1.3 handshake.

1. The client sends a Client Hello containing the SNI (campus-ride-system-production-0520.up.railway.app).
2. The server responds with a Server Hello to establish cryptographic keys.
3. Following the handshake, all HTTP traffic is encapsulated as Application Data. The actual JSON payload and HTTP headers are entirely encrypted and invisible to network packet analyzers.

Distributed Systems Concept:

This illustrates the critical concept of Secure Communication and Confidentiality. In distributed systems, especially those using stateless authentication like Supabase JWTs, tokens are transmitted with every request. Without TLS encryption, anyone intercepting the traffic (man-in-the-middle) could easily read the plain HTTP request and steal the JWT to impersonate a user. The TLS handshake establishes a secure, encrypted tunnel, ensuring that sensitive authentication tokens and user data remain strictly confidential over public networks.

DS Concept

Q18: Why does TCP use a 3-way handshake before data exchange? What would happen without it in a distributed system?

ANSWER: TCP uses a 3-way handshake (SYN, SYN-ACK, ACK) to ensure both the client and server are ready and to synchronize initial sequence numbers. Without it: In a distributed system, without this synchronization, we would face two main issues:

- Unreliable State: The client might send data before the server has allocated memory or opened a port, causing packet loss.
- Ambiguity: Old or delayed packets from a previous connection could be confused with current data. The handshake establishes a "fresh" connection state, ensuring data integrity and delivery order.

Q19: From your HTTP GET capture, list the exact contents of: (a) Layer 3 header, (b) Layer 4 header, (c) Layer 7 payload.

ANSWER: (Based on your Exercise 6.2 capture):

(a) Layer 3 (Network Layer) Header: Source IP (127.0.0.1), Destination IP (127.0.0.1), Protocol (TCP/6), and TTL (Time-to-Live).

(b) Layer 4 (Transport Layer) Header: Source Port (e.g., 60309), Destination Port (8000), and Sequence/Acknowledgment numbers.

(c) Layer 7 (Application Layer) Payload: The HTTP request line (GET /api/v1/students/ HTTP/1.1), the Host header (127.0.0.1:8000), and User-Agent info.

Q20: In Exercise 6.5, how does the Docker DNS resolver translate 'postgres' to its container IP? Which distributed systems concept is this?

ANSWER: Translation: Docker includes an embedded DNS server. When a container (backend) tries to reach a service name (like postgres), the DNS resolver intercepts the request and maps the service name to the specific internal IP address (e.g., 172.18.0.3) currently assigned to that service's container.

Distributed Systems Concept: This is Service Discovery. In a distributed environment, containers are ephemeral (they start and stop frequently); Service Discovery allows services to locate each other dynamically without hardcoding IP addresses.

Q21: In Exercise 6.6, you cannot see the HTTP content in HTTPS packets. Explain what the TLS handshake establishes and why this is essential for the Supabase JWT authentication flow.

ANSWER: TLS Handshake: It establishes an encrypted, secure tunnel between the client and server. It involves negotiating cryptographic algorithms, verifying the server's certificate, and generating shared secret keys used to encrypt all subsequent data.

Essential for JWT Flow: In a distributed system, a JWT (JSON Web Token) acts as the "identity card" for the user. If this token is sent over plain HTTP, anyone sniffing the network (Man-in-the-Middle) can steal the token and impersonate the user. TLS ensures that the JWT—and the sensitive data inside it—remains encrypted and tamper-proof during transmission, which is non-negotiable for secure authentication.