

Bootstrap 5 Flex

彈性盒子

Bootstrap 3 與 Bootstrap 4 和 5 之間最大的區別在於 Bootstrap 5 現在使用 flexbox 而不是浮動來處理佈局。

彈性盒式佈局模組，讓您無需使用浮動或定位，即可輕鬆設計靈活的響應式佈局結構。如果您不熟悉彈性盒式佈局，可以閱讀我們的[CSS 彈性盒式佈局教學](#)。

注意： IE9 及更早版本不支援 Flexbox。

如果您需要 IE8-9 支持，請使用[Bootstrap 3](#)。它是 Bootstrap 最穩定的版本，團隊仍在支援它，修復了關鍵錯誤並更新了文件。但是，不會新增任何新功能。

若要建立 flexbox 容器並將直接子項轉換為 flex 項目，請使用下列 **d-flex** 類別：

例子

Flex item 1 Flex item 2 Flex item 3

例子

```
<div class="d-flex p-3 bg-secondary text-white">
  <div class="p-2 bg-info">Flex item 1</div>
  <div class="p-2 bg-warning">Flex item 2</div>
  <div class="p-2 bg-primary">Flex item 3</div>
</div>
```

若要建立內嵌 flexbox 容器，請使用以下 `d-inline-flex` 類別：

例子

Flex item 1 Flex item 2 Flex item 3

例子

```
<div class="d-inline-flex p-3 bg-secondary text-white">
  <div class="p-2 bg-info">Flex item 1</div>
  <div class="p-2 bg-warning">Flex item 2</div>
  <div class="p-2 bg-primary">Flex item 3</div>
</div>
```

水平方向

用於 `.flex-row` 水平（並排）顯示彈性項目。這是預設值。

提示：用於 `.flex-row-reverse` 水平方向右對齊：

例子

Flex item 1 Flex item 2 Flex item 3

Flex item 3 Flex item 2 Flex item 1

例子

```
<div class="d-flex flex-row bg-secondary">
  <div class="p-2 bg-info">Flex item 1</div>
  <div class="p-2 bg-warning">Flex item 2</div>
  <div class="p-2 bg-primary">Flex item 3</div>
</div>

<div class="d-flex flex-row-reverse bg-secondary">
  <div class="p-2 bg-info">Flex item 1</div>
  <div class="p-2 bg-warning">Flex item 2</div>
  <div class="p-2 bg-primary">Flex item 3</div>
</div>
```

垂直方向

用於 `.flex-column` 垂直顯示彈性項目（彼此堆疊），或 `.flex-column-reverse` 反轉垂直方向：

例子

Flex item 1

Flex item 2

Flex item 3

Flex item 3

Flex item 2

Flex item 1

例子

```
<div class="d-flex flex-column">  
  <div class="p-2 bg-info">Flex item 1</div>  
  <div class="p-2 bg-warning">Flex item 2</div>  
  <div class="p-2 bg-primary">Flex item 3</div>  
</div>  
  
<div class="d-flex flex-column-reverse">  
  <div class="p-2 bg-info">Flex item 1</div>  
  <div class="p-2 bg-warning">Flex item 2</div>  
  <div class="p-2 bg-primary">Flex item 3</div>  
</div>
```

廣告

移除廣告

內容合理化

使用 `.justify-content-*` 類別來變更彈性項目的對齊方式。有效類別包括（`start` 預設）`end`、`center` 或 `between`：`around`

例子

Flex item 1 Flex item 2 Flex item 3

Flex item 1 Flex item 2 Flex item 3

Flex item 1 Flex item 2 Flex item 3

Flex item 1

Flex item 2

Flex item 3

Flex item 1

Flex item 2

Flex item 3

例子

```
<div class="d-flex justify-content-start">...</div>
<div class="d-flex justify-content-end">...</div>
<div class="d-flex justify-content-center">...</div>
<div class="d-flex justify-content-between">...</div>
<div class="d-flex justify-content-around">...</div>
```

填充/等寬

在彈性項目上使用 `.flex-fill` 以強制它們具有相同的寬度：

例子

Flex item 1

Flex item 2

Flex item 3

例子

```
<div class="d-flex">
  <div class="p-2 bg-info flex-fill">Flex item 1</div>
  <div class="p-2 bg-warning flex-fill">Flex item 2</div>
  <div class="p-2 bg-primary flex-fill">Flex item 3</div>
</div>
```

生長

在彈性項目上使用 `.flex-grow-1` 來佔據剩餘空間。在下面的範例中，前兩個彈性項目佔據了其必要的空間，而最後一個彈性項目佔據了剩餘的可用空間：

例子

Flex item 1 Flex item 2 Flex item 3

例子

```
<div class="d-flex">
  <div class="p-2 bg-info">Flex item 1</div>
  <div class="p-2 bg-warning">Flex item 2</div>
  <div class="p-2 bg-primary flex-grow-1">Flex item 3</div>
</div>
```

提示：如有必要，在柔性物品上使用 `.flex-shrink-1` 可使其收縮。

命令

使用類別來變更特定彈性項目的視覺順序 `.order`。有效的類號範圍為 0 到 5，其中數字越小，優先順序越高（例如，順序 1 顯示在順序 2 之前，等等）。

例子

Flex item 3 Flex item 2 Flex item 1

例子

```
<div class="d-flex bg-secondary">  
  <div class="p-2 bg-info order-3">Flex item 1</div>  
  <div class="p-2 bg-warning order-2">Flex item 2</div>  
  <div class="p-2 bg-primary order-1">Flex item 3</div>  
</div>
```

自動邊距

`.ms-auto` 使用（將項目推到右側）或使用 `.me-auto` （將項目推到左側）輕鬆為彈性項目添加自動邊距：

例子

Flex item 1 Flex item 2 Flex item 3

Flex item 1 Flex item 2 Flex item 3

例子


```
<div class="d-flex bg-secondary">
  <div class="p-2 ms-auto bg-info">Flex item 1</div>
  <div class="p-2 bg-warning">Flex item 2</div>
  <div class="p-2 bg-primary">Flex item 3</div>
</div>

<div class="d-flex bg-secondary">
  <div class="p-2 bg-info">Flex item 1</div>
  <div class="p-2 bg-warning">Flex item 2</div>
  <div class="p-2 me-auto bg-primary">Flex item 3</div>
</div>
```

裏

`.flex-nowrap` 使用（預設） `.flex-wrap` 或控制彈性項目如何在彈性容器中包裝 `.flex-wrap-reverse` 。

點擊下面的按鈕，透過更改範例框中彈性項目的包裝來查看三個類別之間的差異：

例子

Flex item 1	Flex item 2	Flex item 3	Flex item 4	Flex item 5	Flex item 6	Flex item 7	Flex item 8	Flex item 9	Flex item 10
Flex item 11	Flex item 12	Flex item 13	Flex item 14	Flex item 15	Flex item 16	Flex item 17	Flex item 18	Flex item 19	
Flex item 20	Flex item 21	Flex item 22	Flex item 23	Flex item 24	Flex item 25				

例子

```
<div class="d-flex flex-wrap">..<div class="d-flex flex-wrap-reverse">..<div class="d-flex flex-nowrap">..
```

對齊內容

使用類別控制聚合彈性項目的垂直對齊方式。 `.align-content-*` 有效類別包括（ `.align-content-start` 預設） `.align-content-end` 、 、 、 和。 `.align-content-center` `.align-content-between` `.align-content-around` `.align-content-stretch`

注意：這些類別對單行彈性項目沒有影響。

點擊下面的按鈕，透過更改範例框中彈性項目的垂直對齊方式，查看五個類別之間的差異：

例子

Flex item 1	Flex item 2	Flex item 3	Flex item 4	Flex item 5	Flex item 6	Flex item 7	Flex item 8	Flex item 9	Flex item 10
Flex item 11	Flex item 12	Flex item 13	Flex item 14	Flex item 15	Flex item 16	Flex item 17	Flex item 18	Flex item 19	
Flex item 20	Flex item 21	Flex item 22	Flex item 23	Flex item 24	Flex item 25				

例子

```
<div class="d-flex flex-wrap align-content-start">..<div class="d-flex flex-wrap align-content-end">..<div class="d-flex flex-wrap align-content-center">..<div class="d-flex flex-wrap align-content-around">..<div class="d-flex flex-wrap align-content-stretch">..
```

對齊項目

使用類別控制單行彈性項目的垂直對齊方式 `.align-items-*`。有效類別包括 `.align-items-start`、`.align-items-end`、`.align-items-center`、`.align-items-baseline` 和 `.align-items-stretch`（預設）。

點擊下面的按鈕可以查看五個類別之間的差異：

例子

Flex item 1	Flex item 2	Flex item 3
-------------	-------------	-------------

例子

```
<div class="d-flex align-items-start">..<div class="d-flex align-items-end">..<div class="d-flex align-items-center">..<div class="d-flex align-items-baseline">..<div class="d-flex align-items-stretch">..
```

自我對齊

使用類別控制**指定彈性項目**的垂直對齊方式 `.align-self-*`。有效類別包括 `.align-self-start`、`.align-self-end`、`.align-self-center`、`.align-self-baseline` 和 `.align-self-stretch`（預設）。

點擊下面的按鈕可以查看五個類別之間的差異：

例子



例子

```
<div class="d-flex bg-light" style="height:150px">
  <div class="p-2 border">Flex item 1</div>
  <div class="p-2 border align-self-start">Flex item 2</div>
  <div class="p-2 border">Flex item 3</div>
</div>
```

響應式 Flex 類

所有 flex 類都帶有額外的響應類，這使得在特定螢幕尺寸上設定特定 flex 類變得容易。

此 * 符號可用 sm、md、lg、xl 或 xxl 替換，分別代表小、中、大、xlarge 和 xxlarge 螢幕。

搜尋特定的彈性類別..

Class	Description	Example
-------	-------------	---------

Flex Container	
<code>.d-*-flex</code>	Creates a flexbox container for different screens
<code>.d-*-inline-flex</code>	Creates an inline flexbox container for different screens
Direction	
<code>.flex-*-row</code>	Display flex items horizontally on different screens
<code>.flex-*-row-reverse</code>	Display flex items horizontally, and right-aligned, on different screens
<code>.flex-*-column</code>	Display flex items vertically on different screens
<code>.flex-*-column-reverse</code>	Display flex items vertically, with reversed order, on different screens screens
Justified Content	
<code>.justify-content-*-start</code>	Display flex items from the start (left-aligned) on different screens
<code>.justify-content-*-end</code>	Display flex items at the end (right-aligned) on different screens
<code>.justify-content-*-center</code>	Display flex items in the center of a flex container on different screens
<code>.justify-content-*-between</code>	Display flex items in "between" on different screens
<code>.justify-content-*-around</code>	Display flex items "around" on different screens
Fill / Equal Width	
<code>.flex-*-fill</code>	Force flex items into equal widths on different screens

Grow	
<code>.flex-*-grow-0</code>	Don't make the items grow on different screens
<code>.flex-*-grow-1</code>	Make items grow on different screens
Shrink	
<code>.flex-*-shrink-0</code>	Don't make the items shrink on diferent screens
<code>.flex-*-shrink-1</code>	Make items shrink on different screens
Order	
<code>.order-*-0-12</code>	Change the order from 0 to 5 on small screens
Wrap	
<code>.flex-*-nowrap</code>	Don't wrap items on different screens
<code>.flex-*-wrap</code>	Wrap items on different screens
<code>.flex-*-wrap-reverse</code>	Reverse the wrapping of items on different screens
Align Content	
<code>.align-content-*-start</code>	Align gathered items from the start on different screens
<code>.align-content-*-end</code>	Align gathered items at the end on different screens
<code>.align-content-*-center</code>	Align gathered items in the center on different screens
<code>.align-content-*-around</code>	Align gathered items "around" on different screens
<code>.align-content-*-stretch</code>	Stretch gathered items on different screens
Align Items	

<code>.align-items-*-start</code>	Align single rows of items from the start on different screens
<code>.align-items-*-end</code>	Align single rows of items at the end on different screens
<code>.align-items-*-center</code>	Align single rows of items in the center on different screens
<code>.align-items-*-baseline</code>	Align single rows of items on the baseline on different screens
<code>.align-items-*-stretch</code>	Stretch single rows of items on different screens
Align Self	
<code>.align-self-*-start</code>	Align a flex item from the start on different screens
<code>.align-self-*-end</code>	Align a flex item at the end on different screens
<code>.align-self-*-center</code>	Align a flex item in the center on different screens
<code>.align-self-*-baseline</code>	Align a flex item on the baseline on different screens
<code>.align-self-*-stretch</code>	Stretch a flex item on different screens