

R Basics (induction week)

Last Updated 28 Sep 2022

Dr Wei Miao

Wed, Sep 28 2022

Table of contents

1	Hello R	2
1.1	Bilingual arrangements at MSc BA	2
1.2	A brief history of R	2
1.3	Why learn R?	2
1.4	One-One comparison with Python	3
1.5	A first look at the RStudio Interface	3
1.6	Where to write R codes (I): Console	4
1.7	Where to write R codes (II): .R script	4
1.8	Where to write R codes (III): .qmd script	5
2	Introduction to Quarto	5
2.1	YAML header	5
2.2	Authoring with normal texts	5
2.3	Coding with code blocks	6
2.4	Rendering a report	7
2.5	More learning resources for Quarto	7
3	Basics of R	7
3.1	Named objects	7
3.2	Rules for object names	8
3.3	Functions	9
3.4	Collection of functions: Packages	10
3.5	Comment codes	10
3.6	Data structures	11
3.7	Data types	11
3.8	Check data types using class()	12
3.9	Data type: conversion	13
4	Vectors	13
4.1	Creating vectors	13
4.2	Indexing and subsetting	15
4.3	Element-wise operations	15

4.4	Relational operations	16
4.5	Special relational operation: <code>%in%</code>	18
5	After-class exercise	18

1 Hello R

1.1 Bilingual arrangements at MSc BA

- Primary language is Python
 - Programming (MSIN00143), Business Strategy (MSIN0093), Machine Learning electives
- Secondary language is R
 - Marketing Analytics (MSIN0094), Operations Analytics (MSIN0095), Statistical Foundations (MSIN0096)

1.2 A brief history of R

- R project was initiated by **R**obert Gentleman and **R**oss Ihaka (Univ of Auckland) in 1991; both are statisticians, who later made the language open-source.
- Since 1997, R has been developed by the R Core Team on CRAN.
- As of January 2022, it has 18,728 contributed packages. As of March 2022, R ranks 11th in the TIOBE index¹; the language peaked in 8th place in August 2020.

1.3 Why learn R?

- Super powerful data analytics and visualizations, including²
 - Data wrangling (`dplyr`) and data visualization (`ggplot`)
 - Econometrics (numerous packages)
 - Predictive analytics (numerous packages)
- Write beautiful reports/dissertations/presentations using `quarto`
 - Write your MSc dissertation (highly recommended; super efficient)
 - Effortlessly build websites. I built and maintain my [personal website](#) and the marketing course website all in R.

¹A measure of programming language popularity

²There are many R-exclusive packages, such as the state-of-the-art causal machine learning library `grf`, which we will learn in the final week.

1.4 One-One comparison with Python

Table 1: R versus Python


	R	Python
Language purpose	R is a statistical language specialized in the data analytics and visualization . Best for data science, may not be robust for production environment.	Python is a general-purpose language that is used for the deployment and development of various projects. Best for production environment.
Data analytics	R is better at statistical models and econometrics .	Python is better at machine learning due to support from PyTorch and TensorFlow.
IDEs	RStudio	Many options such as Jupyter Notebook, Spyder, Pycharm, etc.
Targeted users	Primary users of R include researchers in academia and data scientists , who heavily rely on data analyses and visualization.	Primary users of python include developers and programmers .

1.5 A first look at the RStudio Interface

R is the **programming language**, and we need a “place” to write codes. This place is called an **Integrated development environment (IDE)**.

RStudio is THE BEST R IDE to date. And it’s interface consists of the following:

- **script**: (top left) where you do the coding
- **console**: (bottom left) where you can run commands interactively with R and see code outputs
- **environment**: (top right) a list of named objects that we have generated
- **history**: (top right) the list of past commands that we have used
- **help**: (bottom right) user manuals of functions available in R
- **package**: (bottom right) a collection of ready-to-use packages written by others



1.6 Where to write R codes (I): Console

- You can write codes *interactively* in the R console. See an example: Type the following code into your console and see what happens.

```
1 print('Hello World')

[1] "Hello World"
```

- Often used for simple exploratory tasks, where you don't need to keep a record of codes.
 - check summary statistics; inspect datasets; etc.

1.7 Where to write R codes (II): .R script

- R **script** is a text-readable file ending with .R suffix. See an example.
 - codes can be run line-by-line or *sourced* altogether

! Important

All texts in the script will be treated as R codes unless commented out.

- Often used for project development and deployment, where you don't need to communicate results to others

1.8 Where to write R codes (III): .qmd script

- Quarto³ files have a .qmd suffix. You can think of Quarto as Microsoft Word that can run R codes.
- Quarto can create dynamic content with Python and R, conveniently combining data analytics work with beautiful reporting.
 - Quarto can be thought of as the R equivalent of Jupyter Notebook but is much more powerful.
 - We will be mainly using Quarto in the marketing analytics module. You can also use Quarto to do your assignments, write your dissertation, and build your own blogging websites.
- Let's create a new quarto file together!

2 Introduction to Quarto

2.1 YAML header

- You can think of YAML header as a MS Word template, which determines how your final report looks like (font, font size, color, margins, etc.).
- The YAML header is typically at the beginning of a document, separated from the main text by three dashes (---). YAML will not appear in the final report.
- To make life easier, I will set YAML headers for all .qmd files for you in Marketing Analytics module.

2.2 Authoring with normal texts

RStudio provides two ways to edit a quarto file (1) **visual mode** and (2) **source mode**.

- RStudio's [visual editor](#) offers an [WYSIWYM](#) (Microsoft Word like) authoring experience for markdown
 - recommended and easier to learn; we will be using this mode in class
 - check the rich formatting tools we can use for authoring a report
- In the source mode, you can edit the file using markdown syntax
 - optional; for advanced users once you're familiar with the markdown syntax

Exercise

Create a new quarto file from RStudio with the following level-1 and level-2 headers

- Basics of R

³Why the name Quarto? “We wanted to use a name that had meaning in the history of publishing and landed on Quarto, which is the format of a book or pamphlet produced from full sheets printed with eight pages of text, four to a side, then folded twice to produce four leaves. The earliest known European printed book is a Quarto, the [Sibyllenbuch](#), believed to have been printed by [Johannes Gutenberg](#) in 1452–53.”




Figure 1: Visual Mode versus Source Mode

- Vectors
 - Creating vectors

2.3 Coding with code blocks

- In qmd files, we write actual R codes in **code chunks** identified with `{r}`.
- You can run each code chunk interactively by clicking the render icon. RStudio executes the code and displays the results below the code chunks.
- To insert a code chunk, click Insert ->Code Chunk -> R.
- See an example and try on your computer!

```
1 print('R is the Best Language! Better than Python! And dont tell David I said this!')
```

```
[1] "R is the Best Language! Better than Python! And dont tell David I said this!"
```


Exercise

Insert the above R code block in your quarto file under any section.

2.4 Rendering a report

At the end, when codes and main texts are ready, use the **Render** button in the RStudio IDE to render the file.

The rendered report will be in the same folder with your qmd file.



Exercise

Render your quarto file into a document and see how it looks like.

2.5 More learning resources for Quarto

- The available YAML fields vary based on document format
 - [Here](#) for YAML fields for PDF documents
 - [Here](#) for MS Word
 - [Here](#) for HTML documents
- Markdown syntax
 - [Markdown basics](#)
 - [Markdown practice](#)
- Quarto (recommended to be reviewed after-class)
 - [Get started](#)

3 Basics of R

3.1 Named objects

- R is an **object-oriented language**, so we will be working on named objects.

- We use the **left arrow** `<-` to create a named object, which assigns the **objects** on the RHS to the **name** on the LHS.⁴

– The below code creates a new object called ‘x’ in the **environment**, which is a number 2.

```
1 x <- 3
2 x
```

```
[1] 3
```

- After an object is created, we can refer to the object by its name, and operates on it.

```
1 # Question: why Wei chooses these two numbers?
2 x^2
```

```
[1] 9
```

```
1 x^3
```

```
[1] 27
```

Exercise

Insert a code block in your quarto file, which does the following:

- Create an object with name ‘x’ with value $2 + 2$

3.2 Rules for object names

For a variable to be valid, it should follow these rules

- It should contain **letters**, **numbers**, and only **dot** or **underscore** characters.
- It *cannot* start with a number (eg: 2iota).

```
1 # 2iota <- 2
```

- It *cannot* start with a dot followed by a number (eg: .2iota).

```
1 # .iota <- 2
```

- It should not start with an underscore (eg: __iota).

⁴You can also use equal sign `=`, but it’s recommended to stick with R’s tradition.


```
1 # _iota <- 2
```

- It should not be a [reserved keyword](#).

```
1 # mean <- 2
```

Tip

It's good practice to use memorable names to name an object

- For instance, use prefix “df_” or “data_” to name datasets.

3.3 Functions

- In R, a **function** takes object(s) as input, run specific actions on the object(s) defined by the function, and then return an outcome object.
 - The example below shows the function `mean`, which computes the average of several numbers.

```
1 a <- 1:3 # which generates a sequence 1,2,3
2 a
```

```
[1] 1 2 3
```

```
1 mean(a)
```

```
[1] 2
```

- We will heavily rely on functions to conduct data analyses. For how to use a new function, search the function in RStudio's **help** panel.
 - **Description:** what the function does in a nutshell
 - **Usage:** how to call the function
 - **Arguments:** how you would like to run the function
 - **Value:** what will be returned
 - **Examples:** examples of how to use the function

Exercise

1. Search and learn the usage of function “sum”
2. Insert a code block in your quarto file to compute the sum of vector 1:3

3.4 Collection of functions: Packages

The base R already has many useful built-in functions to perform basic tasks, but as data scientists, we need more.

To perform certain tasks (such as a machine learning model), we can definitely write our own code from scratch, but it takes lots of (unnecessary) effort. Fortunately, many packages have been written by others for us to directly use.

- Install the package using the built-in function `install.packages()`. R will download the package.

```
1 install.packages('praise')
```

Error in contrib.url(repos, "source"): trying to use CRAN without setting a mirror

- Load the packages using `library()`. Every time you restart the RStudio, packages need to be reloaded.

```
1 library(praise)
```

- Now that the package is loaded, you can use the functions in it. `praise()` is a function in the `praise` package.

```
1 praise()
```

```
[1] "You are funkadelic!"
```

Tips

Installation of a package is only needed for the first time. After installation, just need to reload the packages using `library()` every time your restart RStudio.

3.5 Comment codes


You can put a `#` before any code, to indicate that any codes after the `#` on the same line are your comments, and will not be run by R.

It's a good practice to often comment your codes, so that you can help the future you to remember what you were trying to achieve.

```
1 # print("Support Wei for an iPhone 14 Pro!")
2
3 # Below, x will be 1 rather than 1+1
4 x <- 1 # +1
```

3.6 Data structures

Below are the complete list of objects in R.



3.7 Data types

To make the best of the R language, you'll need a strong understanding of the basic data types and data structures and how to operate on them. Data structures are very important to understand because these are the objects you will manipulate on a day-to-day basis in R.

- Numeric (e.g., 2.5)
 - We can use R as a calculator for numeric objects

```
1 # Numeric Vector
2 num2 <- 2.5
3 log(num2)
```

```
[1] 0.9162907
```

```
1 num2^2
```

```
[1] 6.25
```

```
1 exp(num2)
```

```
[1] 12.18249
```

- Logical (TRUE, FALSE)
 - TRUE is equivalent to 1 in R; FALSE is equivalent to 0.

```
1 log1 <- TRUE
2 log2 <- FALSE
```

- Character (e.g. “Wei”, “UCL”, “1 + 1 = 3”, “TRUE”, etc.)
 - within a pair of quotation marks; single or double quotation marks can both work.

```
1 str1 <- "1 + 1 = 2"
```

- Factor (“male”, “female”, etc.)
 - this is an important class for describing categories. We will discuss in more detail later in class when we learn linear regression.

```
1 country <- c('UK', 'Spain', 'Italy', 'Multiverse')
2 factor(country)
```

```
[1] UK      Spain    Italy    Multiverse
Levels: Italy Multiverse Spain UK
```

3.8 Check data types using class()

We can use `class()` to check the type of an object in R.

```
1 a <- '1+1'
2 class(a)
```

```
[1] "character"
```

```
1 b <- 1+1
2 class(b)
```

```
[1] "numeric"
```

This is very useful when we first load data from external databases, we need to make sure variables are of the correct data types.

3.9 Data type: conversion

Sometimes, data types of variables from raw data may not be what we want; we need to change the data type of a variable to the appropriate one.

See the following example:

- `a` is a string, and we cannot use mathematical operations on it, or R will report errors.

```
1 a <- '1'
2 class(a)
```

```
[1] "character"
```

```
1 a + 1
```

Error in `a + 1`: non-numeric argument to binary operator

- We can convert `a` to a numeric value. To convert from character to numeric, we use `as.numeric()`

```
1 b <- as.numeric(a)
2 class(b)
```

```
[1] "numeric"
```

4 Vectors

4.1 Creating vectors

Creating vectors: `c()`

Vector can be created using the function `c()` by listing all the values in the parenthesis, separated by comma `,`.

```
1 x <- c(1, 3, 5, 10)
2 x
```

```
[1] 1 3 5 10
```

```
1 class(x)
```

```
[1] "numeric"
```

Vectors must contain elements of the same data type. Otherwise, it will implicitly convert elements into the same type.

```

1 x <- c(1, "intro", TRUE)
2
3 class(x)

```

```
[1] "character"
```

Checking the number of elements in a vector: `length()`

You can measure the length of a **vector** using the command `length()`

```

1 x <- c('R', ' is', ' fun')
2 length(x)

```

```
[1] 3
```

```

1 y <- c()
2 length(y)

```

```
[1] 0
```

Creating numeric sequences: `seq()` and `rep()`

It is also possible to easily create sequences with patterns

- use `seq()` to create sequence with fixed steps

```

1 # use seq()
2 seq(from = 1, to = 2, by = 0.1)

```

```
[1] 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.0
```

- If step is 1, there's a simpler way using :

```
1 1:5
```

```
[1] 1 2 3 4 5
```

- use `rep()` to create repeated sequences.

```

1 # replication using rep()
2 rep(c("A","B"), times = 5)

```

```
[1] "A" "B" "A" "B" "A" "B" "A" "B" "A" "B"
```

Combine vectors

You can use `c()` to combine different vectors; this is very commonly used to concatenate vectors.

```
1 x <- 1:3 # from 1 to 3
2 y <- c(10, 15) # 10 and 15
3 z <- c(x,y) # x first and then y
4 z
```

```
[1] 1 2 3 10 15
```

Exercise

Create a sequence of $\{1,1,2,2,3,3,3\}$ using different methods.

4.2 Indexing and subsetting

We put the **index** of elements we would like to extract in a **square bracket** `[]`.⁵

- Which element is in the second position?

```
1 x <- c(1,3,8,7)
2 x[2]
```

```
[1] 3
```

- What are the first 2 elements?

```
1 x[1:2]
```

```
[1] 1 3
```

- What are the 1st, 3rd and 4th elements?

```
1 x[c(1,3,4)]
```

```
[1] 1 8 7
```

4.3 Element-wise operations

R is a **vectorized** language, meaning by default it will do vector operation internally.

- If you operate on a vector with a single number, the operation will be applied to all elements in the vector

⁵Note that Python uses different ways to index and subset vectors and matrices.

```
1 x <- c(1,3,8,7)
2 x+2
```

```
[1] 3 5 10 9
```

```
1 x^2
```

```
[1] 1 9 64 49
```

Caveats

When the length of vectors do not match, R will still do it for you without reporting error but a warning message. As you can see, even if the length of vectors does not match, R can still return an output but throws a warning message. It's important to check the warning messages when there is any!

```
1 x <- c(1,3,8,7)
2
3 y <- c(1,3,4) # careful!!! does not report error
4 x + y
```

```
Warning in x + y: longer object length is not a multiple of shorter object
length
```

```
[1] 2 6 12 8
```

Exercise

Create a geometric sequence {2,4,8,16,32} using seq().

4.4 Relational operations

- We can compare a vector with a vector **of the same length**, which will do element-wise (element-by-element) comparison

```
1 x <- c(1,3,8,7)
2 y <- c(2,3,7,8)
3 x > y
```

```
[1] FALSE FALSE TRUE FALSE
```



```
1 x == y
```

```
[1] FALSE TRUE FALSE FALSE
```

- We can also compare a vector with a scalar, because R is vectorized

```
1 x <- c(1,3,8,7)
2 x < 6 # is each element lower than 6?
```

```
[1] TRUE TRUE FALSE FALSE
```

```
1 x == 10 # is the element equal to 10?
```

```
[1] FALSE FALSE FALSE FALSE
```

- Return the positions of elements that satisfy certain conditions: `which()`

```
1 which(x == 8) # which element equals 8
```

```
[1] 3
```

```
1 which.max(x) # which is the max element
```

```
[1] 3
```

```
1 which.min(x)
```

```
[1] 1
```

Exercise

Find the minimum value of vector `x` using `which()`

- Sometimes, we may need to operation on multiple relational operations using `and` or `no`

```
1 T & F # and
```

```
[1] FALSE
```

```
1 T | F # or
```

```
[1] TRUE
```

```
1 !T # not
```

```
[1] FALSE
```

- For instance, we may want to find out elements that are smaller than 8 **and** larger than 3.

```
1 which(x < 8 & x > 3 )
```

```
[1] 4
```

4.5 Special relational operation: %in%

- A special relational operation is %in% in R, which tests whether an element exists in the object.

```
1 x <- c(1,3,8,7)
```

```
2
```

```
3 3 %in% x
```

```
[1] TRUE
```

```
1 4 %in% x
```

```
[1] FALSE
```

5 After-class exercise

- Datacamp [Introduction to R](#), finish the following:
 - Intro to basics
 - Vectors