Forced Oscillations

Department of Mathematics

Salt Lake Community College

Let us look at the mass-spring system described by

$$\ddot{x} + x = 2\cos(3t)$$

Let us look at the mass-spring system described by

$$\ddot{x} + x = 2\cos(3t)$$

The characteristic equation is $r^2 + 1 = 0$ and thus

$$x_h = c_1 \cos(t) + c_2 \sin(t)$$

Let us look at the mass-spring system described by

$$\ddot{x} + x = 2\cos(3t)$$

The characteristic equation is $r^2 + 1 = 0$ and thus

$$x_h = c_1 \cos(t) + c_2 \sin(t)$$

Using the method of undetermined coefficients

$$x_p = A\cos(3t) + B\sin(3t)$$

Let us look at the mass-spring system described by

$$\ddot{x} + x = 2\cos(3t)$$

The characteristic equation is $r^2 + 1 = 0$ and thus

$$x_h = c_1 \cos(t) + c_2 \sin(t)$$

Using the method of undetermined coefficients

$$x_p = A\cos(3t) + B\sin(3t)$$

Which leads to

$$x_p = -\frac{1}{4}\cos(3t)$$

Let us look at the mass-spring system described by

$$\ddot{x} + x = 2\cos(3t)$$

The characteristic equation is $r^2 + 1 = 0$ and thus

$$x_h = c_1 \cos(t) + c_2 \sin(t)$$

Using the method of undetermined coefficients

$$x_p = A\cos(3t) + B\sin(3t)$$

Which leads to

$$x_p = -\frac{1}{4}\cos(3t)$$

and

$$x = c_1 \cos(t) + c_2 \sin(t) - \frac{1}{4} \cos(3t)$$

General Solution

We can now look at the general solution for the undamped system

$$m\ddot{x} + kx = F_0 \cos(\omega_f t)$$

Where ω_f is the forcing frequency and F_0 is the forcing amplitute.

General Solution

We can now look at the general solution for the undamped system

$$m\ddot{x} + kx = F_0 \cos(\omega_f t)$$

Where ω_f is the forcing frequency and F_0 is the forcing amplitute.

We know that

$$x_h = c_1 \cos(\omega_0 t) + c_2 \sin(\omega_0 t)$$
 where $\omega_0 = \sqrt{\frac{k}{m}}$

General Solution

We can now look at the general solution for the undamped system

$$m\ddot{x} + kx = F_0 \cos(\omega_f t)$$

Where ω_f is the forcing frequency and F_0 is the forcing amplitute.

We know that

$$x_h = c_1 \cos(\omega_0 t) + c_2 \sin(\omega_0 t)$$
 where $\omega_0 = \sqrt{\frac{k}{m}}$

This leaves two separate cases for x_p :

- **1** The frequencies ω_f and ω_0 are different.
- 2 The frequencies ω_f and ω_0 are the same.

This means we want to look for

$$x_p = A\cos(\omega_f t) + B\sin(\omega_f t)$$

This means we want to look for

$$x_p = A\cos(\omega_f t) + B\sin(\omega_f t)$$

and so, we find that

$$A = \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \quad \text{and} \quad B = 0$$

This means we want to look for

$$x_p = A\cos(\omega_f t) + B\sin(\omega_f t)$$

and so, we find that

$$A = \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \quad \text{and} \quad B = 0$$

So, where c_1 and c_2 are determined by initial conditions, we have

$$x(t) = c_1 \cos(\omega_0 t) + c_2 \sin(\omega_0 t) + \frac{F_0}{m(\omega_0^2 - \omega_f^2)} \cos(\omega_f t)$$

This means we want to look for

$$x_p = A\cos(\omega_f t) + B\sin(\omega_f t)$$

and so, we find that


$$A = \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \quad \text{and} \quad B = 0$$

So, where c_1 and c_2 are determined by initial conditions, we have


$$x(t) = c_1 \cos(\omega_0 t) + c_2 \sin(\omega_0 t) + \frac{F_0}{m(\omega_0^2 - \omega_f^2)} \cos(\omega_f t)$$
$$= C \cos(\omega_0 t - \delta) + \frac{F_0}{m(\omega_0^2 - \omega_f^2)} \cos(\omega_f t)$$

where
$$C = \sqrt{c_1^2 + c_2^2}$$
 and $\tan(\delta) = \frac{c_2}{c_1}$.

An example of $\omega_f \neq \omega_0$ being different, but close, is



An example of $\omega_f \neq \omega_0$ being different, but close, is



The regular periodic patterns are called beats.

Resonance $(\omega_f = \omega_0)$

This means we want to look at

$$x_p = At\cos(\omega_0 t) + Bt\sin(\omega_0 t)$$

Resonance ($\omega_f = \omega_0$)

This means we want to look at

$$x_p = At\cos(\omega_0 t) + Bt\sin(\omega_0 t)$$

and so, we find that

$$A = 0$$
 and $B = \frac{F_0}{2m\omega_0}$

Resonance $(\omega_f = \omega_0)$

This means we want to look at

$$x_p = At\cos(\omega_0 t) + Bt\sin(\omega_0 t)$$

and so, we find that

$$A=0$$
 and $B=rac{F_0}{2m\omega_0}$

So, where c_1 and c_2 are determined by initial conditions, we have

$$x(t) = c_1 \cos(\omega_0 t) + c_2 \sin(\omega_0 t) + \frac{F_0}{2m\omega_0} t \sin(\omega_0 t)$$

We can see an example of resonance

$$\ddot{x} + x = 2\cos(t), \quad x(0) = 0, \quad \dot{x}(0) = 0$$

We can see an example of resonance

$$\ddot{x} + x = 2\cos(t), \quad x(0) = 0, \quad \dot{x}(0) = 0$$

Since
$$\frac{F_0}{2m\omega_0} = \frac{2}{2\cdot 1\cdot 1} = 1$$
, we have $x_p = t\sin(t)$.

We can see an example of resonance

$$\ddot{x} + x = 2\cos(t), \quad x(0) = 0, \quad \dot{x}(0) = 0$$

Since
$$\frac{F_0}{2m\omega_0} = \frac{2}{2\cdot 1\cdot 1} = 1$$
, we have $x_p = t\sin(t)$.


So, given that x(0) = 0 and $\dot{x}(0) = 0$ we have $x = t \sin(t)$.

We can see an example of resonance

$$\ddot{x} + x = 2\cos(t), \quad x(0) = 0, \quad \dot{x}(0) = 0$$

Since
$$\frac{F_0}{2m\omega_0} = \frac{2}{2\cdot 1\cdot 1} = 1$$
, we have $x_p = t\sin(t)$.

So, given that x(0) = 0 and $\dot{x}(0) = 0$ we have $x = t \sin(t)$.



As we saw earlier when ω_f is close to ω_0 , though still not equal, there is clearly periodic behavior.

As we saw earlier when ω_f is close to ω_0 , though still not equal, there is clearly periodic behavior.

This periodic pattern has a frequency, called the **beat frequency**, that is lower than both ω_f and ω_0 .

As we saw earlier when ω_f is close to ω_0 , though still not equal, there is clearly periodic behavior.

This periodic pattern has a frequency, called the **beat frequency**, that is lower than both ω_f and ω_0 .

If the system is initially at rest $(x(0) = 0 \text{ and } \dot{x}(0) = 0)$ then the solution is

$$x(t) = -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_0 t\right) + \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_f t\right)$$

As we saw earlier when ω_f is close to ω_0 , though still not equal, there is clearly periodic behavior.

This periodic pattern has a frequency, called the **beat frequency**, that is lower than both ω_f and ω_0 .

If the system is initially at rest $(x(0) = 0 \text{ and } \dot{x}(0) = 0)$ then the solution is

$$x(t) = -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_0 t\right) + \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_f t\right)$$

So, we can simplify using the trigonometric identity

$$\cos(u) - \cos(v) = -2\sin\left(\frac{u-v}{2}\right)\sin\left(\frac{u+v}{2}\right)$$

$$x(t) = -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_0 t\right) + \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_f t\right)$$

$$x(t) = -\frac{F_0}{m(\omega_0^2 - \omega_f^2)} \cos(\omega_0 t) + \frac{F_0}{m(\omega_0^2 - \omega_f^2)} \cos(\omega_f t)$$
$$= -\frac{F_0}{m(\omega_0^2 - \omega_f^2)} (\cos(\omega_0 t) - \cos(\omega_f t))$$

$$\begin{split} x(t) &= -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_0 t\right) + \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_f t\right) \\ &= -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\left(\cos\left(\omega_0 t\right) - \cos\left(\omega_f t\right)\right) \\ &= \frac{2F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\sin\left(\frac{\omega_0 - \omega_f}{2} t\right)\sin\left(\frac{\omega_0 + \omega_f}{2} t\right) \end{split}$$

$$x(t) = -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_0 t\right) + \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\cos\left(\omega_f t\right)$$

$$= -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\left(\cos\left(\omega_0 t\right) - \cos\left(\omega_f t\right)\right)$$

$$= \frac{2F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\sin\left(\frac{\omega_0 - \omega_f}{2}t\right)\sin\left(\frac{\omega_0 + \omega_f}{2}t\right)$$

When the difference between ω_f and ω_0 is small, then $\omega_0 - \omega_f$ is much smaller than $\omega_0 + \omega_f$.

$$\begin{aligned} x(t) &= -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \cos\left(\omega_0 t\right) + \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \cos\left(\omega_f t\right) \\ &= -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \left(\cos\left(\omega_0 t\right) - \cos\left(\omega_f t\right)\right) \\ &= \frac{2F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \sin\left(\frac{\omega_0 - \omega_f}{2} t\right) \sin\left(\frac{\omega_0 + \omega_f}{2} t\right) \end{aligned}$$

When the difference between ω_f and ω_0 is small, then $\omega_0 - \omega_f$ is much smaller than $\omega_0 + \omega_f$.

Thus $\sin\left(\frac{\omega_0-\omega_f}{2}t\right)$ oscillates much slower than $\sin\left(\frac{\omega_0+\omega_f}{2}t\right)$.

$$\begin{split} x(t) &= -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \cos\left(\omega_0 t\right) + \frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \cos\left(\omega_f t\right) \\ &= -\frac{F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \left(\cos\left(\omega_0 t\right) - \cos\left(\omega_f t\right)\right) \\ &= \frac{2F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \sin\left(\frac{\omega_0 - \omega_f}{2} t\right) \sin\left(\frac{\omega_0 + \omega_f}{2} t\right) \end{split}$$

When the difference between ω_f and ω_0 is small, then $\omega_0 - \omega_f$ is much smaller than $\omega_0 + \omega_f$.

Thus
$$\sin\left(\frac{\omega_0-\omega_f}{2}t\right)$$
 oscillates much slower than $\sin\left(\frac{\omega_0+\omega_f}{2}t\right)$.

The two curves

$$\pm \frac{2F_0}{m\left(\omega_0^2 - \omega_f^2\right)} \sin\left(\frac{\omega_0 - \omega_f}{2}t\right)$$

form an envelope of the more rapid oscillation and is called the **sinusoidal** amplitude.

Solutions to the Undamped Forced Oscillator ($\omega_{\it f} \neq \omega_{\it 0}$)

For

$$m\ddot{x} + kx = F_0 \cos(\omega_f t)$$

Solutions to the Undamped Forced Oscillator ($\omega_f \neq \omega_0$)

For

$$m\ddot{x} + kx = F_0 \cos(\omega_f t)$$

The general solution is

$$x(t) = c_1 \cos(\omega_0 t) + c_2 \cos(\omega_0 t) + \frac{F_0}{m(\omega_0^2 - \omega_f^2)} \cos(\omega_f t)$$

where c_1 and c_2 are determined by initial conditions and $\omega_0=\sqrt{\frac{k}{m}}$.

Solutions to the Undamped Forced Oscillator ($\omega_f \neq \omega_0$)

For

$$m\ddot{x} + kx = F_0 \cos(\omega_f t)$$

The general solution is

$$x(t) = c_1 \cos(\omega_0 t) + c_2 \cos(\omega_0 t) + \frac{F_0}{m(\omega_0^2 - \omega_f^2)} \cos(\omega_f t)$$

where c_1 and c_2 are determined by initial conditions and $\omega_0 = \sqrt{\frac{k}{m}}$.

If the system starts from rest (x(0) = 0) and $\dot{x}(0) = 0$, the solution can be written as

$$x(t) = \underbrace{\frac{2F_0}{m\left(\omega_0^2 - \omega_f^2\right)}\sin\left(\frac{\omega_0 - \omega_f}{2}t\right)}_{\text{sinusoidal amplitude}} \underbrace{\sin\left(\frac{\omega_0 + \omega_f}{2}t\right)}_{\text{rapid oscillation within beats}}$$

Given an oscillator with $\omega_0=22\pi$, $\omega_f=20\pi$, m=1, and $F_0=42\pi^2$.

Given an oscillator with $\omega_0=22\pi$, $\omega_f=20\pi$, m=1, and $F_0=42\pi^2$.

Given an oscillator with $\omega_0=22\pi$, $\omega_f=20\pi$, m=1, and $F_0=42\pi^2$.

$$\omega_0 = \sqrt{\frac{k}{m}}$$

Given an oscillator with $\omega_0=22\pi$, $\omega_f=20\pi$, m=1, and $F_0=42\pi^2$.

$$\omega_0 = \sqrt{\frac{k}{m}} \quad \to \quad \omega_0^2 = \frac{k}{m}$$

Given an oscillator with $\omega_0=22\pi$, $\omega_f=20\pi$, m=1, and $F_0=42\pi^2$.

$$\omega_0 = \sqrt{\frac{k}{m}} \quad \rightarrow \quad \omega_0^2 = \frac{k}{m} \quad \rightarrow \quad k = m\omega_0^2$$

Given an oscillator with $\omega_0=22\pi$, $\omega_f=20\pi$, m=1, and $F_0=42\pi^2$.

$$\omega_0 = \sqrt{\frac{k}{m}} \rightarrow \omega_0^2 = \frac{k}{m} \rightarrow k = m\omega_0^2 = 484\pi^2$$

Given an oscillator with $\omega_0=22\pi$, $\omega_f=20\pi$, m=1, and $F_0=42\pi^2$.

We can then calculate k:

$$\omega_0 = \sqrt{\frac{k}{m}} \rightarrow \omega_0^2 = \frac{k}{m} \rightarrow k = m\omega_0^2 = 484\pi^2$$

Since

$$rac{\omega_0 - \omega_f}{2} = \pi$$
 and $rac{\omega_0 + \omega_f}{2} = 21\pi$

Given an oscillator with $\omega_0=22\pi$, $\omega_f=20\pi$, m=1, and $F_0=42\pi^2$.

We can then calculate k:

$$\omega_0 = \sqrt{\frac{k}{m}} \quad \rightarrow \quad \omega_0^2 = \frac{k}{m} \quad \rightarrow \quad k = m\omega_0^2 = 484\pi^2$$

Since

$$\frac{\omega_0 - \omega_f}{2} = \pi$$
 and $\frac{\omega_0 + \omega_f}{2} = 21\pi$

The solution is

$$x(t) = 1 \cdot \sin(\pi t) \sin(21\pi t)$$

Given an oscillator with $\omega_0=22\pi$, $\omega_f=20\pi$, m=1, and $F_0=42\pi^2$.

We can then calculate k:

$$\omega_0 = \sqrt{\frac{k}{m}} \quad \rightarrow \quad \omega_0^2 = \frac{k}{m} \quad \rightarrow \quad k = m\omega_0^2 = 484\pi^2$$

Since


$$\frac{\omega_0 - \omega_f}{2} = \pi$$
 and $\frac{\omega_0 + \omega_f}{2} = 21\pi$

The solution is

$$x(t) = 1 \cdot \sin(\pi t) \sin(21\pi t)$$

Thus, envelope curves are

$$y = \pm 1 \cdot \sin(\pi t)$$



Let us consider the damped forced oscillator

$$\ddot{x} + 4\dot{x} + 5x = 10\cos(3t), \qquad x(0) = \dot{x}(0) = 0$$

Let us consider the damped forced oscillator

$$\ddot{x} + 4\dot{x} + 5x = 10\cos(3t), \qquad x(0) = \dot{x}(0) = 0$$

First, we need to find the solution to the associated homogeneous equation.

Let us consider the damped forced oscillator

$$\ddot{x} + 4\dot{x} + 5x = 10\cos(3t), \qquad x(0) = \dot{x}(0) = 0$$

First, we need to find the solution to the associated homogeneous equation.

The characteristic equation $r^2 + 4r + 5 = 0$ has solutions $r = -2 \pm i$, so we have

$$x_h = e^{-2t} (c_1 \cos(t) + c_2 \sin(t))$$

Let us consider the damped forced oscillator

$$\ddot{x} + 4\dot{x} + 5x = 10\cos(3t), \qquad x(0) = \dot{x}(0) = 0$$

First, we need to find the solution to the associated homogeneous equation.

The characteristic equation $r^2 + 4r + 5 = 0$ has solutions $r = -2 \pm i$, so we have

$$x_h = e^{-2t} \left(c_1 \cos \left(t \right) + c_2 \sin \left(t \right) \right)$$

Next we need to find a particular solution.

Let us consider the damped forced oscillator

$$\ddot{x} + 4\dot{x} + 5x = 10\cos(3t), \qquad x(0) = \dot{x}(0) = 0$$

First, we need to find the solution to the associated homogeneous equation.

The characteristic equation $r^2 + 4r + 5 = 0$ has solutions $r = -2 \pm i$, so we have

$$x_h = e^{-2t} (c_1 \cos(t) + c_2 \sin(t))$$

Next we need to find a particular solution.

We can use the method of undetermined coefficients:

$$x(t) = A\cos(3t) + B\sin(3t)$$

 $\dot{x}(t) = -3A\sin(3t) + 3B\cos(3t)$
 $\ddot{x}(t) = -9A\cos(3t) - 9B\sin(3t)$

Substituting into the DE gives

$$(-9A\cos(3t) - 9B\sin(3t)) + 4(-3A\sin(3t) + 3B\cos(3t)) + 5(A\cos(3t) + B\sin(3t)) = 10\cos(3t)$$

Substituting into the DE gives

$$(-9A\cos(3t) - 9B\sin(3t)) + 4(-3A\sin(3t) + 3B\cos(3t)) + 5(A\cos(3t) + B\sin(3t)) = 10\cos(3t)$$

Which gives the system

$$-9A + 12B + 5A = 10$$

 $-9B - 12A + 5B = 0$

Substituting into the DE gives

$$(-9A\cos(3t) - 9B\sin(3t)) + 4(-3A\sin(3t) + 3B\cos(3t)) + 5(A\cos(3t) + B\sin(3t)) = 10\cos(3t)$$

Which gives the system

$$-9A + 12B + 5A = 10$$

 $-9B - 12A + 5B = 0$

Which has solution

$$A = -\frac{1}{4} \quad \text{and} \quad B = \frac{3}{4}$$

Substituting into the DE gives

$$(-9A\cos(3t) - 9B\sin(3t)) + 4(-3A\sin(3t) + 3B\cos(3t)) + 5(A\cos(3t) + B\sin(3t)) = 10\cos(3t)$$

Which gives the system

$$-9A + 12B + 5A = 10$$

 $-9B - 12A + 5B = 0$

Which has solution

$$A = -\frac{1}{4} \quad \text{and} \quad B = \frac{3}{4}$$

Thus,

$$x_p = -\frac{1}{4}\cos(3t) + \frac{3}{4}\sin(3t)$$

The general solution is

$$x = e^{-2t} \left(c_1 \cos(t) + c_2 \sin(t) \right) - \frac{1}{4} \cos(3t) + \frac{3}{4} \sin(3t)$$

The general solution is

$$x = e^{-2t} \left(c_1 \cos(t) + c_2 \sin(t) \right) - \frac{1}{4} \cos(3t) + \frac{3}{4} \sin(3t)$$

To solve the IVP, we need to calculate

$$\dot{x} = -2e^{-2t} \left(c_1 \cos(t) + c_2 \sin(t) \right) + e^{-2t} \left(-c_1 \sin(t) + c_2 \cos(t) \right) + \frac{1}{4} \sin(3t) - \frac{3}{4} \cos(3t)$$

The general solution is

$$x = e^{-2t} \left(c_1 \cos(t) + c_2 \sin(t) \right) - \frac{1}{4} \cos(3t) + \frac{3}{4} \sin(3t)$$

To solve the IVP, we need to calculate

$$\dot{x} = -2e^{-2t} \left(c_1 \cos(t) + c_2 \sin(t) \right)$$
 $+ e^{-2t} \left(-c_1 \sin(t) + c_2 \cos(t) \right)$
 $+ \frac{1}{4} \sin(3t) - \frac{3}{4} \cos(3t)$

Next, we need to plug in the initial conditions

$$x(0) = 0$$

$$\dot{x}(0) = 0$$

The general solution is

$$x = e^{-2t} \left(c_1 \cos(t) + c_2 \sin(t) \right) - \frac{1}{4} \cos(3t) + \frac{3}{4} \sin(3t)$$

To solve the IVP, we need to calculate

$$\dot{x} = -2e^{-2t} \left(c_1 \cos(t) + c_2 \sin(t) \right)$$
 $+ e^{-2t} \left(-c_1 \sin(t) + c_2 \cos(t) \right)$
 $+ \frac{1}{4} \sin(3t) - \frac{3}{4} \cos(3t)$

Next, we need to plug in the initial conditions

$$x(0) = 0$$
 \Rightarrow $c_1 - \frac{1}{4} = 0$
 $\dot{x}(0) = 0$ \Rightarrow $c_2 + \frac{7}{4} = 0$

The general solution is

$$x = e^{-2t} \left(c_1 \cos(t) + c_2 \sin(t) \right) - \frac{1}{4} \cos(3t) + \frac{3}{4} \sin(3t)$$

To solve the IVP, we need to calculate

$$\dot{x} = -2e^{-2t} \left(c_1 \cos(t) + c_2 \sin(t) \right)$$
 $+ e^{-2t} \left(-c_1 \sin(t) + c_2 \cos(t) \right)$
 $+ \frac{1}{4} \sin(3t) - \frac{3}{4} \cos(3t)$

Next, we need to plug in the initial conditions

$$x(0) = 0$$
 \Rightarrow $c_1 - \frac{1}{4} = 0$ \Rightarrow $c_1 = \frac{1}{4}$
 $\dot{x}(0) = 0$ \Rightarrow $c_2 + \frac{7}{4} = 0$ \Rightarrow $c_2 = -\frac{7}{4}$

The solution to the IVP is

$$x = e^{-2t} \left(\frac{1}{4} \cos(t) - \frac{7}{4} \sin(t) \right) - \frac{1}{4} \cos(3t) + \frac{3}{4} \sin(3t)$$

The solution to the IVP is

$$x = \underbrace{e^{-2t} \left(\frac{1}{4} \cos\left(t\right) - \frac{7}{4} \sin\left(t\right)\right)}_{\text{Transient}} \underbrace{-\frac{1}{4} \cos\left(3t\right) + \frac{3}{4} \sin\left(3t\right)}_{\text{Steady-State}}$$


We call x_h transient, because for b > 0 the solution tends towards zero.

The solution to the IVP is

$$x = \underbrace{e^{-2t} \left(\frac{1}{4} \cos(t) - \frac{7}{4} \sin(t) \right)}_{\text{Transient}} \underbrace{-\frac{1}{4} \cos(3t) + \frac{3}{4} \sin(3t)}_{\text{Steady-State}}$$

We call x_h transient, because for b > 0 the solution tends towards zero.

The particular solution x_p may either be constant or a periodic **steady-state** solution.



Particular Solution x_p of a Damped Mass-Spring System

The damped mass-spring system

$$m\ddot{x} + b\dot{x} + kx = F_0 \cos(\omega_f t)$$

has particular solution

$$x_p = A\cos(\omega_f t) + B\sin(\omega_f t)$$

with

$$A = \frac{m(\omega_0^2 - \omega_f^2) F_0}{m^2(\omega_0^2 - \omega_f^2)^2 + (b\omega_f)^2} \quad \text{and} \quad B = \frac{b\omega_f F_0}{m^2(\omega_0^2 - \omega_f^2)^2 + (b\omega_f)^2}$$

with natural circular frequency $\omega_0 = \sqrt{\frac{k}{m}}.$

Particular Solution x_p of a Damped Mass-Spring System

The damped mass-spring system

$$m\ddot{x} + b\dot{x} + kx = F_0 \cos(\omega_f t)$$

has particular solution

$$x_p = A\cos(\omega_f t) + B\sin(\omega_f t)$$

with

$$A = \frac{m(\omega_0^2 - \omega_f^2) F_0}{m^2(\omega_0^2 - \omega_f^2)^2 + (b\omega_f)^2} \quad \text{and} \quad B = \frac{b\omega_f F_0}{m^2(\omega_0^2 - \omega_f^2)^2 + (b\omega_f)^2}$$

with natural circular frequency $\omega_0 = \sqrt{\frac{k}{m}}$.

Note

You will verify this in the homework.