

Implementing Design Patterns Using Java

St. Louis Java Special Interest Group

Eric M. Burke

Object Computing, Inc.

Presented on July 9, 1998

(updated July 14, 1998)

Implementing Design Patterns Using Java

What are Design Patterns?

- A **Design Pattern** systematically names, explains, and evaluates an important and recurring design in object-oriented systems.
 - **Patterns** are also used outside of the software profession
- Software Design Patterns...
 - are typically targeted toward object-oriented development
 - describe time-proven ways in which good OO concepts can be used to solve common problems
 - encapsulation, inheritance, polymorphism
 - satisfy specific application needs
 - patterns are not domain specific

Four essential elements

- Pattern Name
 - a word or two to describe the pattern
 - allows designers to communicate using a common vocabulary
- Problem
 - describes where to apply the pattern
- Solution
 - describes the elements that make up a design
 - does not describe a particular, concrete solution
- Consequences
 - results and trade-offs of applying the pattern

3 Basic Types of Patterns

- **Creational**
 - a family of patterns which abstract the creation of new objects
- **Structural**
 - describe how to compose groups of cooperating objects into larger systems
- **Behavioral**
 - characterize patterns of communication between a system of objects


How are Patterns Used?

- Salvaging legacy systems
 - the **Facade** pattern can be used to simplify the interface to a complex legacy system
 - the **Adapter** pattern allows designers to adapt the interface of an existing class or application to work with newer code
- Distributed applications
 - the **Observable** pattern is described in detail later in this presentation
- Object-Oriented class libraries
 - **Iterator** provides a way to access the elements of a collection without violating encapsulation

The Spaghetti Problem


- As the number of objects increases, the number of potential communication paths increases **geometrically**
- If structural and behavioral patterns are not used, code quickly becomes too complex to understand

3 objects




3 paths

4 objects




6 paths

5 objects



10 paths


10 objects



45 paths

How Not to Do It

- Arrows indicate "update" messages




The Observable Pattern

- A notification mechanism which allows one object to notify many **observers** when a state change has occurred
- Known by many names
 - Doc-View, Model-View-Controller, Subject-Observer, Publish-Subscribe
 - the example implementation uses Model and View classes
 - the **Model** contains data (Subject)
 - one or more **Views** (Observers) display the data contained in the **Model**

Typical Uses

- Distributed computing
 - a server may notify many client machines when data changes
 - CORBA, RMI, Sockets, or other forms of communication may be utilized - **patterns are independent of implementation**
- Graphical User Interfaces
 - a spreadsheet notifies several different graphical charts whenever a cell is edited
 - Emacs and other text editors provide paned windows which display different views of the same document
 - CAD programs allow multiple 3D views of the same data

The "Observable" Approach




- Views are not dependent upon one another
 - new views can be coded without impacting existing code
- Views are always displaying the correct data
- Ownership of the "Color" object is clearly defined in the **ColorModel** class

Implementing the Pattern

- Extend the Model class or implement the ModelI interface
 - business data is stored in your subclass
 - no GUI code is written here
 - no explicit connections to view subclasses
- Implement the ViewI interface
 - GUI panels, Frames, and Dialogs will do this
 - may hold a reference to one or more Model subclasses
 - provide a visual representation of business data
 - may be read-only or editable
 - must update display when notified by the Model

UML Object Model



Modell.java

```
/**
 * Define a protocol for notifying dependent views whenever a data model
 * changes. This is an implementation of the Observable pattern.
 * @author Eric M. Burke, Object Computing, Inc.
 * @version $Name$ $Revision$
 */
public interface ModelI {
    /**
     * @param v the view to register.
     */
    void addView(ViewI v);

    /**
     * @param v the view to un-register.
     */
    void removeView(ViewI v);

    /**
     * Notify all registered views that this model has changed.
     * @param obj optional data to pass to each view. May be null.
     */
    void notifyChanged(Object obj);
}
```

ViewI.java

```
package com.ocweb.patterns.observer;

/**
 * A notification mechanism when a data model changes.
 * @author Eric M. Burke, Object Computing, Inc.
 * @version $Name$ $Revision$
 */
public interface ViewI {
    /**
     * The data model has changed. Views implementing this interface
     * should update their displays.
     * @param model the data model which has changed.
     * @param obj optional data from the model, may be null.
     */
    void modelChanged(ModelI model, Object obj);
}
```

ColorModel.java

```
/**
 * A concrete type of Model.  Represents an AWT Color.
 */
public class ColorModel extends Model {
    private Color color;

    /**
     * @return a reference to a Color object.
     */
    public Color getColor() {
        return color;
    }

    /**
     * Set a new color and notify dependent views.
     * @param color the new Color.
     */
    public void setColor(Color color) {
        this.color = color;
        notifyChanged(null);
    }
}
```

ColorPreviewDialog.java

```
// some details omitted to fit on slide
public class ColorPreviewDialog extends Dialog implements ViewI {
    ColorModel colorModel;

    public ColorPreviewDialog(Frame parent, ColorModel model) {
        super(parent, "Color Preview", false);
        this.colorModel = model;
        model.addView(this);
        setBackground(model.getColor());

        setSize(150,150);
    }

    // implement the ViewI interface
    public void modelChanged(ModelI model, Object obj) {
        setBackground(colorModel.getColor());
    }
}
```


JDK Observable

- The JDK includes a class called `java.util.Observable`
 - important methods include:
 - `addObserver(Observer o)`
 - `deleteObserver(Observer o)`
 - `notifyObservers(Object arg)`
 - `setChanged()`, `clearChanged()`
- Why use `Model.java` and `ModelI.java` instead of just using `java.util.Observable`?
 - `Observable` requires the extra step of setting the "changed" flag
 - `Observable` is a class, which **requires** inheritance
 - `ModelI` is an interface, which offers more flexibility

Advantages of the Observable Pattern

- Business data can be coded independently of specific GUI views
 - developers can work independently
 - text-only unit tests can be written to test data model before GUI is finished
- GUI views have no knowledge of each other
 - allows developers to work independently
 - allows new views to be added later without breaking existing views
 - reduces web of interconnected views

JDK Patterns

- Java is full of patterns - look at the source code
 - Factory Method `java.util.Calendar`
 - Composite `java.awt.Container`
 - Iterator `java.util.Enumeration`
 - Observer `java.util.Observer`
 - Strategy `java.awt.LayoutManager`
- The entire JavaBeans and AWT 1.1 event model is based upon a variation of the Observer pattern

Learning More

- Read the book "Design Patterns: Elements of Reusable Object-Oriented Software"
Addison-Wesley, 1994 - Gamma, Helm, Johnson, Vlissides
- Study the JDK source code
- Practice
 - learning to recognize recurrent patterns and apply them to concrete designs takes experience

Time for Demo and Questions...

- Source code for demonstration application can be found at <http://www.ociweb.com/javasig/>
 - look for the Knowledge Base, under July, 1998