

EDS-Unigraphics MIS DataBroker Architecture

Jeff Greiner
Bob Wooldridge

October 9, 1996



UG/MIS DataBroker Architecture

Topics

- | UG/MIS Problem Domain
- | Requirements for New Architecture
- | Selection of Java
- | Developing Java Based Intranet Solutions
- | Current Status

UG/MIS DataBroker Architecture

UG/MIS Problem Domain

- | EDS-Unigraphics provides *Enterprise Engineering* solutions to help its customers achieve a competitive advantage. These solutions are directed at the areas of Product Modeling (Unigraphics CAD/CAM/CAE), Product Data Management (Information Manager), and Process Modeling and Reengineering (consultative services). Please visit our external Web Page at : <http://www.ug.eds.com> for additional information.
- | EDS-Unigraphics employs ~1600 people world-wide. Revenue for 1996 was approximately \$320M.

UG/MIS DataBroker Architecture

UG/MIS Problem Domain

- | UG/MIS provides internal support for the business processes of the EDS-Unigraphics Division.

This support includes systems for :

Billing and Revenue Reporting

Hardware Product Delivery

License Transfer

Resource Management

Sales Order Management

Maintenance Release Order

Export Compliance

Software Product Delivery

Maintenance Billing

Sales Inquiry

Installed Base Reporting

Product/Customer/Employee DB

- | Enterprise Data stored in CA-Ingres RDBMS.
- | Legacy Systems primarily 4GL based, character based UI, run on RDBMS node through VT emulation.

UG/MIS DataBroker Architecture

Requirements for New Architecture

- | Graphical User Interface
- | Single Logon, User-Specific Application Palette
- | Improved Application Library Release Management
- | Distributed Network Solution
- | Standards Based
- | Consistent, extendible, secure API for RDBMS access
- | Support for Heterogeneous Client Environment
- | Coexistence with Legacy Systems during transition
- | Improved Performance
- | Easy to use Development Toolkits

UG/MIS DataBroker Architecture

Selection of Java

I Use of Java directly supports :

Graphical User Interface

Single Logon, User-Specific Application Palette

Improved Application Library Release Management

Distributed Network Solution

Standards Based

Consistent, extendible, secure API for RDBMS access

Support for Heterogeneous Client Environment

Coexistence with Legacy Systems during transition

Improved Performance

Easy to use Development Toolkits

UG/MIS DataBroker Architecture

Selection of Java

I Other Benefits from Java :

Automatic Documentation Generation (javadoc)

Object-Oriented Model

APIs (java.*) are “part of the Standard”

Good Market Momentum / Industry Acceptance

Language / API features :

Exceptions

Threads

Sockets

Event Model

Object Serialization

Interfaces

UG/MIS DataBroker Architecture

Developing Java Based Intranet Solutions

I Three Tier Architecture

Client (*Applications*)

- Runs on user desktop (PC / Unix workstation)
- Presents GUI layout of data, responds to user actions
- Business Rules related to usage of data


Middle Tier (*DataBroker*)

- Runs on (one of) UNIX/NT Intranet Servers
- Receives data requests from Client, obtains data from Database Server, applies data-related Business Rules, format and returns response to Client

Database Server (*Enterprise Database*)

- Runs on (one of) UNIX/NT Database Servers
- Serves information from RDBMS based on SQL requests

UG/MIS DataBroker Architecture



UG/MIS DataBroker Architecture

DataBroker Architecture Components

I Enterprise Database

A Relational Database that is the central repository for the vast majority of company data. The Enterprise Database serves as the primary integration point between existing legacy systems and the new, intranet-based applications that have been deployed using the DataBroker Architecture.

UG/MIS DataBroker Architecture

DataBroker Architecture Components

I Legacy Application

Existing application that provides a point solution for part of the enterprise. It is important for these applications to become integrated to the point that they share a common Enterprise Database wherever possible. These applications must continue to operate until they are replaced by applications using the new architecture. Some legacy applications may never be replaced.

UG/MIS DataBroker Architecture

DataBroker Architecture Components

I Client Applications

Applications written for the new, intranet-based architecture. They typically are written using HTML, CGI (shell scripts), and Java. They are run from within a web browser, such as Netscape. A common feature of all of these client applications is that they are capable of communicating with the DataBroker to obtain data from the Enterprise Database (and possibly other sources). This communication is based on a well-defined API.

UG/MIS DataBroker Architecture

DataBroker Architecture Components

I DataBroker

A Java server application that receives API requests from client applications, processes those requests, and returns the resulting objects. Processing the request usually will involve accessing data in the Enterprise Database, via the Java JDBC interface. Other data sources may also be accessed, if required.

Using a three-tiered architecture means that changes to the database schema, security policy, or data source location are centralized in the DataBroker. Individual client applications are unaware of these details and therefore protected from changes to them.

Any number of DataBroker servers may be deployed, in a variety of configurations, based on network performance, network topology, and number of users.

UG/MIS DataBroker Architecture

DataBroker Architecture Components

I 3rd Party Data Source

In some cases, data that must be accessed by the DataBroker to process a client API request may not be owned by the enterprise. In these cases, an interface may be developed to the third party data source to enable acquisition of the data.