

OMTF performance study using L1 Ntuple

July 2018

Andrew Brinkerhoff, Karol Bunkowski, Georgios Karathanasis,
Marcin Konecki, Thomas Reis and **Wei Shi**



Motivations

- Compare efficiency and rate performance for several OMTF algorithm options [\[1\]](#)
 - Default
 - Prefer DT
 - FW_V5
 - Mitigate degraded performance when RPC not available
 - Allow the coincidence of two DT segments or one DT + one CSC to produce a muon
 - Allow the “uncorrelated” DT segments (quality 2 and 3, i.e. based on only one superlayer) to be used by the algorithm
- With RPC and without RPC



Tools

- L1T muon [tool](#) from Thomas Reis
- L1 [Ntuples](#) for various OMTF algo options
- Samples
 - /SingleMuon/Run2018A-ZMu-PromptReco-v1/RAW-RECO
 - /ZeroBias/Run2018A-v1/RAW
- Json
 - /afs/cern.ch/cms/CAF/CMSCOMM/COMM_DQM/certification/Collisions18/13TeV/DCSOnly/json_DCSONLY.txt


Default vs Prefer DT (both with RPC)





Prefer DT vs Prefer DT + FW_v5 (both with RPC)





Default vs Prefer DT+FW_5 (both with RPC)






RICE






Default w/o RPC



Prefer DT: w/o RPC



Prefer DT+FW_v5: w/o RPC



Back Up

Geometry

