

CS230 Game Implementation Techniques

Lecture 11



Outline

- Binary Collision Map
 - Introduction
 - Initialization
- Sprite Collision using Hot Spots
- Snapping
- Normalized Coordinates System



What is Binary Collision Map?




What Type of Games do we use it for?





Example





Outline

- Binary Collision Map
 - Introduction
 - Initialization
- Sprite Collision using Hot Spots
- Snapping
- Normalized Coordinates System



Binary Collision Map: Initialization (1/2)

- The map should be a grid (which is formed from cells)
- The collision map is a 2D array of "bools"
- Game objects are able to access a cell depending on that cell's value in the array



Binary Collision Map: Initialization (2/2)

• Example:

Map Data	Collision Data
11111	11111
10001	10001
13201	10001
11131	11101
11111	11111



Outline

- Binary Collision Map
 - Introduction
 - Initialization
- Sprite Collision using Hot Spots
- Snapping
- Normalized Coordinates System




Checking for Point Collision (1/2)


• Knowing that the cell's dimension is (1; 1), to check if a point is in a "solid" cell we get its position in the array (using array indices) and check its value.



Checking for Point Collision (2/2)

- Example:
 - A point is located at (3.3, 2.7)








Hot Spots (1/3)

- Our object is not just one point but is encapsulated with a bounding rectangle
- We are dealing with more than one point
- These points are called "Hot Spots"
- Note that this method assumes that both width and height of an object are both 1 (same size of a cell)




Hot Spots (2/3)

• Example:





Hot Spots (3/3)





Sprite Collision using Hot Spots (1/4)

- The collision can occur on the four sides of the sprite (top, bottom, left and right) and on more than one side.
- Each game object instance will have a collision flag, where each bit represents one side.



Sprite Collision using Hot Spots (2/4)

- The least significant bit represents the left side.
- The second bit represents the right side.
- The third bit represents the top side.
- The fourth bit represents the bottom side.



Sprite Collision using Hot Spots (3/4)

- When a certain side is found in a collision state, we set its corresponding bit in the collision flag variable to 1
- How do we set the corresponding bit to 1?



Answer

• This is done by OR-ing the flag with the correspondent collision side value.

Collision side values

```
#define
             COLLISION LEFT
                                                      //0001
                                     0X0000001
             COLLISION_RIGHT
#define
                                                      //0010
                                     0x00000002
#define
             COLLISION TOP
                                                      //0100
                                     0x0000004
#define
             COLLISION BOTTOM
                                                      //1000
                                     8000000008
```



Sprite Collision using Hot Spots (4/4)

After storing the collision information, how can I check on which side I collided with?

Answer:

 This is done by checking the collision flag AND-ed with the correspondent collision side value.



Outline

- Binary Collision Map
 - Introduction
 - Initialization
- Sprite Collision using Hot Spots
- Snapping
- Normalized Coordinates System



Snapping (1/2)

 If at least one hot spot is inside a collision area, we should snap the sprite back to the center of the cell that it belongs to.



Snapping (2/2)

1	1	1	1	1
1	0	0	0	1
1	О	О		1
1	1	1	O Sprite	1
1	1	1	1	1



Outline

- Binary Collision Map
 - Introduction
 - Initialization
- Sprite Collision using Hot Spots
- Snapping
- Normalized Coordinates System



Normalized Coordinates System (1/3)

• Why?

- We might want to scale the entire map to the window size, regardless of the grid's width and height.
- A cell's width might be greater than its height,
 where the art assets might require that.
- The cell's width and height directly affect the collision check



Normalized Coordinates System (2/3)

How?

- Have the width and height of each cell in the normalized coordinates system to be 1, independently from the final result
- All the physics (velocity, acceleration, etc...),
 movement and collision checks are done in the
 normalized coordinate system



Normalized Coordinates System (3/3)


- Moving our binary map from normalized coordinates system to the world coordinates system requires a transformation matrix made from:
 - Translation
 - Scale


- Grid Width


-Grid Height



Translation














Scale (1/2)










Scale (2/2)

• Scaling could be bigger than the viewport (i.e. scrolling games)



0	C		0	1
0	C		0	1
0	С	0,0	0	1
1	1		1	1



$\lceil Scale X \rceil$	0	0
0	Scale Y	0
0	0	1