

CS380
Artificial Intelligence for Games


**Navigation Graphs And Meshes.
Flood-Fill Search**

Outline

- Navigation graphs
 - Tile-based graph
 - Point of Visibility graph
- Navigation meshes
- Uninformed search
 - Flood-fill algorithm


Navigation graphs. Finding a Path

- Often seems obvious and natural in real life
 - e.g., Get from point A to B go around lake
- For computer controlled player or non-player character (NPC), may be difficult
 - e.g., Going from A to B goes through enemy base!
- Want to pick “best” path
- Need to do it in real-time



Navigation graphs. Path

- **Path** – a list of cells, points or nodes that NPC must traverse to get to from start to goal
 - Some paths are better than others
 - So need a **measure of quality**
- A* is commonly used heuristic search
 - *Complete* algorithm in that if there is a path, will find
 - Using “distance” as heuristic measure, then guaranteed optimal




Navigation graphs. Practical Path Planning

- Sometimes, **basic A*** is not enough
- Also often need:
 - Navigation graphs/meshes
 - Path smoothing (optional)
 - Compute-time optimizations (optional)
 - Hierarchical pathfinding (optional)
 - Special case methods (optional)


Navigation Graphs. Tile-Based

- Common, especially if environment already designed in squares or hexagons
- Node center of cell; edges to adjacent cells
- Each cell already labeled with material (mud, river, etc.)
- Downside:
 - Can burden CPU and memory
 - e.g., Modest 100x100 cell map has 10,000 nodes and 78,000 edges!
 - Especially if multiple AI's calling at same time



Navigation Graphs. Point of Visibility (POV)


- Place graph nodes (usually by hand) at **important points** in environment
- Such that each node has line of sight to at least one other node



Navigation Graphs. POV Navigation


- Find closest **visible** node (a) to current location
- Find closest **visible** node (b) to target location
- Search for least cost path from (a) to (b), e.g. A*
- Move to (a)
- Follow path to (b)
- Move to target location

Note, move to (a) is not the best option



Navigation Graphs. Blind Spots in POV

- No POV point is visible from red spots!
- Easy to fix manually in small graphs
 - Move to **visible** edge at **shortest** distance!
- A problem in larger graphs



Navigation Graphs. POV

- **Advantage**

- Obvious how to build and expand manually

- **Disadvantages**

- Can take a lot of developer time, especially if design is rapidly evolving
- Problematic for random or user generated maps
- Can have “blind spots”
- Can have “jerky” (backtracking) paths

- **Solutions**

- Automatically generate POV graphs
- Make finer grained graphs
- Path smoothing




Navigation Graphs. Automatic POV by Expanded Geometry

A. Expand geometry


- By amount proportional to bounding radius of NPC
- Note: works best if bounding radius similar for all NPCs

B. Connect all vertices

C. Prune non-line of sight points to avoid objects hitting edges when pathing




Navigation Graphs. Finely Grained Graphs



- Upside?
 - Improves blind spots and path smoothness
 - Can often generate automatically using Flood-fill algorithm
- Downside?
 - Back to similar performance issues as tiled graphs


Navigation Graphs. Kinky Path Smoothing

- Problem: Path does not look “natural”
- Solution: “smoothing”




Navigation Graphs. Smoothing

- Check for “passability” between adjacent edges
- Also known as “ray-cast” since if can cast a ray between A and C then waypoint B is not needed








Navigation Graphs. Simple Smoothing Algorithm

1. Grab source edge E1
2. Grab destination E2
3. If NPC can move between,
 - a. Assign destination E1 to destination E2
 - b. Remove E2
 - c. Advance E2
4. If NPC cannot move,
 - a. Assign E2 to E1
 - b. Advance E2
5. Repeat until destination E1 or destination E2 is endpoint



Navigation Graphs. Smoothing Example




Outline

- Navigation graphs
 - Tile-based graph
 - Point of Visibility graph
- Navigation meshes
- Uninformed search
 - Flood-fill algorithm

Navigation Mesh

- Partition open space into a network of convex polygons
 - Convex shape guaranteed path from any point to any point inside
- Instead of network of points, have network of polygons
- Can be automatically generated from arbitrary polygons
- Becoming very popular (e.g., UE4)



Navigation Mesh

- Has more information (i.e., can walk anywhere in polygon)
- POV needs lots of points. Navmesh needs fewer polygons to cover same area
- No need smoothing, but smoothing works too
- Navmesh is also a graph where nodes are polygons



Navigation Mesh. Generating

- Can be generated by hand
 - e.g., lay out polygons (e.g., squares) to cover terrain for map
 - Takes a few hours for typical FPS map
- Can be generated automatically
 - Various algorithm choices



Outline

- Navigation graphs
 - Tile-based graph
 - Point of Visibility graph
- Navigation meshes
- Uninformed search
 - Flood-fill algorithm

Search. Definition

- **Search** - the process of looking for a sequence of actions/nodes that reaches the **goal/target**
- **Input:**
 - Navigation graph or mesh, state graph,
 - Starting point S and target T
- **Result:**
 - If found, the sequence from S to T (or from T to S)
 - Else “not found” flag
- Sometimes, result can be a flag of existence of such sequence
 - Use Flood-fill algorithm

Uninformed search. Definition

- AKA Blind search, bcs **blindly try all possible ways** to reach the goal (see Brute-Force Search next)
- Uninformed search is a search that has no information about its domain
 - The only things that such search can do are
 - iterate through all states (takes time)
 - distinguish a non-goal state from a goal state
- Form the basis for some of the intelligent searches
- The order in which a blind search expand the nodes:
 - Breadth-First Search (BFS)
 - Depth-First Search (DFS)



Brute-force search

- AKA **exhaustive** search or **generate and test** search
- Is a very general problem-solving technique and algorithmic paradigm that consists of systematically enumerating all possible candidates for the solution and checking whether each candidate satisfies the problem's statement. ([Wikipedia](#))

Uninformed search. Flood-Fill Algorithm

- Given a tile-based graph
- Input:
 - start node S,
 - replacement color R,
 - border/obstacle color B/O
 - Optional: target color T
 - If given, the search stopped once R replaces T
- The algorithm recursively looks for all nodes in the graph that are connected to S, that are not B/O or T and changes them to R

Uninformed search. Flood-Fill Example




Uninformed search. Flood-Fill Code

```
Flood_Fill_Recursive(S, R)
{
    var adjacents = getAdjacents(S);
    for (var adjacent of adjacents)
    {
        adjacent.setColor(R);
        Flood_Fill_Recursive(adjacent, R);
    }
}
```

Construct Navigation Graph using Flood-Fill Algorithm

- Place “seed” in graph
- Expand outward in all “walkable” directions
- Making sure nodes and edges passable by bounding radius
- Continue until all area covered
- Same algorithm used by “paint” programs to flood fill color



Next Week

- More uninformed searches
- Dijkstra's algorithm

Readings

- Artificial Intelligence: A Modern Approach
 - Chapter 3: Solving Problems by Searching
 - Section 3.41 to Section 3.45