

Assignment #4
CS 180 FALL 2020

Due Date:	As specified on the moodle
Topics covered:	Contiguous Memory Allocation
Deliverables:	<p>Your submission should consist of two files: the header (interface) file, and the source (implementation) file. The header file must be named MemoryManager.h (with capital letters as indicated); this file should declare the class MemoryManager whose public interface is identical with that given at beginning of this handout. The source file must be named MemoryManager.cpp (again, with capital letters as indicated). These files must be placed in a directory and further zipped according to the specifications detailed in the syllabus.</p> <p>For this assignment, you may only use the standard C++ header files <code>iostream</code>, <code>list</code>, <code>iomanip</code>, <code>cstdlib</code>, and <code>cstdio</code>; in particular, the <code>windows.h</code> header file may not be included. Your submission should compile without errors or warnings using</p> <pre style="text-align: center;">cl /W4 /EHsc /c MemoryManager.cpp</pre> <p>on the command line.</p>
Objectives:	To demonstrate an understanding of how a simple memory manager allocates memory using the contiguous allocation scheme.

1 Programming Statement

In this assignment you will write a simple memory manager for dynamically allocated memory. The memory manager will make use of a linked list to keep track of allocated and unallocated blocks of memory; the algorithm for this was discussed in class (see the class lecture notes).

2 Public interface

The *public* interface for the memory manager must be as follows (it assumes that the file `iostream` has been included):

```
class MemoryManager {
public:
    MemoryManager(int total_bytes);
    ~MemoryManager(void);
    void *allocate(int bytes);
    void deallocate(void *pointer);
    void dump(std::ostream& out);
};
```

The public member functions listed above are defined in detail below. You are free to specify the *private* portion of the class as you see fit. Also, you may implement the **MemoryManager**

using either the STL `list` class, or you may wish to create the linked list yourself from scratch; note however, that you will need a doubly linked list.

2.1 Member functions

MemoryManager — create a memory manager instance of a specified heap size (in bytes).

Your memory manager should use `new` (or `malloc`) only once to create the entire heap of memory that it will use for memory allocation (note: if you decide to make your own linked list, you may also use `new` (or `malloc`) to create new nodes for the list). The construction parameter `total_bytes` gives the total size of the heap in bytes. For example, the code fragment

```
MemoryManager mm(1<<20);
```

creates an instance of the memory manager, named `mm`, with a heap size of 1 Mb. Each subsequent call to the `allocate` member function will return a pointer to a chunk of memory within this 1 Mb block.

~MemoryManger — destroys a memory manager instance. As a bare minimum, the destructor will deallocate the heap created by the memory manager constructor. This should be done with a single `delete` (or `free` if you used `malloc` to allocate the heap). Again, if you are making your own linked list, you may invoke `delete` (or `free`) for the nodes in the list that you remove).

allocate — get a block of memory of a specified size (in bytes) from the heap. On success, the function returns a pointer to a memory block of the requested size; on failure, a zero (null) pointer is returned. Note that the pointer should be recast to a pointer of the desired type. For example, the code fragment

```
int *array = (int*)mm.allocate(100*sizeof(int));
```

will allocate space on the heap for an array of 100 integers.

deallocate — frees a block of memory (that was allocated using `allocate`) from the heap. The value of `pointer` should be a non-zero pointer that was returned by the `allocate` member function. The code fragment

```
mm.deallocate(array);
```

frees the space on the heap used by the array of integers allocated above. If `pointer` has a value of zero, refers to an address that was not returned by `allocate`, or refers to the address of a block that was previously deallocated, then the effect of `deallocate` is undefined; no error checking is performed.

dump — prints information about the current structure of the heap to the specified output stream. This function is intended for debugging purposes; it prints a list of the current blocks on the heap: the starting address of the block, the block size (in bytes), and whether the block is currently in use (allocated) or not (deallocated/free). The code fragment

```
mm.dump(std::cout);
```

prints information about block structure of the heap to the standard output. An example of the output from this function might be something like this

```
start address: 804c008
  byte count: 78
  allocated? false
start address: 804c080
  byte count: 28
  allocated? true
start address: 804c0a8
  byte count: f60
  allocated? false
```

which indicates that the heap is currently divided into three blocks of size 78h, 28h, and F60h bytes, respectively; only the middle block is allocated, the other two are free. Your code should emulate this output as much as possible; in particular, *all numerical values should be in hexadecimal*.

2.2 Details on allocate and deallocate

The **allocate** member function should search for a block of memory on the heap of the requested size. Other than this, you are free to implement the function as you see fit: you may choose the first available block, or you may wish to choose the *best fit* block (smallest block that is at least large as the requested size), or the *worst fit* block (the largest block).

Not only should the **deallocate** function mark the specified block as free (deallocated), but should also consolidate adjacent free blocks into a single free block. For example, if the heap currently has the structure indicated above in the description of the **dump** function, then the call

```
mm.deallocate(0x804c080);
```

would result in the heap having the structure

```
start address: 804c008
  byte count: 1000
  allocated? false
```

i.e., all three of the blocks on the heap are consolidated into a single free block.