

MULTI-AXIS LASER INTERFEROMETER

80 METER
LINEAR RANGE

6DOF
MEASUREMENT

0.5 PPM
ACCURACY/METER

4.2 KG
TOTAL WEIGHT



特點：

- 依據 **ANSI B5.54** 美國國家標準對工具機評估校驗。
- 九個子系統組合可依校驗項目選擇，操作簡便快速。
- 感應器均經雷射校正及軟體補償，精度高。
- 軟體可作圖形組合顯示，數值分析列印等，功能強。
- 相容性佳，可配合 **PC-286** 以上機種及 **EGA/VGA** 螢幕使用。
- 最新 **6D** 雷射量測系統，可同時量測位移，雙軸向角度〔**Pitch**、**Yaw**〕，雙軸向直度〔**XX**、**YY**〕，及 **Roll** 角度偏差

產品規格

- API 雷射線性量測範圍：40m〔可選用 80m〕
- API 雷射直度與角度量測範圍：25m

XD SERIES SPECIFICATIONS		XD™ STANDARD SERIES (LS)			
Features		XD1 LS	XD3 LS	XD5 LS	XD6 LS
Measurement Range	0 - 45 m 80 m (optional)	X	X	X	X
Accuracy	0.2 µm/m				
	0.5 µm/m	X	X	X	X
Measurement Range	± 0.3 mm*				
	± 0.5 mm*		X	X	X
Accuracy	± (0.5 µm + 0.1 µm/m) or 1% of max measured error				
	± (1 µm + 0.2 µm/m) or 1% of max measured error				X
	± (2 µm + 0.4 µm/m) or 2% of max measured error		X		
Measurement Range	± 800 arcsec			X	X
	± 400 arcsec				
Pitch & Yaw Accuracy	± (1.0 arcsec + 0.1 arcsec/m)			X	X
	± (0.5 arcsec + 0.05 arcsec/m)				
Roll Accuracy (Horizontal Axes Only)	± 0.5 arcsec or 1% of max measured error				
	± 1.0 arcsec or 1% of max measured error				X
Accuracy	± (1.0 arcsec + 0.2 arcsec/m)				
	± (1.0 arcsec + 0.4 arcsec/m)			X	X
Accuracy	± (1.0 arcsec + 0.2 arcsec/m)			X	X
	± (1.0 arcsec + 0.4 arcsec/m)		X		

Environmental Compensation		
Air Temperature Accuracy	$\pm 0.2^{\circ}\text{C}$	XD™ LS
	$\pm 0.1^{\circ}\text{C}$	XD™ LP
Air Pressure Accuracy	$\pm 1.0\text{ mm Hg X}$	XD™ LS
	$\pm 0.4\text{ mm Hg}$	XD™ LP
Relative Humidity Accuracy	$\pm 5\%$	All Models
Material Temperature Accuracy	0.1°C	All Models

Laser Specifications	
Wavelength Compensation	$\pm 0.05\text{ ppm}$
Operating Temperature	$-5^{\circ}\text{C} - 40^{\circ}\text{C}$
Operating Humidity	0 - 95% non condensing
Output Power	Class 2 Laser
Laser Head Weight	Body: 3.8 kg, Sensor: 0.4 kg
Laser Dimensions	Body: 230 x 108 x 102 mm Sensor: 70 x 94 x 45 mm