

 ROHS 2 according to 2011/65/EU  
REACH according to EC 1907/2006  
WEEE according to 2002/96/EC

 10 x 5 mm

 For a temperature of 20°C and a relative humidity of ≤ 50 %:  
Analogue and digital response time: ≤ 100 ms. Holding of digital display: ≥ 100 ms.

 Supply: 4 batteries AA 1,5 V, type LRC 6.  
Power consumption: ≈ 7 mW/3,5 V.  
Probe supply voltage: 0,7 V.  
Supply frequency: 13 ± 0,65 kHz

 For a temperature of 20°C and a relative humidity of ≤ 50 %:  
Zero drift and signal amplification: ≤ 0,005 %/°C.  
Display frequency limit with respect to input signal: 10 Hz

 IP63 (IEC 60529)

 2004/ 108/EC  
EN 61326-1  
annex A

 RS232 via TLC connector

 100 x 170 x 38 mm  
(W x D x H)

 LCD display size:  
70 x 62 mm

 500 g  
(including batteries)

 5 decades plus minus sign

 ± 1 digital step

 Value limit for a temperature of 20°C and a relative humidity of ≤ 50 %:  
Analogue display: 1 %  
Digital display: 1 %

## TESATRONIC TWIN-T10 probe display unit

- Portable display TESATRONIC TWIN-T10 for TESA inductive probe.
- Autonomous instrument used during assembly, on an inspection workstation of a production line, for final inspection or directly on a machine on the shop floor.
- Frequently used with a GT 31 lever probe for geometry measurements: form tolerances (straightness, flatness etc.) or orientation tolerances (parallelism, perpendicularity, etc.).
- Function TOL for measurements with tolerances.
- Memory function for values MAX, MIN or MAX-MIN for dynamic measurements.
- Function for zero-setting of the display, for easy comparative measurements with a reference part.
- Special ZOOM mode for a more detailed visualization of the analogue scale. This mode simplifies the alignment and fine adjustment during assembly.

### Other features:

- 4 or 7 measuring ranges from ± 5 µm to ± 5 mm, or switchable automatically depending on the measured value.
- Access to functions by direct keys.
- Millimetre/inch conversion.
- 1 probe signal input.
- Power supply by standard AA batteries.
- RS232 digital output (TLC connector).



TWIN-T10



Designation



Number of probe inputs



Automatic conversion of range



Analogue scale zoom x5



Memory function for values MAX, MIN, MAX-MIN

04430013

TESATRONIC TWIN-T10 1

•

•

•





Run-out measurement with TWIN-T10 and GT 31 lever probe

#### STANDARD ACCESSORIES:

|          |                                                                                                                                              |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------|
| 03210802 | GT31 lever probe, $\pm 0,3$ mm, $F = 0,10$ N, standard version                                                                               |
| 04768000 | Hand switch for manually triggering data transfer. Jack plug connector, 1,8 m<br>- TESA SPC PRINTER printer<br>- TESATRONIC TT display units |
| 04768001 | Foot switch for triggering data transfer. Jack plug, 1,8 m<br>- TESA SPC PRINTER printer<br>- TESATRONIC (TT) display units                  |
| 04760181 | TESA TLC-USB CABLE for instruments with a TLC connector                                                                                      |
| 04760182 | TLC-DIGIMATIC CABLE for instruments with a TLC connector                                                                                     |
| 04760180 | TESA TLC-TWIN wireless transceiver. Compatible with any instrument equipped with a TLC connector (TESA Link Connector)                       |
| 05030012 | TWIN-STATION Receiver for wireless TLC-TWIN transceiver                                                                                      |
| 04981001 | DATA-DIRECT software and dongle                                                                                                              |
| 04981002 | STAT-EXPRESS Software and dongle                                                                                                             |
| 01460008 | Back with central lug                                                                                                                        |
| 01460009 | Back with offset lug                                                                                                                         |