

扭力轉接頭

9x12 & 14x18 型式接頭,適用於 WUMA
MIT 2, CPS, MEB 等型式可換頭扭力工具使用
20x28.5 大扭力轉接頭 適用於 WUMA MIT2,
CPS型式 800 N.M 以上的可換頭扭力扳手使用



RH 棘輪頭扭力轉接頭

齒數: 24 T
可左右切換棘輪功能

ITEM NO.	inch	mm	Teeth	W mm	H mm	L mm	L1 mm	g
RH0912-14	1/4"	9x12	24	27	20.5	56	26	84
RH0912-38S	3/8"	9x12	24	27	23.6	56	26	88
RH0912-38	3/8"	9x12	24	36	28.0	69	35	176
RH1418-38	3/8"	14x18	24	36	28.0	78	35	212
RH0912-12S	1/2"	9x12	24	36	31.5	69	35	186
RH1418-12S	1/2"	14x18	24	36	31.5	78	35	222
RH1418-12	1/2"	14x18	24	47	37.0	94	45	412



FH 驅動方頭 扭力轉接頭

固定方頭, 無棘輪功能

ITEM NO.	inch	mm	W mm	H mm	L mm	L1 mm	g
FH0912-14	1/4"	9x12	26.0	25.5	59.2	30.0	164
FH0912-38S	3/8"	9x12	26.0	29.0	59.2	30.0	169
FH0912-38	3/8"	9x12	26.0	29.0	59.2	30.0	169
FH0912-12S	1/2"	9x12	26.0	33.0	59.2	30.0	189
FH1418-38	3/8"	14x18	26.0	29.0	68.7	30.0	198
FH1418-12S	1/2"	14x18	26.0	33.0	68.7	30.0	223
FH1418-12	1/2"	14x18	26.0	33.0	68.7	30.0	223

扭力轉接頭型式依使用需求, 可搭配於 WUMA 各款可換頭扭力扳手使用.



精密螺帽 扭力轉接頭

ITEM NO.	mm	Clamping Range mm	g
ER16	14x18	31.6±5	218
ER20	14x18	34.9±5	234
ER25	14x18	41.9±5	242
ER32	14x18	50.0±5	259
ER40	14x18	62.9±5	313



勾型頭 扭力轉接頭

ITEM NO.	mm	Clamping Range mm	g
OZ16	14x18	43.0±5	272
OZ25	14x18	60.0±5	272
OZ32	14x18	72.0±5	292
TG75	14x18	50.0±5	262
TG100	14x18	63.2±5	260
TG150	14x18	82.0±5	296
MLC12	14x18	32.0±5	236