

61R-0.02-140



- 靈敏度 0.1mm/m,0.05 mm/m,0.04mm/m,0.02 mm/m,0.01 mm/m
- 底座長度 140mm,200mm,300mm,500mm
- 可選擇磁性底座及矩型底座。

Specifications 61 R

- Stabilized cast iron body.
- Grooved base for measurement on flat surfaces and cylinders.
- Hollowed base to provide precise seating.
- Hardened and grinded seatings (level type 61r in 140, 200, 300 and 500 mm only).
- Protected vials with clear visibility.
- Both vials are adjustable.
- For easier use on cylinders, the main vial is set so that a small transverse inclination will not modify the bubble position.

Note: the 100 mm level is not equipped with a transverse vial.

Dimensions (mm)			Approximate weight (gr)	
Length	Width	Height	w/o case	with case
100	40	40	750	920
140	40	41	950	1130
200	40	41	1300	1550
300	40	51	2100	2600
500	40	60	3500	4400

Levels of every dimension may be provided with the following precisions:

Model	Vial sensitivity				Base precision as of a 200 mm length(mm)
	mm / m	Inch / 10 inch	Arcseconds	Micro-radians	
61 R 0.1	0.1	0.001	20	100	0.01
61 R 0.05	0.05	0.0005	10	50	0.005
61 R 0.04	0.04	0.0004	8	40	0.004
61 R 0.02	0.02	0.0002	4	20	0.002
61 R 0.01	0.01	0.0001	2	10	0.002