

Easy Torque Tester



Item No. ETT-150N
Measurement and calibration
Capacity: 7.5 – 150 Nm (Metric)

Item No. ETT-110F
Measurement and calibration
Capacity: 5 – 110 ft.lb (SAE)



Packed in the blow case

- Specifications:
- * Accuracy : $\pm 1\%$
 - * Display :
 - 5 Digits (Above 1000N), 7 segment LED (update of 5 per second)
 - 4 Digits (Above 500N), 7 segment LED (update of 5 per second)
 - * Units Available in Nm, ft.lb, in.lb, kg-m
 - * Temp.Range-Operating : $\pm 5^{\circ}\text{C}$ to $+40^{\circ}\text{C}$
 - * Temp.Range-Storage : -20°C to $+70^{\circ}\text{C}$
 - * Sampling Rate : 333 SPS
 - * Auto Reset Hold Time : 2 Seconds
 - * Real Time Torque Reading
 - * Direction : C.W.
 - * AC 100 ~ 240V 50 ~ 60 Hz / DC 9 ~ 24V
 - * Aluminum Alloy House
 - * Calibration : According to BS7882:2008 method

Metric

ITEM NO.	Capacity	Dimension mm	 kg	Packing
ETT-15N	1-15 Nm	205 (D) x 155 (W) x 76 (H)	2.94	1 pcs/CTN
ETT-30N	1.5-30 Nm	205 (D) x 155 (W) x 76 (H)	2.94	1 pcs/CTN
ETT-150N	7.5-150 Nm	205 (D) x 155 (W) x 76 (H)	3.44	1 pcs/CTN
ETT-500N	25-500 Nm	205 (D) x 155 (W) x 76 (H)	4.06	1 pcs/CTN
ETT-1000N	50-1000 Nm	205 (D) x 155 (W) x 76 (H)	4.06	1 pcs/CTN
ETT-2000N	100-2000 Nm	205 (D) x 155 (W) x 76 (H)	4.56	1 pcs/CTN