



Model :

**ETT-150N, ETT-500N, ETT-1000N, ETT-2000N
ETT-110F, ETT-370F, ETT-740F, ETT-1500F**

► Specification

Metric

ITEM NO.	Capacity	Dimension mm	 kg	Packing
ETT-15N	1-15 Nm	205 (D) x 155 (W) x 76 (H)	2.94	1 pcs/CTN
ETT-30N	1.5-30 Nm	205 (D) x 155 (W) x 76 (H)	2.94	1 pcs/CTN
ETT-150N	7.5-150 Nm	205 (D) x 155 (W) x 76 (H)	3.44	1 pcs/CTN
ETT-500N	25-500 Nm	205 (D) x 155 (W) x 76 (H)	4.06	1 pcs/CTN
ETT-1000N	50-1000 Nm	205 (D) x 155 (W) x 76 (H)	4.06	1 pcs/CTN
ETT-2000N	100-2000 Nm	205 (D) x 155 (W) x 76 (H)	4.56	1 pcs/CTN

SAE

ITEM NO.	Capacity	Dimension mm	 kg	Packing
ETT-11F	0.74-11 ft.lb	205 (D) x 155 (W) x 76 (H)	2.94	1 pcs/CTN
ETT-22F	1-22 ft.lb	205 (D) x 155 (W) x 76 (H)	2.94	1 pcs/CTN
ETT-110F	5-110 ft.lb	205 (D) x 155 (W) x 76 (H)	3.44	1 pcs/CTN
ETT-370F	18-370 ft.lb	205 (D) x 155 (W) x 76 (H)	4.06	1 pcs/CTN
ETT-740F	36-740 ft.lb	205 (D) x 155 (W) x 76 (H)	4.06	1 pcs/CTN
ETT-1500F	75-1500 ft.lb	205 (D) x 155 (W) x 76 (H)	4.56	1 pcs/CTN

- Accuracy : $\pm 1\%$
- Display : 5 Digits (Above 1000N), 7 segment LED (update rate of 5 per second)
4 Digits (Below 500N), 7 segment LED (update rate of 5 per second)
- Units Available in Nm, ft.lb, in.lb, kg-m
- Temp. Range-Operating : $+5^{\circ}\text{C}$ to $+40^{\circ}\text{C}$
- Temp. Range-Storage : -20°C to $+70^{\circ}\text{C}$
- Sampling Rate : 333 SPS
- Auto Reset Hold Time : 2 Seconds
- Real Time Torque Reading
- Direction : C.W.
- AC 100~240V 50~60HZ / DC 9~24V
- Aluminum Alloy House
- Calibration : According to BS7882:2008 method