



1500N.M以上皆分為前後段組裝使用，不可單獨使用，將提供更好的扭力力距使用

CPS 固定式 單能型可換頭扭力扳手

單向扭力使用
CW:± 4%



Metric

ITEM NO.	mm	Range	L mm	kg	
CPS-12N	9x12	2-12 Nm	188	0.22	
CPS-50N	9x12	10-50 Nm	288	0.51	
CPS-50NS	14x18	10-50 Nm	293	0.51	
CPS-100N	9x12	20-100 Nm	345	0.69	
CPS-100NS	14x18	20-100 Nm	350	0.69	
CPS-200N	14x18	50-200 Nm	480	1.25	
CPS-300N	14x18	80-300 Nm	510	3.55	
✓ CPS-500N	14x18	100-500 Nm	650	5.80	
ITEM NO.	mm	Range	L mm	kg	
CPS-800N	20x28.5	150-800 Nm	900	6.30	
CPS-1200N	20x28.5	240-1200 Nm	1380	8.80	
CPS-1500N	20x28.5	300-1500 Nm	1580	11.45	

SAE

ITEM NO.	mm	Range	L mm	kg	
CPS-120i	9x12	20-120 in.lb	188	0.22	
CPS-40F	9x12	4-40 ft.lb	288	0.51	
CPS-40FS	14x18	4-40 ft.lb	293	0.51	
CPS-80F	9x12	10-80 ft.lb	345	0.69	
CPS-80FS	14x18	10-80 ft.lb	350	0.69	
CPS-150F	14x18	40-150 ft.lb	480	1.25	
CPS-230F	14x18	60-230 ft.lb	510	3.55	
CPS-400F	14x18	80-400 ft.lb	650	5.80	
ITEM NO.	mm	Range	L mm	kg	
CPS-600F	20x28.5	120-600 ft.lb	900	6.30	
CPS-800F	20x28.5	150-800 ft.lb	1380	8.80	
CPS-1000F	20x28.5	200-1000 ft.lb	1580	11.45	



扭力值設定與校驗

固定扭力值單能型扭力扳手，每款型式的扭力範圍內，皆可設定單一扭力值使用，主要有利於防呆，提高耐用性以及精準度，適用於產線組立規畫使用(扭力值設定需搭配扭力測試機使用)

可搭配P12 ~ P15各型式可換頭配件





扭力轉接頭

9 X 12 & 14 X 18 型式接頭,適用於 WUMA
MIT 2, CPS, MEB 等型式可換頭扭力工具使用



BH

梅花頭 轉接頭
9X12 & 14X18
20X28.5





ITEM NO.	B mm	mm	W mm	H mm	L mm	L1 mm	L2 mm	g
BH0912-7m	7	9x12	24.9	5.0	42.4	17.5	11.5	42
BH0912-8m	8	9x12	24.9	5.0	42.4	17.5	11.5	42
BH0912-9m	9	9x12	24.9	5.5	43.9	17.5	11.5	42
BH0912-10m	10	9x12	26.5	5.5	45.1	17.5	11.5	52
BH0912-11m	11	9x12	26.5	6.0	45.2	17.5	11.5	50
BH0912-12m	12	9x12	26.7	6.0	45.5	17.5	11.5	48
BH0912-13m	13	9x12	27.2	7.0	49.0	20.0	11.5	60
BH0912-14m	14	9x12	27.0	7.0	50.0	20.0	11.5	64
BH0912-15m	15	9x12	27.0	8.0	50.2	20.0	11.5	64
BH0912-16m	16	9x12	27.0	8.0	50.3	20.0	11.5	62
BH0912-17m	17	9x12	28.6	9.0	53.9	22.0	11.5	74
BH0912-18m	18	9x12	28.6	9.0	53.9	22.0	11.5	74
BH0912-19m	19	9x12	38.0	9.0	72.3	22.0	11.5	68

ITEM NO.	B mm	mm	W mm	H mm	L mm	L1 mm	L2 mm	g
BH1418-13m	13	14x18	38.0	11.5	72.3	32.0	15.0	200
BH1418-14m	14	14x18	38.0	11.5	72.3	32.0	15.0	200
BH1418-15m	15	14x18	38.0	11.5	72.5	32.0	15.0	194
BH1418-16m	16	14x18	38.0	12.0	72.5	32.0	15.0	204
BH1418-17m	17	14x18	38.0	12.0	72.5	32.0	15.0	198
BH1418-18m	18	14x18	44.0	13.5	74.5	32.0	15.0	234
BH1418-19m	19	14x18	44.0	13.5	74.5	32.0	15.0	230
BH1418-21m	21	14x18	41.0	14.5	75.6	32.0	15.0	236
BH1418-22m	22	14x18	42.0	16.0	77.0	32.0	15.0	250
BH1418-24m	24	14x18	42.0	16.0	78.0	32.0	15.0	254
BH1418-26m	26	14x18	42.0	16.0	78.0	32.0	15.0	240
BH1418-27m	27	14x18	43.4	17.0	81.5	34.0	15.0	280
BH1418-29m	29	14x18	43.3	19.0	84.5	36.0	15.0	306
BH1418-30m	30	14x18	47.3	19.0	86.7	36.0	15.0	328
BH1418-32m	32	14x18	47.3	19.0	86.7	36.0	15.0	312
BH1418-34m	34	14x18	50.0	19.0	89.6	38.0	15.0	324
BH1418-36m	36	14x18	54.6	19.0	91.0	38.0	15.0	316
BH1418-38m	38	14x18	60.0	19.0	94.2	40.0	15.0	342
BH1418-40m	40	14x18	60.0	19.0	98.5	42.0	15.0	392
BH1418-41m	41	14x18	60.0	20.0	98.5	42.0	15.0	392
BH1418-42m	42	14x18	60.0	20.0	98.5	42.0	15.0	376
BH1418-44m	44	14x18	60.0	20.0	99.2	44.0	15.0	393
BH1418-46m	46	14x18	64.8	20.0	103.0	42.0	15.0	396



20 X 28.5 大扭力 轉接頭 適用於 WUMA MIT 2,
CPS 型式 800 N . M 以上的可換頭扭力扳手使用

ITEM NO.	B mm	mm	W mm	H mm	L mm	L1 mm	L2 mm	g
BH2028-50m	50	20x28.5	77	29	138	52	24.5	990
BH2028-55m	55	20x28.5	84	30	147	57	24.5	1217
BH2028-60m	60	20x28.5	92	31	156	62	24.5	1220
BH2028-65m	65	20x28.5	98	33	163	66	24.5	1225



搭配 WUMA 可換頭扭力工具, 尺寸可從7mm-65mm搭配使用