



# Security Assessment



# Ether-Fi – v2.49

February 2025

Prepared for EtherFi

## Table of Contents

<b>Project Summary.....</b>	<b>3</b>
Project Scope.....	3
Project Overview.....	3
Findings Summary.....	4
Severity Matrix.....	4
<b>Medium Severity Issues.....</b>	<b>5</b>
M-01 Value sent with LiquidityPool.batchDeposit is lost.....	5
<b>Informational Severity Issues.....</b>	<b>7</b>
I-01. _sendFunds call can be removed from batchCancelDeposit.....	7
I-02. Outbound amounts are unnecessarily re-calculated.....	7
I-03. executeValidatorManagementTask does not follow CEI pattern.....	8
I-04. setValidatorTaskBatchSize allows for setting batch size at zero.....	8
I-05. validator tasks can be executed out of order or skipped entirely.....	9
<b>Appendix 1: Late-stage revision - PR240.....</b>	<b>10</b>
H-01 Unintentional Removal of _distributePayouts in partialWithdraw().....	11
I-06. Typo in comment.....	11
<b>Appendix 2: Late-stage improvements.....</b>	<b>12</b>
Adding MAX_ROLE.....	12
Renaming roles.....	12
<b>Disclaimer.....</b>	<b>13</b>
<b>About Certora.....</b>	<b>13</b>

# Project Summary

## Project Scope

Project Name	Repository (link)	Commit Hashes	Platform
EtherFi smart contracts	<a href="#">etherfi-protocol/smart-contracts</a>	Audit start: <a href="#">19503982</a> Audit end: <a href="#">3e9f54ec</a> Latest version reviewed: <a href="#">abc96405</a>	EVM

## Project Overview

This document describes the manual code review of [PR 230](#) related to v2.49.

The work was a 5 day-effort undertaken from **10/02/2025** to **14/02/2025**.

The following contract list is included in our scope:

1. `src/EtherFiAdmin.sol`
2. `src/LiquidityPool.sol`
3. `src/RoleRegistry.sol`
4. `src/WeETH.sol`

The team performed a manual audit of all the Solidity smart contracts. During the manual audit, the Certora team discovered bugs in the Solidity smart contracts code, as listed on the following page.

**Note 1:** A late-stage revision ([PR 240](#)) was also reviewed on **11/03/2025** with a 1 day-effort. The additional findings can be found in the following section: **Appendix 1: Late-stage revision - PR240**

**Note 2:** Some late-stage improvements were reviewed on **14/03/2025** with a 1 day-effort. There were no findings. See the following section: **Appendix 2: Late-stage improvements**

## Findings Summary

The table below summarizes the findings of the review, including type and severity details.

Severity	Discovered	Confirmed	Fixed
Critical	-	-	-
High	1	1	1
Medium	1	1	1
Low	-	-	-
<b>Total</b>	<b>2</b>	<b>2</b>	<b>2</b>

## Severity Matrix

Impact	High	Medium	High	Critical
	Medium	Low	Medium	High
	Low	Low	Low	Medium
		Low	Medium	High
		Likelihood		

## Medium Severity Issues

### M-01 Value sent with LiquidityPool.batchDeposit is lost

Severity: <b>Medium</b>	Impact: <b>High</b>	Likelihood: <b>Low</b>
Files: <a href="#">LiquidityPool.sol#L297</a>	Status: Fixed	

#### Description:

Within the changes in scope, LiquidityPool has been modified to always operate as BNFT holder. Within this context, the `batchDeposit` function remained payable, but the `msg.value` provided by callers is no longer accounted for:

JavaScript

File: LiquidityPool.sol

```
292:     function batchDeposit(uint256[] calldata _candidateBidIds, uint256
_numberOfValidators, uint256 _validatorIdToShareSafeWith) public payable whenNotPaused
returns (uint256[] memory) {
293:         address tnftHolder = address(this);
294:         address bnftHolder = address(this);
295:
296:         require(validatorSpawner[msg.sender].registered, "Incorrect Caller");
297:         require(totalValueInLp + msg.value >= 32 ether * _numberOfValidators, "Not
enough balance");
298:
299:         uint256[] memory newValidators =
stakingManager.batchDepositWithBidIds(_candidateBidIds, _numberOfValidators, msg.sender,
tnftHolder, bnftHolder, SourceOfFunds.EETH, restakeBnftDeposits,
_validatorIdToShareSafeWith);
300:         numPendingDeposits += uint32(newValidators.length);
301:
302:         return newValidators;
303:     }
```



We recommend making the `batchDeposit` function not payable because any value sent is a donation to the protocol which also cannot be used because it would increase the contract balance but not `totalValueInLp`.

**ether.fi's response:** Fixed in commit [b7a8d04d](#)

**Certora's response:** Fix confirmed

## Informational Severity Issues

### I-01. `_sendFunds` call can be removed from `batchCancelDeposit`

Affected code:

- [src/LiquidityPool.sol:L384](#)

The `batchCancelDeposit` function keeps track of a cumulative `returnAmount` which is then sent at the end of the iteration for canceling deposits.

However, `returnAmount` is never increased so the `_sendFund` call is useless.

We recommend removing `returnAmount` and the `_sendFund` call from the `batchCancelDeposit` function.

**ether.fi's response:** Fixed in commit [b7a8d04d](#)

**Certora's response:** Fix confirmed

### I-02. Outbound amounts are unnecessarily re-calculated

Affected code:

- [src/LiquidityPool.sol:L328](#)
- [src/LiquidityPool.sol:L366](#)

The contract `LiquidityPool`, in the `batchRegister` and `batchApproveRegistration` functions, calculates native amounts to be sent out and stores this value in the `outboundEthAmountFromLp` variable.

However, later, when transferring this amount, it recalculates the amount instead of reusing the pre-calculated `outboundEthAmountFromLp`:

JavaScript

File: `LiquidityPool.sol`

```
325:         uint256 outboundEthAmountFromLp = 1 ether * _validatorIds.length;
326:         _accountForEthSentOut(outboundEthAmountFromLp);
327:
328:         stakingManager.batchRegisterValidators{value: 1 ether *
_outboundEthAmountFromLp}(...);
329:
```

```
---
363:         uint256 outboundEthAmountFromLp = 31 ether * _validatorIds.length;
364:         _accountForEthSentOut(outboundEthAmountFromLp);
365:
366:         stakingManager.batchApproveRegistration{value: 31 ether *
_validatorIds.length}(, , ,);
367:     }
```

**ether.fi's response:** Fixed in commit [3e9f54ec](#)

**Certora's response:** Fix confirmed

### I-03. `executeValidatorManagementTask` does not follow CEI pattern

Affected code:

- [src/EtherFiAdmin.sol:L228](#)

The function `executeValidatorManagementTask` in `EtherFiAdmin` allows for asynchronous execution of validator actions after oracle report delivery. This function makes several external calls; however, a management task is marked as executed only after the external calls, thus violating the check-effect-interaction pattern

**ether.fi's response:** Fixed in commit [b7a8d04d](#)

**Certora's response:** Fix confirmed

### I-04. `setValidatorTaskBatchSize` allows for setting batch size at zero

Affected code:

- [src/EtherFiAdmin.sol:L171](#)

The `setValidatorTaskBatchSize` misses a sanity check for the new batch size being strictly greater than zero. When the size is set to zero, oracle delivery can fail for a division-by-zero revert at L281

**ether.fi's response:** Fixed in commit [3e9f54ec](#)



**Certora's response:** Fix confirmed, it is recommended to add an extra check for the new values set in `setValidatorTaskBatchSize`

## I-05. validator tasks can be executed out of order or skipped entirely

Affected code:

- [src/EtherFiAdmin.sol](#)

With the validator tasks executed asynchronously, oracle report delivery only stores hashes of tasks to be executed later. This means that, despite the intention of the code of using a queued mechanism, validator tasks can be executed out of order, skipped altogether, or even executed after tasks from a following oracle report.

**ether.fi's response:** We don't think this is an issue even if it happens out of order. Do you see any issue with doing them out of order?

## Appendix 1: Late-stage revision – [PR240](#)

### Update `partialWithdraw` to sweep ETH from `EtherFiNode` contracts

The ETH validators earn the staking rewards and they are sent to the `EtherFiNode` contracts.

The process of sweeping those ETH is called `partialWithdraw`.

Currently, `EtherFiNodesManager.partialWithdraw` can't process the withdrawal beyond 16 ETH because the `EtherFiNodesManager._getTotalRewardsPayoutsFromSafe` reverts if the contract's balance  $\geq 16$  ETH.

This constraint was added in the past due to the complexity in handling the distribution of staking rewards and principal after exit (= 32 ETH); while the earned staking rewards were distributed to (T-NFT, B-NFT, NodeOperator, Treasury), the principal (32 ETH) were sent to (B-NFT, T-NFT).

This complexity was removed while ago and now the below constraints are true:

- for all validators, its T-NFT holder == B-NFT holder
- `stakingRewardsSplit.tnft` is set to SCALE (100%); `stakingRewardsSplit.{treasury, nodeOperator, bnft}` are 0.
  - The staking rewards distribution to (treasury, node operator) is handled with eETH (instead of ETH from `EtherFiNode` contracts) by Oracle minting eETH

Therefore, all ETH in (`EtherFiNode`) contracts belongs to the T-NFT holder (= LiquidityPool).

This allows us to remove the constraint on the withdrawal amount.

The file affected by this merge is:

- `src/EtherFiNodesManager.sol`

The first review commit hash is [ffd0b87a](#)

The last reviewed commit hash is [260ec8bb](#)

## Findings

### H-01 Unintentional Removal of `_distributePayouts` in `partialWithdraw()`

Severity: <b>High</b>	Impact: <b>Medium</b>	Likelihood: <b>High</b>
Files: <a href="#">EtherFiNodesManager.sol</a>	Status: Fixed	

**Description:** `_distributePayouts()` was unintentionally removed, meaning `partialWithdraw()` now calculates payout amounts but does not distribute funds.

**ether.fi's response:** Fixed in commit [ffd0b87a](#)

### I-06. Typo in comment

Affected code:

- [EtherFiNodesManager.sol](#)

JavaScript

```
/// @dev This function is will be deprecated in the future for simpler operations using  
the advanced rewards distribution
```

**ether.fi's response:** Fixed in this PR which is now merged to v2.49:

<https://github.com/etherfi-protocol/smart-contracts/pull/230/commits/260ec8bb443401d873e0e55a18be76ac5ccfbf9f>

## Appendix 2: Late-stage improvements

### Adding MAX\_ROLE

The reviewed commit hash is [a1dec631](#).

The Ether.Fi team noticed that, while the transaction does not fail without defining MAX\_ROLE, there is still an “Error in Internal Transaction” every time grantRole() is called (see <https://etherscan.io/address/Ox13555cba55155796c70A5C8CC424E9ab6750A29F>).

This improvement aims to have cleaner transactions.

The code review didn’t reveal any bugs.

### Renaming roles

The reviewed PR is [PR 243](#), with the latest commit hash being [abc96405](#).

The changes were fairly trivial and didn’t reveal any bugs.

# Disclaimer

Even though we hope this information is helpful, we provide no warranty of any kind, explicit or implied. The contents of this report should not be construed as a complete guarantee that the contract is secure in all dimensions. In no event shall Certora or any of its employees be liable for any claim, damages, or other liability, whether in an action of contract, tort, or otherwise, arising from, out of, or in connection with the results reported here.

# About Certora

Certora is a Web3 security company that provides industry-leading formal verification tools and smart contract audits. Certora's flagship security product, Certora Prover, is a unique SaaS product that automatically locates even the most rare & hard-to-find bugs on your smart contracts or mathematically proves their absence. The Certora Prover plugs into your standard deployment pipeline. It is helpful for smart contract developers and security researchers during auditing and bug bounties.

Certora also provides services such as auditing, formal verification projects, and incident response.