

Soketi setup

Docker compose:

```
1  services:
2    soketi:
3      image: 'quay.io/soketi/soketi:latest-16-alpine'
4      ports:
5        - '6001:6001'
6        - '9601:9601'
7      environment:
8        SOKETI_DEBUG: '1'
9        SOKETI_DEFAULT_APP_ID: 'app-id'
10       SOKETI_DEFAULT_APP_KEY: 'app-key'
11       SOKETI_DEFAULT_APP_SECRET: 'app-secret'
12       SOKETI_DEFAULT_APP_ENABLE_CLIENT_MESSAGES: true
13       SOKETI_USER_AUTHENTICATION_TIMEOUT: '30000'
```

.env variables:

```
1  BETTER_AUTH_SECRET="your betterauth secret"
2  BETTER_AUTH_URL=http://localhost:3000 # Base URL of your app
3  DATABASE_URL="postgres://postgres:postgrespw@localhost:5432"
4
5  NEXT_PUBLIC_CLOUDINARY_CLOUD_NAME="your cloudinary name"
6  NEXT_PUBLIC_CLOUDINARY_API_KEY="your cloudinary api key"
7  CLOUDINARY_API_SECRET="your cloudinary api secret"
8
9  # NEXT_PUBLIC_PUSHER_APP_KEY="your pusher app key"
10 # PUSHER_APP_ID="your pusher app id"
11 # PUSHER_SECRET="your pusher secret"
12
13 NEXT_PUBLIC_PUSHER_APP_KEY="app-key"
14 PUSHER_APP_ID="app-id"
15 PUSHER_SECRET="app-secret"
16
17 # Soketi (local Pusher-compatible server)
18 NEXT_PUBLIC_PUSHER_HOST="127.0.0.1"
19 NEXT_PUBLIC_PUSHER_PORT="6001"
20 NEXT_PUBLIC_PUSHER_USE_TLS="false"
21
```

pusher.ts

```
1  import PusherServer from 'pusher';
2
3  declare global {
4    var pusherServerInstance: PusherServer | undefined;
5  }
6
7  // pusher cloud
8  // if (!global.pusherServerInstance) {
9  //   global.pusherServerInstance = new PusherServer({
10 //     appId: process.env.PUSHER_APP_ID!,
11 //     key: process.env.NEXT_PUBLIC_PUSHER_APP_KEY!,
12 //     secret: process.env.PUSHER_SECRET!,
13 //     cluster: 'ap1',
```

```

14 //      useTLS: true,
15 //    });
16 // }
17
18 // socket
19 if (!global.pusherServerInstance) {
20   global.pusherServerInstance = new PusherServer({
21     appId: process.env.PUSHER_APP_ID!,
22     key: process.env.NEXT_PUBLIC_PUSHER_APP_KEY!,
23     secret: process.env.PUSHER_SECRET!,
24     useTLS: false,
25     host: process.env.PUSHER_HOST || 'localhost',
26     port: process.env.PUSHER_PORT || '6001',
27   });
28 }
29
30 export const pusherServer = global.pusherServerInstance;
31

```

pusher client

```

1  import PusherClient from 'pusher-js';
2
3  declare global {
4    var pusherClientInstance: PusherClient | undefined;
5  }
6
7  export function getPusherClient(): PusherClient {
8    // pusher cloud config
9    // if (!global.pusherClientInstance) {
10     //   global.pusherClientInstance = new
PusherClient(process.env.NEXT_PUBLIC_PUSHER_APP_KEY!, {
11       //       channelAuthorization: {
12         //         endpoint: '/api/pusher-auth',
13         //         transport: 'ajax',
14         //       },
15       //       cluster: 'ap1'
16     //   });
17   // }
18
19   // socket
20   if (!global.pusherClientInstance) {
21     global.pusherClientInstance = new
PusherClient(process.env.NEXT_PUBLIC_PUSHER_APP_KEY!, {
22       channelAuthorization: {
23         endpoint: '/api/pusher-auth',
24         transport: 'ajax',
25       },
26       cluster: 'ap1',
27       wsHost: process.env.NEXT_PUBLIC_PUSHER_HOST,
28       wsPort: parseInt(process.env.NEXT_PUBLIC_PUSHER_PORT || '6001'),
29       forceTLS: process.env.NEXT_PUBLIC_PUSHER_USE_TLS === 'true',
30       disableStats: true,
31       enabledTransports: ['ws', 'wss']
32     });
33   }
34
35   return global.pusherClientInstance;
36

```

```
36 }
```

```
37
```