CISC 473: Deep Learning — Midterm Report

P08: Abstractive Summarization via Parameter-Efficient Fine-Tuning

Group Members:
Choo Wen Bin (20630085) (Project Lead) Nai Junn Rong (20630086) (Research Lead)

GitHub: https://github.com/wenbin05/DeepLearningP08 **Date:** October 17, 2026

Abstract

Abstractive text summarization demands substantial computational and memory resources when adapting pre-trained sequence-to-sequence models through full fine-tuning. While Parameter-Efficient Fine-Tuning (PEFT) techniques like Low-Rank Adaptation (LoRA) dramatically reduce trainable parameter counts, standard practice applies adapters uniformly across all attention projections without considering functional module roles. In this project, we investigate how the architectural placement of LoRA adapters influences summarization performance, factual consistency, and cross-domain robustness in BART-base. To date, we have implemented the data preprocessing and evaluation pipeline for CNN/DailyMail and XSum, reproduced the published BART-base full fine-tuning baseline within 0.5% ROUGE error, and established a budget-matched framework isolating encoder self-attention, decoder self-attention, and cross-attention adapters at exactly 147,456 trainable parameters (0.11% of the model). Our preliminary results demonstrate that cross-attention LoRA achieves a ROUGE-1 score of 41.42 ± 0.16, capturing over 95% of standard LoRA's performance while utilizing one-third of its parameter budget and substantially outperforming encoder-only adaptation (39.82 ± 0.22). In the second half of the semester, we will complete multi-seed evaluations across out-of-domain XSum data, execute the human factuality study, and deliver our final comparative analysis.

Introduction and Problem Statement

Abstractive summarization compresses lengthy source documents into fluent, salient, and factually accurate summaries. Pre-trained sequence-to-sequence Transformers such as BART [1] achieve high ROUGE scores by leveraging bidirectional encoder representations coupled with autoregressive decoder generation. However, conventional adaptation requires updating all 139.4 million parameters in BART-base, incurring steep computational overhead and high storage requirements when maintaining separate checkpoints for multiple domains or tasks. Parameter-efficient fine-tuning (PEFT) methods, particularly Low-Rank Adaptation (LoRA) [2], circumvent this cost by freezing the pre-trained weights $W_0 \in \mathbb{R}^{d \times k}$ and injecting trainable rank-decomposition matrices $\Delta W = BA$.

Scope Refinement and Changes Since Proposal. In our initial proposal, we outlined extensive multi-factor ablations spanning various LoRA ranks ($r \in \{4, 8, 16\}$), target projection subsets (Q, K, V, O), and alternative PEFT paradigms (Prefix-Tuning). Following faculty feedback advising a more focused scope for a two-member team, we refined our investigation to prioritize the core architectural question: *where* adaptation capacity should be allocated within an encoder-decoder model when total capacity is strictly controlled. Rather than conflating module placement with parameter volume, we exploit the structural symmetry of BART-base—wherein both the encoder and decoder contain 6 layers of identical hidden dimension ($d = 768$)—to fix the parameter budget to exactly 147,456 trainable parameters across all isolated placement variants.

Research Question. Under strictly matched trainable parameter budgets and identical training conditions, how does the architectural placement of LoRA adapters (encoder self-attention vs. decoder self-attention vs. encoder-decoder cross-attention) govern summarization performance, factual consistency, and zero-shot cross-domain generalization?

Related Work (Updated)

Parameter-efficient fine-tuning for conditional text generation has evolved rapidly, transitioning from uniform parameter perturbation to structural and capacity-aware allocation.

Parameter-Efficient Sequence-to-Sequence Modeling. Large-scale pre-training of sequence-to-sequence architectures, exemplified by BART [1], established denoising objectives as the foundation for modern summarization. While full fine-tuning updates all parameters, Prefix-Tuning [3] introduced continuous virtual prefix vectors prepended to attention keys and values, preserving frozen model weights while achieving competitive generation on XSum with under 2% parameter overhead. Concurrently, LoRA [2] demonstrated that task-specific parameter updates exhibit low intrinsic dimensionality, parametrizing weight updates via low-rank matrices $\Delta W = BA$. In their foundational work, Hu et al. observed that adapting attention query and value projections suffices for autoregressive language models. However, their primary benchmarks focused on decoder-only models, leaving the distinct functional components of encoder-decoder architectures unexamined.

Non-Uniform Capacity Allocation and Layer Sensitivity. Recognizing that uniform low-rank parameterization across all layers may be sub-optimal, recent research has explored dynamic allocation. AdaLoRA [4] parameterizes weight matrices using singular value decomposition and iteratively prunes singular values based on importance scores, allocating higher rank to influential matrices. Similarly, WeightLoRA [7] evaluates adapter significance during fine-tuning, demonstrating that adapters are not uniformly useful throughout BART. In a broader theoretical analysis, He et al. [5] established a unified framework connecting adapters, prefix tuning, and LoRA, proving that modification location directly shapes representation subspace alignment. Furthermore, Valipour et al. [6] introduced DyLoRA to train models across a spectrum of ranks dynamically, showing that representation rank requirements differ sharply between early feature encoding and autoregressive token emission. While these methods demonstrate parameter non-uniformity, they optimize allocation dynamically via complex heuristics, leaving open the empirical question of how distinct, interpretable architectural blocks perform under an identical, static budget.

Factual Consistency in Abstractive Summarization. A known limitation of n-gram overlap metrics such as ROUGE-1, ROUGE-2, and ROUGE-L is their insensitivity to factual hallucinations. Kryscinski et al. [8] demonstrated that high-ROUGE summaries frequently introduce factual inconsistencies unsupported by the source text, proposing FactCC as a weakly supervised evaluation metric. Because FactCC's accuracy degrades when evaluated out-of-domain (e.g., dropping from 72.65% on CNN/DailyMail to 54.11% on XSum), human evaluation remains essential for reliable factuality assessment. Our study combines lexical ROUGE metrics with human evaluation to determine whether adapter placement influences factual hallucination rates.

Method	Year	Key Idea	Relation to Our Work
BART [1]	2020	Bidirectional encoder + autoregressive decoder seq2seq pre-training.	Primary backbone architecture for our summarization study.
LoRA [2]	2022	Low-rank weight update factorization ($\Delta W = BA$).	Core PEFT mechanism evaluated across architectural placements.
Prefix-Tuning [3]	2021	Virtual task-specific prefix vectors prepended to attention keys/values.	Baseline conditional conditioning approach for comparison.
AdaLoRA [4]	2023	SVD-based parameterization with dynamic rank allocation.	Demonstrates non-uniform capacity importance; motivates explicit placement study.
Unified PEFT [5]	2022	Unified functional framework linking adapters, prefixes, and LoRA.	Theoretical grounding for structural placement effects.
DyLoRA [6]	2023	Dynamic search of LoRA ranks during training.	Highlights layer-wise capacity sensitivity in generation tasks.
WeightLoRA [7]	2026	Selectable LoRA units pruned during training.	Confirms adapter utility varies across BART layers.
FactCC [8]	2020	Factual-consistency classifier for abstractive summarization.	Highlights ROUGE limitations and justifies our human evaluation protocol.

Table 1: Comparative taxonomy of related work and foundational methods.

Methodology

Our methodology enforces strict experimental consistency to guarantee that performance differences originate solely from adapter placement rather than training variations or capacity disparities.

Model Architecture and Placement Isolation

We use pre-trained `facebook/bart-base` as our backbone, which comprises an encoder with 6 Transformer layers and a decoder with 6 Transformer layers ($d_{\text{model}} = 768$, 16 attention heads, feed-forward dimension $d_{\text{ff}} = 3072$, totaling 139,420,416 parameters). For any weight matrix $W_0 \in \mathbb{R}^{d \times k}$, LoRA parameterizes the forward pass as:

$$h = W_0 x + \Delta W x = W_0 x + \frac{\alpha}{r} BAx \tag{1}$$

where $A \in \mathbb{R}^{r \times k}$ is initialized from $\mathcal{N}(0, \sigma^2)$, $B \in \mathbb{R}^{d \times r}$ is initialized to zero, r is the adaptation rank, and α is a scaling hyperparameter. We set $r = 8$ and $\alpha = 16$, targeting the query (W_q) and value (W_v) projections ($k = d = 768$). Each adapted projection introduces $2 \times 768 \times 8 = 12,288$ parameters.

We construct four distinct LoRA configurations:

1. **Standard LoRA (All Attention):** Injects adapters into W_q and W_v across all 6 encoder self-attention, 6 decoder self-attention, and 6 decoder cross-attention blocks (18 attention layers total $\times 24,576 = 442,368$ trainable parameters, 0.32% of the base model).

2. **Encoder Self-Attention LoRA:** Adapts only `model.encoder.layers.*.self_attn` ($6 \times 24,576 = 147,456$ trainable parameters, 0.11%).
3. **Decoder Self-Attention LoRA:** Adapts only `model.decoder.layers.*.self_attn` ($6 \times 24,576 = 147,456$ trainable parameters, 0.11%).
4. **Cross-Attention LoRA:** Adapts only `model.decoder.layers.*.encoder_attn` ($6 \times 24,576 = 147,456$ trainable parameters, 0.11%).

Crucially, configurations (2), (3), and (4) share an identical parameter budget of exactly 147,456 parameters, providing an unconfounded comparison of architectural regions.

Training Setup

To ensure fair and reproducible comparisons, all models are trained under strictly matched hyperparameters as detailed in Table 2. We use the AdamW optimizer with a linear learning rate warmup followed by linear decay. Effective batch size is maintained at 32 across all runs via gradient accumulation.

Hyperparameter	**Value**
Backbone checkpoint	`facebook/bart-base` (139.4M parameters)
Optimiser	AdamW ($\beta_1 = 0.9, \beta_2 = 0.999, \epsilon = 1 \times 10^{-8}$)
Learning rate	3×10^{-4} (LoRA variants); 3×10^{-5} (Full Fine-Tuning)
Learning rate schedule	Linear warmup (500 steps) with linear decay
Batch size	8 per device $\times$ 4 gradient accumulation steps = 32 effective
Training epochs	3 epochs
Weight decay	0.01
Precision	Mixed precision FP16 with gradient clipping ($\max \|\mathbf{g}\|_2 = 1.0$)
Generation beam search	Beam width = 4, length penalty = 2.0, min length = 56, max length = 128
Repetition penalty	3-gram blocking (`no_repeat_ngram_size = 3`)
Random seeds evaluated	42, 123, 999

Table 2: Standardized training and generation hyperparameters.

Dataset and Preprocessing

We evaluate in-domain summarization on the CNN/DailyMail dataset (Version 3.0.0), comprising 287,113 training, 13,368 validation, and 11,490 test document-summary pairs. Source news stories are truncated to a maximum of 1,024 BPE tokens, and target multi-sentence summaries are capped at 128 tokens. Special tokens (`<s>`, `</s>`) are prepended and appended, with target padding tokens replaced by -100 to exclude them from cross-entropy loss computation. For zero-shot cross-domain evaluation, we use the test split of XSum (204,045 total samples, 11,334 test samples), which features highly abstractive, single-sentence summaries of BBC news articles.

Preliminary Results

Baseline Reproduction and Placement Comparison

Table 3 presents our quantitative evaluation. We first established the zero-shot baseline of BART-base on CNN/DailyMail, yielding a low ROUGE-1 score of 28.52 ± 0.31, confirming that pre-trained BART requires task adaptation. Next, we reproduced the published full fine-tuning benchmark:

our replicated full fine-tuning achieved ROUGE-1/2/L of 42.54/19.68/39.52, matching published benchmark performance (42.30 / 19.50 / 39.40) within 0.5%, successfully clearing the course's 1–2% reproduction threshold.

Model Configuration	Trainable Params	Trainable %	ROUGE-1	ROUGE-2	ROUGE-L
Published BART-base [1]	139,420,416	100.00%	42.30	19.50	39.40
Zero-Shot BART-base	0	0.00%	28.52 ± 0.31	8.84 ± 0.22	24.15 ± 0.28
Full Fine-Tuning (Ours)	139,420,416	100.00%	**42.54 ± 0.18**	**19.68 ± 0.14**	**39.52 ± 0.16**
Standard LoRA (All Attention)	442,368	0.32%	41.88 ± 0.15	19.12 ± 0.12	38.94 ± 0.14
Budget-Matched Placement Variants (Identical Budget: 147,456 Parameters, 0.11%)					
Encoder Self-Attention LoRA	147,456	0.11%	39.82 ± 0.22	17.41 ± 0.18	36.95 ± 0.20
Decoder Self-Attention LoRA	147,456	0.11%	40.65 ± 0.19	18.15 ± 0.16	37.82 ± 0.15
Cross-Attention LoRA	147,456	0.11%	<u>41.42 ± 0.16</u>	<u>18.74 ± 0.14</u>	<u>38.56 ± 0.15</u>

Table 3: Preliminary results on CNN/DailyMail test set. All reported experimental metrics are mean ± standard deviation across 3 random seeds (42, 123, 999). Best overall results are bolded; best budget-matched results are underlined.

Qualitative Analysis

Table 4 displays an illustrative test example from CNN/DailyMail comparing predictions across model configurations. Zero-shot BART struggles with prompt alignment and extracts verbatim fragments. Full fine-tuning generates fluent and accurate summaries. Notably, Cross-Attention LoRA captures the core factual points (the agency's mandate, the proposed timeline, and budgetary figures) with fluency nearly identical to full fine-tuning, while Encoder Self-Attention LoRA fails to synthesize the source's conclusion.




Figure 1: Parameter efficiency versus summarization performance across adaptation strategies on CNN/DailyMail. Cross-attention LoRA achieves 41.42 ROUGE-1 with only 147k trainable parameters (0.11% of the base model), closely trailing standard LoRA while utilizing one-third of the adapter budget.

Source Snippet	The Federal Aviation Administration announced Thursday a comprehensive plan to modernize national airspace radar tracking systems by 2028. The $1.4 billion infrastructure initiative aims to replace legacy secondary radar installations with satellite-based ADS-B monitoring, reducing mid-flight routing delays by an estimated 18 percent across major hubs. Industry representatives praised the timeline, though congressional budget analysts raised concerns regarding procurement milestones.
Reference Summary	The FAA has unveiled a $1.4B plan to modernize air traffic radar with satellite tracking by 2028. The initiative expects to cut flight delays by 18 percent, though budget analysts caution procurement risks.
Zero-Shot	The Federal Aviation Administration announced Thursday a comprehensive plan to modernize national airspace radar tracking systems by 2028. The $1.4 billion infrastructure initiative aims to replace legacy secondary.
Full Fine-Tuning	The FAA has announced a $1.4 billion plan to upgrade radar systems with satellite-based tracking by 2028. The project is expected to reduce flight delays by 18% across major airports, despite budget scrutiny.
Cross-Attention LoRA	The FAA announced a $1.4 billion modernization project to implement satellite flight tracking by 2028. The plan aims to reduce flight delays by 18 percent, while facing congressional budget questions.
Encoder LoRA	The Federal Aviation Administration will modernize radar systems by 2028 under a new infrastructure plan to cut flight delays.

Table 4: Qualitative comparison of generated summaries on a representative CNN/DailyMail test article.

Discussion

Our preliminary findings reveal three crucial insights:

1. **High Efficiency of LoRA in Seq2Seq Models:** Standard LoRA achieves 41.88 ROUGE-1, retaining 98.4% of full fine-tuning performance (42.54) while updating only 0.32% of the parameters.

2. **Cross-Attention as the Primary Adaptation Locus:** Under the matched 147,456 parameter budget, Cross-Attention LoRA (41.42 ROUGE-1) outperforms Decoder Self-Attention (40.65) by +0.77 points and Encoder Self-Attention (39.82) by +1.60 points. Cross-attention alone captures 98.9% of standard LoRA performance while using only one-third of its adapter budget.

3. **Functional Specialization:** Encoder representations benefit heavily from pre-training and require minimal adaptation; generation relies primarily on dynamically conditioning the decoder on source tokens through the cross-attention bridge.

Challenges and Adaptations

Throughout Weeks 3–6, we encountered both technical and conceptual challenges, which we successfully addressed:

1. Memory Overhead During Autoregressive Beam Search: Initial multi-seed training scripts caused CUDA out-of-memory errors during validation evaluation due to tensor accumulation

across 4 generation beams. We resolved this by reducing per-device batch size from 16 to 8 while increasing gradient accumulation steps to 4, maintaining an identical effective batch size of 32 without memory spikes.

2. Experimental Scope Streamlining: Originally, our proposal called for full hyperparameter grids across multiple LoRA ranks, Prefix-Tuning variations, and projection subsets. In accordance with faculty feedback emphasizing thoroughness on core placement questions, we prioritized the budget-matched placement ablation. We fixed the rank ($r = 8$) and projection targets (W_q, W_v) to isolate architectural location as the sole independent variable.

3. Inconsistent Parameter Counting Across PEFT Configurations: Initial tests using default PEFT wrappers reported inconsistent parameter counts due to differing bias configurations. We standardized the injection pipeline using explicit module path targeting and verified exact parameter matching ($147,456$ parameters) with unit tests before launching multi-seed runs.

Updated Week 7–10 Plan

Table 5 outlines our roadmap for the remaining project period.

Week	Tasks	Responsible
7	Evaluate trained models on XSum test set for zero-shot cross-domain generalization; conduct training throughput (tokens/sec) and peak memory profiling.	Wen Bin / Junn Rong
8	Conduct human factual consistency evaluation (10 participants, 20 summaries per configuration); calculate inter-annotator agreement (Fleiss' κ); run FactCC metric.	Junn Rong / Wen Bin
9	Synthesize ROUGE, factuality, and efficiency results; generate parameter-performance Pareto trade-off curves; conduct qualitative failure case analysis.	Both
10	Final report drafting, comprehensive code clean-up, reproduction verification from a clean environment, and presentation deck preparation. **(Final due)**	Both

Table 5: Updated project schedule and task allocation for Weeks 7–10.

Preliminary Novel Contribution (Optional Bonus)

Our primary novel contribution is an unconfounded, budget-matched empirical study of adapter placement in encoder-decoder Transformers. Prior studies (such as AdaLoRA [4] and WeightLoRA [7]) demonstrate that adaptation capacity is non-uniform, but they either optimize capacity dynamically or compare modules with unequal parameter counts.

By capitalizing on BART-base's architectural symmetry (6 encoder and 6 decoder layers, $d = 768$), we proved that adapting W_q and W_v with rank $r = 8$ in Encoder Self-Attention, Decoder Self-Attention, or Encoder-Decoder Cross-Attention yields the **exact same budget of 147,456 parameters (**0.1058% **of the base model)**. Our early empirical results provide strong evidence that:

- Adapting cross-attention alone yields 41.42 ROUGE-1, within 0.46 points of adapting all attention layers (41.88) despite using 66.7% fewer parameters.

- Parameter placement is as decisive as parameter quantity: shifting the same 147k parameter budget from encoder self-attention to cross-attention yields a substantial +1.60 ROUGE-1 and +1.33 ROUGE-2 improvement under identical training conditions.

Contribution Declaration

Both team members have contributed equally to the project across Weeks 3–6 (50%/50%).

Member	Contributions (Midterm Period: Weeks 3–6)	%
Choo Wen Bin (20630085)	Model architecture implementation; PEFT/LoRA module targeting; training pipeline automation; GPU hyperparameter tuning; preliminary novel contribution analysis; LaTeX report drafting.	50%
Nai Junn Rong (20630086)	Dataset preprocessing pipeline (CNN/DM, XSum); ROUGE evaluation suite; parameter counting verification tools; baseline reproduction experiments; qualitative analysis synthesis; updated literature review.	50%

References

[1] M. Lewis, Y. Liu, N. Goyal, M. Ghazvininejad, A. Mohamed, O. Levy, V. Stoyanov, and L. Zettlemoyer. BART: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 7871–7880, 2020.

[2] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

[3] X. L. Li and P. Liang. Prefix-tuning: Optimizing continuous prompts for generation. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (ACL-IJCNLP)*, pages 4582–4597, 2021.

[4] Q. Zhang, M. Chen, A. Bukharin, P. He, Y. Cheng, W. Chen, and T. Zhao. Adaptive budget allocation for parameter-efficient fine-tuning. In *International Conference on Learning Representations (ICLR)*, 2023.

[5] J. He, C. Zhou, X. Ma, T. Berg-Kirkpatrick, and G. Neubig. Towards a unified view of parameter-efficient transfer learning. In *International Conference on Learning Representations (ICLR)*, 2022.

[6] M. Valipour, M. Rezagholizadeh, I. Kobyzev, and A. Ghodsi. DyLoRA: Parameter-efficient tuning of large language models with dynamic search of ranks. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics (EACL)*, pages 3266–3279, 2023.

[7] A. Veprikov, V. Solodkin, Z. Alexander, A. Savchenko, and A. Beznosikov. WeightLoRA: Keep only necessary adapters. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL)*, Volume 1, pages 12419–12437, 2026.

[8] W. Kryscinski, B. McCann, C. Xiong, and R. Socher. Evaluating the factual consistency of abstractive text summarization. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 9332–9346, 2020.