4 Process Synchronization

Process Synchronization

LEARNING OUTCOMES

By the end of this module, students will be able to:

1. Analyze the impact of inadequate synchronization, including race conditions and data inconsistencies.
2. Apply semaphores, mutexes, and condition variables to solve critical section problems effectively.
3. Implement approaches for designing deadlock-free concurrent systems.

Table of Contents

4.1 Concurrency and the need for synchronization 4

4.2 Semaphores, mutexes, and condition variables 9

4.3 Deadlocks and deadlock prevention 13

4.4 SUMMARY 22

4.1 Concurrency and the need for synchronization

Concurrency is a fundamental concept in modern computing systems where multiple processes or threads execute simultaneously, either on a single processor or across multiple processors. Concurrency allows systems to perform multiple tasks at once, improving resource utilization and system efficiency. However, with this increased capability comes the challenge of ensuring data consistency and preventing conflicts, leading to the critical need for synchronization.

Concurrency refers to the ability of a system to execute multiple tasks concurrently, rather than sequentially. It is a crucial aspect of multitasking and multiprocessing systems where numerous tasks share the CPU and other system resources. Concurrency can be achieved through:

- Multiprocessing: Running multiple processes on separate CPUs or CPU cores.
- Multithreading: Running multiple threads within a single process, sharing the same memory space.

Benefits of Concurrency

- Improved CPU Utilization: Maximizes the use of CPU cycles by running tasks simultaneously.
- Enhanced Responsiveness: Enables systems to handle multiple tasks, improving user experience.
- Parallel Processing: Distributes tasks across multiple processors for faster execution.

Despite these advantages, concurrency introduces significant challenges, especially when multiple tasks share resources, leading to potential race conditions, deadlocks, and data inconsistency.

The Need for Synchronization

Synchronization in concurrent systems ensures that multiple threads or processes can work together without conflicts. When tasks share resources, synchronization mechanisms coordinate access to prevent data corruption and inconsistencies.

Why Synchronization is Necessary

- Data Consistency: Prevents multiple processes from modifying the same resource simultaneously, which can lead to incorrect results.
- Avoiding Race Conditions: Occurs when the system's behavior depends on the sequence or timing of process execution. Synchronization prevents such unpredictable behavior.
- Ensuring Mutual Exclusion: Ensures that only one process can access a critical section (shared resource) at a time.
- Coordination Between Processes: Helps processes work together efficiently by managing dependencies and preventing resource conflicts.
- Preventing Deadlocks: Synchronization helps avoid situations where processes wait indefinitely for resources.

Example of the Need for Synchronization

Consider a banking system where two threads attempt to withdraw money from a single account simultaneously. If proper synchronization is not implemented, both threads may check the balance simultaneously, leading to an overdraft or incorrect balance updates.

Understanding Concurrency

Concurrency occurs when multiple processes or threads run together, either:

- Parallel: Tasks run on different cores simultaneously on a multi-core processor.
- Interleaved: Tasks take turns running on a single-core processor.
- Importance of Concurrency
- Efficiency: Maximizes CPU and resource usage.
- Faster Execution: Speeds up task completion through parallel execution.
- Responsiveness: Improves user experience, especially in GUI applications.
- Resource Sharing: Facilitates multiple processes using shared resources effectively.




Figure 1 Concept of concurrency

Challenges in Concurrency

While beneficial, concurrency presents several risks:

1. Race Conditions: Occurs when multiple processes access shared resources without proper control, leading to incorrect results.
2. Data Inconsistency: Data corruption when simultaneous operations interfere with each other.
3. Deadlock: When two or more processes are stuck waiting for each other to release resources.
4. Starvation: When some processes experience indefinite delays due to continuous execution of higher-priority tasks.




Figure 2 Challenges in concurrency control

Synchronization Mechanisms

Several tools help manage concurrency effectively:

- Mutex (Mutual Exclusion): Prevents multiple threads from accessing a resource simultaneously by locking access.
- Semaphores: Control resource access through counters.
- Condition Variables: Allow processes to wait for specific conditions before continuing.
- Locks and Critical Sections: Ensure only one process can execute critical code sections at a time.

Real-Life Example: Banking System

In a banking system, two users attempting to withdraw money from the same account simultaneously can lead to incorrect balances without synchronization. For example:

- User A and B both check the balance of $1000.
- User A withdraws $500, leaving $500.
- User B also withdraws $500, believing the balance is still $1000, causing incorrect results.
- With Synchronization: Only one withdrawal is processed at a time, ensuring accuracy.

Problems Arising Without Synchronization

1. Race Condition:

Occurs when multiple processes access shared resources concurrently, leading to unpredictable outcomes.

Example: Two threads checking and updating the balance simultaneously in a bank account system.

2. Deadlock:

A state where two or more processes wait indefinitely for resources held by each other.

Example: Process A holds Resource 1 and waits for Resource 2, while Process B holds Resource 2 and waits for Resource 1.

3. Data Corruption:

When multiple threads modify shared data without synchronization, data can become corrupted.

Example: Updating a shared counter without synchronization can result in incorrect values.

4. Starvation:

A low-priority task gets indefinitely delayed while high-priority tasks keep executing.

Example: A low-priority print job being postponed while urgent print jobs keep occupying the printer.

Synchronization Techniques

Several techniques are used to achieve synchronization in concurrent systems:

1. Locks (Mutexes):

A mutex (mutual exclusion) allows only one process to access a critical section at a time.

Example: A file lock preventing simultaneous editing of a document.

2. Semaphores:

A semaphore is a signaling mechanism used to control access to shared resources.

Example: Limiting the number of users accessing a database simultaneously.

3. Monitors:

A monitor is a high-level abstraction that combines mutual exclusion and synchronization.

Example: A monitor controlling access to a shared printer.

4. Condition Variables:

Condition variables work with locks to pause a process until a certain condition is met.

Example: A process waiting for data to be available before proceeding with computation.

5. Spinlocks:

A spinlock continuously checks for resource availability without releasing the CPU.

Example: Busy-waiting for a resource in low-latency systems.

Conclusion

Concurrency enhances performance but can introduce issues like race conditions and deadlocks. Synchronization mechanisms such as mutexes, semaphores, and locks are essential for ensuring consistency and process coordination, leading to a stable and reliable computing environment.

Here are some short-answer questions.

1. What is concurrency, and why is it important in modern computing
2. Explain the critical section problem and why it requires synchronization.
3. Describe how a mutex works and provide a real-world example.
4. What role do semaphores play in process synchronization?
5. Why can data corruption occur without proper synchronization?

4.2 Semaphores, mutexes, and condition variables

Synchronization mechanisms such as semaphores, mutexes, and condition variables are essential tools in concurrent programming, helping prevent race conditions, ensure data integrity, and manage shared resources among multiple threads or processes.

Semaphores

A semaphore is a synchronization primitive used to control access to shared resources. It uses a counter to track how many threads can access a critical section concurrently.

Types of Semaphores:

- Binary Semaphore: Acts like a mutex, with values 0 and 1.
- Counting Semaphore: Allows multiple threads to access a resource concurrently.

Working:

- Initialize: A counter is set for available resources.
- Wait (P Operation): Decrements the counter; if zero, the process waits.
- Signal (V Operation): Increments the counter, allowing another thread to proceed.

Use Cases:

- Managing resource pools.
- Controlling access to limited hardware devices.

Advantages:

- Effective for managing multiple resources.

Disadvantages:

- Complex debugging.
- Risk of deadlocks and priority inversion.

Mutexes (Mutual Exclusion)

A mutex is a locking mechanism ensuring that only one thread accesses a critical section at a time.

Working:

- Lock: A thread locks the mutex before entering the critical section.
- Unlock: Mutex is released after the thread completes its task.

Use Cases:

- Preventing race conditions.
- Exclusive access to shared resources.

Advantages:

- Simple and effective for single-threaded access.

Disadvantages:

- Deadlock risk if mismanaged.
- No condition waiting support.

Condition Variables

A condition variable allows thread communication based on specific conditions. It works in combination with a mutex.

Key Functions:

- wait: Releases the mutex and waits for a signal.
- signal: Wakes up one waiting thread.
- broadcast: Wakes up all waiting threads.

Use Case:

- Producer-Consumer Problem: Producers notify consumers when data is available.

Advantages:

- Prevents busy-waiting.

Disadvantages:

- Risk of missed signals if used incorrectly.

Comparison Table:

Feature	Semaphore	Mutex	Condition Variable
Purpose	Control access to resources	Ensure mutual exclusion	Thread communication
Resource Management	Manages multiple resources	Only one resource at a time	Based on condition check
Blocking Mechanism	Wait and Signal	Lock and Unlock	Wait and Signal/Broadcast
Use Case	Resource pools	Critical sections	Producer-Consumer problems
Concurrency Level	Multiple threads can proceed	Only one thread at a time	Depends on condition
Risk of Deadlock	High (if misused)	Moderate	High (if signals are missed)

Figure 3 Comparison between Semaphore, Mutex, and Condition Variable

Best Practices:

- Use mutexes for simple exclusive locks.
- Use semaphores for managing multiple resource availability.
- Use condition variables when thread communication based on conditions is required.
- Avoid nested locks to prevent deadlocks.
- Always release locks properly to avoid resource leaks.

Conclusion

Effective synchronization is crucial in concurrent programming to ensure proper management of resources and data integrity. Various tools such as semaphores, mutexes, and condition variables offer different advantages for managing concurrency challenges.

Semaphores are particularly suitable for managing resources with multiple instances, making them ideal for situations where a limited number of identical resources need to be accessed by multiple processes or threads concurrently.

Mutexes excel in protecting single resources from simultaneous access, ensuring mutual exclusion by allowing only one thread or process to access the resource at a time. This makes them essential for critical

sections where data consistency is a priority.

Condition Variables play a vital role in thread coordination, enabling threads to wait for certain conditions to be met before proceeding with execution. This helps in synchronizing complex thread interactions where dependencies exist between multiple tasks.

Understanding and utilizing these synchronization mechanisms effectively is fundamental for preventing race conditions, ensuring data integrity, and maintaining overall system stability in concurrent programming environments. Proper implementation of these tools helps achieve efficient and reliable multitasking in modern software systems.

Here are some short-answer questions.

1. What is the primary purpose of a semaphore in concurrent programming
2. How does a mutex differ from a semaphore
3. In what scenario would you prefer to use a condition variable over a mutex?
4. Explain how semaphores help in managing multiple instances of a resource.
5. Why is a mutex suitable for protecting a single resource?
6. How does a condition variable facilitate thread condition?



Here are some useful YouTube videos:

1. Condition Variables + Semaphores. Watch here
2. Multithreading, Condition Variables, and Semaphores. Watch here

4.3 Deadlocks and deadlock prevention

Deadlock is a condition in operating systems where a set of processes get stuck indefinitely because each process is waiting for a resource held by another process. Deadlock occurs in systems with limited resources where multiple processes compete for exclusive access to resources, leading to a circular wait situation.




Figure 4 Deadlock OS

A deadlock happens when multiple processes wait indefinitely for resources held by each other. Example: Process P1 holds Resource A while waiting for Resource B, and Process P2 holds Resource B while waiting for Resource A, leading to a circular wait with no progress.

Conditions for Deadlock (Coffman's Conditions)

A deadlock can occur if all four of these conditions are true:

- Mutual Exclusion: Only one process can hold a resource at a time.
- Hold and Wait: A process holding resources waits for additional resources held by others.
- No Preemption: Resources cannot be forcibly taken; they must be released voluntarily.
- Circular Wait: A cycle exists where each process waits for a resource held by the next.

Deadlock Handling Techniques

1. Deadlock Prevention

Prevention ensures at least one Coffman condition is violated:

- Eliminate Mutual Exclusion: Share resources if possible.
- Eliminate Hold and Wait: Request all resources before starting execution.
- Eliminate No Preemption: Allow preemption of resources.
- Eliminate Circular Wait: Enforce a strict order for resource requests.

Pros: Prevents deadlock entirely.

Cons: May reduce resource utilization.




Figure 5 Deadlock Presentation

2. Deadlock Avoidance

Avoidance ensures the system stays in a safe state:

- Safe State: Exists when resources can be allocated to avoid deadlock.
- Banker's Algorithm: Grants resources only if it keeps the system safe.

Pros: Prevents deadlock dynamically.

Cons: Needs prior knowledge of resource requirements.

3. Deadlock Detection and Recovery

Detection involves monitoring for deadlocks and recovering after they occur:

- Detection Tools: Wait-for Graph, Resource Allocation Graph (RAG).
- Recovery Methods:
  - Process Termination.
  - Resource Preemption.
  - Rollback.

Pros: No need to avoid deadlocks proactively.

Cons: Complex and risky recovery process.

4. Deadlock Ignorance (Ostrich Algorithm)

Infrequent deadlocks may be ignored in simpler systems like UNIX.

Pros: Simplifies design.

Cons: Risk of system failure if deadlocks occur.

Resource Allocation Graph (RAG) for Deadlock Detection

A Resource Allocation Graph (RAG) is a graphical representation used to detect deadlocks.

Key Components:

- Processes: Represented by circles (P1, P2).
- Resources: Represented by squares (R1, R2).

Edges:

- Request Edge: Process → Resource (indicating a request for a resource).
- Assignment Edge: Resource → Process (indicating a resource is allocated to a process).

Deadlock Example in RAG:

- P1 → R2 (P1 is waiting for R2)
- R2 → P2 (R2 is allocated to P2)
- P2 → R1 (P2 is waiting for R1)
- R1 → P1 (R1 is allocated to P1)

Example of Deadlock

Deadlock can frequently occur in database management systems (DBMS), especially when multiple transactions attempt to access the same set of data resources simultaneously. Here's a detailed breakdown of a classic deadlock scenario involving two transactions and two database rows.

Consider a database with two rows: Row 1 and Row 2, and two transactions, Transaction A and Transaction B.

Steps Leading to Deadlock

1. Transaction A locks Row 1 (Exclusive Lock):

- Transaction A begins and locks Row 1 to perform an update.
- This lock is exclusive, meaning no other transaction can modify Row 1 until the lock is released.

2. Transaction B locks Row 2 (Exclusive Lock):

- Meanwhile, Transaction B begins and locks Row 2 for modification.
- Similarly, the exclusive lock prevents other transactions from modifying Row 2 until B completes its operation.

3. Transaction A requests Row 2:

- Transaction A now attempts to lock Row 2 to complete its operation.
- However, Row 2 is already locked by Transaction B.
- Transaction A is forced to wait for Transaction B to release Row 2.

4. Transaction B requests Row 1:

- Transaction B now attempts to lock Row 1 to complete its operation.
- However, Row 1 is already locked by Transaction A.
- Transaction B is forced to wait for Transaction A to release Row 1.

Deadlock Condition:

- Transaction A is waiting for Transaction B to release Row 2.
- Transaction B is waiting for Transaction A to release Row 1.

Since both transactions are holding a resource and waiting for each other, a circular wait occurs, and neither transaction can proceed, causing a deadlock.

Deadlock Representation Using Resource Allocation Graph

- Processes: Transaction A, Transaction B
- Resources: Row 1, Row 2

| Transaction A → Row 2 → Transaction B → Row 1 → Transaction A |

The circular chain indicates a deadlock where each process is waiting for a resource held by the other.

Causes of Deadlock in Database Transactions:

1. **Exclusive Locks:** When transactions acquire exclusive locks on data resources and prevent access by others.
2. **Circular Wait Condition:** Transactions waiting for resources held by other transactions.
3. **Hold and Wait:** A transaction holding one resource while waiting for another.
4. **No Preemption:** Once a resource is locked, it cannot be forcefully taken from the transaction.
5. **Improper Locking Order:** Transactions accessing resources in different orders can lead to circular wait situations.

How to Prevent Deadlock in Databases:

To avoid deadlocks in database systems, several strategies can be employed:

1. **Resource Lock Ordering:**

- Enforce a consistent order of accessing resources.
- Example: Always lock Row 1 before Row 2 for all transactions.

2. Two-Phase Locking Protocol (2PL):

- Divides the transaction into two phases:
- Growing Phase: Locks are acquired but cannot be released.
- Shrinking Phase: Locks can be released, but no new locks can be acquired.

3. Timeout Mechanism:

- Set a time limit for a transaction to wait for a lock.
- If the lock is not acquired within the timeout, the transaction is aborted.

4. Deadlock Detection and Rollback:

- Use Wait-for Graphs to detect cycles indicating deadlock.
- Abort one of the transactions to break the deadlock.

5. Lock Granularity Control:

- Use finer-grained locks (e.g., row-level instead of table-level locks).

Deadlock Resolution Example

If the deadlock occurs, the DBMS can break the cycle by:

1. Aborting Transaction B: Releasing the lock on Row 2, allowing Transaction A to complete.
2. Rolling Back Transaction B: The transaction would be retried after Transaction A completes.

Deadlock in database systems is a serious issue that can halt operations and lead to performance degradation. It occurs when multiple transactions hold resources while waiting for other resources locked by different transactions. By implementing strategies like two-phase locking, timeout mechanisms, and resource ordering, deadlocks can be prevented or resolved effectively, ensuring smooth and reliable database operations.

Deadlock Prevention Best Practices

Deadlock prevention is a critical aspect of concurrent programming and operating system design, ensuring that multiple processes can run simultaneously without indefinite blocking. Deadlocks occur when processes wait indefinitely for resources held by each other. To mitigate such issues, specific strategies can be implemented, such as lock hierarchies, resource allocation limits, timeout mechanisms, and minimizing resource holding.

Lock Hierarchies: Acquire Locks in a Defined Order

Lock hierarchies refer to establishing a predefined order in which locks must be acquired. This method helps prevent circular wait conditions, one of the necessary conditions for deadlock occurrence. By ensuring that all processes acquire locks in the same sequence, circular dependencies are avoided, reducing the likelihood of deadlock.

How it Works:

- Resources are assigned a strict numerical order.
- Processes must acquire locks in ascending order based on this sequence.
- If a process needs multiple resources, it must request them following the defined order.

Example:

- Lock order defined: Lock A → Lock B → Lock C.
- Process P1 requests Lock A, then Lock B.
- Process P2 must also follow the same sequence, avoiding circular dependencies.

Benefits:

- Simple to implement.
- Prevents circular wait.

Drawbacks:

- Difficult to implement in dynamic systems where resource requirements change during execution.

Resource Allocation Limits: Restrict Simultaneous Resource Requests

Resource allocation limits involve restricting the number of resources a process can request at a time. This strategy prevents the hold and wait condition by ensuring processes do not hold some resources while waiting for others.

How it Works:

- Each process must request all required resources before execution begins.
- If all requested resources are available, the process continues execution.
- If not, the process must wait without holding any resources.

Example:

- A process requires 3 resources (R1, R2, R3).
- If R2 is unavailable, the process releases R1 and reattempts when all resources are free.

Benefits:

- Simple implementation in batch processing systems.
- Prevents deadlock due to hold and wait condition.

Drawbacks:

- Can lead to inefficient resource utilization since processes may hold resources longer than necessary.
- Some processes might starve while waiting for all required resources to become available.

Timeout Mechanism: Set Timeouts for Resource Requests

The timeout mechanism involves setting a predefined time limit for a process to wait for a resource before it is forced to release all held resources and restart.

How it Works:

- Each resource request is associated with a timer.
- If the resource cannot be acquired within the specified time, the process releases all held resources and retries.
- Prevents indefinite waiting and breaks circular wait conditions.

Example:

- Process P1 requests Resource R1 and R2.
- If R2 is not available within 5 seconds, P1 releases R1 and retries after a cooldown period.

Benefits:

- Suitable for real-time systems where processes need guaranteed resource availability.
- Reduces the chances of deadlock.

Drawbacks:

- Inefficient in systems with frequent contention for resources.
- Timeouts need to be carefully calibrated to avoid excessive process restarts.

Minimize Resource Holding: Release Resources Early

Minimizing resource holding involves releasing resources as soon as they are no longer needed, reducing the duration a process holds onto resources.

How it Works:

- Processes release resources immediately after completing their task instead of holding them until process termination.
- The system encourages processes to break tasks into smaller phases, each requiring fewer resources.

Example:

A file editing software locks a file for editing but releases the lock as soon as the edit is saved rather than keeping it locked until the entire session ends.

Benefits:

- Reduces the likelihood of deadlock.
- Increases resource availability for other processes.

Drawbacks:

- May require frequent lock and unlock operations, increasing overhead.
- Difficult to manage in complex systems with interdependent tasks.

Deadlock prevention is crucial for ensuring smooth and efficient system operation in concurrent environments. Techniques such as lock hierarchies, resource allocation limits, timeout mechanisms, and minimizing resource holding help in effectively managing resource allocation and preventing deadlocks. Each method has its advantages and limitations, and the choice of strategy often depends on the specific requirements of the system. A combination of these techniques can significantly improve the reliability and performance of modern operating systems and multi-threaded applications.

Summary of Deadlock Management Strategies

Summary of Deadlock Management Strategies

Approach	Method	Pros	Cons
Prevention	Break one Coffman's condition	Prevents deadlock entirely	Reduces resource efficiency
Avoidance	Banker's Algorithm	Prevents deadlocks dynamically	Needs advance resource knowledge
Detection & Recovery	Detect and recover post-deadlock	Handles deadlocks afterward	Complex, risk of data loss
Ignorance	Ostrich Algorithm	Simplifies system design	Risk of system failure

Deadlocks can disrupt system operations and must be managed effectively. Techniques such as prevention, avoidance, detection, and recovery help mitigate deadlock risks. Implementing proper resource management strategies ensures both efficiency and reliability in concurrent systems.

4.4 SUMMARY

Process synchronization is a crucial aspect of operating system design that ensures the orderly execution of processes when they access shared resources. It aims to prevent conflicts and ensure data integrity in a concurrent execution environment.

Concurrency and the Need for Synchronization

Concurrency occurs when multiple processes execute simultaneously, either on single-core or multi-core processors. While concurrency enhances system efficiency and resource utilization, it introduces challenges related to data consistency and coordination between processes. If multiple processes try to access or modify shared resources (e.g., files, memory) simultaneously without proper synchronization, race conditions can occur, leading to unpredictable results and data corruption.

Process synchronization is necessary to avoid these issues by coordinating the execution of concurrent processes. It ensures that only one process accesses a shared resource at a time or that multiple processes access resources safely without conflicts. This coordination maintains data consistency and prevents errors in critical operations like banking transactions, ticket booking systems, and industrial automation.

Semaphores, Mutexes, and Condition Variables

To manage synchronization effectively, operating systems provide synchronization tools such as semaphores, mutexes, and condition variables.

Semaphores:

- A semaphore is a synchronization primitive used to control access to a resource.
- It is an integer variable with two atomic operations: wait (P) and signal (V).
- When a process executes a wait(), it checks if the resource is available (semaphore > 0). If available, it decrements the semaphore. If not, the process is blocked.
- The signal() operation increments the semaphore and wakes up a waiting process if one exists.

Mutexes (Mutual Exclusion Locks):

- A mutex is a simpler synchronization tool specifically designed to allow only one process to access a resource at a time.
- It ensures mutual exclusion by allowing a process to lock a resource before accessing it and unlocking it once done.
- Mutexes are commonly used in critical sections where only one process can modify shared data at a time.

Condition Variables:

- Condition variables work alongside mutexes to allow processes to wait for a specific condition before continuing execution.
- A process can wait on a condition variable, which blocks the process until another process signals that the condition has been met.
- They are useful for situations where a process must wait for a shared resource to become available or for a certain condition to be true before proceeding.

These synchronization mechanisms are essential for preventing race conditions and ensuring safe interaction among concurrent processes.

Deadlocks and Deadlock Prevention

A deadlock occurs when a group of processes becomes permanently blocked while waiting for resources held by each other, forming a circular waiting chain. Deadlocks prevent further progress in the system and can cause severe performance issues or complete system failure.

Necessary Conditions for Deadlock (Coffman's Conditions):

A deadlock can occur if all four of these conditions hold simultaneously:

1. Mutual Exclusion: At least one resource is non-shareable and can only be used by one process at a time.
2. Hold and Wait: A process holding a resource can request additional resources while holding its current ones.
3. No Preemption: Resources cannot be forcibly taken from a process; they must be released voluntarily.
4. Circular Wait: A circular chain exists where each process holds a resource and waits for a resource held by the next process.

Deadlock Prevention Techniques:

Deadlock prevention aims to break one of the necessary conditions to avoid deadlocks:

1. Eliminate Mutual Exclusion: Make resources sharable where possible (e.g., read-only files).
2. Avoid Hold and Wait: Require processes to request all needed resources at once, preventing partial resource allocation.
3. Allow Preemption: Enable the OS to forcibly take resources from a process if necessary.
4. Break Circular Wait: Impose a total ordering on resource acquisition, ensuring resources are requested in a fixed sequence.

Conclusion

Process synchronization is essential for managing concurrent processes in modern operating systems. By ensuring that processes coordinate their access to shared resources using tools like semaphores, mutexes, and condition variables, synchronization prevents data inconsistencies and race conditions. However, challenges like deadlocks must also be addressed through careful prevention strategies to maintain system stability and efficiency. Proper synchronization ensures reliable process execution, making it a fundamental aspect of operating system design.

Review Question

Fill in the Blanks.

Choose an appropriate term.

Concurrency	Semaphore	Deadlock	Mutex	Registers

Questions:

1. A _____ is a type of lock that allows only one process to access a resource at a time.
2. A _____ is a synchronization tool using an integer variable to manage resource access.
3. A condition where processes are waiting for each other indefinitely is called _____.
4. The fastest memory in the hierarchy used directly by the CPU is called _____.
5. In process synchronization, _____ refers to the simultaneous execution of processes.

Matching Puzzle (Column A & Column B)

Questions:

Semaphore		A synchronization tool for waiting on specific conditions.
Mutex		A circular wait where processes block indefinitely.
Deadlock		A region where shared data is accessed.
Condition Variable		A lock that restricts access to one process only.
Critical Section		A counter used for managing multiple access to a resource.

Anagram Puzzle (Rearrange the Letters)

Questions:

Letter	**Appropriate keyword (after rearrange)**
CADKEDOL	
NEZROTIACSYHNON	
PEMASHORE	