

SEGi Student Clubs and Societies Database

BCL1223 Database Fundamentals — Continuous Assessment (40%)

Student Name: Chan Jing Yi

Student ID: SUOL2500321

Programme: Bachelor of Information Technology (Hons) / Bachelor of Computer Science

Submission Date: 25 July 2026

Report Date: 18 July 2026

Executive Summary

The Student Affairs Department requires a database that can coordinate club membership, faculty approval, advisors, elected presidents, venues and activities across academic semesters. The design developed in this report separates persistent objects from operational relationships: students and clubs are independent entities, while the date on which a student joins a club belongs to the `MEMBERSHIP` relationship. Event registration is modelled separately from club membership because attending an activity and belonging to its organising club represent different facts.

The implemented Oracle schema contains eleven normalized relations, 10 faculties, 30 students, 15 clubs, 50 memberships, 15 presidents, 10 venues, 45 events and 30 event registrations. Referential constraints enforce two rules that are easily lost in a purely diagrammatic design. A club president must already be a member of that club, and a student cannot register for an event unless the student belongs to the club that runs it. The complete script was executed twice on Oracle AI Database 26ai Free, version 23.26.2.0.0. Every object and row was recreated successfully; six deliberate invalid transactions were rejected, and all required queries returned meaningful results.

Contents

1. Task 1 — Database Design
 2. Task 2 — Data Definition and Population
 3. Task 3 — Data Manipulation and Queries
 4. Task 4 — Demonstration Guide
 5. References
 6. Appendices
-

Task 1 — Database Design (40 Marks)

1.1 Requirements Interpretation

The case study contains several facts whose location is not explicit in the supplied data list. The registration date cannot be an attribute of `STUDENT`, because the same student may join several clubs on different dates. It also cannot be an attribute of `CLUB`, because different members join one club on different dates. The attribute is therefore stored in the associative entity `MEMBERSHIP`, which resolves the many-to-many relationship between students and clubs.

The event requirements imply two further entities. `SEMESTER` gives stable labels and date boundaries for cross-semester reporting. `EVENT_REGISTRATION` records students who sign up for events. Without that relation, the rule in Task 3 Question 6—every event registrant must be assigned to a club—cannot be represented or tested. This decomposition follows the relational design principle that each relation should describe one entity or one relationship, with non-key attributes dependent on its key (Elmasri & Navathe, 2016).

The supplied club examples were expanded to 15 credible student organisations. Names were informed by the active SEGi College Petaling Jaya clubs and societies page, while the database remains a fictional assessment dataset rather than a copy of operational college records (SEGi College Petaling Jaya, n.d.).

1.2 Entity Relationships and Multiplicities

Table 1. Relationship summary

First entity	Multiplicity	Relationship	Second entity	Multiplicity	Business interpretation
<code>FACULTY</code>	1	has	<code>STUDENT</code>	0..*	A faculty may have many students; each student belongs to exactly one faculty.
<code>STUDENT</code>	1	holds	<code>MEMBERSHIP</code>	1..*	A participating student has one or more memberships; every membership belongs to one student.
<code>CLUB</code>	1	receives	<code>MEMBERSHIP</code>	1..*	A club contains one or more members; every membership refers to one club.
<code>ADVISOR</code>	1	advises	<code>CLUB</code>	0..*	An advisor may handle several clubs; each club has exactly one advisor.
<code>MEMBERSHIP</code>	1	qualifies	<code>CLUB_PRESIDENT</code>	0..1	A president appointment must use a valid membership; most memberships are not presidencies.
<code>CLUB</code>	1	elects	<code>CLUB_PRESIDENT</code>	1	Each club has one current president; a presidency belongs to one club.
<code>VENUE_PIC</code>	1	manages	<code>VENUE</code>	1..*	A person in charge may manage venues; each venue has exactly one PIC.

First entity	Multiplicity	Relationship	Second entity	Multiplicity	Business interpretation
CLUB	1	organises	EVENT	1..*	A club runs one or more events; every event belongs to one club.
VENUE	1	hosts	EVENT	0..*	A venue may host many events; each event uses one venue.
SEMESTER	1	schedules	EVENT	0..*	A semester contains events; each event occurs in one semester.
CLUB_PRESIDENT	1	oversees	EVENT	1..*	The elected president oversees the club's events.
EVENT	1	receives	EVENT_REGISTRATION	0..*	An event may receive many registrations; each registration is for one event.
MEMBERSHIP	1	permits	EVENT_REGISTRATION	0..*	Only a member of the organising club may register for its event.

The phrase “one advisor can handle one or more clubs” defines an advisor’s possible workload, but it does not require every lecturer in the advisor master table to be assigned immediately. The physical model therefore permits zero clubs on the advisor side and requires one advisor on the club side. Minimum child counts such as “each club runs at least one event” cannot be guaranteed by a foreign key alone; the dataset and audit query establish three events per club, one in each modelled semester.

1.3 Normalization Rationale

The unstructured requirement list contains repeating groups: a student may list several clubs, an advisor may list several assigned clubs, and a club may list many events. Storing these values in single columns would violate first normal form because the values would not be atomic. Creating `MEMBERSHIP`, `EVENT` and `EVENT_REGISTRATION` gives each occurrence its own row.

The composite-key relations satisfy second normal form. In `MEMBERSHIP`, `date_registered` and `membership_status` describe the complete pair `(club_id, student_id)` rather than only one part. In `EVENT_REGISTRATION`, the registration date and attendance status describe the student’s registration for a particular event. Advisor details are not repeated in `CLUB`; venue PIC details are not repeated in `VENUE`; faculty names are not repeated in `STUDENT`. These separations remove transitive dependencies and place the design in third normal form.

Two purposeful key copies appear in `EVENT_REGISTRATION`: `club_id` accompanies `event_id`, and the same `club_id` accompanies `student_id`. This value is not an uncontrolled duplicate. It enables two composite foreign keys to prove that the selected event belongs to the club and that the selected student is a member of that same club. The design trades one constrained key copy for enforceable cross-relationship integrity.

1.4 Data Dictionary

Oracle's relational tables are defined with `CREATE TABLE`; enabled primary-key, unique, foreign-key and check constraints cause invalid changes to fail rather than allowing contradictory data (Oracle, 2026a). The lengths below reflect identifiers and values required by the case study while retaining room for realistic names and notes.

Table 2. Final database data dictionary

Entity	Attribute	Oracle data type	Key / constraint	Null rule and purpose
FACULTY	faculty_id	VARCHAR2 (6)	PK	Not null; stable faculty identifier.
	faculty_name	VARCHAR2 (100)	UNIQUE	Not null; official faculty name.
STUDENT	student_id	VARCHAR2 (6)	PK, CHECK	Not null; exactly two letters followed by four digits.
	student_name	VARCHAR2 (100)	—	Not null; full name.
	phone_number	VARCHAR2 (20)	UNIQUE	Not null; contact number.
	faculty_id	VARCHAR2 (6)	FK → FACULTY	Not null; owning faculty.
	approval_form	CHAR (1)	CHECK Y/N	Not null, default N; faculty approval received.
	scholarship	CHAR (1)	CHECK Y/N	Not null, default N; scholarship indicator.
ADVISOR	advisor_id	VARCHAR2 (6)	PK	Not null; lecturer identifier.
	advisor_name	VARCHAR2 (100)	—	Not null; lecturer name.
	office_room	VARCHAR2 (10)	—	Not null; room such as R2.1.
	office_phone	VARCHAR2 (20)	UNIQUE	Not null; internal contact number.
CLUB	club_id	VARCHAR2 (6)	PK	Not null; club identifier.
	club_name	VARCHAR2 (100)	UNIQUE	Not null; club name.
	advisor_id	VARCHAR2 (6)	FK → ADVISOR	Not null; assigned advisor.
	club_notes	VARCHAR2 (500)	—	Nullable; purpose or administrative notes.
MEMBERSHIP	club_id	VARCHAR2 (6)	PK, FK → CLUB	Not null; membership's club.
	student_id	VARCHAR2 (6)	PK, FK → STUDENT	Not null; membership's student.

Entity	Attribute	Oracle data type	Key / constraint	Null rule and purpose
	date_registered	DATE	DEFAULT	Not null; date the student joined this club.
	membership_status	VARCHAR2 (10)	CHECK	Not null; ACTIVE or INACTIVE.
CLUB_PRESIDENT	club_id	VARCHAR2 (6)	PK, composite FK	Not null; exactly one current president row per club.
	student_id	VARCHAR2 (6)	Composite FK → MEMBERSHIP	Not null; elected student must be a club member.
	appointment_date	DATE	—	Not null; election or appointment date.
VENUE_PIC	pic_id	VARCHAR2 (6)	PK	Not null; PIC identifier.
	pic_name	VARCHAR2 (100)	—	Not null; PIC name.
	phone_number	VARCHAR2 (20)	UNIQUE	Not null; PIC contact number.
	office_room	VARCHAR2 (10)	—	Not null; PIC office location.
VENUE	venue_id	VARCHAR2 (6)	PK	Not null; room/hall identifier.
	venue_name	VARCHAR2 (100)	UNIQUE	Not null; display name.
	venue_type	VARCHAR2 (30)	CHECK	Not null; classroom, laboratory, hall, studio or outdoor.
	capacity	NUMBER (4)	CHECK > 0	Not null; safe planning capacity.
	pic_id	VARCHAR2 (6)	FK → VENUE_PIC	Not null; responsible PIC.
SEMESTER	semester_id	VARCHAR2 (8)	PK	Not null; semester identifier.
	semester_name	VARCHAR2 (30)	UNIQUE	Not null; report heading.
	start_date	DATE	CHECK pair	Not null; semester opening date.
	end_date	DATE	CHECK pair	Not null; later than start_date.
EVENT	event_id	VARCHAR2 (8)	PK	Not null; event number.
	club_id	VARCHAR2 (6)	FK → CLUB	Not null; organising club.
	venue_id	VARCHAR2 (6)	FK → VENUE	Not null; booked venue.
	semester_id	VARCHAR2 (8)	FK → SEMESTER	Not null; reporting semester.

Entity	Attribute	Oracle data type	Key / constraint	Null rule and purpose
	president_student_id	VARCHAR2 (6)	Composite FK → CLUB_PRESIDENT	Not null; president responsible for the event.
	activity_name	VARCHAR2 (150)	—	Not null; activity title.
	event_date	DATE	—	Not null; required by Task 3 Question 4.
EVENT_REGISTRATION	event_id	VARCHAR2 (8)	PK, composite FK → EVENT	Not null; selected event.
	club_id	VARCHAR2 (6)	Composite FK	Not null; common club linking event and member.
	student_id	VARCHAR2 (6)	PK, composite FK → MEMBERSHIP	Not null; registered club member.
	registration_date	DATE	DEFAULT	Not null; sign-up date.
	attendance_status	VARCHAR2 (10)	CHECK	Not null; REGISTERED, ATTENDED or ABSENT.

1.5 Complete Entity–Relationship Diagram




Figure 1. Complete logical ERD in Crow's Foot notation. The two associative entities resolve the student–club and student–event many-to-many relationships. `CLUB_PRESIDENT` makes the election rule visible and enforceable rather than leaving “president” as an unverified text field.

Task 2 — Data Definition Language (30 Marks)

2.1 Oracle Schema and Constraints (15 Marks)

The database schema was implemented in Oracle using named primary-key, foreign-key, unique, check and not-null constraints. Naming each constraint allows an Oracle error to be traced to the business rule that rejected the operation. The following extract shows the two most consequential junction structures.

```
CREATE TABLE membership (
  club_id          VARCHAR2(6),
  student_id       VARCHAR2(6),
  date_registered  DATE DEFAULT SYSDATE NOT NULL,
  membership_status VARCHAR2(10) DEFAULT 'ACTIVE' NOT NULL,
  CONSTRAINT pk_membership PRIMARY KEY (club_id, student_id),
  CONSTRAINT fk_membership_club FOREIGN KEY (club_id)
    REFERENCES club (club_id) ON DELETE CASCADE,
  CONSTRAINT fk_membership_student FOREIGN KEY (student_id)
    REFERENCES student (student_id) ON DELETE CASCADE,
  CONSTRAINT ck_membership_status
    CHECK (membership_status IN ('ACTIVE', 'INACTIVE'))
);

CREATE TABLE event_registration (
  event_id          VARCHAR2(8),
  club_id           VARCHAR2(6),
  student_id        VARCHAR2(6),
  registration_date  DATE DEFAULT SYSDATE NOT NULL,
  attendance_status VARCHAR2(10) DEFAULT 'REGISTERED' NOT NULL,
  CONSTRAINT pk_event_registration PRIMARY KEY (event_id, student_id),
  CONSTRAINT fk_registration_event FOREIGN KEY (event_id, club_id)
    REFERENCES event (event_id, club_id) ON DELETE CASCADE,
  CONSTRAINT fk_registration_member FOREIGN KEY (club_id, student_id)
    REFERENCES membership (club_id, student_id),
  CONSTRAINT ck_attendance_status
    CHECK (attendance_status IN ('REGISTERED', 'ATTENDED', 'ABSENT'))
);
```

Oracle applies enabled constraints to subsequent data changes. A primary key combines uniqueness with a non-null requirement, a foreign key requires a matching parent key, and a check constraint evaluates a stated domain condition (Oracle, 2026a). `ON DELETE CASCADE` is restricted to dependent records whose meaning disappears with the parent—memberships when a club or student is deleted, and registrations when an event is deleted. Master records such as advisors, venues and semesters use Oracle’s default restrictive behaviour so that referenced history cannot be removed accidentally.

Eight explicit indexes support foreign-key joins and integrity checks. Primary-key and unique constraints already create their own supporting indexes, so duplicating those indexes would waste storage without improving the model.

2.2 Data Population (15 Marks)

`INSERT ALL` statements keep the seed data readable while inserting independent, realistic rows. Operational tables exceed ten rows; `SEMESTER` contains three rows because only three consecutive teaching periods are required for the requested cross-tab report.

Table 3. Live Oracle row-count evidence

Table	Rows	Table	Rows
<code>FACULTY</code>	10	<code>ADVISOR</code>	10
<code>VENUE_PIC</code>	10	<code>SEMESTER</code>	3
<code>STUDENT</code>	30	<code>CLUB</code>	15
<code>VENUE</code>	10	<code>MEMBERSHIP</code>	50
<code>CLUB_PRESIDENT</code>	15	<code>EVENT</code>	45
<code>EVENT_REGISTRATION</code>	30	Total	228

Each club has exactly three events—one in May–August 2026, one in September–December 2026 and one in January–April 2027. The integrity audit returned zero event registrations without a matching club membership.

```
Oracle AI Database 26ai Free Release 23.26.2.0.0
INVALID_EVENT_REGISTRATIONS
-----
                                0
EVENTS_OUTSIDE_SEMESTER
-----
                                0
```

Constraint Rejection Evidence

The script attempts six invalid changes inside recoverable savepoints. A successful test means Oracle rejected the change and preserved the valid dataset.

```
PASS - malformed student ID rejected (-2290)
PASS - invalid approval status rejected (-2290)
PASS - duplicate club membership rejected (-1)
PASS - club with missing advisor rejected (-2291)
PASS - president who is not a member of the club rejected (-2291)
PASS - event registration by a non-member rejected (-2291)
```

This evidence distinguishes declared rules from working rules. The composite foreign key on `CLUB_PRESIDENT` rejects a president outside the club, while the pair of registration foreign keys rejects a student who belongs to another club but not to the event's organiser.

Task 3 — Data Manipulation Language and Queries (30 Marks)

Oracle `SELECT` statements use joins to reconstruct related facts from normalized tables. Column aliases give report-friendly headings, while `ORDER BY`, grouping and `PIVOT` shape each result for its operational user (Oracle, 2026b).

3.1 Student Phone List (5 Marks)

```
SELECT DISTINCT s.student_id, s.student_name, s.phone_number
FROM student s
JOIN membership m ON m.student_id = s.student_id
ORDER BY s.student_name;
```

The inner join excludes students who have never enrolled in a club. `DISTINCT` prevents a student with several memberships from appearing repeatedly, and alphabetical ordering supports quick lookup.

Table 4. Verified phone-list result (30 rows)

Student ID	Student name	Phone	Student ID	Student name	Phone
aa1001	Adam Abdullah	012-810-1001	pp1016	Pravin Prakash	012-810-1016
aa1027	Amirul Anwar	012-810-1027	qq1017	Qistina Qamar	012-810-1017
bb1028	Bella Bahar	012-810-1028	rr1018	Rachel Raj	012-810-1018
bb1002	Brenda Balan	012-810-1002	ss1019	Syafiq Salleh	012-810-1019
cc1029	Caleb Chan	012-810-1029	tt1020	Tan Tze Wei	012-810-1020
cc1003	Chong Cai Wen	012-810-1003	uu1021	Umair Usman	012-810-1021
dd1004	Devi Krishnan	012-810-1004	vv1022	Vanessa Voon	012-810-1022
dd1030	Diyana Daud	012-810-1030	ww1023	Wong Wai Kit	012-810-1023
ee1005	Ethan Elias	012-810-1005	xx1024	Xavier Xian	012-810-1024
ff1006	Farah Faisal	012-810-1006	yy1025	Yasmin Yusof	012-810-1025
gg1007	Gan Hui Min	012-810-1007	zz1026	Zara Zainal	012-810-1026
hh1008	Harith Hakim	012-810-1008	ii1009	Irene Ismail	012-810-1009
jj1010	Jason Jamil	012-810-1010	kk1011	Kavitha Kumar	012-810-1011
ll1012	Lee Li Ann	012-810-1012	mm1013	Muhammad Malik	012-810-1013
nn1014	Nur Nabila	012-810-1014	oo1015	Ong Ooi Wei	012-810-1015

3.2 Advisors Assigned to More Than One Club (5 Marks)

```
SELECT a.advisor_id,
       a.advisor_name,
       COUNT(c.club_id) AS number_of_clubs,
       LISTAGG(c.club_name, ';' ' ')
         WITHIN GROUP (ORDER BY c.club_name) AS assigned_clubs
FROM advisor a
JOIN club c ON c.advisor_id = a.advisor_id
GROUP BY a.advisor_id, a.advisor_name
HAVING COUNT(c.club_id) > 1
ORDER BY a.advisor_name;
```

`GROUP BY` produces one workload group per advisor. `HAVING` is evaluated after the count and retains only workloads above one club; `LISTAGG` preserves the club identities that a count alone would hide.

Table 5. Verified multi-club advisor result

Advisor	Number of clubs	Assigned clubs
Dr. Aisha Rahman	3	Cybersecurity Club; Information Technology Club; Robotics Club
Dr. Kelvin Wong	2	Accounting Club; Photography Club
Mr. Daniel Lee	2	Dance Club; Debate Club
Ms. Nur Izzati	2	Entrepreneurship Club; Music Club

3.3 Missing Faculty Approval Forms (5 Marks)

```
SELECT s.student_id,
       s.student_name,
       s.phone_number,
       'Faculty Approval Form' AS missing_form
FROM student s
WHERE s.approval_form = 'N'
      AND EXISTS (
        SELECT 1 FROM membership m WHERE m.student_id = s.student_id
      )
ORDER BY s.student_name;
```

The correlated `EXISTS` condition limits the calling list to students who have actually joined a club. The constant output column identifies the required document rather than forcing staff to infer it from a one-character flag.

Table 6. Verified missing-form result

Student ID	Student name	Phone	Missing form
cc1029	Caleb Chan	012-810-1029	Faculty Approval Form
cc1003	Chong Cai Wen	012-810-1003	Faculty Approval Form
ee1005	Ethan Elias	012-810-1005	Faculty Approval Form

Student ID	Student name	Phone	Missing form
hh1008	Harith Hakim	012-810-1008	Faculty Approval Form
kk1011	Kavitha Kumar	012-810-1011	Faculty Approval Form
nn1014	Nur Nabila	012-810-1014	Faculty Approval Form
qq1017	Qistina Qamar	012-810-1017	Faculty Approval Form
tt1020	Tan Tze Wei	012-810-1020	Faculty Approval Form
ww1023	Wong Wai Kit	012-810-1023	Faculty Approval Form
zz1026	Zara Zainal	012-810-1026	Faculty Approval Form

3.4 Advisor, Club and Event Schedule (5 Marks)

```

SELECT a.advisor_name,
       c.club_name,
       e.activity_name,
       s.semester_name,
       TO_CHAR(e.event_date, 'DD-MON-YYYY') AS event_date
FROM advisor a
JOIN club c ON c.advisor_id = a.advisor_id
JOIN event e ON e.club_id = c.club_id
JOIN semester s ON s.semester_id = e.semester_id
ORDER BY a.advisor_name, e.event_date, c.club_name;

```

The four-table join produces 45 verified schedule rows. Table 7 compresses those rows by club while retaining every event and date; the uncompressed Oracle result remains in the accompanying output file.

Table 7. Verified advisor and three-semester event schedule

Advisor	Club	May–Aug 2026	Sep–Dec 2026	Jan–Apr 2027
Dr. Aisha Rahman	Information Technology	Python Coding Clinic — 06-Jun	Web Application Hackathon — 12-Sep	Database Design Sprint — 16-Jan
Dr. Aisha Rahman	Robotics	Line-Following Robot Lab — 20-Jun	Drone Navigation Challenge — 10-Oct	Robotics Open Day — 13-Feb
Dr. Aisha Rahman	Cybersecurity	Phishing Defence Workshop — 18-Jul	Capture-the-Flag Practice — 05-Dec	Secure Coding Clinic — 10-Apr
Dr. Kelvin Wong	Accounting	Budgeting Challenge — 14-Jun	Tax Literacy Seminar — 03-Oct	Investment Case Competition — 06-Feb
Dr. Kelvin Wong	Photography	Portrait Photography Lab — 28-Jun	Night Photography Walk — 31-Oct	Documentary Photo Exhibition — 06-Mar
Mr. Daniel Lee	Dance	Cultural Dance Workshop — 07-Jun	Contemporary Dance Clinic — 19-Sep	Traditional Dance Exchange — 23-Jan
Mr. Daniel Lee	Debate	Interfaculty Debate — 21-Jun	Public Speaking Bootcamp — 17-Oct	Policy Debate Finals — 20-Feb
Ms. Nur Izzati	Music	Campus Music Showcase — 13-Jun	Acoustic Night — 26-Sep	Battle of the Bands — 30-Jan

Advisor	Club	May–Aug 2026	Sep–Dec 2026	Jan–Apr 2027
Ms. Nur Izzati	Entrepreneurship	Student Startup Pitch — 27-Jun	Social Enterprise Forum — 24-Oct	Business Model Workshop — 27-Feb
Ms. Priya Nair	Environmental	Campus Recycling Drive — 04-Jul	Tree Planting Day — 07-Nov	Earth Hour Campaign — 13-Mar
Mr. Hafiz Osman	Sports	Interclub Sports Day — 05-Jul	Wellness Fun Run — 14-Nov	Campus Badminton Open — 20-Mar
Dr. Siti Hamidah	Volunteer	Community Care Packing — 11-Jul	Food Bank Collection — 21-Nov	Volunteer Leadership Forum — 27-Mar
Mr. Marcus Tan	Drama	One-Act Play Festival — 12-Jul	Stagecraft Workshop — 28-Nov	Student Theatre Premiere — 03-Apr
Ms. Joanne Lim	Culinary	Malaysian Cuisine Workshop — 19-Jul	Healthy Baking Lab — 12-Dec	Sustainable Cooking Challenge — 17-Apr
Dr. Farid Iskandar	Chess	Rapid Chess Tournament — 25-Jul	Team Chess League — 19-Dec	Intercollege Chess Cup — 24-Apr

3.5 Events per Advisor and Semester (5 Marks)

The first sentence of the question asks how many clubs each advisor handles, but its required cell definition asks for the number of events. The query follows the explicit cell definition and counts events. Oracle's `PIVOT` clause rotates semester values into columns, matching the requested spreadsheet layout (Oracle, 2026b).

```

SELECT advisor_name,
       NVL(may_aug_2026, 0) AS may_aug_2026,
       NVL(sep_dec_2026, 0) AS sep_dec_2026,
       NVL(jan_apr_2027, 0) AS jan_apr_2027
FROM (
    SELECT a.advisor_name, s.semester_name, e.event_id
    FROM advisor a
    LEFT JOIN club c ON c.advisor_id = a.advisor_id
    LEFT JOIN event e ON e.club_id = c.club_id
    LEFT JOIN semester s ON s.semester_id = e.semester_id
)
PIVOT (
    COUNT(event_id)
    FOR semester_name IN (
        'May-Aug 2026' AS may_aug_2026,
        'Sep-Dec 2026' AS sep_dec_2026,
        'Jan-Apr 2027' AS jan_apr_2027
    )
)
ORDER BY advisor_name;

```

Table 8. Verified Oracle pivot result

Advisor	May–Aug 2026	Sep–Dec 2026	Jan–Apr 2027
Dr. Aisha Rahman	3	3	3
Dr. Farid Iskandar	1	1	1

Advisor	May–Aug 2026	Sep–Dec 2026	Jan–Apr 2027
Dr. Kelvin Wong	2	2	2
Dr. Siti Hamidah	1	1	1
Mr. Daniel Lee	2	2	2
Mr. Hafiz Osman	1	1	1
Mr. Marcus Tan	1	1	1
Ms. Joanne Lim	1	1	1
Ms. Nur Izzati	2	2	2
Ms. Priya Nair	1	1	1
Column total	15	15	15

The 15-event total in every semester reconciles with the 45 rows stored in `EVENT`.

3.6 Clubs and Their Assigned Students (5 Marks)

```
SELECT c.club_name,
       s.student_id,
       s.student_name,
       TO_CHAR(m.date_registered, 'DD-MON-YYYY') AS date_registered
FROM club c
JOIN membership m ON m.club_id = c.club_id
JOIN student s ON s.student_id = m.student_id
WHERE m.membership_status = 'ACTIVE'
ORDER BY c.club_name, s.student_name;
```

The query uses `MEMBERSHIP` as the authoritative club assignment. The database separately checks every event registration against that table; the orphan audit returned zero.

Table 9. Verified club assignments (50 membership rows summarized)

Club	Assigned students
Accounting	Amirul Anwar; Devi Krishnan; Yasmin Yusof; Zara Zainal
Chess	Ong Ooi Wei; Tan Tze Wei; Umair Usman
Culinary	Nur Nabila; Rachel Raj; Syafiq Salleh
Cybersecurity	Muhammad Malik; Pravin Prakash; Qistina Qamar
Dance	Brenda Balan; Syafiq Salleh; Tan Tze Wei; Umair Usman
Debate	Adam Abdullah; Brenda Balan; Farah Faisal
Drama	Lee Li Ann; Nur Nabila; Ong Ooi Wei
Entrepreneurship	Chong Cai Wen; Devi Krishnan; Gan Hui Min
Environmental	Gan Hui Min; Harith Hakim; Irene Ismail

Club	Assigned students
Information Technology	Adam Abdullah; Pravin Prakash; Qistina Qamar; Rachel Raj
Music	Chong Cai Wen; Vanessa Voon; Wong Wai Kit; Xavier Xian
Photography	Ethan Elias; Farah Faisal; Harith Hakim
Robotics	Bella Bahar; Caleb Chan; Diyana Daud; Ethan Elias
Sports	Irene Ismail; Jason Jamil; Kavitha Kumar
Volunteer	Kavitha Kumar; Lee Li Ann; Muhammad Malik

Task 4 — Demonstration Guide

During the Week 11 demonstration, the completed report and the populated Oracle database should be open and ready for inspection. The demonstration can proceed in four short stages: show the ERD and explain the two junction tables; inspect the named constraints; show the row counts and rejection-test passes; run Tasks 3.2, 3.3 and 3.5 as representative join, correlated-subquery and pivot queries. This sequence connects the conceptual model to its physical implementation and then to the reports required by Student Affairs.

References

Elmasri, R., & Navathe, S. B. (2016). *Fundamentals of database systems* (7th ed.). Pearson. <https://www.pearson.com/en-us/subject-catalog/p/Elmasri-Fundamentals-of-Database-Systems-7th-Edition/P2000000003546/9780133970777>

Oracle. (2026a). *CREATE TABLE*. Oracle AI Database SQL Language Reference. <https://docs.oracle.com/en/database/oracle/oracle-database/26/sqlrf/CREATE-TABLE.html>

Oracle. (2026b). *SELECT*. Oracle AI Database SQL Language Reference. <https://docs.oracle.com/en/database/oracle/oracle-database/26/sqlrf/SELECT.html>

SEGi College Petaling Jaya. (n.d.). *Student clubs & societies*. <https://colleges.segi.edu.my/petalingjaya/student-clubs-societies/>

Appendices

Appendix A — Verification Statement

The SQL script was executed repeatedly from an empty student schema on Oracle AI Database 26ai Free 23.26.2.0.0 on 18 July 2026. The repeated execution proved that the cleanup blocks and rebuild sequence are rerunnable. Eleven tables, eight explicit foreign-key indexes and 228 seed rows were created. All six rejection tests passed, all clubs returned three events, the event-registration orphan count was zero, every event date fell within its referenced semester, and the six assessment queries completed without Oracle errors.