

ASDAN 商业竞赛项目 API 设计

Tomato 小组

2017 年 10 月 18 日

Contents

1	Client API Endpoints	2
1.1	Get Property	2
1.2	Get Information	3
1.3	Update Information	4
1.4	Get History	5
2	Admin API Endpoints	6
2.1	Get All Competitions	6
2.2	Create Competition	7
2.3	Delete Competition By ID	8
2.4	Update Competition Status	9
2.5	Generate Accounts	9
2.6	Get Competition Property	10
2.7	Update Competition Property	11
2.8	Get Competition Information	13
2.9	Update Competition Information	15
3	Administrative Endpoints	18
3.1	Login Admin	18
3.2	Login Client	18
4	Utility Endpoints	19

1. Client API Endpoints: 为特定用户提供相关信息。
2. Admin API Endpoints: 为管理员提供相关信息。
3. Administrative Endpoints: 登录和交易时使用。
4. Utility Endpoints: 询问系统相关信息。

1 Client API Endpoints

为特定用户提供相关信息。

1.1 Get Property

输入 ID，获得与这一 ID 相关的用户的全部信息。用户有默认头像。如果比赛还没有开始，则 rank 为 0。

TO-DO: 用户自己设置头像。TO-DO: 三个用户同时登录。

Request

```
GET /api/client/property/id={id}
```

```
Host: localhost:8080
```

```
Auth:
```

```
Content-type: application/json
```

```
Accept: application/json
```

Returns

```
HTTP 200 OK
```

```
{
  "name": "team1",
  "image": "/9j/4QAYRXhpZg ...",
  "members": ["member11", "member12"],
  "wealth": 100,
  "rank": 1
}
```

Error

```
HTTP 404 NOT FOUND
```

1.2 Get Information

输入 ID，获得与这一 ID 相关的用户的信息。包括机器的使用情况和材料的价格。

Request

```
GET /api/client/info/id={id}

Host: localhost:8080
Auth:
Content-type: application/json
Accept: application/json
```

Returns

```
HTTP 200 OK

{
  "name": "team1",
  "wealth": 100,
  "machine":
  [
    {
      "id": "machine1_id",
      "type": "type1",
      "left": "3"
    },
    {
      "id": "machine2_id",
      "type": "type2",
      "left": "2"
    }
  ],
  "material":
  [
    {
      "price": "10",
      "number": "20",
    },
    {
      "price": "20",
      "number": "0",
    },
    {
      "price": "80",
```

```
        "number": "150",
      }
    ]
  }
}
```

Error

HTTP 404 NOT FOUND

1.3 Update Information

向服务器发送更改过的信息。

Request

PUT /api/client/info/id={id}

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

```
{
  "name": "team1",
  "wealth": 100,
  "machine":
  [
    {
      "id": "machine1_id",
      "left": "3"
    },
    {
      "id": "machine2_id",
      "left": "2"
    }
  ],
  "material":
  [
    {
      "price": "10",
      "number": "20",
    },
    {
      "price": "20",
      "number": "0",
    }
  ]
}
```

```
    },
    {
      "price": "80",
      "number": "150",
    }
  ]
}
```

Returns

HTTP 200 OK

```
{
  "name": "team1",
  "wealth": 100,
  "machine": ["machine1_id", "machine2_id", "machine3_id"],
  "material": ["10", "20", "0"]
}
```

Error

HTTP 404 NOT FOUND

```
{
  "error": "Unable to update. User with id xxx not found."
}
```

1.4 Get History

获取与某一用户相关的历史信息。在发订单的时候客户端手动更新 History。

Request

GET /api/client/history/id={id}

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

Returns

HTTP 200 OK

```
[
  {
    "time": "hh:MM:ss",
  }
]
```

```
    "target": "team1",
    "action": "sell",
    "content": {"material1": 1},
    "price": "10",
    "status": "success",
  },
  {
    "time": "hh:MM:ss",
    "target": "team1",
    "action": "buy",
    "content": {"material1": 1},
    "price": "10",
    "status": "fail",
  }
]
```

Error

HTTP 404 NOT FOUND

2 Admin API Endpoints

2.1 Get All Competitions

列出全部比赛。

Request

GET /api/admin/competition/getall

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

Returns

HTTP 200 OK

```
[
  {
    "id": "competiton1_id",
    "name": "competition1",
    "status": "processing"
  },
]
```

```
{
  "id": "competiton2_id",
  "name": "competition2",
  "status": "end"
}
]
```

Error

HTTP 204 NO CONTENT

2.2 Create Competition

新建一场比赛。注意，底层也要生成机器的 id。

Request

POST /api/admin/competition/new

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

```
{
  "name": "competition_name",
  "round": "2",
  "start_wealth": "1000",
  "round_parameter":
  [
    {
      "machine_start_price": ["300", "350", "400"],
      "material_produce_cost": ["10", "20", "30"],
      "time": "900",
    },
    {
      "machine_start_price": ["300", "350", "400"],
      "material_produce_cost": ["10", "20", "30"],
      "time": "900",
    }
  ]
}
```

Returns

HTTP 201 CREATED

```
{
  "id": "competition_id",
  "name": "competition_name",
  "status": "not started",
  "round": "2",
  "start_wealth": "1000",
  "round_parameter":
  [
    {
      "machine_start_price": ["300", "350", "400"],
      "material_produce_cost": ["10", "20", "30"],
      "time": "900",
    },
    {
      "machine_start_price": ["300", "350", "400"],
      "material_produce_cost": ["10", "20", "30"],
      "time": "900",
    }
  ]
}
```

Error

HTTP 404 NOT FOUND

```
{
  "error": "Unable to delete. Competition with id xxx not found."
}
```

2.3 Delete Competition By ID

通过 ID 删除比赛。

Request

DELETE /api/admin/competiton/id={competition_id}

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

Returns

HTTP 204 NO CONTENT

Error

```
{  
  "error": "Unable to delete. Competition with id xxx not found."  
}
```

2.4 Update Competition Status

更新比赛状态。

Request

```
POST /api/admin/competition/status/id={id}
```

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

```
{  
  "status": "processing"  
}
```

Returns

```
HTTP 200 OK
```

Error

```
HTTP 404 NOT FOUND
```

```
{  
  "error": "Unable to update. Competition with id xxx not found"  
}
```

2.5 Generate Accounts

要求系统生成比赛账户和密码。

Request

```
POST /api/admin/competition/accounts/id={id}?number={number}
```

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

Returns

HTTP 201 CREATED

```
[
  {
    "client_id": "id1",
    "username": "username1",
    "password": "password1",
  },
  {
    "client_id": "id2",
    "username": "username2",
    "password": "password2",
  },
]
```

Error

HTTP 404 NOT FOUND

```
{
  "error": "Competition with id xxxx not found"
}
```

HTTP 409 CONFLICT

```
{
  "error": "Cannot generate accounts for competition with id xxxx"
}
```

2.6 Get Competition Property

从服务器按 id 获取某一比赛的各种属性。如果该比赛的属性尚未被设置，则该项为空。属性包括名称、比赛轮数（如果比赛已开始，则不能删除已开始或结束的轮）、比赛各项参数（不能修改已开始或结束的轮的参数）、机器的 id 等等。

Request

GET /api/admin/competition/property/id={id}

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

Returns

HTTP 200 OK

```
{
  "id": "competition_id",
  "name": "competition_name",
  "status": "not started",
  "round": "2",
  "start_wealth": "1000",
  "round_parameter":
  [
    {
      "machine_start_price": ["300", "350", "400"],
      "machine_id": ["id1", "id2", "id3"],
      "material_produce_cost": ["10", "20", "30"],
      "time": "900",
    },
    {
      "machine_start_price": ["300", "350", "400"],
      "machine_id": ["id1", "id2", "id3"],
      "material_produce_cost": ["10", "20", "30"],
      "time": "900",
    }
  ]
}
```

Error

HTTP 404 NOT FOUND

```
{
  "error": "Competition with id xxx not found."
}
```

2.7 Update Competition Property

更新比赛的各种属性。属性包括名称、比赛轮数（如果比赛已开始，则不能删除已开始或结束的轮）、比赛各项参数（不能修改已开始或结束的轮的参数）。

Request

PUT /api/admin/competition/property/id={id}

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

```

{
  "name": "competition_name",
  "round": "2",
  "start_wealth": "1000",
  "round_parameter":
  [
    {
      "machine_start_price": ["300", "350", "400"],
      "material_produce_cost": ["10", "20", "30"],
      "time": "900",
    },
    {
      "machine_start_price": ["300", "350", "400"],
      "material_produce_cost": ["10", "20", "30"],
      "time": "900",
    }
  ]
}

```

Returns

HTTP 201 CREATED

```

{
  "id": "competition_id",
  "name": "competition_name",
  "round": "2",
  "start_wealth": "1000",
  "round_parameter":
  [
    {
      "machine_start_price": ["300", "350", "400"],
      "material_produce_cost": ["10", "20", "30"],
      "machine_id": ["id1", "id2", "id3"],
      "time": "900",
    },
    {
      "machine_start_price": ["300", "350", "400"],
      "material_produce_cost": ["10", "20", "30"],
      "machine_id": ["id1", "id2", "id3"],
      "time": "900",
    }
  ]
}

```

Error

HTTP 404 NOT FOUND

```
{
  "error": "Competition with id xxx not found."
}
```

HTTP 400 INVALID REQUEST

```
{
  "error": "Cannot update competition id xxx with given changes."
}
```

2.8 Get Competition Information

获取当前比赛信息，包括队伍的数量、资产、交易记录、机器的使用情况等。

Request

GET /api/admin/competition/info/id={id}

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

Returns

HTTP 200 OK

```
{
  "id": "competition_id",
  "name": "competition_name",
  "status": "not started",
  "round": "2",
  "present_round": "0",
  "team_info":
  [
    {
      "id": "id1",
      "wealth": "100",
      "material": ["30", "40", "50"],
      "machine":
      [
        {
          "id": "machine1_id",
          "type": "type1",

```

```

        "left": "3"
    },
    {
        "id": "machine2_id",
        "type": "type2",
        "left": "2"
    }
]
},
{
    "id": "id2",
    "wealth": "100",
    "material": ["30", "40", "50"],
    "machine":
    [
        {
            "id": "machine1_id",
            "type": "type1",
            "left": "3"
        },
        {
            "id": "machine2_id",
            "type": "type2",
            "left": "2"
        }
    ]
}
],
"trade_history":
[
    {
        "time": "hh:MM:ss",
        "sell": "team_id1",
        "buy": "team_id2",
        "content": {"material1": 1},
        "price": "10"
    },
    {
        "time": "hh:MM:ss",
        "sell": "team_id1",
        "buy": "team_id2",
        "content": {"material2": 1},
        "price": "20"
    }
]

```

```
}
```

Error

HTTP 404 NOT FOUND

```
{
  "error": "Competition with id 1 not found."
}
```

2.9 Update Competition Information

向服务器发送对比赛的更新信息。增加机器、分配财产之类的。

Request

PUT /api/admin/competition/info/id={id}

Host: localhost:8080

Auth:

Content-type: application/json

Accept: application/json

```
{
  "round": "2",
  "present_round": "0",
  "team_info":
  [
    {
      "id": "id1",
      "wealth": "100",
      "machine":
      [
        {
          "id": "machine1_id",
          "left": "3"
        },
        {
          "id": "machine2_id",
          "left": "2"
        }
      ]
    },
    {
      "id": "id2",
      "wealth": "100",

```

```

        "machine":
        [
            {
                "id": "machine1_id",
                "left": "3"
            },
            {
                "id": "machine2_id",
                "left": "2"
            }
        ]
    }
}

```

Returns

HTTP 200 OK

```

{
    "id": "competition_id",
    "name": "competition_name",
    "status": "not started",
    "round": "2",
    "present_round": "0",
    "team_info":
    [
        {
            "id": "id1",
            "wealth": "100",
            "material": ["30", "40", "50"],
            "machine":
            [
                {
                    "id": "machine1_id",
                    "type": "type1",
                    "left": "3"
                },
                {
                    "id": "machine2_id",
                    "type": "type2",
                    "left": "2"
                }
            ]
        },
        {

```



```

        "id": "id2",
        "wealth": "100",
        "material": ["30", "40", "50"],
        "machine":
        [
            {
                "id": "machine1_id",
                "type": "type1",
                "left": "3"
            },
            {
                "id": "machine2_id",
                "type": "type2",
                "left": "2"
            }
        ]
    },
    "trade_history":
    [
        {
            "time": "hh:MM:ss",
            "sell": "team_id1",
            "buy": "team_id2",
            "content": {"material1": 1},
            "price": "10"
        },
        {
            "time": "hh:MM:ss",
            "sell": "team_id1",
            "buy": "team_id2",
            "content": {"material2": 1},
            "price": "20"
        }
    ]
}

```

Error

HTTP 404 NOT FOUND

```

{
    "error": "Competition with id xxx not found."
}

```

HTTP 400 INVALID REQUEST

```
{  
  "error": "Cannot update competition id xxx with given information."  
}
```

3 Administrative Endpoints

登录和交易时使用。

3.1 Login Admin

管理员登录。

Request

```
POST /api/admin/login  
  
Host: localhost:8080  
Auth:  
Content-type: application/json  
Accept: application/json  
  
{  
  "username": "admin",  
  "password": "admin",  
}
```

Returns

```
HTTP 200 OK  
  
{  
  "username": "admin",  
  "token": "1283091828021803120",  
}
```

Error

```
HTTP 401 NOTAUTHORIZED  
  
{  
  "error": "Admin with username admin doesn't exist or password is wrong."  
}
```

3.2 Login Client

管理员登录。

Request

```
POST /api/client/login

Host: localhost:8080
Auth:
Content-type: application/json
Accept: application/json

{
  "username": "client",
  "password": "client",
}
```

Returns

```
HTTP 200 OK

{
  "username": "client",
  "token": "1283091828021803120",
}
```

Error

```
HTTP 401 NOTAUTHORIZED

{
  "error": "Client with username admin doesn't exist or password is wrong."
}
```

4 Utility Endpoints

询问系统相关信息。