

# Recurrent Event Analysis with **reda** and **reReg**

Recurrent event data arise in situations where the event of interest, such as hospital admissions, infections, or tumor recurrences, can recur in the same individual during follow-up. The standard “time-to-first” event analysis cannot capture the cumulative experience of the recurrent events and could lead to invalid inferences. The R packages **reda** (Wang et al., 2019) and **reReg** (Chiou and Huang, 2020) provide a collection of visualization tools and statistical methods for exploring and analyzing recurrent event data.

Suppose in a study consists of a random sample of  $n$  subjects and  $N_i(t)$  be the number of events the  $i$ th subject experienced over the interval  $[0, t]$ . Let  $D$  be the failure time of interest that could either be a terminal event (e.g., death) or a non-terminal event (e.g., treatment failure). Let  $C$  be the potential censoring time for reasons other than the failure event, the observed data are independent and identically distributed copies  $\{N_i(t), Y_i, X_i; t \leq Y_i, i = 1, \dots, n\}$ , where  $Y_i = \min(D, C)$ ,  $\Delta_i = I(D \leq C)$ ,  $X_i$  is a covariate vector,  $I(\cdot)$  is the indicator function, and the recurrent event process  $N_i(\cdot)$  is observed up to the composite censoring time  $Y_i$ . Suppose we are interested in making inference about the recurrent event process and the failure event in the time interval  $[0, \tau]$ , where the constant  $\tau$  is determined with the knowledge that recurrent and failure events could potentially be observed up to time  $\tau$ . We will illustrate the rehospitalization data (González et al., 2005) from the **frailtypack** package (Rondeau et al., 2019).

In the packages **reda** and **reReg**, recurrent event data are represented using an object of type **Recur** created by the **Recur()** function. The **Recur** object is an S4 class object that bundles together a set of recurrent times, failure time, and censoring status, allowing users an easy first glance of the recurrent event data. The **Recur** object is also used as the formula response for many key functions in **reda** and **reReg**. The following commands can be used to create a **Recur** object corresponding to the rehospitalization data:

```
library(reda); library(reReg)
data(readmission, package = "frailtypack")
with(readmission, Recur(t.stop, id, event, death))
```

```
## Error: Subjects having multiple terminal events:
## 60, 109, 280.
```

The **Recur()** internally calls **check\_Recur()** to check whether the specified data fits into the recurrent event data framework and detected a possible issue on the data structure. Without these subjects, the **Recur** object is presented by intervals

```
readmission0 <-
  subset(readmission, !(id %in% c(60, 109, 280)))
options(max.print = 5)
(obj <- with(readmission0,
  Recur(t.stop, id, event, death)))
```


```
## [1] 1: (0, 24], (24, 457], (457, 1037+]
## [2] 2: (0, 489], (489, 1182+]
## [3] 3: (0, 15], (15, 783*]
## [4] 4: (0, 163], (163, 288], ..., (686, 2048+]
```

```
## [5] 5: (0, 1134], (1134, 1144+]
## [ reached getOption("max.print") -- omitted 395 entries]
```

For a concise printing, up to three recurrent intervals are printed. Users can modify this by specifying **reda.Recur.maxPrint** in **options()**. Another quick and easy way to glance at recurrent event data is by event plots. The **reReg** provides a convenient way to create event plots by allowing users to plot the **Recur** object with the generic function **plot()**.


More specifically, the event plot can be stratified by discrete variables. For example, an event plot stratified by whether the patients receive chemotherapy (**chemo** = 1 if no and **chemo** = 2 if yes) can be created by the **plotEvents()** function with the **Recur** object as a formula response and **chemo** as a covariate.

Figure 1: Event plots




## Reference

- Chiou, S. H. S. and Huang, C.-Y. (2020), *reReg: Recurrent Event Regression*, R package version 1.2.1.
- González, J. R., Fernandez, E., Moreno, V., Ribes, J., Peris, M., Navarro, M., Cambray, M., and Borràs, J. M. (2005), “Sex differences in hospital readmission among colorectal cancer patients,” *Journal of Epidemiology & Community Health*, 59, 506–511.
- Rondeau, V., Gonzalez, J. R., Mazroui, Y., Mauguén, A., Diakite, A., Laurent, A., Lopez, M., Król, A., and Sofeu, C. L. (2019), *frailtypack: General Frailty Models: Shared, Joint and Nested Frailty Models with Prediction; Evaluation of Failure-Time Surrogate Endpoints*, R package version 3.0.3.
- Wang, W., Fu, H., and Yan, J. (2019), *reda: Recurrent Event Data Analysis*, R package version 0.5.0.9002.



Wenjie Wang  
Research Scientist  
Machine Learning, Artificial  
Intelligence, and Connected Care  
Advanced Analytics and Data Sciences  
Eli Lilly and Company  
Email: wang-wenjie@lilly.com



Sy Han Chiou  
Assistant Professor  
Department of Mathematical Sciences  
University of Texas at Dallas  
Email: schiou@utdallas.edu