

Recurrent Event Analysis with **reda** and **reReg**

Recurrent event data arise in situations where the event of interest, such as hospital admissions, infections, or tumor recurrences, can recur in the same individual during follow-up. The standard “time-to-first” event analysis cannot capture the cumulative experience of the recurrent events and could lead to invalid inferences. The R packages **reda** (Wang et al., 2020) and **reReg** (Chiou and Huang, 2020) provide a collection of visualization tools and statistical methods for exploring and analyzing recurrent event data.

Suppose in a study consists of a random sample of n subjects and $N_i(t)$ be the number of events the i th subject experienced over the interval $[0, t]$. Let D be the failure time of interest that could either be a terminal event (e.g., death) or a non-terminal event (e.g., treatment failure). Let C be the potential censoring time for reasons other than the failure event, the observed data are independent and identically distributed copies $\{N_i(t), Y_i, X_i; t \leq Y_i, i = 1, \dots, n\}$, where $Y_i = \min(D, C)$, $\Delta_i = I(D \leq C)$, X_i is a covariate vector, $I(\cdot)$ is the indicator function, and the recurrent event process $N_i(\cdot)$ is observed up to the composite censoring time Y_i . Suppose we are interested in making inference about the recurrent event process and the failure event in the time interval $[0, \tau]$, where the constant τ is determined with the knowledge that recurrent and failure events could potentially be observed up to time τ . We will illustrate the rehospitalization data (González et al., 2005) from the **frailtypack** package (Rondeau et al., 2019).

In the packages **reda** and **reReg**, recurrent event data are represented using an object of type **Recur** created by the **Recur()** function. The **Recur** object is an S4 class object that bundles together a set of recurrent times, failure time, and censoring status, allowing users an easy first glance of the recurrent event data. The **Recur** object is also used as the formula response for many key functions in **reda** and **reReg**. The following commands can be used to create a **Recur** object corresponding to the rehospitalization data:

```
library(reda); library(reReg)
data(readmission, package = "frailtypack")
with(readmission, Recur(t.stop, id, event, death))
```

Error: Subjects having multiple terminal events:
60, 109, 280.


The **Recur()** internally checks whether the specified data fits into the recurrent event data framework and detected a possible issue on the data structure. The **show()** method for **Recur** objects presents recurrent events in intervals, where events happened at end of the recurrent episodes with censoring due to (or not) terminal indicated by a trailing + (or *). The following prints the **Recur** object for the first five subjects.

```
with(readmission[1:14,], Recur(t.stop, id, event, death))
```

```
[1] 1: (0, 24], (24, 457], (457, 1037+]
[2] 2: (0, 489], (489, 1182+]
[3] 3: (0, 15], (15, 783*]
[4] 4: (0, 163], (163, 288], ..., (686, 2048+]
[5] 5: (0, 1134], (1134, 1144+]
```

Another easy way to glance at recurrent event data is by event plots, which can be created by applying the generic function **plot()** to the **Recur** object when the **reReg** package is loaded. Additionally, the **plotEvents()** function from the **reReg** package allows users to stratify the event plots by discrete variables. The following codes produces event plots with and without stratifying by whether the patients receive chemotherapy.

```
df0 <- subset(readmission, !(id %in% c(60, 109, 280)))
obj <- with(df0, Recur(t.stop, id, event, death))
plot(obj, legend = "bottom") ## no stratification
fn <- Recur(t.stop, id, event, death) ~ chemo
plotEvents(fn, data = df0, legend = "bottom") ## by chemo
```



(a) No stratification

(b) Stratified by **chemo**


Figure 1: Event plots

The mean cumulative function (MCF) is often the focus in a nonparametric analysis of recurrent data. Let $M_i(t) = \mathbb{E}\{N_i(t)\}$ denote the MCF of $N_i(t)$. The Nelson-Aalen estimator (Nelson, 2003) are widely utilized in exploring the trend of recurrent event data.

$$\hat{M}(t) = \int_0^t \frac{dN(s)}{\delta(s)},$$

where $dN(s) = \sum_{i=1}^k dN_i(s)$, $\delta(s) = \sum_{i=1}^k \delta_i(s)$, $dN_i(s)$ and $\delta_i(s)$ is, respectively, the jump size and at-risk indicator of process i at time s . The MCF can be visualized by plotting the **Recur** object with argument **MCF = TRUE** when the **reReg** package is active. The **reReg** package also offers the **plotMCF()** function for plotting MCF estimates to be stratified by discrete variables. Alternatively, the **mcf()** function from the **reda** package provides a more sophisticated approach to plot MCFs. Some of the unique features the **mcf()** has include the different variance estimations, confidence interval constructions, and predictions. The following example uses the **mcf()** function to visualize MCF estimates stratified by whether the patients receive chemotherapy. The **plot()** method, as well as the **plotEvents()** function, return a **ggplot2** object (Wickham, 2016) so that users may further customize the plot easily.

```
re_mcf <- mcf(fn, data = df0)
plot(re_mcf, conf.int = TRUE, lty = 1:2) +
  ggplot2::theme(legend.position = "bottom")
```



Furthermore, the MCF difference between two groups can be tested with the two-sample pseudo-score tests (Cook et al., 1996) via `mcfDiff.test()` as follows:

```
mcfDiff.test(re_mcf)
```

Two-Sample Pseudo-Score Tests:

	Statistic	Variance	Chisq	DF	Pr(>Chisq)
Constant Weight	47.49	416.71	5.41	1	0.020 *
Linear Weight	36.56	263.59	5.07	1	0.024 *

Signif. codes:

0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Variance Estimator: robust

Both the constant weighted and the linear weighted tests indicate the MCF estimates are statistically different at a significance level of 0.05.

When the study interest is placed on evaluating the covariate effect on the recurrent event process and/or the terminal event, the `reReg()` function from the `reReg` package provides approaches to fit semiparametric regression model to recurrent event data. The `reReg()` function offers users options to choose from some of the most common models. In general, a joint scale-change model for the rate function of the recurrent event process and the hazard function of the failure time is formulated as follow:

$$\lambda(t) = Z\lambda_0(te^{X^\top\alpha})e^{X^\top\beta}; h(t) = Zh_0(te^{X^\top\eta})e^{X^\top\theta}, \quad (1)$$

where Z is a latent shared frailty variable to account for association between the two types of outcomes, $\lambda_0(\cdot)$ is the baseline rate function, $h_0(\cdot)$ is the baseline hazard function, and the regression coefficients (α, η) and (β, θ) correspond to the shape and size parameters of the rate function and hazard function, respectively. In contrast to usual shared-frailty models that require a parametric assumption on the distribution of the frailty random variable, the `reReg()` function provides semiparametric estimation procedures that do not require the knowledge about the frailty as motivated by Wang et al. (2001). As a result, the dependence between recurrent events and failure event is left unspecified

and the proposed implementations accommodate informative censoring.

Model 1 includes several popular semiparametric models as special cases, which can be specified via the `method` argument with the type of rate function and hazard separated by `|`. For examples, the joint Cox model proposed by Huang and Wang (2004) is a special case of 1 when $\alpha = \eta = 0$ and can be called by `method = "cox|cox"`; the joint Accelerated Mean model proposed by Xu et al. (2017) is a special case when $\alpha = \eta$ and can be called by `method = "am|am"`. When the primary interest is in the covariate effects on the risk of recurrent events and treating the terminal event as nuisances, i.e., $\eta = \theta = 0$, model 1 reduces to the generalized scale-change model proposed in Xu et al. (2019), called by `method = "sc|."`. Users can mixed and match the `method` arguments depending on the application. For example, `method = "cox|ar"` fits a Cox proportional model for the recurrent event rate function and an accelerated rate model for the terminal event hazard function, i.e., this assumes $\alpha = \theta = 0$ in 1. For inference, the asymptotic variance is estimated from an efficient resampling-based sandwich estimator motivated by Zeng and Lin (2008). The resampling approach is faster than the conventional bootstrap method as it only requires evaluating perturbed estimating equations a large number of times rather than solving them. The following codes fit the joint Cox model with 200 (default) resampling replicates:

```
system.time(fit <- reReg(fn, df0, method = "cox|cox"))
```

user	system	elapsed
1.884	0.016	1.903

The `summary()` method prints the results of the model fits:

```
summary(fit)
```

Call:

```
reReg(formula = fn, data = df0, method = "cox|cox")
```

Recurrent event process:

	Estimate	StdErr	z.value	p.value
chemoTreated	-0.189	0.244	-0.778	0.437

Terminal event:

	Estimate	StdErr	z.value	p.value
chemoTreated	0.519	0.286	1.815	0.07

After a model is fitted, the baseline rate function and hazard function can be visualized by plotting the `reReg()` object. Methods proposed by authors Lin et al. (2000), Ghosh and Lin (2002), and Ghosh and Lin (2003) are also implemented in `reReg`. See wenjie-stat.me/rede/ and www.sychiou.com/reReg/ for the full package documents.

Reference

- Chiou, S. H. and Huang, C.-Y. (2020), **reReg: Recurrent Event Regression**, R package version 1.2.1.
- Cook, R. J., Lawless, J. F., and Nadeau, C. (1996), "Robust Tests for Treatment Comparisons Based on Recurrent Event Responses," *Biometrics*, 52, 557–571.
- Ghosh, D. and Lin, D. (2003), "Semiparametric analysis of recurrent events data in the presence of dependent censoring," *Biometrics*, 59, 877–885.

Ghosh, D. and Lin, D. Y. (2002), “Marginal regression models for recurrent and terminal events,” *Statistica Sinica*, 663–688.

González, J. R., Fernandez, E., Moreno, V., Ribes, J., Peris, M., Navarro, M., Cambray, M., and Borràs, J. M. (2005), “Sex differences in hospital readmission among colorectal cancer patients,” *Journal of Epidemiology & Community Health*, 59, 506–511.

Huang, C.-Y. and Wang, M.-C. (2004), “Joint modeling and estimation for recurrent event processes and failure time data,” *Journal of the American Statistical Association*, 99, 1153–1165.

Lin, D. Y., Wei, L.-J., Yang, I., and Ying, Z. (2000), “Semiparametric regression for the mean and rate functions of recurrent events,” *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 62, 711–730.

Nelson, W. B. (2003), *Recurrent Events Data Analysis for Product Repairs, Disease Recurrences, and Other Applications*, Society for Industrial and Applied Mathematics.

Rondeau, V., Gonzalez, J. R., Mazroui, Y., Mauguén, A., Diakite, A., Laurent, A., Lopez, M., Król, A., and Sofeu, C. L. (2019), *frailtypack: General Frailty Models: Shared, Joint and Nested Frailty Models with Prediction; Evaluation of Failure-Time Surrogate Endpoints*, R package version 3.0.3.

Wang, M.-C., Qin, J., and Chiang, C.-T. (2001), “Analyzing recurrent event data with informative censoring,” .

Wang, W., Fu, H., and Yan, J. (2020), **reda**: *Recurrent Event Data Analysis*, R package version 0.5.1.

Wickham, H. (2016), *ggplot2: Elegant Graphics for Data Analysis*, Springer-Verlag New York.

Xu, G., Chiou, S. H., Huang, C.-Y., Wang, M.-C., and Yan, J. (2017), “Joint scale-change models for recurrent events and failure time,” *Journal of the American Statistical Association*, 112, 794–805.

Xu, G., Chiou, S. H., Yan, J., Marr, K., and Huang, C.-Y. (2019), “Generalized scale-change models for recurrent event processes under informative censoring,” *Statistica Sinica*.

Zeng, D. and Lin, D. (2008), “Efficient resampling methods for nonsmooth estimating functions,” *Biostatistics*, 9, 355–363.



Wenjie Wang
Research Scientist
Machine Learning, Artificial
Intelligence, and Connected Care
Advanced Analytics and Data Sciences
Eli Lilly and Company
Email: wang_wenjie@lilly.com



Sy Han Chiou
Assistant Professor
Department of Mathematical Sciences
University of Texas at Dallas
Email: schiou@utdallas.edu